

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	Smart visual ear-clean Rod
Model Name	E3, E3 SE, E3 SE-CC, E3S, E3Pro, E3Pro Max, E3-WM, W3, W3 SE, W3 SE-CC, W3S, W3Pro, W3Pro Max, W3-WM, bebird E3, bebird E3 SE, bebird E3 SE-CC, bebird E3S, bebird E3Pro, bebird E3Pro Max, bebird E3-WM
FCC ID	2AU63-E3

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

$$P_t = 7.63 \text{ dBm} = 5.79 \text{ mW}$$

The value of the Maximum output power P_t is referred to the test report of the CFR47

§15.247.

The result for RF exposure evaluation $\text{SAR} = (5.79 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.462(\text{GHz})}] = 1.81 < 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

4. CONCLUSION

The SAR evaluation is not required.