

材质105g哑粉+哑油

尺寸:80x165mm

**Open bebird E3**

- 1 iOS: Search for "bebird" in App Store
- 2 Android: Search for "bebird" in Google Play
- 3 Enter APP: Select bebird E3
- 4 Open the cover: Powers on automatically

Please read the enclosed safety instructions before using.

**WiFi Connectivity**

- 1 Connect product WiFi "bebird-XXXX" WiFi Password:12345678
- 2 Press Start, to power the App

**Replacement of Accessories**

Unscrew the current accessory and pull it out. Put in the desired accessory and screw it in to secure.

**Accessories**

- 1 Oral covering x 1
- 2 Q-Elastic large spoons x 1 PC and silica gel synthetic ear spoon
- 3 Silver needle massage villi rod x 1
- 4 Type-C cable x 1 Fast and convenient charging
- 5 Ear canal sheath x 1
- 6 Q-Elastic round ear spoon x 1 PC and silica gel synthetic ear spoon
- 7 Q-Elastic ear spoons x 1 PC and silica gel synthetic ear spoon

正面

**Trouble Shooting**

Trouble	Solution
Start up and no response	Please try several more times according to the correct boot-up method. Please use the attached charging base for charging. The charging time is about 3h.
Camera does not turn on	Shut down and restart the ear cleaning rod.
APP quits quickly	Delete the existing APP and re-scan the QR code for installation.
The power indicator of the ear cleaning rod shows blue light flashing rapidly	Charge the ear cleaning rod with the charging base from the original packing.
WiFi connection is unstable, sometimes it is disconnected in seconds	Restart ear cleaning rod, reconnect bebird APP.
The product failed to display the real-time image after successfully connecting the bebird APP	Disconnect the phone from WiFi, restart the product and reconnect the WiFi.

If the above operation still fails to solve the problem, please contact Customer Service for further assistance.

Please read the enclosed safety instructions before using.

**Product parameter**

Brand: bebird  
Product Name: Smart visual ear cleaning rod  
Model: E3  
Rod weight: 20g  
Network standard: IEEE 802.11b/g/n  
Antenna: Internal FPC antenna  
Working frequency: 2.4GHz  
Image transmission rate: 30fps  
Image sensor: CMOS  
Working temperature: -10 ~ 50°C  
Battery: 300mAh lithium battery  
Battery life: About 75 minutes  
Charging time: 3h  
Input parameters: 5V=0.4A  
Working voltage: 4.2V  
Rated power: 1.5W  
Lens diameter: 3.5mm  
Optimum focal length: 1.5 ~ 2cm  
Pixel: 300W  
Gyroscope: 3 axis

**Warranty Card**

User information: User name: Telephone number:  
Purchase date:  
Seller: Telephone number:

**FCC Warning**

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions:  
(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates and can receive radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:  
• Reorient or relocate the receiving antenna.  
• Increase the separation between the equipment and receiver.  
• Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.  
• Consult the dealer or an experienced radio/TV technician for help.

背面

**Hazardous Material**

Part name	Hazardous Material					
	(Pb)	(Hg)	(Cd)	(Cr(VI))	(PBB)	(PBDE)
Printed Circuit Components	X	○	○	○	○	○
Case	○	○	○	○	○	○
Plastic rubber accessory	○	○	○	○	○	○

This form is formulated in accordance with SJ/T 11364  
 ○ represent the hazardous material ratio below 0.1% (0.01%~0.1%)  
 X: represent the hazardous material ratio over 0.1% (0.01%~0.1%)