



# RF Exposure Evaluation Report

## 1. Product Information

FCC ID:	2AU7V-WC-008
Number of tested samples	2
Sample number	A070423123-1(Engineer sample), A070423123-2(Normal sample)
Product Name	Mag-Modular 3in1 wireless charging
Model Number	WC-008
Power Supply	Input: DC 5V, 1A Wireless Charging: 2.5W/5W/15W
Modulation Type	Continuous Wave
Frequency Range	110.5~205.0KHz
Antenna Type	Coil Antenna
Hardware version	/
Software version	/
Accessories	/
Exposure category	General population/uncontrolled environment
EUT Type	Production Unit
Device Type	Mobile Device

## 2. Evaluation Method

Per KDB 680106 D01 Section 3. RF Exposure Requirements;

- Consumer wireless power transfer devices approved under Part 18 in some cases have to demonstrate compliance with RF exposure requirements. The potential for exposure must be assessed according to the operating configurations of the wireless system and the exposure conditions of users and bystanders. RF exposure must be evaluated with the client device(s) being charged by the primary at maximum output power. The RF exposure requirements must be determined in conjunction with the device operating characteristics, according to the mobile and portable exposure requirements in Section 2.1091 and Section 2.1093 of the rules. SAR and MPE limits do not cover the frequency range for wireless power transfer applications which operate below 100 kHz and 300 kHz respectively; therefore, RF exposure compliance needs to be determined with respect to 1.1307 (c) and (d) of the FCC rules.
- Based on the design and implementation of the power transfer application, it must be clearly identified if mobile or portable RF exposure conditions apply. Devices that are installed to provide separation of at least 20 cm from users and bystanders may qualify for mobile exposure conditions. For some conditions where users and bystanders may be exposed at closer than 20 cm, section 2.1091(d) (4) of the rules may apply.
- For devices designed for typical desktop applications, such a wireless charging pads, RF exposure evaluation should be conducted assuming a user separation distance of 15 cm. E and H field strength measurements or numerical modeling may be used to demonstrate compliance. Measurements should be made from all sides and the top of the primary/client pair, with the 15 cm measured from the center of the probe(s) to the edge of the device. Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614 V/m and 1.63 A/m. A KDB inquiry is required to determine the applicable exposure limits below 100 kHz.
- Portable exposure conditions from 100 kHz to 6 GHz are determined with respect to SAR requirements. Existing SAR systems and test procedures are generally intended for measurements



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add:101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



above 100 MHz. While numerical modeling can be an alternative, the constraints of substantial computational resources at low frequencies could introduce further limitations. Under these circumstances, including operations below 100 kHz, the Commission may consider a combination of analytical analysis, field strength, radiated and conducted power measurements, in conjunction with some limited numerical modeling to assess compliance.

- 5) Depending on the operating frequency, existing SAR and MPE measurement procedures may be adapted to evaluate wireless power transfer devices for compliance with respect to mobile or portable exposure conditions. If the grantee or its test lab have any questions regarding RF exposure evaluation they should contact the FCC Laboratory with sufficient system operating configuration details to determine if RF exposure evaluation is necessary and, if required, how to apply specific test procedures. Below 100 MHz, when SAR testing is required and the device is operating at close proximity to persons, information on device design, implementation, operating configurations, exposure conditions of users and bystanders are needed to determine the evaluation and testing requirements. In addition, the influence of nearby objects may also need consideration according to the wireless power transfer system implementation; for example, the effects of placing the device, its coils or radiating elements on or near metallic surfaces

### 3. Evaluation Limit

#### 3.1 Refer evaluation method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 680106 D01 RF Exposure Wireless Charging Apps v03](#): RF Exposure Considerations for Low Power Consumer Wireless Power Transfer Applications

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices

[FCC CFR 47 part 18.107](#): Industrial, Scientific, and Medical Equipment



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: [webmaster@lcs-cert.com](mailto:webmaster@lcs-cert.com) | Web: [www.lcs-cert.com](http://www.lcs-cert.com)

Scan code to check authenticity



### 3.2 Limit

#### Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500	/	/	f/300	6
1,500-100,000	/	/	5	6

#### Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500	/	/	f/1500	30
1,500-100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density

According to FCC KDB 680106 D01 Section 3. RF Exposure Requirements clause 3 the Emission-Limits in the frequency range from 100 KHz to 300 KHz should be assessed versus the limits at 300 KHz in Table 1 of CFR 47 – Section 1.310 as following (measured distance shall be 15cm from the center of the probe to the edge of the device):

	E-Field	*/*	B-Field
Frequency	V/m	A/m	uT
0.3 MHz – 3.0 MHz	614	1.613	2.0
3.0 MHz – 30 MHz	824/f (=27.5 <sub>30MHz</sub> )	2.19/f (=0.073 <sub>30MHz</sub> )	--

A KDB inquire was required to determine/confirm the applicable limits below 100 KHz.



Shenzhen LCS Compliance Testing Laboratory Ltd.


Add:101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



### 4. Test Setup Diagram



### 5. Test Equipment

Equipment	Manufacturer	Model	Serial no.	Calibrated date	Calibrated Due
Exposure Level Tester	Narda	ELT-400	N-0713	2022-10-29	2023-10-28
B-Field Probe	Narda	ELT-400	M-1154	2022-10-29	2023-10-28

### 6. Support equipment List

Manufacturer	Description	Model	Serial Number	Certificate
Honor	Phone	V30pro	---	FCC
SHENZHEN TIANYIN ELECTRONICS CO., LTD	Power Adapter	TPA-46050200UU	---	FCC
Redmi	Watch	Redmi Watch 3	---	FCC
B&O	TWS Earphone	Beoplay EQ	---	FCC

### 7. Measurement Procedure

- a) The RF exposure test was performed on 360 degree turn table in anechoic chamber.
- b) The measurement probe was placed at test distance (15cm and 20cm) which is between the edges of the charger and the geometric center of probe.
- c) The turn table was rotated 360d degree to search of highest strength.
- d) The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E) were completed.
- e) The EUT were measured according to the dictates of KDB 680106D01v03.





## 8. Equipment Approval Considerations

The EUT does comply with item 5.2 of KDB 680106 D01v03 as follows table;

Requirements of KDB 680106 D01	Yes / No	Description
Power transfer frequency is less than 1 MHz	Yes	The device operate in the frequency range 110.5 KHz - 205 KHz
Output power from each primary coil is less than or equal to 15 watts	Yes	The maximum output power of the primary coil is 15W.
The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time.	Yes	The transfer system includes three primary and secondary coils .Charging systems have three primary coils and clients that are able to detect and allow coupling only between individual pairs of coils and the coil pairs powered on at the same time.
Client device is placed directly in contact with the transmitter.	Yes	Client device is placed directly in contact with the transmitter.
Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).	Yes	Mobile exposure conditions only
The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.	Yes	The EUT H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

In all other cases, unless excluded above, an RF exposure evaluation report must be reviewed and accepted through a KDB or PBA inquiry to enable authorization of the equipment. When evaluation is required to show compliance; for example, using field strength, power density, SAR measurements or computational modeling etc., the specific authorization requirements will be determined based on the results of the RF exposure evaluation.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add:101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: [webmaster@lcs-cert.com](mailto:webmaster@lcs-cert.com) | Web: [www.lcs-cert.com](http://www.lcs-cert.com)

Scan code to check authenticity

**9. E and H field Strength**

Test Modes		
Mode 1	AC/DC Adapter(5V/1A)+EUT+mobile phone+Watch+TWS Earphone(Battery Status: <1%)	Record
Mode 2	AC/DC Adapter(5V/1A)+EUT+mobile phone+Watch+TWS Earphone(Battery Status: <50%)	Record
Mode 3	AC/DC Adapter(5V/1A)+EUT+mobile phone+Watch+TWS Earphone(Battery Status: 100%)	Record
Mode 4	AC/DC Adapter(5V/1A)+EUT+ mobile phone(Battery Status: <1%)	Record
Mode 5	AC/DC Adapter(5V/1A)+EUT+ mobile phone(Battery Status: <50%)	Record
Mode 6	AC/DC Adapter(5V/1A)+EUT+ mobile phone(Battery Status: <100%)	Record
Mode 7	AC/DC Adapter(5V/1A)+EUT+Watch(Battery Status: <1%)	Record
Mode 8	AC/DC Adapter(5V/1A)+EUT+Watch(Battery Status: <50%)	Record
Mode 9	AC/DC Adapter(5V/1A)+EUT+Watch(Battery Status: <100%)	Record
Mode 10	AC/DC Adapter(5V/1A)+TWS Earphone(Battery Status: <1%)	Record
Mode 11	AC/DC Adapter(5V/1A)+TWS Earphone(Battery Status: <50%)	Record
Mode 12	AC/DC Adapter(5V/1A)+TWS Earphone(Battery Status: <100%)	Record
Mode 13	AC/DC Adapter(5V/1A)+EUT+mobile phone+Watch(Battery Status: <1%)	Pre-tested
Mode 14	AC/DC Adapter(5V/1A)+EUT+mobile phone+Watch(Battery Status: <50%)	Pre-tested
Mode 15	AC/DC Adapter(5V/1A)+EUT+mobile phone+Watch(Battery Status: <100%)	Pre-tested
Mode 16	AC/DC Adapter(5V/1A)+EUT+mobile phone+TWS Earphone(Battery Status: <1%)	Pre-tested
Mode 17	AC/DC Adapter(5V/1A)+EUT+mobile phone+TWS Earphone(Battery Status: <50%)	Pre-tested
Mode 18	AC/DC Adapter(5V/1A)+EUT+mobile phone+TWS Earphone(Battery Status: <100%)	Pre-tested
Mode 19	AC/DC Adapter(5V/1A)+EUT+Watch+TWS Earphone(Battery Status: <1%)	Pre-tested
Mode 20	AC/DC Adapter(5V/1A)+EUT+Watch+TWS Earphone(Battery Status: <50%)	Pre-tested
Mode 21	AC/DC Adapter(5V/1A)+EUT+Watch+TWS Earphone(Battery Status: <100%)	Pre-tested
Note: All test modes were pre-tested, but we only recorded the worst case in this report.		



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add:101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Field Strength at 15 cm from the edges surrounding the EUT and 20cm from the top surface of the EUT

Load mode	Frequency Range (KHz)	Field Strength	Measured E - Field Strength Values (V/m)					50% Limits	Limits
			Measured H - Field Strength Values (A/m)						
			Test Position A	Test Position B	Test Position C	Test Position D	Test Position E		
Mode 1	110.5~205.0	uT	0.129	0.140	0.144	0.128	0.144	--	--
Mode 1	110.5~205.0	A/m	0.103	0.112	0.115	0.102	0.115	0.815	1.63
Mode 1	110.5~205.0	V/m	38.888	42.000	43.288	38.405	43.357	307	614
Mode 2	110.5~205.0	uT	0.129	0.136	0.144	0.127	0.143	--	--
Mode 2	110.5~205.0	A/m	0.103	0.109	0.115	0.102	0.114	0.815	1.63
Mode 2	110.5~205.0	V/m	38.714	40.979	43.150	38.225	42.981	307	614
Mode 3	110.5~205.0	uT	0.125	0.135	0.142	0.124	0.142	--	--
Mode 3	110.5~205.0	A/m	0.100	0.108	0.113	0.099	0.113	0.815	1.63
Mode 3	110.5~205.0	V/m	37.677	40.666	42.547	37.301	42.565	307	614
Mode 4	110.5~205.0	uT	0.128	0.139	0.142	0.127	0.142	--	--
Mode 4	110.5~205.0	A/m	0.103	0.111	0.114	0.101	0.114	0.815	1.63
Mode 4	110.5~205.0	V/m	38.886	42.000	43.287	38.403	43.356	307	614
Mode 5	110.5~205.0	uT	0.127	0.135	0.143	0.126	0.142	--	--
Mode 5	110.5~205.0	A/m	0.102	0.108	0.115	0.101	0.113	0.815	1.63
Mode 5	110.5~205.0	V/m	38.712	40.979	43.149	38.222	42.979	307	614
Mode 6	110.5~205.0	uT	0.124	0.133	0.141	0.124	0.141	--	--
Mode 6	110.5~205.0	A/m	0.099	0.107	0.113	0.099	0.113	0.815	1.63
Mode 6	110.5~205.0	V/m	37.677	40.664	42.545	37.299	42.564	307	614
Mode 7	110.5~205.0	uT	0.126	0.138	0.142	0.126	0.142	--	--
Mode 7	110.5~205.0	A/m	0.101	0.111	0.114	0.101	0.114	0.815	1.63
Mode 7	110.5~205.0	V/m	38.885	41.997	43.285	38.401	43.355	307	614
Mode 8	110.5~205.0	uT	0.126	0.134	0.143	0.124	0.140	--	--
Mode 8	110.5~205.0	A/m	0.100	0.107	0.114	0.099	0.112	0.815	1.63
Mode 8	110.5~205.0	V/m	38.709	40.976	43.149	38.221	42.977	307	614
Mode 9	110.5~205.0	uT	0.123	0.132	0.140	0.122	0.141	--	--
Mode 9	110.5~205.0	A/m	0.098	0.105	0.112	0.097	0.113	0.815	1.63
Mode 9	110.5~205.0	V/m	37.674	40.662	42.545	37.299	42.562	307	614
Mode 10	110.5~205.0	uT	0.126	0.138	0.140	0.126	0.140	--	--
Mode 10	110.5~205.0	A/m	0.101	0.110	0.112	0.101	0.112	0.815	1.63
Mode 10	110.5~205.0	V/m	38.884	41.994	43.284	38.401	43.353	307	614
Mode 11	110.5~205.0	uT	0.125	0.133	0.141	0.122	0.139	--	--
Mode 11	110.5~205.0	A/m	0.100	0.106	0.113	0.098	0.111	0.815	1.63
Mode 11	110.5~205.0	V/m	38.708	40.975	43.146	38.220	42.977	307	614
Mode 12	110.5~205.0	uT	0.121	0.130	0.138	0.120	0.140	--	--
Mode 12	110.5~205.0	A/m	0.097	0.104	0.111	0.096	0.112	0.815	1.63
Mode 12	110.5~205.0	V/m	37.672	40.660	42.542	37.296	42.559	307	614

Note:A/m=uT/1.25



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add:101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China


Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



### 10. Test Setup Photos

Test Position A - Exposure photo from side edge surface-Rear(15cm)



(TM1)

Test Position B - Exposure photo from side edge surface-Left(15cm)




(TM1)







**Test Position C - Exposure photo from side edge surface-Front(15cm)**



(TM1)

**Test Position D - Exposure photo from side edge surface-Right(15cm)**



(TM1)






**Test Position E - Exposure photo from top surface (20cm)**



(TM1)

**Test Position E- Exposure photo from top surface (15cm)**



(TM1)





### 11. Conclusion

A minimum safety distance of at 15 cm surrounding the device and 20 cm above the top surface of the device is required when the device is charging a smart phone. The detected emissions with a distance of 15 cm surrounding the device and 20 cm above the top surface of the device are below the limitations according to FCC KDB 680106 D01 Section 3. RF Exposure Requirement Clause 3.

### Revision History

Report Version	Issue Date	Revision Content	Revised By
000	July 31, 2023	Initial Issue	--

.....END OF REPORT.....

