



RF TEST REPORT

Applicant Shanghai Smawave Technology Co. ,Ltd
FCC ID 2AU8HMGL6201A
Product LTE Module
Brand Smawave
Model MGL6201A
Report No. R2003A0163-R1
Issue Date April 21, 2020

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 2 (2019)/ FCC CFR 47 Part 96E (2019)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Performed by: Peng Tao

Approved by: Kai Xu

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



TABLE OF CONTENT

- 1. Test Laboratory4
 - 1.1. Notes of the Test Report 4
 - 1.2. Test facility.....4
 - 1.3. Testing Location 4
- 2. General Description of Equipment under Test.....5
 - 2.3. Applicant and Manufacturer Information5
 - 2.4. General Information..... 5
- 3. Applied Standards6
- 4. Test Configuration.....7
- 5. Test Case Results.....8
 - 5.3. RF Power Output..... 8
 - 5.4. Maximum Effective Isotropic Radiated Power..... 15
 - 5.5. Occupied Bandwidth 24
 - 5.6. Band Edge Compliance..... 33
 - 5.7. Peak-to-Average Power Ratio (PAPR) 43
 - 5.8. Frequency Stability..... 46
 - 5.9. Spurious Emissions at Antenna Terminals 50
 - 5.10. Radiates Spurious Emission..... 54
- 6. Main Test Instruments57

Summary of measurement results

No.	Test Type	Clause in FCC rules	Verdict
1	RF power output	2.1046/ 96.41(b)	PASS
2	Maximum Effective Isotropic Radiated Power	96.41(b)	PASS
3	Occupied Bandwidth	2.1049/ 96.41	PASS
4	Band Edge Compliance	2.1051/ 96.41(e)	PASS
5	Peak-to-Average Power Ratio	96.41(g)	PASS
6	Frequency Stability	2.1055	PASS
7	Spurious Emissions at Antenna Terminals	2.1051 / 96.41(e)	PASS
8	Radiates Spurious Emission	2.1051 / 96.41(e)	PASS

Date of Testing: April 5, 2020 ~ April 15, 2020

Note: PASS: The EUT complies with the essential requirements in the standard.

FAIL: The EUT does not comply with the essential requirements in the standard.

All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.



1. Test Laboratory

1.1. Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein .Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2. Test facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

1.3. Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: xukai@ta-shanghai.com

2. General Description of Equipment under Test

2.3. Applicant and Manufacturer Information

Applicant	Shanghai Smawave Technology Co. ,Ltd
Applicant address	3/F, Building 8, 1001 North Qinzhou Road, Xuhui District, Shanghai, China
Manufacturer	Shanghai Smawave Technology Co. ,Ltd
Manufacturer address	3/F, Building 8, 1001 North Qinzhou Road, Xuhui District, Shanghai, China

2.4. General Information

EUT Description			
Model	MGL6201A		
IMEI	860524031979485		
Hardware Version	V1.0		
Software Version	MG62_BYPASS		
Power Supply	External Power Supply		
Antenna Type	External Antenna		
Antenna Gain	3.18dBi		
Test Mode(s)	LTE Band 48;		
Test Modulation	QPSK 16QAM 64QAM;		
LTE Category	12		
Maximum E.I.R.P	LTE Band 48:	21.01dBm	
Rated Power Supply Voltage	3.3V		
Extreme Voltage	Minimum: 3V Maximum: 3.6V		
Extreme Temperature	Lowest: -40°C Highest: +70°C		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	LTE Band 48	3550-3700	3550-3700
Note: 1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant.			



3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards:

FCC 47 CFR Part 96E (2019)

ANSI / TIA-603-E

Reference standard:

FCC 47 CFR Part 2 (2019)

FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01

4. Test Configuration

There is more than one SIM card slot, each one should be applied throughout the compliance test respectively, and however, only the worst case (SIM 1) will be recorded in this report.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes. EUT stand-up position (Z axis), lie-down position (X, Y axis). Receiver antenna polarization (horizontal and vertical), the worst emission was found in position (X axis, horizontal polarization) and the worst case was recorded.

All mode and data rates and positions were investigated. Subsequently, only the worst case emissions are reported.

The following testing in LTE is set based on the maximum RF Output Power.

Test modes are chosen to be reported as the worst case configuration below:

Test modes are chosen as the worst case configuration below for LTE Band 48.

Test items	Bandwidth (MHz)				Modulation			RB			Test Channel		
	5	10	15	20	QPSK	16QAM	64QAM	1	50%	100%	L	M	H
RF power output	O	O	O	O	O	O	O	O	O	O	O	O	O
Maximum Effective Isotropic Radiated Power	O	O	O	O	O	O	O	O	O	O	O	O	O
Occupied Bandwidth	O	O	O	O	O	O	O	-	-	O	O	O	O
Band Edge Compliance	O	O	O	O	O	O	O	O	-	O	O	-	O
Peak-to-Average Power Ratio	O	O	O	O	O	O	O	-	-	O	O	O	O
Frequency Stability	O	O	O	O	O	O	O	O	O	O	O	O	O
Spurious Emissions at Antenna Terminals	O	O	O	O	O	-	-	O	-	-	O	O	O
Radiates Spurious Emission	O	-	-	O	O	-	-	O	-	-	-	O	-
Note	1. The mark "O" means that this configuration is chosen for testing. 2. The mark "-" means that this configuration is not testing.												

5. Test Case Results

5.3. RF Power Output

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

Test Setup



The loss between RF output port of the EUT and the input port of the tester has been taken into consideration.

Limits

Rule Part 96.41(b) specifies that

Device	Maximum EIRP (dBm/10MHz)	Maximum PSD (dBm/MHz)
End User Device	23	n/a

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4$ dB.

**Test Results**

Band	Bandwidth	Modulation	Channel	RB Configuration	Conducted Power(dBm)
LTE Band48	5M	QPSK	55265	1RB#0	18.39
LTE Band48	5M	QPSK	55265	1RB#13	17.83
LTE Band48	5M	QPSK	55265	1RB#24	18.60
LTE Band48	5M	QPSK	55265	12RB#0	18.04
LTE Band48	5M	QPSK	55265	12RB#6	17.90
LTE Band48	5M	QPSK	55265	12RB#13	17.90
LTE Band48	5M	QPSK	55265	25RB#0	17.71
LTE Band48	5M	QPSK	55990	1RB#0	18.65
LTE Band48	5M	QPSK	55990	1RB#13	18.24
LTE Band48	5M	QPSK	55990	1RB#24	18.57
LTE Band48	5M	QPSK	55990	12RB#0	18.11
LTE Band48	5M	QPSK	55990	12RB#6	18.14
LTE Band48	5M	QPSK	55990	12RB#13	18.20
LTE Band48	5M	QPSK	55990	25RB#0	18.17
LTE Band48	5M	QPSK	56715	1RB#0	19.03
LTE Band48	5M	QPSK	56715	1RB#13	18.84
LTE Band48	5M	QPSK	56715	1RB#24	18.18
LTE Band48	5M	QPSK	56715	12RB#0	18.34
LTE Band48	5M	QPSK	56715	12RB#6	18.02
LTE Band48	5M	QPSK	56715	12RB#13	17.89
LTE Band48	5M	QPSK	56715	25RB#0	18.18
LTE Band48	5M	16QAM	55265	1RB#0	18.47
LTE Band48	5M	16QAM	55265	1RB#13	18.04
LTE Band48	5M	16QAM	55265	1RB#24	18.50
LTE Band48	5M	16QAM	55265	12RB#0	17.93
LTE Band48	5M	16QAM	55265	12RB#6	17.88
LTE Band48	5M	16QAM	55265	12RB#13	17.81
LTE Band48	5M	16QAM	55265	25RB#0	17.83
LTE Band48	5M	16QAM	55990	1RB#0	18.21
LTE Band48	5M	16QAM	55990	1RB#13	18.23
LTE Band48	5M	16QAM	55990	1RB#24	18.56
LTE Band48	5M	16QAM	55990	12RB#0	18.11
LTE Band48	5M	16QAM	55990	12RB#6	18.17
LTE Band48	5M	16QAM	55990	12RB#13	18.18
LTE Band48	5M	16QAM	55990	25RB#0	18.12
LTE Band48	5M	16QAM	56715	1RB#0	19.36
LTE Band48	5M	16QAM	56715	1RB#13	19.21
LTE Band48	5M	16QAM	56715	1RB#24	18.43



LTE Band48	5M	16QAM	56715	12RB#0	18.45
LTE Band48	5M	16QAM	56715	12RB#6	18.35
LTE Band48	5M	16QAM	56715	12RB#13	18.07
LTE Band48	5M	16QAM	56715	25RB#0	18.24
LTE Band48	10M	QPSK	55290	1RB#0	18.34
LTE Band48	10M	QPSK	55290	1RB#25	17.77
LTE Band48	10M	QPSK	55290	1RB#49	18.53
LTE Band48	10M	QPSK	55290	25RB#0	17.97
LTE Band48	10M	QPSK	55290	25RB#13	17.86
LTE Band48	10M	QPSK	55290	25RB#25	17.83
LTE Band48	10M	QPSK	55290	50RB#0	17.69
LTE Band48	10M	QPSK	55990	1RB#0	18.52
LTE Band48	10M	QPSK	55990	1RB#25	18.20
LTE Band48	10M	QPSK	55990	1RB#49	18.49
LTE Band48	10M	QPSK	55990	25RB#0	18.07
LTE Band48	10M	QPSK	55990	25RB#13	18.10
LTE Band48	10M	QPSK	55990	25RB#25	18.12
LTE Band48	10M	QPSK	55990	50RB#0	18.09
LTE Band48	10M	QPSK	56690	1RB#0	18.97
LTE Band48	10M	QPSK	56690	1RB#25	18.78
LTE Band48	10M	QPSK	56690	1RB#49	18.08
LTE Band48	10M	QPSK	56690	25RB#0	18.28
LTE Band48	10M	QPSK	56690	25RB#13	17.97
LTE Band48	10M	QPSK	56690	25RB#25	17.90
LTE Band48	10M	QPSK	56690	50RB#0	18.19
LTE Band48	10M	16QAM	55290	1RB#0	18.44
LTE Band48	10M	16QAM	55290	1RB#25	18.02
LTE Band48	10M	16QAM	55290	1RB#49	18.48
LTE Band48	10M	16QAM	55290	25RB#0	17.90
LTE Band48	10M	16QAM	55290	25RB#13	17.85
LTE Band48	10M	16QAM	55290	25RB#25	17.76
LTE Band48	10M	16QAM	55290	50RB#0	17.81
LTE Band48	10M	16QAM	55990	1RB#0	18.18
LTE Band48	10M	16QAM	55990	1RB#25	18.18
LTE Band48	10M	16QAM	55990	1RB#49	18.49
LTE Band48	10M	16QAM	55990	25RB#0	18.08
LTE Band48	10M	16QAM	55990	25RB#13	18.12
LTE Band48	10M	16QAM	55990	25RB#25	18.18
LTE Band48	10M	16QAM	55990	50RB#0	18.12
LTE Band48	10M	16QAM	56690	1RB#0	19.31
LTE Band48	10M	16QAM	56690	1RB#25	19.17
LTE Band48	10M	16QAM	56690	1RB#49	18.39
LTE Band48	10M	16QAM	56690	25RB#0	18.41



LTE Band48	10M	16QAM	56690	25RB#13	18.29
LTE Band48	10M	16QAM	56690	25RB#25	18.04
LTE Band48	10M	16QAM	56690	50RB#0	18.22
LTE Band48	15M	QPSK	55315	1RB#0	18.33
LTE Band48	15M	QPSK	55315	1RB#38	17.75
LTE Band48	15M	QPSK	55315	1RB#74	18.50
LTE Band48	15M	QPSK	55315	36RB#0	17.95
LTE Band48	15M	QPSK	55315	36RB#18	17.83
LTE Band48	15M	QPSK	55315	36RB#39	17.80
LTE Band48	15M	QPSK	55315	75RB#0	17.67
LTE Band48	15M	QPSK	55990	1RB#0	18.48
LTE Band48	15M	QPSK	55990	1RB#38	18.19
LTE Band48	15M	QPSK	55990	1RB#74	18.44
LTE Band48	15M	QPSK	55990	36RB#0	18.03
LTE Band48	15M	QPSK	55990	36RB#18	18.05
LTE Band48	15M	QPSK	55990	36RB#39	18.09
LTE Band48	15M	QPSK	55990	75RB#0	18.05
LTE Band48	15M	QPSK	56665	1RB#0	18.95
LTE Band48	15M	QPSK	56665	1RB#38	18.75
LTE Band48	15M	QPSK	56665	1RB#74	18.04
LTE Band48	15M	QPSK	56665	36RB#0	18.25
LTE Band48	15M	QPSK	56665	36RB#18	17.93
LTE Band48	15M	QPSK	56665	36RB#39	17.86
LTE Band48	15M	QPSK	56665	75RB#0	18.14
LTE Band48	15M	16QAM	55315	1RB#0	18.39
LTE Band48	15M	16QAM	55315	1RB#38	18.00
LTE Band48	15M	16QAM	55315	1RB#74	18.45
LTE Band48	15M	16QAM	55315	36RB#0	17.87
LTE Band48	15M	16QAM	55315	36RB#18	17.82
LTE Band48	15M	16QAM	55315	36RB#39	17.74
LTE Band48	15M	16QAM	55315	75RB#0	17.78
LTE Band48	15M	16QAM	55990	1RB#0	18.16
LTE Band48	15M	16QAM	55990	1RB#38	18.15
LTE Band48	15M	16QAM	55990	1RB#74	18.45
LTE Band48	15M	16QAM	55990	36RB#0	18.06
LTE Band48	15M	16QAM	55990	36RB#18	18.07
LTE Band48	15M	16QAM	55990	36RB#39	18.14
LTE Band48	15M	16QAM	55990	75RB#0	18.07
LTE Band48	15M	16QAM	56665	1RB#0	19.29
LTE Band48	15M	16QAM	56665	1RB#38	19.15
LTE Band48	15M	16QAM	56665	1RB#74	18.36
LTE Band48	15M	16QAM	56665	36RB#0	18.38
LTE Band48	15M	16QAM	56665	36RB#18	18.25



LTE Band48	15M	16QAM	56665	36RB#39	18.01
LTE Band48	15M	16QAM	56665	75RB#0	18.18
LTE Band48	20M	QPSK	55340	1RB#0	18.30
LTE Band48	20M	QPSK	55340	1RB#50	17.74
LTE Band48	20M	QPSK	55340	1RB#99	18.48
LTE Band48	20M	QPSK	55340	50RB#0	17.92
LTE Band48	20M	QPSK	55340	50RB#25	17.81
LTE Band48	20M	QPSK	55340	50RB#50	17.77
LTE Band48	20M	QPSK	55340	100RB#0	17.64
LTE Band48	20M	QPSK	55990	1RB#0	18.44
LTE Band48	20M	QPSK	55990	1RB#50	18.15
LTE Band48	20M	QPSK	55990	1RB#99	18.43
LTE Band48	20M	QPSK	55990	50RB#0	17.98
LTE Band48	20M	QPSK	55990	50RB#25	18.01
LTE Band48	20M	QPSK	55990	50RB#50	18.04
LTE Band48	20M	QPSK	55990	100RB#0	18.00
LTE Band48	20M	QPSK	56640	1RB#0	18.92
LTE Band48	20M	QPSK	56640	1RB#50	18.73
LTE Band48	20M	QPSK	56640	1RB#99	18.01
LTE Band48	20M	QPSK	56640	50RB#0	18.21
LTE Band48	20M	QPSK	56640	50RB#25	17.90
LTE Band48	20M	QPSK	56640	50RB#50	17.82
LTE Band48	20M	QPSK	56640	100RB#0	18.10
LTE Band48	20M	16QAM	55340	1RB#0	18.37
LTE Band48	20M	16QAM	55340	1RB#50	17.96
LTE Band48	20M	16QAM	55340	1RB#99	18.43
LTE Band48	20M	16QAM	55340	50RB#0	17.84
LTE Band48	20M	16QAM	55340	50RB#25	17.79
LTE Band48	20M	16QAM	55340	50RB#50	17.71
LTE Band48	20M	16QAM	55340	100RB#0	17.76
LTE Band48	20M	16QAM	55990	1RB#0	18.12
LTE Band48	20M	16QAM	55990	1RB#50	18.13
LTE Band48	20M	16QAM	55990	1RB#99	18.42
LTE Band48	20M	16QAM	55990	50RB#0	18.02
LTE Band48	20M	16QAM	55990	50RB#25	18.05
LTE Band48	20M	16QAM	55990	50RB#50	18.09
LTE Band48	20M	16QAM	55990	100RB#0	18.03
LTE Band48	20M	16QAM	56640	1RB#0	19.24
LTE Band48	20M	16QAM	56640	1RB#50	19.11
LTE Band48	20M	16QAM	56640	1RB#99	18.34
LTE Band48	20M	16QAM	56640	50RB#0	18.35
LTE Band48	20M	16QAM	56640	50RB#25	18.22
LTE Band48	20M	16QAM	56640	50RB#50	17.97



LTE Band48	20M	16QAM	56640	100RB#0	18.15
LTE Band48	5M	64QAM	55265	1RB#0	18.45
LTE Band48	5M	64QAM	55265	1RB#13	18.01
LTE Band48	5M	64QAM	55265	1RB#24	18.48
LTE Band48	5M	64QAM	55265	12RB#0	17.87
LTE Band48	5M	64QAM	55265	12RB#6	17.80
LTE Band48	5M	64QAM	55265	12RB#13	17.77
LTE Band48	5M	64QAM	55265	25RB#0	17.81
LTE Band48	5M	64QAM	55990	1RB#0	18.65
LTE Band48	5M	64QAM	55990	1RB#13	18.21
LTE Band48	5M	64QAM	55990	1RB#24	18.54
LTE Band48	5M	64QAM	55990	12RB#0	18.07
LTE Band48	5M	64QAM	55990	12RB#6	18.13
LTE Band48	5M	64QAM	55990	12RB#13	18.14
LTE Band48	5M	64QAM	55990	25RB#0	18.07
LTE Band48	5M	64QAM	56715	1RB#0	19.33
LTE Band48	5M	64QAM	56715	1RB#13	19.16
LTE Band48	5M	64QAM	56715	1RB#24	18.42
LTE Band48	5M	64QAM	56715	12RB#0	18.41
LTE Band48	5M	64QAM	56715	12RB#6	18.33
LTE Band48	5M	64QAM	56715	12RB#13	18.03
LTE Band48	5M	64QAM	56715	25RB#0	18.20
LTE Band48	10M	64QAM	55290	1RB#0	18.42
LTE Band48	10M	64QAM	55290	1RB#25	17.99
LTE Band48	10M	64QAM	55290	1RB#49	18.46
LTE Band48	10M	64QAM	55290	25RB#0	17.84
LTE Band48	10M	64QAM	55290	25RB#13	17.77
LTE Band48	10M	64QAM	55290	25RB#25	17.72
LTE Band48	10M	64QAM	55290	50RB#0	17.79
LTE Band48	10M	64QAM	55990	1RB#0	18.62
LTE Band48	10M	64QAM	55990	1RB#25	18.16
LTE Band48	10M	64QAM	55990	1RB#49	18.47
LTE Band48	10M	64QAM	55990	25RB#0	18.04
LTE Band48	10M	64QAM	55990	25RB#13	18.08
LTE Band48	10M	64QAM	55990	25RB#25	18.14
LTE Band48	10M	64QAM	55990	50RB#0	18.07
LTE Band48	10M	64QAM	56690	1RB#0	19.28
LTE Band48	10M	64QAM	56690	1RB#25	19.12
LTE Band48	10M	64QAM	56690	1RB#49	18.38
LTE Band48	10M	64QAM	56690	25RB#0	18.37
LTE Band48	10M	64QAM	56690	25RB#13	18.27
LTE Band48	10M	64QAM	56690	25RB#25	18.00
LTE Band48	10M	64QAM	56690	50RB#0	18.18



LTE Band48	15M	64QAM	55315	1RB#0	18.37
LTE Band48	15M	64QAM	55315	1RB#38	17.97
LTE Band48	15M	64QAM	55315	1RB#74	18.43
LTE Band48	15M	64QAM	55315	36RB#0	17.81
LTE Band48	15M	64QAM	55315	36RB#18	17.74
LTE Band48	15M	64QAM	55315	36RB#39	17.70
LTE Band48	15M	64QAM	55315	75RB#0	17.76
LTE Band48	15M	64QAM	55990	1RB#0	18.60
LTE Band48	15M	64QAM	55990	1RB#38	18.13
LTE Band48	15M	64QAM	55990	1RB#74	18.43
LTE Band48	15M	64QAM	55990	36RB#0	18.02
LTE Band48	15M	64QAM	55990	36RB#18	18.03
LTE Band48	15M	64QAM	55990	36RB#39	18.10
LTE Band48	15M	64QAM	55990	75RB#0	18.02
LTE Band48	15M	64QAM	56665	1RB#0	19.26
LTE Band48	15M	64QAM	56665	1RB#38	19.10
LTE Band48	15M	64QAM	56665	1RB#74	18.35
LTE Band48	15M	64QAM	56665	36RB#0	18.34
LTE Band48	15M	64QAM	56665	36RB#18	18.23
LTE Band48	15M	64QAM	56665	36RB#39	17.97
LTE Band48	15M	64QAM	56665	75RB#0	18.14
LTE Band48	20M	64QAM	55340	1RB#0	18.35
LTE Band48	20M	64QAM	55340	1RB#50	17.93
LTE Band48	20M	64QAM	55340	1RB#99	18.41
LTE Band48	20M	64QAM	55340	50RB#0	17.78
LTE Band48	20M	64QAM	55340	50RB#25	17.71
LTE Band48	20M	64QAM	55340	50RB#50	17.67
LTE Band48	20M	64QAM	55340	100RB#0	17.74
LTE Band48	20M	64QAM	55990	1RB#0	18.56
LTE Band48	20M	64QAM	55990	1RB#50	18.11
LTE Band48	20M	64QAM	55990	1RB#99	18.40
LTE Band48	20M	64QAM	55990	50RB#0	17.98
LTE Band48	20M	64QAM	55990	50RB#25	18.01
LTE Band48	20M	64QAM	55990	50RB#50	18.05
LTE Band48	20M	64QAM	55990	100RB#0	17.98
LTE Band48	20M	64QAM	56640	1RB#0	19.21
LTE Band48	20M	64QAM	56640	1RB#50	19.06
LTE Band48	20M	64QAM	56640	1RB#99	18.33
LTE Band48	20M	64QAM	56640	50RB#0	18.31
LTE Band48	20M	64QAM	56640	50RB#25	18.20
LTE Band48	20M	64QAM	56640	50RB#50	17.93
LTE Band48	20M	64QAM	56640	100RB#0	18.11

5.4. Maximum Effective Isotropic Radiated Power

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The EIRP of the low, middle and high channels were measured.

RBW is set to 10MHz, VBW is set to 10MHz for LTE Band 48 (5MHz/10MHz/15MHz/20MHz).

Test setup



Limits

Unless otherwise specified in this section, the maximum effective isotropic radiated power (EIRP) of and End User Device must comply with the limits shown in following table:

Rule Part 96.41(b) specifies that

Device	Maximum EIRP (dBm/10MHz)	Maximum PSD (dBm/MHz)
End User Device	23	n/a

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 1.19$ dB







**Test Results:**







The measurement is performed for both of horizontal and vertical antenna Polarization, and only the data of worst mode is recorded in this report.







LTE Band 48						
RB	Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	Maximum PSD (dBm/10MHz)	Maximum EIRP(dBm)
100%	QPSK	5	55265	3552.5	16.62	19.80
			55990	3625	17.68	20.86
			56715	3697.5	16.01	19.19
		10	55290	3555	15.67	18.85
			55990	3625	16.92	20.10
			56690	3695	15.46	18.64
		15	55315	3557.5	14.44	17.62
			55990	3625	15.89	19.07
			56665	3692.5	13.96	17.14
		20	55340	3560	13.53	16.71
			55990	3625	14.48	17.66
			5660	3690	12.92	16.10
	16QAM	5	55265	3552.5	17.49	20.67
			55990	3625	17.58	20.76
			56715	3697.5	16.21	19.39
		10	55290	3555	15.97	19.15
			55990	3625	17.10	20.28
			56690	3695	15.65	18.83
		15	55315	3557.5	14.92	18.10
			55990	3625	15.80	18.98
			56665	3692.5	13.44	16.62
		20	55340	3560	13.70	16.88
			55990	3625	14.53	17.71
			5660	3690	12.97	16.15
	64QAM	5	55265	3552.5	17.36	20.54
			55990	3625	17.83	21.01
			56715	3697.5	16.45	19.63
		10	55290	3555	16.27	19.45
			55990	3625	17.09	20.27
			56690	3695	15.41	18.59
15		55315	3557.5	15.46	18.64	
		55990	3625	15.66	18.84	
		56665	3692.5	13.84	17.02	
20		55340	3560	13.66	16.84	









			55990	3625	14.57	17.75
			5660	3690	12.98	16.16













LTE Band 48 5MHz 64QAM CH-Low




Date: 15.APR.2020 16:37:23

LTE Band 48 10MHz 64QAM CH-Low




Date: 15.APR.2020 16:43:12

LTE Band 48 5MHz 64QAM CH-Middle




Date: 15.APR.2020 16:41:16

LTE Band 48 10MHz 64QAM CH-Middle




Date: 15.APR.2020 16:44:09

LTE Band 48 5MHz 64QAM CH-High









Date: 15.APR.2020 16:42:12

LTE Band 48 10MHz 64QAM CH-High



Date: 15.APR.2020 16:45:07



5.5. Occupied Bandwidth

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa


Method of Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The testing follows FCC KDB 971168 D01 v03r01 Section 4.2

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
3. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
4. Set the detection mode to peak, and the trace mode to max hold.
5. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
6. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
7. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
8. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

Test Setup



Limits

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 624\text{Hz}$.

Test Result

LTE Band 48						
RB	Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	99% Power Bandwidth(MHz)	-26dBc Bandwidth(MHz)
100%	QPSK	5	55265	3552.5	4.5430	5.320
			55990	3625	4.5306	5.105
			56715	3697.5	4.5133	5.084
		10	55290	3555	9.0434	10.070
			55990	3625	9.0505	9.924
			56690	3695	9.0781	10.130
		15	55315	3557.5	13.4820	14.980
			55990	3625	13.4420	14.340
			56665	3692.5	13.4500	14.950
		20	55340	3560	17.9140	19.040
			55990	3625	17.8350	18.920
			56660	3690	17.8780	18.780
	16QAM	5	55265	3552.5	4.5218	5.254
			55990	3625	4.5186	5.212
			56715	3697.5	4.5108	5.268
		10	55290	3555	9.0828	10.160
			55990	3625	9.0348	9.963
			56690	3695	9.0611	10.150
		15	55315	3557.5	13.4940	14.510
			55990	3625	13.4650	14.460
			56665	3692.5	13.4900	14.590
		20	55340	3560	17.8870	18.960
			55990	3625	17.8920	19.150
			56660	3690	17.8730	18.960
	64QAM	5	55265	3552.5	4.5234	5.250
			55990	3625	4.5184	5.140



			56715	3697.5	4.5284	5.208
		10	55290	3555	9.0540	10.170
			55990	3625	9.0217	10.060
			56690	3695	9.0293	10.090
		15	55315	3557.5	13.4940	14.860
			55990	3625	13.4430	14.550
			56665	3692.5	13.4360	14.370
		20	55340	3560	17.8780	19.140
			55990	3625	17.8930	18.990
			5660	3690	17.9080	19.000



LTE Band 48 5MHz QPSK CH-Low



LTE Band 48 10MHz QPSK CH-Low



LTE Band 48 5MHz QPSK CH-Middle



LTE Band 48 10MHz QPSK CH-Middle



LTE Band 48 5MHz QPSK CH-High




LTE Band 48 10MHz QPSK CH-High



LTE Band 48 15MHz QPSK CH-Low




LTE Band 48 20MHz QPSK CH-Low



LTE Band 48 15MHz QPSK CH-Middle




LTE Band 48 20MHz QPSK CH-Middle



LTE Band 48 15MHz QPSK CH-High



LTE Band 48 20MHz QPSK CH-High





LTE Band 48 5MHz 16QAM CH-Low



LTE Band 48 10MHz 16QAM CH-Low



LTE Band 48 5MHz 16QAM CH-Middle



LTE Band 48 10MHz 16QAM CH-Middle









LTE Band 48 5MHz 16QAM CH-High



LTE Band 48 10MHz 16QAM CH-High







LTE Band 48 5MHz 64QAM CH-Low



LTE Band 48 10MHz 64QAM CH-Low



LTE Band 48 5MHz 64QAM CH-Middle



LTE Band 48 10MHz 64QAM CH-Middle




LTE Band 48 5MHz 64QAM CH-High



LTE Band 48 10MHz 64QAM CH-High





5.6. Band Edge Compliance

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The testing follows FCC KDB 971168 D01 v03r01 Section 6.0.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The band edges of low and high channels for the highest RF powers were measured.
3. Set RBW \geq 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
4. Beyond the 1 MHz band from the band edge, RBW=1MHz was used
5. Set spectrum analyzer with RMS detector.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

Test Setup



Limits


Rule Part 96.41(e) (1) (i) specifies that “Except as otherwise specified in paragraph (e)(2) of this section, for channel and frequency assignments made by the SAS to CBSDs, the conducted power of any CBSD emission outside the fundamental emission bandwidth as specified in paragraph (e)(3) of this section (whether the emission is inside or outside of the authorized band) shall not exceed -13 dBm/MHz within 0-10 megahertz above the upper SAS-assigned channel edge and within 0-10 megahertz below the lower SAS-assigned channel edge. At all frequencies greater than 10 megahertz above the upper SAS assigned channel edge and less than 10 MHz below the lower SAS assigned channel edge, the conducted power of any CBSD emission shall not exceed -25 dBm/MHz. The upper and lower SAS assigned channel edges are the upper and lower limits of any channel assigned to a CBSD by an SAS, or in the case of multiple contiguous channels, the upper and lower limits of the combined contiguous channels.”



Measurement Uncertainty


The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U=0.684\text{dB}$.

Test Result:






LTE Band 48 QPSK 10MHz CH-Low, 1 RB




Date: 8 APR 2020 12:33:33

LTE Band 48 QPSK 10MHz CH-High, 1 RB




Date: 8 APR 2020 12:45:50

LTE Band 48 QPSK 10MHz CH-Low, 100%RB




Date: 8 APR 2020 12:33:46

LTE Band 48 QPSK 10MHz CH-High, 100%RB




Date: 8 APR 2020 12:46:02

LTE Band 48 QPSK 15MHz CH-Low, 1 RB



Date: 8 APR 2020 12:37:46


LTE Band 48 QPSK 15MHz CH-High, 1 RB



Date: 8 APR 2020 12:48:13




LTE Band 48 QPSK 15MHz CH-Low, 100%RB




Date: 8 APR 2020 12:37:58

LTE Band 48 QPSK 15MHz CH-High, 100%RB




Date: 8 APR 2020 12:48:25

LTE Band 48 QPSK 20MHz CH-Low, 1 RB




Date: 8 APR 2020 12:39:57

LTE Band 48 QPSK 20MHz CH-High, 1 RB




Date: 8 APR 2020 12:50:35

LTE Band 48 QPSK 20MHz CH-Low, 100%RB



Date: 8 APR 2020 12:40:07


LTE Band 48 QPSK 20MHz CH-High, 100%RB



Date: 8 APR 2020 12:50:48




LTE Band 48 16QAM 5MHz CH-Low, 1 RB




Date: 8 APR 2020 12:23:19

LTE Band 48 16QAM 5MHz CH-High, 1 RB




Date: 8 APR 2020 12:43:24

LTE Band 48 16QAM 5MHz CH-Low, 100%RB




Date: 8 APR 2020 12:23:33

LTE Band 48 16QAM 5MHz CH-High, 100%RB




Date: 8 APR 2020 12:43:36

LTE Band 48 16QAM 10MHz CH-Low, 1 RB



Date: 8 APR 2020 12:33:59


LTE Band 48 16QAM 10MHz CH-High, 1 RB



Date: 8 APR 2020 12:46:13




LTE Band 48 16QAM 10MHz CH-Low, 100%RB




Date: 8 APR 2020 12:34:43

LTE Band 48 16QAM 10MHz CH-High, 100%RB




Date: 8 APR 2020 12:46:24

LTE Band 48 16QAM 15MHz CH-Low, 1 RB




Date: 8 APR 2020 12:38:11

LTE Band 48 16QAM 15MHz CH-High, 1 RB




Date: 8 APR 2020 12:48:38

LTE Band 48 16QAM 15MHz CH-Low, 100%RB



Date: 8 APR 2020 12:38:23


LTE Band 48 16QAM 15MHz CH-High, 100%RB



Date: 8 APR 2020 12:48:49




LTE Band 48 16QAM 20MHz CH-Low, 1 RB




Date: 8 APR 2020 12:40:25

LTE Band 48 16QAM 20MHz CH-High, 1 RB




Date: 8 APR 2020 12:51:00

LTE Band 48 16QAM 20MHz CH-Low, 100%RB




Date: 8 APR 2020 12:40:34

LTE Band 48 16QAM 20MHz CH-High, 100%RB




Date: 8 APR 2020 12:51:12

LTE Band 48 64QAM 5MHz CH-Low, 1 RB



Date: 8 APR 2020 12:23:46


LTE Band 48 64QAM 5MHz CH-High, 1 RB



Date: 8 APR 2020 12:43:46




LTE Band 48 64QAM 5MHz CH-Low, 100%RB




Date: 8 APR 2020 12:23:56

LTE Band 48 64QAM 5MHz CH-High, 100%RB




Date: 8 APR 2020 12:44:00

LTE Band 48 64QAM 10MHz CH-Low, 1 RB




Date: 8 APR 2020 12:34:57

LTE Band 48 64QAM 10MHz CH-High, 1 RB




Date: 8 APR 2020 12:46:34

LTE Band 48 64QAM 10MHz CH-Low, 100%RB



Date: 8 APR 2020 12:35:06


LTE Band 48 64QAM 10MHz CH-High, 100%RB



Date: 8 APR 2020 12:46:43




LTE Band 48 64QAM 15MHz CH-Low, 1 RB




Date: 8 APR 2020 12:38:39

LTE Band 48 64QAM 15MHz CH-High, 1 RB




Date: 8 APR 2020 12:49:04

LTE Band 48 64QAM 15MHz CH-Low, 100%RB




Date: 8 APR 2020 12:38:47

LTE Band 48 64QAM 15MHz CH-High, 100%RB




Date: 8 APR 2020 12:49:15

LTE Band 48 64QAM 20MHz CH-Low, 1 RB



Date: 8 APR 2020 12:40:46

LTE Band 48 64QAM 20MHz CH-High, 1 RB




Date: 8 APR 2020 12:51:21




LTE Band 48 64QAM 20MHz CH-Low, 100%RB

LTE Band 48 64QAM 20MHz CH-High, 100%RB



Date: 8 APR 2020 12:40:54



Date: 8 APR 2020 12:51:30

5.7. Peak-to-Average Power Ratio (PAPR)

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa


Methods of Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument’s resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth.

The testing follows FCC KDB 971168 D01 v03r01 Section 5.7.1

1. The EUT was connected to spectrum and system simulator via a power divider.
2. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
3. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio

Test Setup



Limits

Rule Part 96.41(g), The peak-to-average power ratio (PAPR) of any CBSD transmitter output power must not exceed 13 dB.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4$ dB.



Test Results

LTE Band 48								
Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	Peak (dBm)	Avg (dBm)	PAPR (dB)	Limit (dB)	Conclusion
QPSK	5	55265	3552.5	22.36	12.61	9.75	≤13	PASS
		55990	3625	21.78	12.56	9.22	≤13	PASS
		56715	3697.5	21.45	11.70	9.75	≤13	PASS
	10	55290	3555	22.45	13.02	9.43	≤13	PASS
		55990	3625	21.77	12.25	9.52	≤13	PASS
		56690	3695	21.64	12.13	9.51	≤13	PASS
	15	55315	3557.5	22.78	12.56	10.22	≤13	PASS
		55990	3625	22.17	12.95	9.22	≤13	PASS
		56665	3692.5	22.29	12.66	9.63	≤13	PASS
	20	55340	3560	22.14	12.11	10.03	≤13	PASS
		55990	3625	21.52	12.24	9.28	≤13	PASS
		5660	3690	21.31	11.59	9.72	≤13	PASS
16QAM	5	55265	3552.5	23.06	12.80	10.26	≤13	PASS
		55990	3625	22.46	12.28	10.18	≤13	PASS
		56715	3697.5	22.09	12.07	10.02	≤13	PASS
	10	55290	3555	23.21	13.26	9.95	≤13	PASS
		55990	3625	22.52	12.29	10.23	≤13	PASS
		56690	3695	22.41	12.11	10.30	≤13	PASS
	15	55315	3557.5	23.30	12.97	10.33	≤13	PASS
		55990	3625	22.68	12.47	10.21	≤13	PASS
		56665	3692.5	22.80	12.34	10.46	≤13	PASS
	20	55340	3560	23.12	13.39	9.73	≤13	PASS
		55990	3625	22.25	11.81	10.44	≤13	PASS
		5660	3690	22.22	12.13	10.09	≤13	PASS
64QAM	5	55265	3552.5	23.04	12.69	10.35	≤13	PASS
		55990	3625	22.48	12.42	10.06	≤13	PASS
		56715	3697.5	22.08	11.97	10.11	≤13	PASS
	10	55290	3555	23.24	13.22	10.02	≤13	PASS
		55990	3625	22.58	12.66	9.92	≤13	PASS
		56690	3695	22.44	12.11	10.33	≤13	PASS



	15	55315	3557.5	23.33	12.96	10.37	≤13	PASS
		55990	3625	22.71	12.67	10.04	≤13	PASS
		56665	3692.5	22.81	12.59	10.22	≤13	PASS
	20	55340	3560	23.01	12.62	10.39	≤13	PASS
		55990	3625	22.34	12.44	9.90	≤13	PASS
		5660	3690	22.23	12.27	9.96	≤13	PASS

5.8. Frequency Stability

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

Test Procedures for Temperature Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.


1. The EUT was set up in the thermal chamber and connected with the system simulator.
2. With power OFF, the temperature was decreased to -40°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 70°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

Test Procedures for Voltage Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was placed in a temperature chamber at 25±5° C and connected with the system simulator.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

Test setup



Limits

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency



Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 3$, $U = 0.01\text{ppm}$.



Test Result

Condition		Freq. Error (Hz)	Freq. Error (Hz)	Freq. Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	5MHz	(Hz)	(Hz)	(Hz)	(ppm)	(ppm)	(ppm)	
Temperature	Voltage	64QAM	16QAM	QPSK	64QAM	16QAM	QPSK	
Normal(25°C)	Normal	5.11	4.35	5.85	0.00272	0.00231	0.00311	PASS
Extreme(70°C)		8.78	3.85	14.09	0.00467	0.00205	0.00749	PASS
Extreme(60°C)		2.29	4.35	17.21	0.00122	0.00231	0.00915	PASS
Extreme(50°C)		1.83	8.14	16.44	0.00098	0.00433	0.00874	PASS
Extreme(40°C)		4.25	13.97	16.83	0.00226	0.00743	0.00895	PASS
Extreme(30°C)		6.51	9.89	6.86	0.00346	0.00526	0.00365	PASS
Extreme(20°C)		5.59	6.78	10.98	0.00298	0.00360	0.00584	PASS
Extreme(10°C)		12.88	15.61	14.45	0.00685	0.00830	0.00769	PASS
Extreme(0°C)		15.57	13.68	17.54	0.00828	0.00728	0.00933	PASS
Extreme(-10°C)		8.09	10.94	11.68	0.00430	0.00582	0.00621	PASS
Extreme(-20°C)		8.95	13.35	15.37	0.00476	0.00710	0.00817	PASS
Extreme(-30°C)		3.14	8.37	10.13	0.00167	0.00445	0.00539	PASS
Extreme(-40°C)		3.97	7.53	8.69	0.00211	0.00401	0.00462	PASS
25°C	LV	9.17	9.14	11.72	0.00488	0.00486	0.00624	PASS
	HV	16.16	13.30	2.46	0.00860	0.00707	0.00131	PASS
Condition		Freq. Error (Hz)	Freq. Error (Hz)	Freq. Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	10MHz	(Hz)	(Hz)	(Hz)	(ppm)	(ppm)	(ppm)	
Temperature	Voltage	64QAM	16QAM	QPSK	64QAM	16QAM	QPSK	
Normal(25°C)	Normal	10.25	7.05	13.67	0.00545	0.00375	0.00727	PASS
Extreme(70°C)		12.63	15.66	15.10	0.00672	0.00833	0.00803	PASS
Extreme(60°C)		15.40	4.52	13.84	0.00819	0.00241	0.00736	PASS
Extreme(50°C)		10.16	16.50	5.48	0.00540	0.00878	0.00292	PASS
Extreme(40°C)		11.90	16.32	9.05	0.00633	0.00868	0.00481	PASS
Extreme(30°C)		2.27	13.08	16.90	0.00121	0.00695	0.00899	PASS
Extreme(20°C)		14.26	12.55	15.33	0.00759	0.00668	0.00816	PASS
Extreme(10°C)		10.81	15.62	12.04	0.00575	0.00831	0.00640	PASS
Extreme(0°C)		12.95	3.69	17.84	0.00689	0.00196	0.00949	PASS
Extreme(-10°C)		17.25	1.96	5.73	0.00918	0.00104	0.00305	PASS
Extreme(-20°C)		11.78	13.53	11.86	0.00626	0.00720	0.00631	PASS
Extreme(-30°C)		15.48	7.66	17.78	0.00824	0.00407	0.00946	PASS
Extreme(-40°C)		3.43	12.94	17.04	0.00182	0.00689	0.00907	PASS
25°C	LV	12.91	7.94	16.65	0.00687	0.00422	0.00885	PASS
	HV	17.92	17.27	9.99	0.00953	0.00919	0.00531	PASS
Condition		Freq.	Freq.	Freq.	Frequency	Frequency	Frequency	Verdict



BANDWIDTH		15MHz	Error (Hz)	Error (Hz)	Error (Hz)	Stability (ppm)	Stability (ppm)	Stability (ppm)	Verdict
Temperature	Voltage	64QAM	16QAM	QPSK	64QAM	16QAM	QPSK		
Normal(25°C)	Normal	12.97	6.72	4.09	0.00690	0.00357	0.00218	PASS	
Extreme(70°C)		13.08	10.68	11.98	0.00696	0.00568	0.00637	PASS	
Extreme(60°C)		9.46	5.89	4.27	0.00503	0.00313	0.00227	PASS	
Extreme(50°C)		5.31	1.01	1.10	0.00283	0.00054	0.00058	PASS	
Extreme(40°C)		14.85	4.16	1.45	0.00790	0.00221	0.00077	PASS	
Extreme(30°C)		15.23	15.83	9.70	0.00810	0.00842	0.00516	PASS	
Extreme(20°C)		6.20	14.51	13.70	0.00330	0.00772	0.00729	PASS	
Extreme(10°C)		14.88	6.05	13.97	0.00791	0.00322	0.00743	PASS	
Extreme(0°C)		8.45	8.58	1.91	0.00450	0.00456	0.00102	PASS	
Extreme(-10°C)		11.99	8.92	7.56	0.00638	0.00475	0.00402	PASS	
Extreme(-20°C)		3.82	15.59	8.63	0.00203	0.00829	0.00459	PASS	
Extreme(-30°C)		3.52	12.65	8.91	0.00187	0.00673	0.00474	PASS	
Extreme(-40°C)		17.48	1.07	11.02	0.00930	0.00057	0.00586	PASS	
25°C		LV	15.86	1.50	10.58	0.00843	0.00080	0.00563	PASS
	HV	6.07	12.41	1.70	0.00323	0.00660	0.00091	PASS	
Condition		Freq. Error (Hz)	Freq. Error (Hz)	Freq. Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict	
BANDWIDTH	20MHz	64QAM	16QAM	QPSK	64QAM	16QAM	QPSK		
Normal(25°C)	Normal	14.34	11.40	3.82	0.00763	0.00606	0.00203	PASS	
Extreme(70°C)		9.29	1.18	13.86	0.00494	0.00063	0.00737	PASS	
Extreme(60°C)		17.84	14.26	5.23	0.00949	0.00759	0.00278	PASS	
Extreme(50°C)		14.51	16.53	13.21	0.00772	0.00879	0.00703	PASS	
Extreme(40°C)		6.24	17.85	3.63	0.00332	0.00949	0.00193	PASS	
Extreme(30°C)		5.36	10.89	13.65	0.00285	0.00579	0.00726	PASS	
Extreme(20°C)		2.91	10.48	4.49	0.00155	0.00558	0.00239	PASS	
Extreme(10°C)		9.45	12.19	11.79	0.00503	0.00649	0.00627	PASS	
Extreme(0°C)		6.19	5.53	4.00	0.00329	0.00294	0.00213	PASS	
Extreme(-10°C)		12.55	9.51	12.40	0.00668	0.00506	0.00660	PASS	
Extreme(-20°C)		10.57	14.86	2.48	0.00562	0.00791	0.00132	PASS	
Extreme(-30°C)		4.28	15.18	7.20	0.00227	0.00808	0.00383	PASS	
Extreme(-40°C)		16.17	1.37	15.49	0.00860	0.00073	0.00824	PASS	
25°C		LV	17.42	7.04	9.29	0.00926	0.00374	0.00494	PASS
	HV	13.09	3.99	14.96	0.00696	0.00212	0.00796	PASS	

5.9. Spurious Emissions at Antenna Terminals

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The testing follows FCC KDB 971168 D01 v03r01 Section 6.0.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. Make the measurement with the spectrum analyzer's
 - RBW is set to 1 kHz (0.009MHz~ 0.15 MHz),
 - RBW is set to 10 kHz (0.15 MHz~ 30 MHz)
 - RBW is set to 100 kHz (30MHz~1000 MHz)
 - RBW is set to 1000 kHz (above 1000MHz).
6. Set spectrum analyzer with RMS detector.
7. Taking the record of maximum spurious emission.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. The limit line is -40dBm/MHz.

Test setup



Limits

Rule Part 96.41(e) (2) *Additional protection levels*. Notwithstanding paragraph (e)(1) of this section, for CBSDs and End User Devices, the conducted power of emissions below 3540 MHz or above 3710 MHz shall not exceed -25 dBm/MHz, and the conducted power of emissions below 3530 MHz or above 3720 MHz shall not exceed -40dBm/MHz.

**Measurement Uncertainty**







The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 1.96$.

Frequency	Uncertainty
100kHz-2GHz	0.684 dB
2GHz-18GHz	1.407 dB
18GHz-40GHz	1.515 dB




Test Result

If disturbances were found more than 20dB below limit line, the mark is not required for the EUT.
The signal beyond the limit is carrier.






LTE Band 48 15MHz CH- Low 9kHz~37GHz




Date: 8 APR 2020 13:11:35

LTE Band 48 20MHz CH-Low 9kHz~37GHz




Date: 8 APR 2020 13:13:16

LTE Band 48 15MHz CH- Middle 9kHz~37GHz




Date: 8 APR 2020 13:12:03

LTE Band 48 20MHz CH- Middle 9kHz~37GHz




Date: 8 APR 2020 13:13:42

LTE Band 48 15MHz CH-High 9kHz~37GHz



Date: 8 APR 2020 13:12:34

LTE Band 48 20MHz CH- High 9kHz~37GHz



Date: 8 APR 2020 13:02:47

5.10. Radiates Spurious Emission

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

1. The testing follows FCC KDB 971168 D01 v03r01 Section 5.8 and ANSI C63.26 (2015).
2. Below 1GHz: The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H). Above 1GHz: (Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.) The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).
3. A loop antenna, A log-periodic antenna or horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=200Hz,VBW=600Hz for 9kHz150kHz , RBW=10kHz, VBW=30kHz 150kHz-30MHz ,RBW=100kHz,VBW=300kHz for 30MHz to 1GHz and RBW=1MHz, VBW=3MHz for above 1GHz And the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
7. The measurement results are obtained as described below:
$$\text{Power(EIRP)} = \text{PMea} - \text{PAg} - \text{Pcl} + \text{Ga}$$


The measurement results are amend as described below:
$$\text{Power(EIRP)} = \text{PMea} - \text{Pcl} + \text{Ga}$$
8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi)

and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.


The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

Test setup

30MHz~~~ 1GHz



Above 1GHz



Note: Area side:2.4mX3.6m

Limits

Rule Part 96.41(e) (2) specifies that “*Additional protection levels.* Notwithstanding paragraph (e)(1) of this section, for CBSDs and End User Devices, the conducted power of emissions below 3540 MHz or above 3710 MHz shall not exceed -25 dBm/MHz , and the conducted power of emissions below 3530 MHz or above 3720 MHz shall not exceed -40dBm/MHz .”

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U = 3.55\text{ dB}$.

**Test Result**

LTE Band 48 QPSK 5MHz CH-Middle, RB 1

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	7345.5	-51.59	2.6	10.75	Horizontal	-43.44	-40.00	3.44	0
3	11019.0	-57.15	2.4	11.05	Horizontal	-48.50	-40.00	8.50	315
4	14691.0	-55.97	4.5	11.15	Horizontal	-49.32	-40.00	9.32	45
5	18125.0	--	--	--	--	--	--	--	--
6	21750.0	--	--	--	--	--	--	--	--
7	25375.0	--	--	--	--	--	--	--	--
8	29000.0	--	--	--	--	--	--	--	--
9	32625.0	--	--	--	--	--	--	--	--
10	36250.0	--	--	--	--	--	--	--	--

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.
2. The worst emission was found in the antenna is Horizontal position.

LTE Band 48 QPSK 20MHz CH-Middle, RB 1

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	7332.0	-51.82	2.6	10.75	Horizontal	-43.67	-40.00	3.67	135
3	10998.8	-54.19	2.4	11.05	Horizontal	-45.54	-40.00	5.54	90
4	14664.0	-55.26	4.5	11.15	Horizontal	-48.61	-40.00	8.61	225
5	18125.0	--	--	--	--	--	--	--	--
6	21750.0	--	--	--	--	--	--	--	--
7	25375.0	--	--	--	--	--	--	--	--
8	29000.0	--	--	--	--	--	--	--	--
9	32625.0	--	--	--	--	--	--	--	--
10	36250.0	--	--	--	--	--	--	--	--

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.
2. The worst emission was found in the antenna is Horizontal position.

6. Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Base Station Simulator	R&S	CMW500	113824	2019-05-19	2020-05-18
Power Splitter	Hua Xiang	SHX-GF2-2-13	10120101	/	/
Spectrum Analyzer	Key sight	N9010A	MY50210259	2019-05-19	2020-05-18
Signal Analyzer	R&S	FSV30	100815	2019-12-15	2020-12-14
Loop Antenna	SCHWARZBECK	FMZB1519	1519-047	2017-09-26	2020-09-25
Trilog Antenna	SCHWARZBECK	VUBL 9163	9163-201	2017-11-18	2020-11-17
Horn Antenna	R&S	HF907	100126	2018-07-07	2020-07-06
Horn Antenna	ETS-Lindgren	3160-09	00102643	2018-06-20	2020-06-19
Signal generator	R&S	SMB 100A	102594	2019-05-19	2020-05-18
Climatic Chamber	ESPEC	SU-242	93000506	2017-12-17	2020-12-16
Preamplifier	R&S	SCU18	102327	2019-05-19	2020-05-18
MOB COMMS DC SUPPLY	Keysight	66319D	MY43004105	2019-05-19	2020-05-18
RF Cable	Agilent	SMA 15cm	0001	2019-12-13	2020-06-12
Software	R&S	EMC32	9.26.0	/	/

*****END OF REPORT *****