FCC ID: 2AU8YREBE-TZ15L ATTACHMENT

RF EXPOSURE EVULATION

1.1 Limit

According to §1.1310 and §2.1091 RF exposure is calculated.

Frequency range (MHz)	Electric field	Magnetic field	Power	Averaging
	Strength	Strength	density	time
1.34 - 30	824/f	2.19/f	*(180/ f²)	30
30 - 300	27.5	0.073	0.2	30
300 - 1500			f/1500	30
1500 - 100.000			<u>1.0</u>	30

F = frequency in MHz

* = Plane-wave equivalent power density

1.2 MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

Power density at the specific separation:

$S = PG/(4R^2\pi)$	Where,
5 - 1 0/(IR X)	S = Maximum power density (mW/cm2)
$S = (4.47 * 0.32) / (4 * 5^{2} * \pi)$	P = Power input to the antenna (mW)
	G = Numeric power gain of the antenna
$S = 0.46 \text{ mW/cm}^2$	$\mathbf{R} = \mathbf{Distance}$ to the center of the radiation of the antenna
	(20 cm = limit for MPE)

FCC ID: 2AU8YREBE-TZ15L ATTACHMENT

1.3 MAXIMUM PERMISSIBLE EXPOSURE Prediction

- Calculated under the worst-case conditions of each mode.

(Measured power 6.5 dBm \pm 0.5dB)

3-1. 2.4 GHz Zigbee Mode

Max Peak output Power at antenna input terminal	6.51	dBm
Max Peak output Power at antenna input terminal	4.47	mW
Prediction distance	5	cm
Prediction frequency	2,405	MHz
Antenna Gain(typical)	-4.91	dBi
Antenna Gain(numeric)	0.32	-
Power density at prediction frequency(S)	0.46	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.23	mW/cm ²

WLAN

SAR Test exclusion thresholds for 100MHz to 6GHz at test separation distance $\leq 50 \text{ mm} = \text{Used}$ [(max.power of channel, including tune-up torelance, mW)/(min. test separation distance, mm)] * [\sqrt{f} (GHz)] = [4.47 / 5] * [$\sqrt{2.405}$] = 0.89 \leq 7.5, for 1g SAR

Thus, SAR for this device is not required.