



# TEST REPORT

<p style="text-align: center;"><b>KCTL Inc.</b></p> <p style="text-align: center;">65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 <a href="http://www.kctl.co.kr">www.kctl.co.kr</a></p>	<p>Report No.: <b>KR19-SRF0197-A</b></p> <p>Page (1) of (11)</p>				
<p><b>1. Client</b></p> <p>◦ Name : Onekey Inc.</p> <p>◦ Address : #4, BI room, 136, Jiksan-ro, Jiksan-eup, Seobuk-gu, Cheonan-si, Chungcheongnam-do, Republic of Korea</p> <p>◦ Date of Receipt : 2019-10-31</p> <p><b>2. Use of Report</b> : -</p> <p><b>3. Name of Product and Model</b> : Mobile Key Conversion Device / KETO</p> <p><b>4. Manufacturer and Country of Origin</b> : Onekey Inc. / Korea</p> <p><b>5. FCC ID</b> : 2AU9RKETO</p> <p><b>6. IC Certification</b> : 25699-KETO</p> <p><b>7. Date of Test</b> : 2019-11-12 to 2019-12-02</p> <p><b>8. Test Standards</b> : 47 CFR Part 1.1310 RSS-102 Issue 5 Mar. 2015</p> <p><b>9. Test Results</b> : Refer to the test result in the test report</p>					
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%; text-align: center; vertical-align: middle;">Affirmation</td> <td style="width: 40%; padding: 5px;">           Tested by             Name : Euijung Kim  (Signature)         </td> <td style="width: 40%; padding: 5px;">           Technical Manager             Name : Jaehyong Lee  (Signature)         </td> </tr> </table> <p style="text-align: right; margin-top: 20px;">2019-12-18</p> <p style="text-align: center; margin-top: 20px;"><b>KCTL Inc.</b></p> <p style="margin-top: 20px;">As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by KCTL Inc.</p>			Affirmation	Tested by  Name : Euijung Kim  (Signature)	Technical Manager  Name : Jaehyong Lee  (Signature)
Affirmation	Tested by  Name : Euijung Kim  (Signature)	Technical Manager  Name : Jaehyong Lee  (Signature)			

#### Report revision history

Date	Revision	Page No
2019-12-13	Initial report	-
2019-12-18	Updated antenna gain and removed accessory information	5, 10

*This report shall not be reproduced except in full, without the written approval of KCTL Inc. This document may be altered or revised by KCTL Inc. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KCTL Inc. will constitute fraud and shall nullify the document. This test report is a General report that does not use the KOLAS accreditation mark and is not related to KOLAS accreditation.*

Note. The report No. KR19-SRF0197 is superseded by the report No. KR19-SRF0197-A.

**KCTL**

## CONTENTS

1.	General information .....	4
2.	Device information .....	4
2.1.	Frequency/channel operations.....	5
3.	Measurement uncertainty .....	5
4.	RF Exposure.....	6
4.1.	Test results.....	9
5.	Measurement Equipment.....	11

*KCTL*

## 1. General information

Client : Onekey Inc.  
 Address : #4, BI room, 136, Jiksan-ro, Jiksan-eup, Seobuk-gu, Cheonan-si, Chungcheongnam-do, Republic of Korea  
 Manufacturer : Onekey Inc.  
 Address : #4, BI room, 136, Jiksan-ro, Jiksan-eup, Seobuk-gu, Cheonan-si, Chungcheongnam-do, Republic of Korea  
 Laboratory : KCTL Inc.  
 Address : 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea  
 Accreditations : FCC Site Designation No: KR0040, FCC Site Registration No: 687132  
 VCCI Registration No. : R-20080, G-20078, C-20059, T-20056  
 Industry Canada Registration No. : 8035A  
 KOLAS No.: KT231

## 2. Device information

Equipment under test : Mobile Key Conversion Device  
 Model : KETO  
 Modulation technique : GFSK  
 Number of channels : 40 ch  
 Power source : DC 5 V<sup>(Note1)</sup>  
 Antenna specification : PCB Antenna  
 Antenna gain : 2.87 dBi  
 Frequency range : 2 402 MHz ~ 2 480 MHz  
 Software version : Rev 1.0  
 Hardware version : Rev 1.0  
 Test device serial No. : Conducted(1200123), Radiated(1200121)  
 Operation temperature : -20 °C ~ 50 °C

### Notes:

1. The EUT uses a power source that switches from a car battery to USB DC 5V.

## 2.1. Frequency/channel operations

This device contains the following capabilities:

Bluetooth Low Energy

Ch.	Frequency (MHz)
00	2 402
.	.
19	2 440
.	.
39	2 480

Table 2.1.1. Bluetooth Low Energy

## 3. Measurement uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of  $k=2$  to indicated a 95 % level of confidence. The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded uncertainty ( $\pm$ )
Conducted RF power	1.76 dB

## 4. RF Exposure

### FCC

#### Regulation

This document is prepared to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC rules and Regulations.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 1-1. According to FCC §1.1310: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

Table 1 – Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm <sup>2</sup> ]	Averaging Time [minute]
(A) Limits for Occupational / Controlled Exposure				
0.3 ~ 3.0	614	1.63	*100	6
3.0 ~ 30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30 ~ 300	61.4	0.163	1.0	6
300 ~ 1 500	/	/	f/300	6
1 500 ~ 15 000	/	/	5	6
(B) Limits for General Population / Uncontrolled Exposure				
0.3 ~ 1.34	614	1.63	*100	30
1.34 ~ 30	824/f	2.19/f	*180/f <sup>2</sup>	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1 500	/	/	f/1 500	30
1 500 ~ 15 000	/	/	1.0	30

f=frequency in MHz, \*= plane-wave equivalent power density

## IC

### RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)

According to RSS-102 Issue 5, Paragraph "4. Exposure Limits", Industry of Canada has adopted the RF field strength limits established in Health Canada's RF exposure guideline, Safety code 6:

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m <sup>2</sup> )	Reference Period (minutes)
0.003-10 <sup>21</sup>	83	90	-	Instantaneous*
0.1-10	-	0.73/ $f$	-	6**
1.1-10	87/ $f^{0.5}$	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ $f^{0.25}$	0.1540/ $f^{0.25}$	8.944/ $f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
<u>300-6000</u>	<u>3.142 <math>f^{0.3417}</math></u>	<u>0.008335 <math>f^{0.3417}</math></u>	<u>0.02619 <math>f^{0.6834}</math></u>	<u>6</u>
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ $f^{1.2}$
150000-300000	0.158 $f^{0.5}$	4.21 x 10 <sup>-4</sup> $f^{0.5}$	6.67 x 10 <sup>-5</sup> $f$	616000/ $f^{1.2}$
<b>Note:</b> $f$ is frequency in MHz. *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

### **Exemption Limits for Routine Evaluation – RF Exposure Evaluation**

According to RSS-102 Issue 5 section 2.5.2, RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- Below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1W (adjusted for tune-up tolerance);
- At or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $4.49/f^{0.5}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- At or above 48 MHz and below 300 MHz and the source-bands, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- At or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- At or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance.)

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.





## 4.1. Test results

### FCC

#### **MPE (Maximum Permissible Exposure) Prediction**

Prediction of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2 \quad (\Rightarrow R = \sqrt{PG/4\pi S})$$

S = power density [ $\text{mW}/\text{cm}^2$ ]

P = Power input to antenna [ $\text{mW}$ ]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [ $\text{cm}$ ]

### IC

#### **RF Exposure evaluation**

At or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834} \text{ W}$  (adjusted for tune-up tolerance), where  $f$  is in MHz;

#### **RF Exposure Compliance Issue**

The information should be included in the user's manual:

This appliance and its antenna must not be co-located or operation in conjunction with any other antenna or transmitter. A minimum separation distance of 20 cm must be maintained between the antenna and the person for this appliance to satisfy the RF exposure requirements.

### **Calculation Result of RF exposure (FCC)**

Maximum tune-up tolerance

Mode	Frequency [MHz]	Max Tune-up Power [dBm]	Max Tune-up Power [mW]	Ant Gain [dBi]	Ant Gain [mW]	Power density at 20 cm [mW/cm <sup>2</sup> ]	Limit [mW/cm <sup>2</sup> ]
BLE / 1 Mbps	2 402	5.00	3.16	2.87	1.94	0.001 22	1.000 00

**Note.**

- The power density  $P_d$  (5th column) at a distance of 20 cm calculated from the friis transmission Formula is far below the limit of 1 mW/cm<sup>2</sup>.

### **Calculation Results of RF exposure (IC)**

Maximum tune-up tolerance

Mode	Frequency [MHz]	Max Tune-up Power [dBm]	Ant Gain [dBi]	E.I.R.P		Limit [mW]
				[dBm]	[mW]	
BLE / 1 Mbps	2 402	5.00	2.87	7.87	6.12	2 676.42

## 5. Measurement Equipment

Equipment Name	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date
Pulse Power Meter	ANRITSU	ML2495A	1608009	19.07.31	20.07.31
Pulse Power Sensor	ANRITSU	MA2411B	1726174	19.07.31	20.07.31

**End of test report**

*KCTL*