KC.IA.00487(T77)

Antenna Specification

1. Application:

This application shall apply for antenna unit which shall be used such as automotive, conventional communications, smart home, etc..

2. Electrical Specification:

Those specifications were specially defined for customer's model, and all characteristics were measured under the model's handset testing jig.

2-1. Frequency Band:

Frequency Band	MHz
WiFi	2400-2500/5150-5850MHz

2-2. Impedance

50 ohm nominal


2-3. VSWR

2-3-1. Measurement frequency points and VSWR value

Frequency Band(MHz)	2400	2500	5150	5850
Typical Value: (VSWR)	1.7	1.8	1.6	1.5

2-4. Antenna type: FPC Antenna

UNLESS OTHER SPECIFIE X.X=± X.X= ANGLES=±		TOXU 同讯技术	TOXU TECHNOLOGY CO., LTD.
SCALE:	UNIT : mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USI THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATU	
DRAWN BY: LI	CHECKED BY: YS		
DESIGNED BY: De wen	APPROVED BY: YS	DEVICES WITH	OUT PERMISSION
TITLE : KC.IA.00487 Anto	enna Specification	•	SPEC REV.
THEE TROMANDO AND	cinia opecinication		P0




UNLESS OTHER SPECIFIED X=± X.X= ANGLES=±		TOXU 同讯技术	TOXU TECHNOLOGY CO., LTD.
SCALE:	UNIT: mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USE THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATU	
DRAWN BY: LI	CHECKED BY: YS		
DESIGNED BY: De wen	APPROVED BY: YS	DEVICES WITH	HOUT PERMISSION
TITLE: KC.IA.00487 Ante	nna Specification	•	SPEC REV.
THE THOMASON AND			P0

2-4. Efficiency and Gain

4-5.1 Measure method

- 1. Using a low loss coaxial cable to link a standard handset jig
- 2. Fixed this handset jig on chamber's rotator plane
 - 3. Linking jig into network analyzer port and using a probing horn antenna to collect data.
- 4. Using another standard gain horn antenna to calibrated those data

4-5.2 Chamber definition





- 1. An anechoic chamber (7mx4mx3m) which satisfied far-field condition was applied to avoid multi-path effect
- 2. The quite room region is 40cmx40cmx40cm at the center of rotator
- 3. The distance between DUT and standard antenna is 4.38 m
- Probing antenna (9120D horn antenna) and standard gain horn antenna (BBHA9120 LPF 700MHz ~6GHz)


UNLESS OTHER SPECIFIED X = ± X.X = ANGLES = ±		TOXU 同 祇 核 术	O., LTD.	
SCALE:	UNIT: mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF 1		
DRAWN BY: LI	CHECKED BY: YS	TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR U THE BASIS FOR THE MANUFACTURE OR SALE OF APPARA		
DESIGNED BY: De wen	APPROVED BY: YS	DEVICES WITHOUT PERMISSION		
TITLE : KC.IA.00487 Antenna Specification				
TITLE : NO.IA.00407 Ante	P0			


★ тохи тесноосову со., LTD.2-4-1 Efficiency and Gain and 3D Date


Freq	Effi	Gain
(MHz)	(%)	(dBi)
2400	52.71	3.35
2450	51.54	3.42
2500	51.27	3.12
5150	54.33	3.87
5500	49.55	3.27
5700	50.97	3.23
5850	49.71	3.74















Measurement	Azimuths	Elevations	Standard	Band	Channel	Frequency	Max	Min	Total	参考标准
TRP	Every30	Every30	WIFI (AP)	WIFI_B (11M)	1	2412	18.64	3.21	14.5	≥14
TRP	Every30	Every30	WIFI (AP)	WIFI_B (11M)	11	2462	19.09	4.97	15.66	= 14
TIS(EIRP)	Every30	Every30	WIFI (AP)	WIFI_B (11M)	11	2462	-72.75	-86.84	-83.46	≤-81
TRP	Every30	Every30	WIFI (AP)	WIFI_G (54M)	1	2412	16.39	0.72	11.99	≥12
TRP	Every30	Every30	WIFI (AP)	WIFI_G (54M)	11	2462	16.44	2.28	13.13	
TIS(EIRP)	Every30	Every30	WIFI (AP)	WIFI_G (54M)	11	2462	-60.84	-75.07	-71.7	≤-71
TRP	Every30	Every30	WIFI (AP)	WIFI_N_ISM (65M)	1	2412	16.84	1.14	12.43	
TRP	Every30	Every30	WIFI (AP)	WIFI_N_ISM (65M)	11	2462	14.66	-3.35	11.83	≥11
TIS(EIRP)	Every30	Every30	WIFI (AP)	WIFI_N_ISM (65M)	11	2462	-56.75	-71.22	-67.83	≤-67

UNLESS OTHER SPECIFIC	ED TOLERANCES ON:			
$X=\pm$ X.X=	$=\pm$ X.XX $=\pm$		TOXU TECHNOLOGY CO., LTD.	
ANGLES=±	$HOLEDIA = \pm$	问批役外	·	
SCALE:	UNIT: mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF T		
DRAWN BY: LI CHECKED BY: YS		TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS		
DESIGNED BY: De wen	APPROVED BY: YS	DEVICES WITH	OUT PERMISSION	
TITLE : KC.IA.00487 Ant	enna Specification	•	SPEC REV.	
	onna opocinication		P0	

3. Mechanical Specification:

3-1. Mechanical Configuration (Unit: mm)

The appearance of the antenna is according to drawing



UNLESS OTHER SPECIFIED TOLERANCES ON :		
$X=\pm$ $X.X=$	\pm X.XX= \pm	TOXU 同 祝 技 术
ANGLES=±	HOLEDIA =±	同批技术
SCALE:	UNIT: mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF TOXU
DRAWN BY: LI	CHECKED BY: YS	TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR
DESIGNED BY: De wen	APPROVED BY: YS	DEVICES WITHOUT PERMISSION
TITLE : KC.IA.00487 Ante	nna Specification	SPEC REV.
THE TROMANDO TO MILE		P0

4 .Packaging specification:

Product number: xxxxx

Product model: xxxxx

-. Label requirements:

Customer	xxx		
supplier	xxxxx		
Material coding	xx		
Product model	xx		
Number	XXX PCS	Factory date	xxx
Remarks			

二、Boxing:

Job description:

1. Inner packaging:


XXpcs A bag

2. External packaging:

Xx PCS;

- 3. Matters needing attention:
 - a. Whether to add partition and pearl cotton;
 - b. Label attachments, such as ROHS, etc.;





UNLESS OTHER SPECIFIED TOLERANCES ON :			
$X=\pm$ $X.X=\pm$ $X.XX=\pm$		TOXU 同 祇 技术 TOXU TECHNOLOGY CO., LTD.	
ANGLES=±	HOLEDIA =±	同批技术	
SCALE:	UNIT: mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF TOXU	
DRAWN BY: LI CHECKED BY: YS		TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR	
DESIGNED BY: De wen	APPROVED BY: YS	DEVICES WITHOUT PERMISSION	
TITLE : KC.IA.00487 Ant	enna Specification	SPEC REV.	
	oma opoomoation	Do.	

P0