

TEST REPORT

FCC ID :	2AUARTKTOOL195	
Test Report No :	TCT231115E061	
Date of issue :	Dec. 13, 2023	
Testing laboratory	SHENZHEN TONGCE TESTING LAB	
Testing location/ address:	2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China	
Applicant's name :	THINKCAR TECH CO., LTD.	
Address :	2606, building 4, phase II, TiananYungu, Gangtou community, Bantian, Longgang District, Shenzhen, China	
Manufacturer's name ... :	THINKCAR TECH CO., LTD.	
Address :	2606, building 4, phase II, TiananYungu, Gangtou community, Bantian, Longgang District, Shenzhen, China	
Standard(s)	FCC CFR Title 47 Part 15 Subpart E Section 15.407 KDB 662911 D01 Multiple Transmitter Output v02r01 KDB 789033 D02 General U-NII Test Procedures New Rules v02r01	
Product Name :	Modular Comprehensive Automotive Diagnostic Tool	
Trade Mark	THINKCAR, XHINKCAR, MUCAR	
Model/Type reference :	TKX08	
Rating(s) :	Adapter Information: Model: PSYB0502500 Input: AC 100-240V, 50/60Hz, 0.6A Max Output: DC 5.0V, 2.5A, 12.5W Rechargeable Li-ion Battery DC 7.6V	
Date of receipt of test item	Nov. 15, 2023	
Date (s) of performance of test :	Nov. 15, 2023 - Dec. 13, 2023	
Tested by (+signature) ... :	Ronaldo LUO	
Check by (+signature) :	Beryl ZHAO	
Approved by (+signature):	Tomsin	



General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

1. General Product Information 3

1.1. EUT description 3

1.2. Model(s) list..... 3

1.3. Test Frequency 4

2. Test Result Summary 5

3. General Information..... 6

3.1. Test environment and mode..... 6

3.2. Description of Support Units 7

4. Facilities and Accreditations 8

4.1. Facilities 8

4.2. Location 8

4.3. Measurement Uncertainty 8

5. Test Results and Measurement Data 9

5.1. Antenna requirement 9

5.2. Conducted Emission 10

5.3. Maximum Conducted Output Power 14

5.4. 6dB Emission Bandwidth..... 16

5.5. 26dB Bandwidth and 99% Occupied Bandwidth 17

5.6. Power Spectral Density 18

5.7. Band edge 19

5.8. Unwanted Emissions 33

5.9. Frequency Stability Measurement 46

Appendix A: Test Result of Conducted Test

Appendix B: Photographs of Test Setup

Appendix C: Photographs of EUT

1. General Product Information

1.1. EUT description

Product Name:	Modular Comprehensive Automotive Diagnostic Tool
Model/Type reference:	TKX08
Sample Number:	TCT231115E021-0101
Operation Frequency	Band 1: 5180 MHz ~ 5240 MHz Band 3: 5745 MHz ~ 5825 MHz
Channel Bandwidth:	802.11a: 20MHz 802.11n: 20MHz, 40MHz 802.11ac: 20MHz, 40MHz, 80MHz
Modulation Technology	Orthogonal Frequency Division Multiplexing(OFDM)
Modulation Type	256QAM, 64QAM, 16QAM, BPSK, QPSK
Antenna Type:	Internal Antenna
Antenna Gain:	Band 1: 5.02dBi Band 3: 5.39dBi
Rating(s):	Adapter Information: Model: PSYB0502500 Input: AC 100-240V, 50/60Hz, 0.6A Max Output: DC 5.0V, 2.5A, 12.5W Rechargeable Li-ion Battery DC 7.6V

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. Model(s) list

None.

1.3. Test Frequency

Band 1

20MHz		40MHz		80MHz	
Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180	38	5190	42	5210
40	5200	46	5230		
48	5240				

Band 3

20MHz		40MHz		80MHz	
Channel	Frequency	Channel	Frequency	Channel	Frequency
149	5745	151	5755	155	5775
157	5785	159	5795		
165	5825				

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203	PASS
AC Power Line Conducted Emission	§15.207	PASS
Maximum Conducted Output Power	§15.407(a)	PASS
6dB Emission Bandwidth	§15.407(a)	PASS
26dB Emission Bandwidth & 99% Occupied Bandwidth	§15.407(a)	PASS
Power Spectral Density	§15.407(a)	PASS
Restricted Bands around fundamental frequency	§15.407(b)	PASS
Radiated Emission	§15.407(b)	PASS
Frequency Stability	§15.407(g)	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.
5. For the band 5.15-5.25GHz, EUT meet the requirements of 15.407(a)(ii).

3. General Information

3.1. Test environment and mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar
Test Software:	
Software Information:	Engineering Mode
Power Level:	18
Test Mode:	
Engineer mode:	Keep the EUT in continuous transmitting by select channel and modulations with max. duty cycle.
<p>The sample was placed 0.8m/1.5m for blow/above 1GHz above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.</p>	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	Data rate
802.11a	6 Mbps
802.11n(HT20)	6.5 Mbps
802.11n(HT40)	13.5 Mbps
802.11ac(VHT20)	6.5 Mbps
802.11ac(VHT40)	13.5 Mbps
802.11ac(VHT80)	29.3 Mbps

3.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

4. Facilities and Accreditations

4.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

SHENZHEN TONGCE TESTING LAB

CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

4.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339

4.3. Measurement Uncertainty


The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	± 3.10 dB
2	RF power, conducted	± 0.12 dB
3	Spurious emissions, conducted	± 0.11 dB
4	All emissions, radiated(<1 GHz)	± 4.56 dB
5	All emissions, radiated(1 GHz - 18 GHz)	± 4.22 dB
6	All emissions, radiated(18 GHz- 40 GHz)	± 4.36 dB

5. Test Results and Measurement Data

5.1. Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
<p>15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p>	
E.U.T Antenna:	
<p>The EUT antenna is internal antenna which permanently attached, and the maximum gain of the antenna is 5.39dBi at UNII-B3.</p>	



5.2. Conducted Emission

5.2.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2013														
Frequency Range:	150 kHz to 30 MHz														
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
Limits:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test Setup:	<p><i>Remark</i> E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>														
Test Mode:	Charging + Transmitting Mode														
Test Procedure:	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement. 														
Test Result:	PASS														


5.2.2. Test Instruments

Conducted Emission Shielding Room Test Site (843)				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCI3	100898	Jun. 29, 2024
Line Impedance Stabilisation Newtork(LISN)	Schwarzbeck	NSLK 8126	8126453	Feb. 20, 2024
Line-5	TCT	CE-05	/	Jul. 03, 2024
EMI Test Software	Shurple Technology	EZ-EMC	/	/

5.2.3. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room

Phase: L1

Temperature: 23.5 (°C)

Humidity: 52 %

Limit: FCC Part 15C Conduction(QP)

Power: AC 120 V/60 Hz

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1700	38.82	10.13	48.95	64.96	-16.01	QP	
2		0.1700	22.54	10.13	32.67	54.96	-22.29	AVG	
3		0.3300	38.06	9.95	48.01	59.45	-11.44	QP	
4		0.3300	24.92	9.95	34.87	49.45	-14.58	AVG	
5		0.5899	38.33	9.37	47.70	56.00	-8.30	QP	
6		0.5899	22.47	9.37	31.84	46.00	-14.16	AVG	
7		1.4219	39.92	10.00	49.92	56.00	-6.08	QP	
8		1.4219	22.85	10.00	32.85	46.00	-13.15	AVG	
9	*	16.2900	46.42	10.20	56.62	60.00	-3.38	QP	
10		16.2900	29.64	10.20	39.84	50.00	-10.16	AVG	
11		19.5259	44.89	10.23	55.12	60.00	-4.88	QP	
12		19.5259	30.04	10.23	40.27	50.00	-9.73	AVG	

Note:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard


Margin (dB) = Measurement (dBuV) – Limits (dBuV)

Q.P. =Quasi-Peak

AVG =average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room Phase: **N** Temperature: 23.5 (°C) Humidity: 52 %
Limit: FCC Part 15C Conduction(QP) Power: AC 120 V/60 Hz

No.	Mk.	Freq. MHz	Reading Level dBµV	Correct Factor dB	Measure- ment dBµV	Limit dBµV	Over dB	Detector	Comment
1		0.3579	38.64	9.58	48.22	58.78	-10.56	QP	
2		0.3579	21.62	9.58	31.20	48.78	-17.58	AVG	
3		0.4580	39.53	9.50	49.03	56.73	-7.70	QP	
4		0.4580	20.82	9.50	30.32	46.73	-16.41	AVG	
5		0.7179	37.94	9.25	47.19	56.00	-8.81	QP	
6		0.7179	18.99	9.25	28.24	46.00	-17.76	AVG	
7		1.3540	39.16	10.01	49.17	56.00	-6.83	QP	
8		1.3540	21.43	10.01	31.44	46.00	-14.56	AVG	
9	*	16.1140	46.22	10.28	56.50	60.00	-3.50	QP	
10		16.1140	29.70	10.28	39.98	50.00	-10.02	AVG	
11		19.7700	31.72	10.35	42.07	50.00	-7.93	AVG	
12		19.9900	46.12	10.35	56.47	60.00	-3.53	QP	

Note:

Freq. = Emission frequency in MHz

Reading level (dBµV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBµV) = Reading level (dBµV) + Corr. Factor (dB)

Limit (dBµV) = Limit stated in standard

Margin (dB) = Measurement (dBµV) – Limits (dBµV)

Q.P. =Quasi-Peak


AVG =average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

Measurements were conducted in all three channels (high, middle, low) and all modulation (802.11a, 802.11n(HT20), 802.11n(HT40), 802.11ac(VHT20), 802.11ac(VHT40), 802.11ac(VHT80) and the worst case Mode (Middle channel and 802.11n(HT20) in U-NII Band1) was submitted only.

5.3. Maximum Conducted Output Power

5.3.1. Test Specification


Test Requirement:	FCC Part15 E Section 15.407(a)& Part 2 J Section 2.1046										
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E										
Limit:	<table border="1"> <thead> <tr> <th>Frequency Band (MHz)</th> <th>Limit</th> </tr> </thead> <tbody> <tr> <td>5180 - 5240</td> <td>24dBm(250mW) for client device</td> </tr> <tr> <td>5260 - 5320</td> <td>24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz</td> </tr> <tr> <td>5470 - 5725</td> <td>24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz</td> </tr> <tr> <td>5745 - 5825</td> <td>30dBm(1W)</td> </tr> </tbody> </table>	Frequency Band (MHz)	Limit	5180 - 5240	24dBm(250mW) for client device	5260 - 5320	24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz	5470 - 5725	24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz	5745 - 5825	30dBm(1W)
Frequency Band (MHz)	Limit										
5180 - 5240	24dBm(250mW) for client device										
5260 - 5320	24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz										
5470 - 5725	24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz										
5745 - 5825	30dBm(1W)										
Test Setup:	 <p>The diagram illustrates the test setup. On the left is a green 'Power meter' with a screen and two ports. A cable connects one of its ports to a small white 'attenuator' box. Another cable connects the attenuator to a yellow 'EUT' (Equipment Under Test) box on the right.</p>										
Test Mode:	Transmitting mode with modulation										
Test Procedure:	<ol style="list-style-type: none"> 1. The testing follows the Measurement Procedure of KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E, 3, a 2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 5. Measure the conducted output power and record the results in the test report. 										
Test Result:	PASS										
Remark:	Conducted output power= measurement power +10log(1/x) X is duty cycle=1, so 10log(1/1)=0 Conducted output power= measurement power										

5.3.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 28, 2024
Power Meter	Agilent	E4418B	MY45100357	Jun. 27, 2024
Power Sensor	Agilent	8481A	MY41091497	Jun. 27, 2024
Combiner Box	Ascentest	AT890-RFB	/	/

5.4. 6dB Emission Bandwidth

5.4.1. Test Specification


Test Requirement:	FCC CFR47 Part 15 Section 15.407(e)& Part 2 J Section 2.1049
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C
Limit:	>500kHz
Test Setup:	 <p style="text-align: center;">Spectrum Analyzer EUT</p>
Test Mode:	Transmitting mode with modulation
Test Procedure:	<ol style="list-style-type: none"> 1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. 4. Measure and record the results in the test report.
Test Result:	PASS

5.4.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 28, 2024
Combiner Box	Ascentest	AT890-RFB	/	/

5.5. 26dB Bandwidth and 99% Occupied Bandwidth

5.5.1. Test Specification


Test Requirement:	47 CFR Part 15C Section 15.407 (a)& Part 2 J Section 2.1049
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section D
Limit:	No restriction limits
Test Setup:	 <p style="text-align: center;">Spectrum Analyzer EUT</p>
Test Mode:	Transmitting mode with modulation
Test Procedure:	<ol style="list-style-type: none"> 1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section D 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 1% to 5% of the OBW. Set the Video bandwidth (VBW) = 3 *RBW. In order to make an accurate measurement. 4. Measure and record the results in the test report.
Test Result:	PASS

5.5.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 28, 2024
Combiner Box	Ascentest	AT890-RFB	/	/

5.6. Power Spectral Density

5.6.1. Test Specification

Test Requirement:	FCC Part15 E Section 15.407 (a)
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section F
Limit:	≤11.00dBm/MHz for Band 1 5150MHz-5250MHz(client device) ≤11.00dBm/MHz for Band 2A&2C 5250-5350&5470-5725 ≤30.00dBm/500KHz for Band 3 5725MHz-5850MHz
Test Setup:	 <p style="text-align: center;">Spectrum Analyzer EUT</p>
Test Mode:	Transmitting mode with modulation
Test Procedure:	<ol style="list-style-type: none"> Set the spectrum analyzer or EMI receiver span to view the entire emission bandwidth. Set RBW = 510 kHz/1 MHz, VBW ≥ 3*RBW, Sweep time = Auto, Detector = RMS. Allow the sweeps to continue until the trace stabilizes. Use the peak marker function to determine the maximum amplitude level, record as PSD.
Test Result:	PASS

5.6.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 28, 2024
Combiner Box	Ascentest	AT890-RFB	/	/

5.7. Band edge

5.7.1. Test Specification

Test Requirement:	FCC CFR47 Part 15E Section 15.407																				
Test Method:	ANSI C63.10 2013																				
Limit:	In un-restricted band: For Band 1&2A&2C: -27dBm/MHz For Band 3:																				
	<table border="1"> <thead> <tr> <th>Frequency (MHz)</th> <th>Limit (dBm/MHz)</th> <th>Frequency (MHz)</th> <th>Limit (dBm/MHz)</th> </tr> </thead> <tbody> <tr> <td>< 5650</td> <td>-27</td> <td>5850~5855</td> <td>27~15.6</td> </tr> <tr> <td>5650~5700</td> <td>-27~10</td> <td>5855~5875</td> <td>15.6~10</td> </tr> <tr> <td>5700~5720</td> <td>10~15.6</td> <td>5875~5925</td> <td>10~-27</td> </tr> <tr> <td>5720~5725</td> <td>15.6~27</td> <td>> 5925</td> <td>-27</td> </tr> </tbody> </table>	Frequency (MHz)	Limit (dBm/MHz)	Frequency (MHz)	Limit (dBm/MHz)	< 5650	-27	5850~5855	27~15.6	5650~5700	-27~10	5855~5875	15.6~10	5700~5720	10~15.6	5875~5925	10~-27	5720~5725	15.6~27	> 5925	-27
	Frequency (MHz)	Limit (dBm/MHz)	Frequency (MHz)	Limit (dBm/MHz)																	
	< 5650	-27	5850~5855	27~15.6																	
	5650~5700	-27~10	5855~5875	15.6~10																	
5700~5720	10~15.6	5875~5925	10~-27																		
5720~5725	15.6~27	> 5925	-27																		
E[dBμV/m] = EIRP[dBm] + 95.2 @3m																					
In restricted band:																					
<table border="1"> <thead> <tr> <th>Detector</th> <th>Limit@3m</th> </tr> </thead> <tbody> <tr> <td>Peak</td> <td>74dBμV/m</td> </tr> <tr> <td>AVG</td> <td>54dBμV/m</td> </tr> </tbody> </table>		Detector	Limit@3m	Peak	74dBμV/m	AVG	54dBμV/m														
Detector	Limit@3m																				
Peak	74dBμV/m																				
AVG	54dBμV/m																				
Test Setup:	<p>The diagram illustrates the test setup within an anechoic chamber. An Equipment Under Test (EUT) is placed on a turntable at a height of 1.5m. A horn antenna is mounted on an antenna tower at a distance of 3m from the EUT. The test receiver system, including a Test Receiver, Preamplifier, and Controller, is connected to the antenna. A ground reference plane is also indicated.</p>																				
Test Mode:	Transmitting mode with modulation																				
Test Procedure:	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 																				


	6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasipeak or average method as specified and then reported in a data sheet.
Test Result:	PASS

5.7.2. Test Instruments

Radiated Emission Test Site (966)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESIB7	100197	Jun. 29, 2024
Spectrum Analyzer	R&S	FSQ40	200061	Jun. 29, 2024
Spectrum Analyzer	Agilent	N9020A	MY49100619	Feb. 20, 2024
Pre-amplifier	SKET	LNPA_0118G-45	SK2021012102	Feb. 20, 2024
Pre-amplifier	SKET	LNPA_1840G-50	SK202109203500	Jun. 27, 2024
Pre-amplifier	HP	8447D	2727A05017	Jul. 02, 2024
Loop antenna	Schwarzbeck	FMZB1519B	00191	Jul. 01, 2024
Broadband Antenna	Schwarzbeck	VULB9163	340	Jul. 01, 2024
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Feb. 24, 2024
Horn Antenna	Schwarzbeck	BBHA 9170	00956	Jun. 29, 2024
Coaxial cable	SKET	RC-18G-N-M	/	Feb. 24, 2024
Coaxial cable	SKET	RC_40G-K-M	/	Feb. 24, 2024
Antenna Mast	Keleto	CC-A-4M	/	/
EMI Test Software	Shurple Technology	EZ-EMC	/	/

5.7.3. Test Data


AC20-5180



Site: #3 3m Anechoic Chamber Polarization: **Horizontal** Temperature: 23.9(°C) Humidity: 42 %

Limit: FCC part 15.407 band edge (PK) Power: DC 7.6V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	52.91	-9.78	43.13	74.00	-30.87	peak	P	
2 *	5150.000	45.05	-9.78	35.27	54.00	-18.73	AVG	P	




Site: #3 3m Anechoic Chamber Polarization: **Vertical** Temperature: 23.9(°C) Humidity: 42 %

Limit: FCC part 15.407 band edge (PK) Power: DC 7.6V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	51.41	-9.78	41.63	74.00	-32.37	peak	P	
2 *	5150.000	43.79	-9.78	34.01	54.00	-19.99	AVG	P	


AC20-5240



Site: #3 3m Anechoic Chamber Polarization: **Horizontal** Temperature: 23.9(°C) Humidity: 42 %

Limit: FCC part 15.407 band edge (PK) Power: DC 7.6V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	51.12	-9.27	41.85	74.00	-32.15	peak	P	
2 *	5350.000	42.00	-9.27	32.73	54.00	-21.27	AVG	P	




Site: #3 3m Anechoic Chamber Polarization: **Vertical** Temperature: 23.9(°C) Humidity: 42 %

Limit: FCC part 15.407 band edge (PK) Power: DC 7.6V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	50.11	-9.27	40.84	74.00	-33.16	peak	P	
2 *	5350.000	41.13	-9.27	31.86	54.00	-22.14	AVG	P	


AC40-5190



Site: #3 3m Anechoic Chamber Polarization: **Horizontal** Temperature: 23.9(°C) Humidity: 42 %

Limit: FCC part 15.407 band edge (PK) Power: DC 7.6V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	52.50	-9.78	42.72	74.00	-31.28	peak	P	
2 *	5150.000	45.36	-9.78	35.58	54.00	-18.42	AVG	P	




Site: #3 3m Anechoic Chamber Polarization: **Vertical** Temperature: 23.9(°C) Humidity: 42 %

Limit: FCC part 15.407 band edge (PK) Power: DC 7.6V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	55.20	-9.78	45.42	74.00	-28.58	peak	P	
2 *	5150.000	49.05	-9.78	39.27	54.00	-14.73	AVG	P	


AC40-5230



Site: #3 3m Anechoic Chamber Polarization: **Horizontal** Temperature: 23.9(°C) Humidity: 42 %

Limit: FCC part 15.407 band edge (PK) Power:DC 7.6V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	51.10	-9.27	41.83	74.00	-32.17	peak	P	
2 *	5350.000	44.30	-9.27	35.03	54.00	-18.97	AVG	P	




Site: #3 3m Anechoic Chamber Polarization: **Vertical** Temperature: 23.9(°C) Humidity: 42 %

Limit: FCC part 15.407 band edge (PK) Power:DC 7.6V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	51.20	-9.27	41.93	74.00	-32.07	peak	P	
2 *	5350.000	43.89	-9.27	34.62	54.00	-19.38	AVG	P	


AC80-5210



Site: #3 3m Anechoic Chamber Polarization: **Horizontal** Temperature: 23.9(°C) Humidity: 42 %

Limit: FCC part 15.407 band edge (PK) Power:DC 7.6V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	53.62	-9.78	43.84	74.00	-30.16	peak	P	
2 *	5150.000	46.88	-9.78	37.10	54.00	-16.90	AVG	P	
3	5350.000	50.68	-9.27	41.41	74.00	-32.59	peak	P	
4	5350.000	43.23	-9.27	33.96	54.00	-20.04	AVG	P	




Site: #3 3m Anechoic Chamber Polarization: **Vertical** Temperature: 23.9(°C) Humidity: 42 %

Limit: FCC part 15.407 band edge (PK) Power:DC 7.6V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	58.34	-9.78	48.56	74.00	-25.44	peak	P	
2 *	5150.000	50.53	-9.78	40.75	54.00	-13.25	AVG	P	
3	5350.000	51.37	-9.27	42.10	74.00	-31.90	peak	P	
4	5350.000	44.23	-9.27	34.96	54.00	-19.04	AVG	P	


AC20-5745



Site: #3 3m Anechoic Chamber Polarization: **Horizontal** Temperature: 23.9(°C) Humidity: 42 %

Limit: FCC part 15.407 band edge B3 (PK) Power: DC 7.6V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5623.423	51.85	-8.70	43.15	68.20	-25.05	peak	P	




Site: #3 3m Anechoic Chamber Polarization: **Vertical** Temperature: 23.9(°C) Humidity: 42 %

Limit: FCC part 15.407 band edge B3 (PK) Power: DC 7.6V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5653.604	50.72	-8.45	42.27	70.87	-28.60	peak	P	


AC20-5825



Site: #3 3m Anechoic Chamber Polarization: **Horizontal** Temperature: 23.9(°C) Humidity: 42 %

Limit: FCC part 15.407 band edge B3 (PK) Power: DC 7.6V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5904.895	51.28	-7.51	43.77	83.08	-39.31	peak	P	




Site: #3 3m Anechoic Chamber Polarization: **Vertical** Temperature: 23.9(°C) Humidity: 42 %

Limit: FCC part 15.407 band edge B3 (PK) Power: DC 7.6V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5913.911	51.11	-7.52	43.59	76.41	-32.82	peak	P	


AC40-5755



Site: #3 3m Anechoic Chamber Polarization: **Horizontal** Temperature: 23.9(°C) Humidity: 42 %

Limit: FCC part 15.407 band edge B3 (PK) Power:DC 7.6V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5686.486	52.64	-8.28	44.36	95.20	-50.84	peak	P	




Site: #3 3m Anechoic Chamber Polarization: **Vertical** Temperature: 23.9(°C) Humidity: 42 %

Limit: FCC part 15.407 band edge B3 (PK) Power:DC 7.6V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5680.813	53.59	-8.31	45.28	91.00	-45.72	peak	P	


AC40-5795



Site: #3 3m Anechoic Chamber Polarization: **Horizontal** Temperature: 23.9(°C) Humidity: 42 %

Limit: FCC part 15.407 band edge B3 (PK) Power:DC 7.6V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5894.051	52.70	-7.53	45.17	91.10	-45.93	peak	P	
2 *	5934.220	52.66	-7.54	45.12	68.20	-23.08	peak	P	




Site: #3 3m Anechoic Chamber Polarization: **Vertical** Temperature: 23.9(°C) Humidity: 42 %

Limit: FCC part 15.407 band edge B3 (PK) Power:DC 7.6V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5909.357	52.97	-7.51	45.46	79.78	-34.32	peak	P	


AC80-5775



Site: #3 3m Anechoic Chamber Polarization: **Horizontal** Temperature: 23.9(°C) Humidity: 42 %

Limit: FCC part 15.407 band edge B3 (PK) Power:DC 7.6V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5714.004	56.20	-8.17	48.03	109.12	-61.09	peak	P	




Site: #3 3m Anechoic Chamber Polarization: **Vertical** Temperature: 23.9(°C) Humidity: 42 %

Limit: FCC part 15.407 band edge B3 (PK) Power:DC 7.6V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5711.178	63.12	-8.18	54.94	108.33	-53.39	peak	P	


AC80-5775



Site: #3 3m Anechoic Chamber Polarization: **Horizontal** Temperature: 23.9(°C) Humidity: 42 %

Limit: FCC part 15.407 band edge B3 (PK) Power:DC 7.6V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5899.101	52.77	-7.50	45.27	87.37	-42.10	peak	P	
2 *	5997.368	52.51	-7.59	44.92	68.20	-23.28	peak	P	



Site: #3 3m Anechoic Chamber Polarization: **Vertical** Temperature: 23.9(°C) Humidity: 42 %

Limit: FCC part 15.407 band edge B3 (PK) Power:DC 7.6V


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5907.809	52.69	-7.51	45.18	80.92	-35.74	peak	P	

Note: All modulation (802.11a, 802.11n, 802.11ac) have been tested, only the worst case in 802.11ac be reported.


5.8. Unwanted Emissions

5.8.1. Test Specification

Test Requirement:	FCC CFR47 Part 15 Section 15.407 & 15.209 & 15.205				
Test Method:	KDB 789033 D02 v02r01				
Frequency Range:	9kHz to 40GHz				
Measurement Distance:	3 m				
Antenna Polarization:	Horizontal & Vertical				
Operation mode:	Transmitting mode with modulation				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
Peak		1MHz	10Hz	Average Value	
Limit:	Unwanted spurious emissions fallen in restricted bands per FCC Part15.205 shall comply with the general field strength limits set forth in § 15.209 as below table, In restricted bands:				
	Frequency	Detector	Limit@3m		
	Above 1G	Peak	74dB μ V/m		
		AVG	54dB μ V/m		
	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)		
	0.009-0.490	2400/F(KHz)	300		
	0.490-1.705	24000/F(KHz)	3		
	1.705-30	30	30		
	30-88	100	3		
	88-216	150	3		
216-960	200	3			
Above 960	500	3			
In un-restricted bands: 68.2dB μ V/m					
Test setup:	For radiated emissions below 30MHz				
	<p>Distance = 3m</p> <p>EUT</p> <p>Turn table</p> <p>Ground Plane</p> <p>Computer</p> <p>Pre -Amplifier</p> <p>Receiver</p> <p>1m</p>				
30MHz to 1GHz					



Above 1GHz



Test Procedure:


1. For the radiated emission test below 1GHz:
The EUT was placed on a turntable with 0.8 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.
- For the radiated emission test above 1GHz:
Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
3. Corrected Reading: $\text{Antenna Factor} + \text{Cable Loss} + \text{Read Level} - \text{Preamp Factor} = \text{Level}$
4. For measurement below 1GHz, If the emission level

	<p>of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.</p> <p>5. Use the following spectrum analyzer settings:</p> <ul style="list-style-type: none"> (1) Span shall wide enough to fully capture the emission being measured; (2) Set RBW=120 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold; (3) Set RBW = 1 MHz, VBW= 3MHz for $f > 1$ GHz for peak measurement. <p>For average measurement: VBW = 10 Hz, when duty cycle is no less than 98 percent. VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.</p>
Test results:	PASS

5.8.2. Test Data

Please refer to following diagram for individual
Below 1GHz

Horizontal:



Site: #1 3m Anechoic Chamber

Polarization: **Horizontal**

Temperature: 24.3(C)


Humidity: 50 %

Limit: FCC Part 15C RE_3m

Power: DC 7.6V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	52.5753	7.10	13.37	20.47	40.00	-19.53	QP	P	
2	166.0680	7.41	14.00	21.41	43.50	-22.09	QP	P	
3	291.0360	11.63	13.71	25.34	46.00	-20.66	QP	P	
4	390.7226	10.44	16.14	26.58	46.00	-19.42	QP	P	
5	647.3856	7.65	21.51	29.16	46.00	-16.84	QP	P	
6 *	875.2470	8.03	24.10	32.13	46.00	-13.87	QP	P	

Vertical:



Site: #1 3m Anechoic Chamber

Polarization: **Vertical**

Temperature: 24.3(C) Humidity: 50 %

Limit: FCC Part 15C RE_3m

Power: DC 7.6V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	40.5591	6.57	14.17	20.74	40.00	-19.26	QP	P	
2	45.0583	6.06	13.75	19.81	40.00	-20.19	QP	P	
3	144.3347	7.13	14.08	21.21	43.50	-22.29	QP	P	
4	482.2155	7.58	18.21	25.79	46.00	-20.21	QP	P	
5	656.5300	7.03	21.67	28.70	46.00	-17.30	QP	P	
6 *	938.8326	6.91	24.84	31.75	46.00	-14.25	QP	P	

Note: 1. The low frequency, which started from 9KHz~30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported

2. Measurements were conducted in all three channels (high, middle, low) and all modulation (802.11a, 802.11n(HT20), 802.11n(HT40), 802.11ac(VHT20), 802.11ac(VHT40), 802.11ac(VHT80) and the worst case Mode (Middle channel and 802.11n(HT20) in U-NII Band1) was submitted only.

3. Measurement (dBuV) = Reading level + Correction Factor, correction Factor= Antenna Factor + Cable loss – Pre-amplifier.

Modulation Type: Band 1									
11a CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBµV)	AV reading (dBµV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBµV/m)	AV limit (dBµV/m)	Margin (dB)
					Peak (dBµV/m)	AV (dBµV/m)			
10360	H	38.93	---	8.02	46.95	---	68.2	---	-21.25
15540	H	38.24	---	9.87	48.11	---	74	54	-5.89
---	H	---	---	---	---	---	---	---	---
10360	V	38.49	---	8.02	46.51	---	68.2	---	-21.69
15540	V	38.63	---	9.87	48.5	---	74	54	-5.5
---	V	---	---	---	---	---	---	---	---
11a CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBµV)	AV reading (dBµV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBµV/m)	AV limit (dBµV/m)	Margin (dB)
					Peak (dBµV/m)	AV (dBµV/m)			
10400	H	39.72	---	7.97	47.69	---	68.2	---	-20.51
15600	H	38.04	---	9.83	47.87	---	74	54	-6.13
---	H	---	---	---	---	---	---	---	---
10400	V	40.61	---	7.97	48.58	---	68.2	---	-19.62
15600	V	38.47	---	9.83	48.3	---	74	54	-5.7
---	V	---	---	---	---	---	---	---	---
11a CH48: 5240MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBµV)	AV reading (dBµV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBµV/m)	AV limit (dBµV/m)	Margin (dB)
					Peak (dBµV/m)	AV (dBµV/m)			
10480	H	38.03	---	7.97	46	---	68.2	---	-22.2
15720	H	37.89	---	9.83	47.72	---	74	54	-6.28
---	H	---	---	---	---	---	---	---	---
10480	V	38.57	---	7.97	46.54	---	68.2	---	-21.66
15720	V	36.34	---	9.83	46.17	---	74	54	-7.83
---	V	---	---	---	---	---	---	---	---
11n(HT20) CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBµV)	AV reading (dBµV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBµV/m)	AV limit (dBµV/m)	Margin (dB)
					Peak (dBµV/m)	AV (dBµV/m)			
10360	H	41.65	---	8.02	49.67	---	68.2	---	-18.53
15540	H	37.92	---	9.87	47.79	---	74	54	-6.21
---	H	---	---	---	---	---	---	---	---
10360	V	42.13	---	8.02	50.15	---	68.2	---	-18.05
15540	V	37.44	---	9.87	47.31	---	74	54	-6.69
---	V	---	---	---	---	---	---	---	---

11n(HT20) CH40: 5200MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	40.62	---	7.97	48.59	---	68.2	---	-19.61
15600	H	38.41	---	9.83	48.24	---	74	54	-5.76
---	H	---	---	---	---	---	---	---	---
10400	V	40.79	---	7.97	48.76	---	68.2	---	-19.44
15600	V	37.24	---	9.83	47.07	---	74	54	-6.93
---	V	---	---	---	---	---	---	---	---

11n(HT20) CH48: 5240MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	41.18	---	7.97	49.15	---	68.2	---	-19.05
15720	H	39.86	---	9.83	49.69	---	74	54	-4.31
---	H	---	---	---	---	---	---	---	---
10480	V	40.23	---	7.97	48.2	---	68.2	---	-20
15720	V	39.04	---	9.83	48.87	---	74	54	-5.13
---	V	---	---	---	---	---	---	---	---

11n(HT40) CH38: 5190MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10380	H	39.25	---	7.75	47	---	68.2	---	-21.2
15570	H	37.78	---	9.87	47.65	---	74	54	-6.35
---	H	---	---	---	---	---	---	---	---
10380	V	40.67	---	7.75	48.42	---	68.2	---	-19.78
15570	V	37.43	---	9.87	47.3	---	74	54	-6.7
---	V	---	---	---	---	---	---	---	---

11n(HT40) CH46: 5230MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10460	H	41.53	---	7.97	49.5	---	68.2	---	-18.7
15690	H	38.65	---	9.83	48.48	---	74	54	-5.52
---	H	---	---	---	---	---	---	---	---
10460	V	41.84	---	7.97	49.81	---	68.2	---	-18.39
15690	V	38.29	---	9.83	48.12	---	74	54	-5.88
---	V	---	---	---	---	---	---	---	---

11ac(VHT20) CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10360	H	40.14	---	8.02	48.16	---	68.2	---	-20.04
15540	H	37.43	---	9.87	47.3	---	74	54	-6.7
---	H	---	---	---	---	---	---	---	---
10360	V	38.68	---	8.02	46.7	---	68.2	---	-21.5
15540	V	39.82	---	9.87	49.69	---	74	54	-4.31
---	V	---	---	---	---	---	---	---	---

11ac(VHT20) CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	39.77	---	7.97	47.74	---	68.2	---	-20.46
15600	H	38.11	---	9.83	47.94	---	74	54	-6.06
---	H	---	---	---	---	---	---	---	---
10400	V	39.22	---	7.97	47.19	---	68.2	---	-21.01
15600	V	38.43	---	9.83	48.26	---	74	54	-5.74
---	V	---	---	---	---	---	---	---	---

11ac(VHT20) CH48:5240									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	37.04	---	7.97	45.01	---	68.2	---	-23.19
15720	H	37.61	---	9.83	47.44	---	74	54	-6.56
---	H	---	---	---	---	---	---	---	---
10480	V	38.58	---	7.97	46.55	---	68.2	---	-21.65
15720	V	38.13	---	9.83	47.96	---	74	54	-6.04
---	V	---	---	---	---	---	---	---	---

11ac(VHT40) CH38:5190									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10380	H	40.83	---	7.75	48.58	---	68.2	---	-19.62
15570	H	39.22	---	9.87	49.09	---	74	54	-4.91
---	H	---	---	---	---	---	---	---	---
10380	V	38.64	---	7.75	46.39	---	68.2	---	-21.81
15570	V	38.47	---	9.87	48.34	---	74	54	-5.66
---	V	---	---	---	---	---	---	---	---

11ac(VHT40) CH46:5230									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10460	H	38.54	---	7.97	46.51	---	68.2	---	-21.69
15690	H	38.02	---	9.83	47.85	---	74	54	-6.15
---	H	---	---	---	---	---	---	---	---
10460	V	39.19	---	7.97	47.16	---	68.2	---	-21.04
15690	V	37.33	---	9.83	47.16	---	74	54	-6.84
---	V	---	---	---	---	---	---	---	---
11ac(VHT80) CH42:5210									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10420	H	41.64	---	7.96	49.6	---	68.2	---	-18.6
15630	H	39.12	---	9.84	48.96	---	74	54	-5.04
---	H	---	---	---	---	---	---	---	---
10420	V	41.23	---	7.96	49.19	---	68.2	---	-19.01
15630	V	39.59	---	9.84	49.43	---	74	54	-4.57
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 40GHz.
5. Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

Modulation Type: Band 3									
11a CH149: 5745MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11490	H	37.43	---	8.09	45.52	---	74	54	-8.48
17235	H	37.15	---	9.67	46.82	---	68.2	---	-21.38
---	H	---	---	---	---	---	---	---	---
11490	V	40.56	---	8.09	48.65	---	74	54	-5.35
17235	V	38.61	---	9.67	48.28	---	68.2	---	-19.92
---	V	---	---	---	---	---	---	---	---
11a CH157: 5785MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11570	H	39.88	---	8.10	47.98	---	74	54	-6.02
17355	H	38.17	---	9.65	47.82	---	68.2	---	-20.38
---	H	---	---	---	---	---	---	---	---
11570	V	38.69	---	8.10	46.79	---	74	54	-7.21
17355	V	39.42	---	9.65	49.07	---	68.2	---	-19.13
---	V	---	---	---	---	---	---	---	---
11a CH165: 5825MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11650	H	37.14	---	8.12	45.26	---	74	54	-8.74
17475	H	36.47	---	9.62	46.09	---	68.2	---	-22.11
---	H	---	---	---	---	---	---	---	---
11650	V	38.55	---	8.12	46.67	---	74	54	-7.33
17475	V	38.21	---	9.62	47.83	---	68.2	---	-20.37
---	V	---	---	---	---	---	---	---	---
11n(HT20) CH149: 5745MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11490	H	38.66	---	8.09	46.75	---	74	54	-7.25
17235	H	38.54	---	9.67	48.21	---	68.2	---	-19.99
---	H	---	---	---	---	---	---	---	---
11490	V	39.48	---	8.09	47.57	---	74	54	-6.43
17235	V	37.22	---	9.67	46.89	---	68.2	---	-21.31
---	V	---	---	---	---	---	---	---	---

11n(HT20) CH157: 5785MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11570	H	38.94	---	8.10	47.04	---	74	54	-6.96
17355	H	39.42	---	9.65	49.07	---	68.2	---	-19.13
---	H	---	---	---	---	---	---	---	---
11570	V	38.27	---	8.10	46.37	---	74	54	-7.63
17355	V	39.09	---	9.65	48.74	---	68.2	---	-19.46
---	V	---	---	---	---	---	---	---	---
11n(HT20) CH165: 5825MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11650	H	38.53	---	8.12	46.65	---	74	54	-7.35
17475	H	37.2	---	9.62	46.82	---	68.2	---	-21.38
---	H	---	---	---	---	---	---	---	---
11650	V	38.67	---	8.12	46.79	---	74	54	-7.21
17475	V	39.11	---	9.62	48.73	---	68.2	---	-19.47
---	V	---	---	---	---	---	---	---	---
11n(HT40) CH151: 5755MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11510	H	40.58	---	8.09	48.67	---	74	54	-5.33
17265	H	37.19	---	9.67	46.86	---	68.2	---	-21.34
---	H	---	---	---	---	---	---	---	---
11510	V	41.92	---	8.09	50.01	---	74	54	-3.99
17265	V	38.47	---	9.67	48.14	---	68.2	---	-20.06
---	V	---	---	---	---	---	---	---	---
11n(HT40) CH159: 5795MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11590	H	38.17	---	8.10	46.27	---	74	54	-7.73
17385	H	38.64	---	9.65	48.29	---	68.2	---	-19.91
---	H	---	---	---	---	---	---	---	---
11590	V	38.58	---	8.10	46.68	---	74	54	-7.32
17385	V	37.33	---	9.65	46.98	---	68.2	---	-21.22
---	V	---	---	---	---	---	---	---	---

11ac(VHT20) CH149: 5745MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11490	H	40.62	---	8.09	48.71	---	74	54	-5.29
17235	H	37.11	---	9.67	46.78	---	68.2	---	-21.42
---	H	---	---	---	---	---	---	---	---
11490	V	40.73	---	8.09	48.82	---	74	54	-5.18
17235	V	38.59	---	9.67	48.26	---	68.2	---	-19.94
---	V	---	---	---	---	---	---	---	---

11ac(VHT20) CH157: 5785MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11570	H	38.07	---	8.10	46.17	---	74	54	-7.83
17355	H	36.25	---	9.65	45.9	---	68.2	---	-22.3
---	H	---	---	---	---	---	---	---	---
11570	V	37.81	---	8.10	45.91	---	74	54	-8.09
17355	V	38.14	---	9.65	47.79	---	68.2	---	-20.41
---	V	---	---	---	---	---	---	---	---

11ac(VHT20) CH165: 5825MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11650	H	40.36	---	8.12	48.48	---	74	54	-5.52
17475	H	38.93	---	9.62	48.55	---	68.2	---	-19.65
---	H	---	---	---	---	---	---	---	---
11650	V	38.69	---	8.12	46.81	---	74	54	-7.19
17475	V	39.48	---	9.62	49.1	---	68.2	---	-19.1
---	V	---	---	---	---	---	---	---	---

11ac(VHT40) CH151: 5755MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11510	H	39.74	---	8.09	47.83	---	74	54	-6.17
17265	H	37.27	---	9.67	46.94	---	68.2	---	-21.26
---	H	---	---	---	---	---	---	---	---
11510	V	40.55	---	8.09	48.64	---	74	54	-5.36
17265	V	36.18	---	9.67	45.85	---	68.2	---	-22.35
---	V	---	---	---	---	---	---	---	---

11ac(VHT40) CH159: 5795MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11590	H	40.24	---	8.10	48.34	---	74	54	-5.66
17385	H	37.81	---	9.65	47.46	---	68.2	---	-20.74
---	H	---	---	---	---	---	---	---	---
11590	V	39.75	---	8.10	47.85	---	74	54	-6.15
17385	V	38.12	---	9.65	47.77	---	68.2	---	-20.43
---	V	---	---	---	---	---	---	---	---
11ac(VHT80) CH155: 5775MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11550	H	40.37	---	8.09	48.46	---	74	54	-5.54
17325	H	38.98	---	9.66	48.64	---	68.2	---	-19.56
---	H	---	---	---	---	---	---	---	---
11550	V	41.26	---	8.09	49.35	---	74	54	-4.65
17325	V	38.03	---	9.66	47.69	---	68.2	---	-20.51
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 40GHz.
5. Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

5.9. Frequency Stability Measurement

5.9.1. Test Specification

Test Requirement:	FCC Part15 Section 15.407(g) &Part2 J Section 2.1055
Test Method:	ANSI C63.10: 2013
Limit:	The frequency tolerance shall be maintained within the band of operation frequency over a temperature variation of 0 degrees to 45 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.
Test Setup:	<pre> graph LR SA[Spectrum Analyzer] --- EUT[EUT] subgraph TC [Temperature Chamber] EUT end P[AC/DC Power supply] --- EUT </pre>
Test Procedure:	The EUT was placed inside the environmental test chamber and powered by nominal AC/DC voltage. b. Turn the EUT on and couple its output to a spectrum analyzer. c. Turn the EUT off and set the chamber to the highest temperature specified. d. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. e. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature. f. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.
Test Result:	PASS
Remark:	Pre-scan was performed at all models(11a,11n,11ac), the worst case (11ac) was found and test data was shown in this report.

Test plots as follows:

Test mode:		802.11ac(HT20)	Frequency(MHz):	5180
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	7.6V	5180	0	PASS
35		5180.02	20000	PASS
25		5180	0	PASS
15		5180	0	PASS
5		5180.02	20000	PASS
0		5180	0	PASS
25	6.8V	5180	0	PASS
	7.6V	5180	0	PASS
	8.4V	5180	0	PASS

Test mode:		802.11ac(HT20)	Frequency(MHz):	5200
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	7.6V	5200.02	20000	PASS
35		5200	0	PASS
25		5200.02	20000	PASS
15		5200	0	PASS
5		5200.02	20000	PASS
0		5200	0	PASS
25	6.8V	5200	0	PASS
	7.6V	5199.98	-20000	PASS
	8.4V	5200.02	20000	PASS

Test mode:		802.11ac(HT20)	Frequency(MHz):	5240
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	7.6V	5240	0	PASS
35		5239.98	-20000	PASS
25		5239.98	-20000	PASS
15		5239.96	-40000	PASS
5		5240	0	PASS
0		5239.98	-20000	PASS
25	6.8V	5240	0	PASS
	7.6V	5240	0	PASS
	8.4V	5240	0	PASS

Test mode:		802.11ac(HT20)	Frequency(MHz):	5745
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	7.6V	5744.98	-20000	PASS
35		5745	0	PASS
25		5745	0	PASS
15		5745	0	PASS
5		5745	0	PASS
0		5745	0	PASS
25		6.8V	5745	0
	7.6V	5745	0	PASS
	8.4V	5745.02	20000	PASS

Test mode:		802.11ac(HT20)	Frequency(MHz):	5785
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	7.6V	5785	0	PASS
35		5785	0	PASS
25		5785	0	PASS
15		5785	0	PASS
5		5784.98	-20000	PASS
0		5785	0	PASS
25		6.8V	5784.98	-20000
	7.6V	5784.98	-20000	PASS
	8.4V	5785.02	20000	PASS

Test mode:		802.11ac(HT20)	Frequency(MHz):	5825
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	7.6V	5825.02	20000	PASS
35		5825	0	PASS
25		5825	0	PASS
15		5825.02	20000	PASS
5		5825.02	20000	PASS
0		5825.02	20000	PASS
25		6.8V	5825	0
	7.6V	5825	0	PASS
	8.4V	5824.98	-20000	PASS

Test mode:		802.11ac(HT40)	Frequency(MHz):	5190
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	7.6V	5190	0	PASS
35		5190.04	40000	PASS
25		5190	0	PASS
15		5190	0	PASS
5		5190	0	PASS
0		5190	0	PASS
25		6.8V	5190.04	40000
	7.6V	5190	0	PASS
	8.4V	5190	0	PASS

Test mode:		802.11ac(HT40)	Frequency(MHz):	5230
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	7.6V	5229.96	-40000	PASS
35		5229.96	-40000	PASS
25		5229.96	-40000	PASS
15		5230	0	PASS
5		5230	0	PASS
0		5230	0	PASS
25		6.8V	5229.96	-40000
	7.6V	5229.96	-40000	PASS
	8.4V	5230	0	PASS

Test mode:		802.11ac(HT40)	Frequency(MHz):	5755
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	7.6V	5755	0	PASS
35		5755	0	PASS
25		5755	0	PASS
15		5755	0	PASS
5		5755	0	PASS
0		5755	0	PASS
25		6.8V	5755	0
	7.6V	5755	0	PASS
	8.4V	5755	0	PASS

Test mode:		802.11ac(HT40)	Frequency(MHz):	5795
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	7.6V	5795	0	PASS
35		5795	0	PASS
25		5795	0	PASS
15		5795	0	PASS
5		5795	0	PASS
0		5795.04	40000	PASS
25		6.8V	5795	0
	7.6V	5795	0	PASS
	8.4V	5795	0	PASS

Test mode:		802.11ac(VHT80)	Frequency(MHz):	5210
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	7.6V	5210	0	PASS
35		5210	0	PASS
25		5210	0	PASS
15		5210	0	PASS
5		5210	0	PASS
0		5210	0	PASS
25		6.8V	5210	0
	7.6V	5209.92	-80000	PASS
	8.4V	5210	0	PASS


Test mode:		802.11ac(VHT80)	Frequency(MHz):	5775
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	7.6V	5775	0	PASS
35		5775	0	PASS
25		5775	0	PASS
15		5775	0	PASS
5		5775	0	PASS
0		5775	0	PASS
25		6.8V	5775	0
	7.6V	5775	0	PASS
	8.4V	5775	0	PASS

Appendix A: Test Result of Conducted Test


Duty Cycle



Condition	Mode	Frequency (MHz)	Duty Cycle (%)
NVNT	a	5180	100
NVNT	a	5200	100
NVNT	a	5240	100
NVNT	n20	5180	100
NVNT	n20	5200	100
NVNT	n20	5240	100
NVNT	n40	5190	100
NVNT	n40	5230	100
NVNT	ac20	5180	100
NVNT	ac20	5200	100
NVNT	ac20	5240	100
NVNT	ac40	5190	100
NVNT	ac40	5230	100
NVNT	ac80	5210	100
NVNT	a	5745	100
NVNT	a	5785	100
NVNT	a	5825	100
NVNT	n20	5745	100
NVNT	n20	5785	100
NVNT	n20	5825	100
NVNT	n40	5755	100
NVNT	n40	5795	100
NVNT	ac20	5745	100
NVNT	ac20	5785	100
NVNT	ac20	5825	100
NVNT	ac40	5755	100
NVNT	ac40	5795	100
NVNT	ac80	5775	100



Test Graphs Duty Cycle NVNT a 5180MHz





Duty Cycle NVNT a 5200MHz












Duty Cycle NVNT ac20 5180MHz




Duty Cycle NVNT ac20 5200MHz







Duty Cycle NVNT ac20 5240MHz







Duty Cycle NVNT ac40 5190MHz




























Maximum Conducted Output Power


Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	a	5180	13.49	24	Pass
NVNT	a	5200	13.58	24	Pass
NVNT	a	5240	11.63	24	Pass
NVNT	n20	5180	13.06	24	Pass
NVNT	n20	5200	13.96	24	Pass
NVNT	n20	5240	11.78	24	Pass
NVNT	n40	5190	13.18	24	Pass
NVNT	n40	5230	12.44	24	Pass
NVNT	ac20	5180	13.05	24	Pass
NVNT	ac20	5200	13.89	24	Pass
NVNT	ac20	5240	11.27	24	Pass
NVNT	ac40	5190	13.31	24	Pass
NVNT	ac40	5230	12.23	24	Pass
NVNT	ac80	5210	13.21	24	Pass
NVNT	a	5745	11.77	30	Pass
NVNT	a	5785	12.21	30	Pass
NVNT	a	5825	11.66	30	Pass
NVNT	n20	5745	11.72	30	Pass
NVNT	n20	5785	11.86	30	Pass
NVNT	n20	5825	11.16	30	Pass
NVNT	n40	5755	11.8	30	Pass
NVNT	n40	5795	12.01	30	Pass
NVNT	ac20	5745	11.39	30	Pass
NVNT	ac20	5785	11.65	30	Pass
NVNT	ac20	5825	10.9	30	Pass
NVNT	ac40	5755	11.6	30	Pass
NVNT	ac40	5795	11.72	30	Pass
NVNT	ac80	5775	11.74	30	Pass



Test Graphs



Power NVNT a 5180MHz




Power NVNT a 5200MHz












Power NVNT n40 5190MHz




Power NVNT n40 5230MHz












Power NVNT ac40 5230MHz




Power NVNT ac80 5210MHz









Power NVNT n20 5785MHz




Power NVNT n20 5825MHz







Power NVNT n40 5755MHz




Power NVNT n40 5795MHz








Power NVNT ac40 5795MHz



Power NVNT ac80 5775MHz




-26dB Bandwidth


Condition	Mode	Frequency (MHz)	-26 dB Bandwidth (MHz)	Verdict
NVNT	a	5180	20.254	Pass
NVNT	a	5200	20.220	Pass
NVNT	a	5240	20.353	Pass
NVNT	n20	5180	20.623	Pass
NVNT	n20	5200	20.606	Pass
NVNT	n20	5240	20.457	Pass
NVNT	n40	5190	41.328	Pass
NVNT	n40	5230	40.946	Pass
NVNT	ac20	5180	20.334	Pass
NVNT	ac20	5200	20.199	Pass
NVNT	ac20	5240	20.447	Pass
NVNT	ac40	5190	40.615	Pass
NVNT	ac40	5230	40.708	Pass
NVNT	ac80	5210	78.076	Pass



Test Graphs

-26dB Bandwidth NVNT a 5180MHz




-26dB Bandwidth NVNT a 5200MHz







-26dB Bandwidth NVNT n20 5200MHz



-26dB Bandwidth NVNT n20 5240MHz



-26dB Bandwidth NVNT n40 5190MHz



-26dB Bandwidth NVNT n40 5230MHz

