

Hybrid Electronic Steering Terminal

Model : HSA-FUF

FCCID : 2AUBBHSA-FUF

Name: KoalaWin

Scan Type: Hybrid Electronic
Steering

EIRP: 44.7dBW@ 0°

TX LO: 12.8GHz

TX Frequency: 14~14.50GHz

POL: Full Polarization ,
Automatic Switching

Tracking Accuracy: $\leq 0.2^\circ$

Modem: XXXXX

WiFi/PWD: XXXXX

S/N: XXXXXXXXXXXXXXX

Types of Application: Fixed

Mechanical Steering Type: Auto

Frequency Band: Ku

Beam Switching Time: $\leq 3\text{ms}$

G/T: 9.5dB/K@ 0°

RX LO: 9.75/10.6GHz

WEB IP/User/PWD: XXXXX



This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) This device must accept any interference received, including interference that may cause undesired operation.

StarWin China Starwin Science & Technology Co., Ltd

PWR LAN RX TX SYS ON/OFF

Hybrid Electronic Steering Terminal

Model : HSA-FUF	SIN: XXXXXXXXXXXXX
FCCID : 2AUBBHSA-FUF	Types of Application: Fixed
Name: KoalaWin	Mechanical Steering Type: Auto
Scan Type: Hybrid Electronic Steering	Frequency Band: Ku
EIRP: 44.7 dBW@0°	Beam Switching Time: ≤3ms
TX LO: 12.8GHz	GI: 9.5dB/K@0°
TX Frequency: 14~14.5GHz	RX LO: 9.75/10.6GHz
POL: Full Polarization , Automatic Switching	WEB IP / User / PWD: XXXXX
Tracking Accuracy: ≤0.2°	 FC CE
Modem: XXXXX	
WiFi / PWD: XXXXX	

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) This device may not cause harmful interference, and
(2) This device must accept any interference received, including interference that may cause undesired operation.

StarWin China Starwin Science & Technology Co., Ltd