

Hybrid Electronic Steering Terminal

Model : ESA-IOT-Ka

FCCID : 2AUBBHSA-MAC

Scan Type: Hybrid Electronic
Steering

EIRP: 48.7dBW@ 0°

TX Frequency: 29.25~30GHz

POL: Full Polarization ,
Automatic Switching

Tracking Accuracy: $\leq 0.2^\circ$

Modem: XXXXX

WiFi/PWD: XXXXX

S/N: XXXXXXXXXXXXXXX

Types of Application: Fixed

Mechanical Steering Type: Auto

Frequency Band: Ka

Beam Switching Time: $\leq 3\text{ms}$

G/T: 11.4dB/K@ 0°

RX LO: 18.25/19.25 GHz

WEB IP/User/PWD: XXXXX



This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) This device must accept any interference received, including interference that may cause undesired operation.

StarWin China Starwin Science & Technology Co., Ltd

PWR LAN RX TX SYS ON/OFF

Hybrid Electronic Steering Terminal

Model: ESA-IOT-Ka	S/N: XXXXXXXXXXXX
FCCID: 2AUBBHS-MAC	Types of Application: Fixed
Scan Type: Hybrid Electronic Steering	Mechanical Steering Type: Auto
EIRP: 18.7dBW@0°	Frequency Band: Ka
TX Frequency: 29.25-30GHz	Beam Switching Time: ≤3ms
POL: Full Polarization , Automatic Switching	GT: 11.4dB/K@0°
Tracking Accuracy: ≤0.2°	RX LO: 18.25/19.25 GHz
Modem: XXXXX	WEB IP/User/PWD: XXXXX
WiFi/PWD: XXXXX	



This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) This device may not cause harmful interference, and
(2) This device must accept any interference received, including interference that may cause undesired operation.

StarWin China Starwin Science & Technology Co., Ltd