

Full Dimension Electronic Steering Terminal

Model :ESA-MAC

FCCID : 2AUBBHSA-MAC

Scan Type: Full Dimensional
Electronic Steering

EIRP:48.7dBW@ 0°

TX Frequency: 29.25~30GHz

POL: Full Polarization ,
Automatic Switching

Tracking Accuracy: $\leq 0.2^\circ$

Modem: XXXXX

WiFi/PWD: XXXXX

S/N: XXXXXXXXXXXXXXX

Types of Application: COTM

Mechanical Steering Type: NONE

Frequency Band: Ka

Beam Switching Time: $\leq 3\text{ms}$

G/T: 11.4dB/K@ 0°

RX LO: 18.25/19.25 GHz

WEB IP/User/PWD: XXXXX



This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) This device must accept any interference received, including interference that may cause undesired operation.

StarWin China Starwin Science & Technology Co., Ltd

Full Dimension Electronic Steering Terminal

Model : ESA-MAC
FCCID : 2AUBBHSA-MAC

Scan Type: Full Dimensional
Electronic Steering

EIRP: 48.7dBW@0°

TX Frequency: 29.25~30GHz

POL: Full Polarization ,

Automatic Switching

Tracking Accuracy: $\leq 0.2^\circ$

Modem: XXXXX

WiFi/PWD: XXXXX

S/N: XXXXXXXXXXXXX

Types of Application: COTM

Mechanical Steering Type: NONE

Frequency Band: Ka

Beam Switching Time: $\leq 3\text{ms}$

G/T: 11.4dB/K@0°

RX LO: 18.25/19.25 GHz

WEB IP/User/PWD: XXXXX



FC CE

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) This device may not cause harmful interference, and
(2) This device must accept any interference received, including interference that may cause undesired operation.

StarWin China Starwin Science & Technology Co., Ltd