## **Maximum Permissible Exposure**

FCC ID: 2AUCLLD-1001
Product: Linxdot Hotspot
Model: LD-1001

## Applicable Standard

According to §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Remark: 1) **For BT:** The maximum output power for antenna is 5.14dBm (3.27mW) at 2480MHz, 3.2dBi antenna gain(with 2.09 numeric antenna gain.)

**For WIFI:** The maximum output power for antenna is 14.23dBm (26.49mW) at 2462MHz, 3.2dBi antenna gain(with 2.09 numeric antenna gain.)

**For LoRa-DSS:** The maximum output power for antenna is 10.27dBm (10.64mW) at 908.7MHz, 2dBi antenna gain(with 1.58 numeric antenna gain.)

**For LoRa-DTS:** The maximum output power for antenna is 10.57dBm (11.40mW) at 927.5MHz, 2dBi antenna gain(with 1.58 numeric antenna gain.)

2) For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20cm, even if the calculation indicate that the MPE distance would be lesser.

## Calculation

Given  $E = \sqrt{\frac{30 \times P \times G}{d}}$  &  $S = \frac{E^2}{3770}$ 

Where E = Field Strength in Volts / meter

P = Power in Watts

G=Numeric antenna gain

d=Distance in meters

S=Power Density in milliwatts / square centimeter

Substituting the MPE safe distance using d=20cm into above equation.

Yields: S=0.000199\*P\*G

Mode	Power(mW)	numeric antenna gain	Power density (mW/cm²)	Limit (mW/cm²)	Result
ВТ	3.27	2.09	0.001360	1.0	PASS
WIFI	26.49	2.09	0.011017		
LoRa-DTS	10.64	1.58	0.003345		
LoRa-DSS	11.40	1.58	0.003584		

The device contain transmitters (BT & LoRa-DTS BT & LoRa-DSS WIFI & LoRa-DTS W

Maximum Emissions Level						
Mode	Power density (mW/cm²)	Limit (mW/cm²)	Result			
BT& LoRa-DTS	0.004705	1.0	Pass			
BT & LoRa-DSS	0.004944	1.0	Pass			
WIFI & LoRa-DTS	0.014362	1.0	Pass			
WIFI & LoRa-DSS	0.014601	1.0	Pass			

Result:

Base on the calculation value, No SAR measurement is required.