



Maximum Permissible Exposure Evaluation

FCC ID: 2AUDF-CG62X

1. Client Information

| | | |
|---------------------|---|---|
| Applicant | : | Shenzhen ADDX Innovation Technology co., LTD. |
| Address | : | NO. 2902, Building 9A-1. Shenzhen Bay Technology and Ecological Park, Nanshan District, Shenzhen, China |
| Manufacturer | : | Shenzhen ADDX Innovation Technology co., LTD. |
| Address | : | NO. 2902, Building 9A-1. Shenzhen Bay Technology and Ecological Park, Nanshan District, Shenzhen, China |

2. General Description of EUT

| | | |
|-------------------------------|---|--|
| EUT Name | : | Smart Battery Camera |
| Models No. | : | CG6, CG3A |
| Model Difference | : | All these models are identical in the same PCB, layout and electrical circuit, the only difference is appearance. |
| Sample ID | : | RW-C-202305-0271-11-1#&RW-C-202305-0271-11-2# |
| Product Description | : | Operation Frequency: Bluetooth 5.0(BLE): 2402MHz~2480MHz 802.11b/g/n(HT20): 2412MHz~2462MHz |
| Power Rating | : | Input: DC 5V DC 3.7V by 5000mAh 18.5Wh Rechargeable Li-ion battery (FXN) DC 3.7V by 5200mAh 19.24Wh Rechargeable Li-ion battery (PX) |
| Software Version | : | V0.6.1 |
| Hardware Version | : | CG623B_C02_V2 |
| Connecting I/O Port(S) | : | Please refer to the User's Manual |
| Remark | : | the MPE report used the EUT-2(RW-C-202305-0271-11-2#). |

MPE Calculations

1. Antenna Gain:

| Antenna | Brand | Model Name | Type | Antenna Gain(dBi) |
|-----------|-------|------------|------|-------------------|
| Bluetooth | N/A | N/A | PCB | 0.5 |

| Antenna | Brand | Model Name | Type | Antenna Gain(dBi) |
|-----------|-------|------------|----------|-------------------|
| 2.4G WIFI | N/A | N/A | Internal | -2.48 |

2. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = (PG) / 4\pi R^2$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

4. Simultaneous transmission MPE Considerations

According to KDB447498: All transmitters and antennas in the host must be either evaluated for MPE compliance, by measurement or computational modeling, or qualify for the standalone MPE test exclusion in section 7.1. Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 .

This means that:

$$\sum \text{ of MPE ratios } \leq 1.0$$



5. Standalone MPE Evaluation:

| Bluetooth Worst Maximum MPE Result | | | | | | | | |
|------------------------------------|-----------------|-------------|----------------------------|--------------------|-----------------------------|--------------------|-------------------|--|
| Mode | N _{TX} | Freq. (MHz) | Conducted Power(max) (dBm) | Turn-up Power (dB) | Max tune up power (dBm) [P] | ANT Gain (dBi) [G] | Distance (cm) [R] | Power Density (mW/ cm ²) [S] |
| GFSK | 1 | 2402 | -5.68 | -5±1 | -4 | 0.5 | 20 | 0.00009 |
| | | 2440 | -6.35 | -6±1 | -5 | 0.5 | 20 | 0.00007 |
| | | 2480 | -6.94 | -6±1 | -5 | 0.5 | 20 | 0.00007 |

Note:
 N_{TX}= Number of Transmit Antennas
 RF Output power specifies that Maximum Conducted Peak Output Power.

| 2.4G WiFi Worst Maximum MPE Result | | | | | | | | |
|------------------------------------|-----------------|-------------|----------------------------|--------------------|-----------------------------|--------------------|-------------------|--|
| Mode | N _{TX} | Freq. (MHz) | Conducted Power(max) (dBm) | Turn-up Power (dB) | Max tune up power (dBm) [P] | ANT Gain (dBi) [G] | Distance (cm) [R] | Power Density (mW/ cm ²) [S] |
| 802.11b | 1 | 2412 | 15.01 | 15±1 | 16 | -2.48 | 20 | 0.00447 |
| | | 2437 | 14.89 | 14±1 | 15 | -2.48 | 20 | 0.00355 |
| | | 2462 | 14.35 | 14±1 | 15 | -2.48 | 20 | 0.00355 |
| 802.11g | 1 | 2412 | 16.11 | 16±1 | 17 | -2.48 | 20 | 0.00563 |
| | | 2437 | 16.26 | 16±1 | 17 | -2.48 | 20 | 0.00563 |
| | | 2462 | 16.92 | 16±1 | 17 | -2.48 | 20 | 0.00563 |
| 802.11n (HT20) | 1 | 2412 | 13.15 | 13±1 | 14 | -2.48 | 20 | 0.00282 |
| | | 2437 | 13.03 | 13±1 | 14 | -2.48 | 20 | 0.00282 |
| | | 2462 | 13.86 | 13±1 | 14 | -2.48 | 20 | 0.00282 |

Note:
 N_{TX}= Number of Transmit Antennas
 RF Output power specifies that Maximum Conducted Peak Output Power.



Remark:

1. Output power including turn-up tolerance;
2. Output power was adjust to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.
4. Only the worst power was evaluated for each wireless function

6. Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

Limits for General Population/ Uncontrolled Exposure

| Frequency Range (MHz) | Power density (mW/ cm ²) |
|-----------------------|--------------------------------------|
| 300-1,500 | F/1500 |
| 1,500-100,000 | 1.0 |

7. Summary simultaneous transmission information

The sample supports two antennas for Bluetooth and WLAN. The Bluetooth and WLAN can transmit simultaneous. The Bluetooth and WLAN with two different antenna. According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;
 \sum of MPE ratios ≤ 1.0

8. Summary simultaneous transmission results

Bluetooth + 2.4G Wifi Maximum Simultaneous transmission MPE Ratios is
 $0.00009+0.00563=0.00572 \leq 1.0$.

9. Conclusion:

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----END OF THE REPORT-----

