



# Maximum Permissible Exposure Evaluation

**FCC ID: 2AUDF-CG923X**

## 1. Client Information

<b>Applicant</b>	:	Shenzhen ADDX Innovation Technology co., LTD.
<b>Address</b>	:	NO.2902,Building 9A-1.Shenzhen Bay Technology and Ecological Park ,Nanshan District,Shenzhen, China
<b>Manufacturer</b>	:	Shenzhen ADDX Innovation Technology co., LTD.
<b>Address</b>	:	NO.2902,Building 9A-1.Shenzhen Bay Technology and Ecological Park ,Nanshan District,Shenzhen, China

## 2. General Description of EUT

<b>EUT Name</b>	:	Smart Battery Camera	
<b>Models No.</b>	:	CG9	
<b>Model Different</b>	:	----	
<b>Brand Name</b>	:	----	
<b>Sample ID</b>	:	HC-C-202405-0027-01-01	
<b>Product Description</b>	:	Operation Frequency:	2.4G WIFI: 2412MHz~2462MHz BLE: 2402MHz~2480MHz
<b>Power Rating</b>	:	USB Input:5V DC 3.6V 4400mAh Rechargeable Li-ion battery	
<b>Software Version</b>	:	V1.14.0	
<b>Hardware Version</b>	:	CG923 C01 V3	



## Method of Measurement for FCC

### 1. Max. Antenna Gain:

Mode	Antenna Type	Antenna Gain(dBi)
Bluetooth	PCB	0.5
2.4G WIFI	Sheet Steel Antenna	2.55

### 2. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

### 3. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=(PG)/4\pi R^2$$

Where

**S:** power density

**P:** power input to the antenna

**G:** power gain of the antenna in the direction of interest relative to an isotropic radiator.

**R:** distance to the center of radiation of the antenna

### Simultaneous transmission MPE Considerations

According to KDB447498: All transmitters and antennas in the host must be either evaluated for MPE compliance, by measurement or computational modeling, or qualify for the standalone MPE test exclusion in section 7.1. Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is  $\leq 1.0$ .

This means that:

$$\sum \text{ of MPE ratios } \leq 1.0$$





**4. Test Result:**

Worst MPE Result							
Test Mode	Frequency (MHz)	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	Max. ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm <sup>2</sup> ) [S]
BLE.1M	2402	1.596	1±1	2	0.5	20	0.00035
	2440	1.441	1±1	2	0.5	20	0.00035
	2480	1.819	1±1	2	0.5	20	0.00035
Test Mode	Frequency (MHz)	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	Max. ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm <sup>2</sup> ) [S]
2.4GWiFi.b	2412	13.88	13±1	14	2.55	20	0.00899
	2437	13.21	13±1	14	2.55	20	0.00899
	2462	12.71	13±1	14	2.55	20	0.00899
Test Mode	Frequency (MHz)	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	Max. ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm <sup>2</sup> ) [S]
2.4GWiFi.g	2412	10.53	10±1	11	2.55	20	0.00451
	2437	9.8	10±1	11	2.55	20	0.00451
	2462	8.96	9±1	10	2.55	20	0.00358
Test Mode	Frequency (MHz)	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	Max. ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm <sup>2</sup> ) [S]
2.4GWiFi.n20	2412	9.99	9±1	10	2.55	20	0.00358
	2437	9.53	9±1	10	2.55	20	0.00358
	2462	8.77	9±1	10	2.55	20	0.00358

Note: The antenna gain used max. antenna gain

**5. Conclusion:**

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

**Limits for General Population/ Uncontrolled Exposure**

Frequency Range (MHz)	Power density (mW/ cm <sup>2</sup> )
300-1,500	F/1500
1,500-100,000	1.0

For: BLE:2402~2480MHz 2.4G WIFI: 2412~2462MHz

MPE limit S: 1mW/ cm<sup>2</sup>

The MPE is calculated as 0.00899mW / cm<sup>2</sup> < limit 1mW / cm<sup>2</sup>.





## 6. Summary simultaneous transmission results

Bluetooth and WiFi support Synchronization transmitter

Maximum MPE ratio Bluetooth	Maximum MPE ratio WiFi	$\Sigma$ MPE ratios	Limit	Results
0.00035	0.00899	0.00934	1	PASS

So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b). The RF Exposure Information page from the manual is included here for reference.

-----END OF REPORT-----

