

Maximum Permissible Exposure Evaluation

FCC ID: 2AUDF-CQ12X

1. Client Information

Applicant	:	Shenzhen ADDX Innovation Technology co. ,LTD.
Address	:	NO.2902, Building 9A-1. Shenzhen Bay Technology and Ecological Park, Nanshan District,Shenzhen, China
Manufacturer	:	Shenzhen ADDX Innovation Technology co. ,LTD.
Address	:	NO.2902, Building 9A-1. Shenzhen Bay Technology and Ecological Park, Nanshan District, Shenzhen, China

2. General Description of EUT

EUT Name	:	Smart PTZ Battery Camera	
Models No.	:	CQ1, D3, D3K, D4, D4K, D5, D6, X85, X89	
Model Different	:	All these models are identical in the same PCB, layout and electrical circuit, The only difference is model name.	
Product Description	:	Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz
	:	Number of Channel:	802.11b/g/n(HT20):11 channels
	:	RF Output Power:	802.11b: 18.591dBm(MAX)
	:	Antenna Gain:	3 dBi Dipole Antenna
Power Rating	:	Input: DC 5V Output: DC 3.7V by 9000 mAh Rechargeable Li-ion battery	
Software Version	:	V0.4.1	
Hardware Version	:	CQ121_C02_V3	
Connecting I/O Port(S)	:	Please refer to the User's Manual	
Remark	:	the evaluation report used the EUT(20210927-03-02#).	

MPE Calculations for WIFI

1. Antenna Gain:

Dipole Antenna:3 dBi.

2. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=(PG)/4\pi R^2$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

4. Test Result:

2.4G WiFi

Mode	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm ²) [S]	Limit of Power Density (mW/ cm ²) (S)
802.11B	18.591	18±1	19	3	20	0.03153	1
802.11G	18.287	18±1	19	3	20	0.03153	1
802.11N(HT20)	18.181	18±1	19	3	20	0.03153	1

5. Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Power density (mW/ cm ²)
300-1,500	F/1500
1,500-100,000	1.0

For 2.4WIFI:2412~2462 MHz

MPE limit S: $1\text{mW}/\text{cm}^2$

The MPE is calculated as $0.03153\text{mW}/\text{cm}^2 < \text{limit } 1\text{mW}/\text{cm}^2$. So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.

Note

For a more detailed features description, please refer to the RF Test Report.

6. Conclusion:

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----END OF REPORT-----