5. RF EXPOSURE EVALUATION

5.1 MAXIMUM PERMISSIBLE EXPOSURE (MPE)

5.1.1 Applicable Standard

FCC §15.247 (i) & §1.1310 & §2.1091

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See \$1.1307(b)(1) of this chapter.

Report No.: CR22050014-00B

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure									
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)					
0.3–1.34	614	1.63	*(100)	30					
1.34–30	824/f	2.19/f	*(180/f ?)	30					
30–300	27.5	0.073	0.2	30					
300–1500	/	/	f/1500	30					
1500–100,000	/	/	1.0	30					

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

5.1.2 Procedure

Prediction of power density at the distance of the applicable MPE limit

 $S = PG/4\pi R^2$ power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}} \le 1$$

5.1.3 Calculated Result

Operation Modes	Frequency (MHz)	Antenna Gain		Conducted output power including Tune-up Tolerance		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm²)
		(dBi)	(numeric)	(dBm)	(mW)			
Wi-Fi	2412-2462	3.51	2.24	25	316.23	20.00	0.14	1.0
BLE	2402-2480	0.5	1.12	-1	0.79	20.00	0.0002	1.0
SRD	915	-1.17	0.76	-1	0.79	20.00	0.0001	0.610

Report No.: CR22050014-00B

Note:

The SRD, BLE and Wi-Fi can transmit simultaneously.

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}}$$

 $= S_{SRD}/S_{limit\text{-}SRD} + S_{BLE}/S_{limit\text{-}BLE} + S_{Wi\text{-}Fi}/S_{limit\text{-}Wi\text{-}Fi}$

=0.0001/0.610 + 0.0002/1 + 0.14/1

=0.14

< 1.0

Result: The device meet FCC MPE at 20 cm distance.

===== END OF REPORT =====