Wireless Charger User Guide

Model: S9

Thank you for purchasing and using this product!

Please read this Operation Instruction carefully and keep it properly before using this product.

Product Specification

Fast Wireless Charger

- Input: 5V⎓2A/9V⎓1.67A
- Output: 5V⎓1.0A/9V⎓1.2A
- Charging Efficiency: 70%

Applicable Devices

Compatible with all devices with Qi Standard

For all other mobiles without Qi Standard, those will be working with wireless receivers.

MADE IN CHINA

⚠The LED light turns red during wireless charging to indicate a charging failure.

The following situation can cause failures, like charging slowly, stop charging, over-temperature for charging position.

1. The adapter is not run up to standard (No PC USB output power supply).
2. The charging cable is not up to standard.
3. The phone case is too thick (within 2mm thickness phone case recommended).
4. The built-in wireless charging receiver position is not coincided with wireless charger coil position.
5. There is metal/magnet on the back of cell phone or phone case.
6. Smartphone does not support wireless charging function.

⚠ Attention

1. Please keep the charger away from water or other liquid.
2. If you need to clean the charger, please make sure it is not connected to power supply.
3. Using Environment temperature remains –20~45℃.

Support different size of smartphone to wireless charge.



Samsung foldable screen

Samsung

Apple

Step to install air vent

1. Follow the arrows to install 3 parts.



2. Adjust the screw cap to the best active status.

3. Press the button of clip to fix, then adjust the angle and tighten the fixed nut.



4. Installation completed.



Step to Install Suction Cup

1. Follow the arrows to install 3 parts.

2. Adjust the screw cap to the best active status.

3. Adjust the angle of suction cup and empty air.

Press down the lord card buckle

Adjust the appropriate angle

4. Installation completed.



Step to Use wireless charger

1. Input: Connect the wireless charger and car adapter with the charging cord.

Must use Qualcomm quick charging adaptor for fast wireless charging.

2. Place smartphone.

Tesla coil Sensor-wireless charger

Working Principle- After Coil sensor detect smartphone, it generates current signal, and then transmit signal to the motor to drive the clip to close to tighten smartphone.

The both sides of clip open automatically after being powering, putting on smartphone, clip close automatically to tighten smartphone.

3. Take off smartphone.

Press-key

Press the key, the clip open automatically, take your phone out.

4. LED indicator light shows the working status:

1.White LED Light: Standby.
2.Blue LED Light: Charging normally.
3.Red LED Light: Charging abnormally.

LED indicator light

FCC Requirement

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) this device may not cause harmful interference, and

(2) this device must accept any interference received, including interference that may cause undesired operation.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy, and if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

– Reorient or relocate the receiving antenna.

– Increase the separation between the equipment and receiver.

– Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

– Consult the dealer or an experienced radio/TV technician for help.