

RADIO TEST REPORT


The device described below is tested by Dongguan Nore Testing Center Co., Ltd. to determine the maximum emission levels emanating from the device, the severe levels which the device can endure and E.U.T.'s performance criterion. The test results, data evaluation, test procedures, and equipment of configurations shown in this report were made in accordance with the procedures in ANSI C63.10(2013).

Applicant : Annex Products Pty Ltd
Address : Suite 201/168 Greville St Prahran Australia 3181
Manufacturer /Factory : Production Partners
Address : Room 2706, 27th Floor, Intl Chamber of Commerce Tower, No.168, Fuhua 3rd RD, Futian Dist, Shenzhen, China
E.U.T. : Wireless Charging Head
Brand Name : QUAD LOCK
Model No. : QLA-WCH-2
FCC ID : 2AOU9-002
Measurement Standard : FCC PART 15 Subpart C
Date of Receiver : August 03, 2019
Date of Test : August 03, 2019 to August 27, 2019
Date of Report : August 27, 2019

This Test Report is Issued Under the Authority of :

Prepared by

Approved & Authorized Signer


Rose Hu / Engineer


Iori Fan / Authorized Signatory



This test report is for the customer shown above and their specific product only. This report applies to above tested sample only and shall not be reproduced in part without written approval of Dongguan Nore Testing Center Co., Ltd.

Table of Contents

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST	4
1.2 RELATED SUBMITTAL(S) / GRANT (S)	5
1.3 TEST METHODOLOGY	5
1.4 EQUIPMENT MODIFICATIONS	5
1.5 SUPPORT DEVICE	5
1.6 TEST FACILITY AND LOCATION	6
1.7 SUMMARY OF TEST RESULTS	6
2. SYSTEM TEST CONFIGURATION.....	7
2.1 EUT CONFIGURATION	7
2.2 PECIAL ACCESSORIES	7
2.3 DESCRIPTION OF TEST MODES	7
2.4 EUT EXERCISE	7
3. CONDUCTED EMISSIONS TEST	8
3.1 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	8
3.2 TEST CONDITION.....	8
3.3 MEASUREMENT RESULTS	8
4. RADIATED EMISSION TEST.....	11
4.1 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	11
4.2 MEASUREMENT PROCEDURE	12
4.3 LIMIT	13
4.4 MEASUREMENT RESULTS	14
5. 20DB BANDWIDTH.....	21
5.1 MEASUREMENT PROCEDURE	21
5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	21
5.3 MEASUREMENT RESULTS	21
6. ANTENNA APPLICATION	23
6.1 ANTENNA REQUIREMENT.....	23
6.2 MEASUREMENT RESULTS	23
7. TEST EQUIPMENT LIST.....	24



Revision History of This Test Report

Report Number	Description	Issued Date
NTC1908045FV00	Initial Issue	2019-08-27

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test

Product name	: Wireless Charging Head
Main model	: QLA-WCH-2
Additional model	: N/A
Brand name	: QUAD LOCK
Rating	: Input: DC 5V 2A or DC 9V 1.7A Output: DC 5V 1A or DC 9V 1.1A
Test voltage	: AC 120V 60Hz Adapter input
Adapter	: N/A
Cable	: USB Line 1m shielded
Software version	: V1.0
Hardware version	: V1.0
Note	: N/A

Technical Specification:

Frequency Range	: 110.5-204.5KHz
Wireless charger Output	: 10W
Test Channel	: 127KHz
Type of Modulation	: ASK
Type of Antenna	: induction coil
Antenna Gain	: 0 dBi (Declaration by manufacturer)

1.2 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: 2AOU9-002 filing to comply with FCC Part 15 (2017), Subpart C Rule.

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013). Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters.

1.4 Equipment Modifications

Not available for this EUT intended for grant.

1.5 Support Device

Inductive load	:	Provided by the laboratory
Adapter	:	Provided by the laboratory
		Manufacturer: HUWEI
		Model No.: HW-050200C01
		Input: AC100-240V 50/60Hz, 0.5A
		Output: DC5V 2A or 9V 2A

1.6 Test Facility and Location

Site Description

EMC Lab : Listed by CNAS, August 13, 2018
 The certificate is valid until August 13, 2024
 The Laboratory has been assessed and proved to be in compliance with CNAS/CL01
 The Certificate Registration Number is L5795.

Listed by A2LA, November 01, 2017
 The certificate is valid until December 31, 2019
 The Laboratory has been assessed and proved to be in compliance with ISO17025
 The Certificate Registration Number is 4429.01

Listed by FCC, November 06, 2017
 The Designation Number is CN1214
 Test Firm Registration Number: 907417

Listed by Industry Canada, June 08, 2017
 The Certificate Registration Number. Is 46405-9743

Name of Firm : Dongguan Nore Testing Center Co., Ltd.
 (Dongguan NTC Co., Ltd.)

Site Location : Building D, Gaosheng Science and Technology park, Hongtu road, Nancheng district, Dongguan city, Guangdong province, China

1.7 Summary of Test Results

FCC Rules	Description Of Test	Uncertainty	Result
§15.35	20dB Bandwidth	$\pm 1.42 \times 10^{-4}\%$	Compliant
§15.207 (a)	AC Power Conducted Emission	$\pm 1.06\text{dB}$	Compliant
§15.209	Radiated Emission	$\pm 3.70\text{dB}$	Compliant

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 Pecial Accessories

Not available for this EUT intended for grant.

2.3 Description of test modes


The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and normal mode is programmed. The Lowest, middle and highest channel were chosen for testing.

2.4 EUT Exercise

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.

3. Conducted Emissions Test

3.1 Test SET-UP (Block Diagram of Configuration)



3.2 Test Condition

Test Requirement: FCC Part 15.207

Frequency Range: 150KHz ~ 30MHz

Detector: RBW 9KHz, VBW 30KHz

Operation Mode: TX, Standby


3.3 Measurement Results

Please refer to following plots of the worst case: Full Load, TX (10W, MAX)


4. Radiated Emission Test

4.1 Test SET-UP (Block Diagram of Configuration)

4.1.1 Radiated Emission Test Set-Up, Frequency below 30MHz



4.1.2 Radiated Emission Test Set-Up, Frequency above 1GHz



4.2 Measurement Procedure

- Blow 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic chamber room.
- For the radiated emission test above 1GHz:
The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter full anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode.
- A Quasi-peak measurement was then made for that frequency point for below 1GHz test. PK and AV for above 1GHz emission test.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

Frequency Band (MHz)	Level	Resolution Bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	3 MHz
	Average	1 MHz	10 Hz

4.3 Limit

Frequency range MHz	Distance Meters	Field Strengths Limit (15.209)
		$\mu\text{V/m}$
0.009 ~ 0.490	300	$2400/F(\text{kHz})$
0.490 ~ 1.705	30	$24000/F(\text{kHz})$
1.705 ~ 30	30	30
30 ~ 88	3	100
88 ~ 216	3	150
216 ~ 960	3	200
Above 960	3	500

- Remark:
- (1) Emission level $(\text{dB})\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$
 - (2) The smaller limit shall apply at the cross point between two frequency bands.
 - (3) As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
 - (4) The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.


4.4 Measurement Results

Please refer to following plots of the worst case: Full Load, TX (10W, MAX)



Dongguan NTC Co., Ltd.
 Tel:+86-769-22022444 Fax:+86-769-22022799
 Web: [Http://www.ntc-c.com](http://www.ntc-c.com)

Radiated Emission Measurement



Site: 3m Chamber	Polarization: Horizontal	Temperature: 26
Limit: FCC Part 15.209_3M	Power: AC 120V 60Hz	Humidity: 60 %
EUT: Wireless Charging Head	Distance:	
M/N: QLA-WCH-2		
Mode: TX		
Note:		


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuA	dBuA	dB	cm	degree	Comment
1		0.0374	-14.05	32.32	18.27	116.08	-97.81	peak		
2		0.0498	-18.01	32.36	14.35	113.60	-99.25	peak		
3		0.0623	-2.30	32.30	30.00	111.66	-81.66	peak		
4		0.0748	-8.89	32.30	23.41	110.08	-86.67	peak		
5		0.1250	-7.20	32.30	25.10	105.63	-80.53	peak		
6	*	0.1481	4.14	32.29	36.43	104.16	-67.73	peak		



Dongguan NTC Co., Ltd.
 Tel:+86-769-22022444 Fax:+86-769-22022799
 Web: [Http://www.ntc-c.com](http://www.ntc-c.com)

Radiated Emission Measurement

File :QLA-WCH-2 Data :#10 Date: 2019/8/16 Time: 20:46:33



Site: 3m Chamber

Polarization: **Vertical**

Temperature: 26

Limit: FCC Part 15.209_3M

Power: AC 120V 60Hz

Humidity: 60 %

EUT: Wireless Charging Head

Distance:

M/N: QLA-WCH-2

Mode: TX

Note:


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuA	dBuA	dB	cm	degree	Comment
1		0.0157	-4.20	31.83	27.63	123.52	-95.89			peak
2		0.0349	-6.50	32.30	25.80	116.62	-90.82			peak
3		0.0628	-1.12	32.30	31.18	111.55	-80.37			peak
4		0.0747	-7.31	32.30	24.99	110.05	-85.06			peak
5		0.1137	-11.49	32.30	20.81	106.42	-85.61			peak
6	*	0.1293	10.99	32.30	43.29	105.31	-62.02			peak



Dongguan NTC Co., Ltd.
 Tel:+86-769-22022444 Fax:+86-769-22022799
 Web: [Http://www.ntc-c.com](http://www.ntc-c.com)

Radiated Emission Measurement

File :QLA-WCH-2 Data :#12 Date: 2019/8/16 Time: 20:42:53




Site: 3m Chamber Polarization: *Horizontal* Temperature: 26
 Limit: FCC Part 15.209_3M Power: AC 120V 60Hz Humidity: 60 %
 EUT: Wireless Charging Head Distance:
 M/N: QLA-WCH-2
 Mode: TX
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuA	dBuA	dB	cm	degree	Comment
1	*	0.1500	30.26	32.29	62.55	104.02	-41.47	peak		
2		0.4112	4.73	32.23	36.96	95.31	-58.35	peak		
3		0.7097	-5.61	32.19	26.58	72.82	-46.24	peak		
4		1.0082	-8.67	32.17	23.50	71.90	-48.40	peak		
5		1.4186	-9.85	32.17	22.32	71.00	-48.68	peak		
6		1.9410	-10.39	32.17	21.78	70.18	-48.40	peak		



Dongguan NTC Co., Ltd.
 Tel:+86-769-22022444 Fax:+86-769-22022799
 Web: [Http://www.ntc-c.com](http://www.ntc-c.com)

Radiated Emission Measurement



Site: 3m Chamber Polarization: **Vertical** Temperature: 26
 Limit: FCC Part 15.209_3M Power: AC 120V 60Hz Humidity: 60 %
 EUT: Wireless Charging Head Distance:
 M/N: QLA-WCH-2
 Mode: TX
 Note:


No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
	MHz	dBuV	dB/m	dBuA	dBuA	dB	cm	degree	Comment
1	0.1929	-3.36	32.28	28.92	101.85	-72.93			peak
2	0.3738	-5.61	32.24	26.63	96.14	-69.51			peak
3	0.7097	-9.37	32.19	22.82	72.82	-50.00			peak
4	1.1574	-10.39	32.17	21.78	71.54	-49.76			peak
5	1.6052	-9.40	32.17	22.77	70.68	-47.91			peak
6 *	2.6499	-9.58	32.17	22.59	69.36	-46.77			peak



Dongguan NTC Co., Ltd.
 Tel:+86-769-22022444 Fax:+86-769-22022799
 Web: [Http://www.ntc-c.com](http://www.ntc-c.com)

Radiated Emission Measurement

File :QLA-WCH-2 Data :#13 Date: 2019/8/16 Time: 20:58:13



Site: 3m Chamber Polarization: *Horizontal* Temperature: 26
 Limit: FCC Part 15_ClassB_3M Power: AC 120V 60Hz Humidity: 47 %
 EUT: Wireless Charging Head Distance: 3m
 M/N: QLA-WCH-2
 Mode: TX
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		53.2800	39.73	-17.57	22.16	40.00	-17.84			peak
2	*	90.1400	44.43	-13.90	30.53	43.50	-12.97			peak
3		159.0100	43.35	-15.20	28.15	43.50	-15.35			peak
4		177.4400	37.94	-14.32	23.62	43.50	-19.88			peak
5		245.3400	30.73	-11.85	18.88	46.00	-27.12			peak
6		345.2500	35.72	-9.20	26.52	46.00	-19.48			peak



Dongguan NTC Co., Ltd.
 Tel:+86-769-22022444 Fax:+86-769-22022799
 Web: [Http://www.ntc-c.com](http://www.ntc-c.com)

Radiated Emission Measurement

File :QLA-WCH-2 Data :#3 Date: 2019/8/16 Time: 20:59:43
 80.0 dBuV/m



Site: 3m Chamber Polarization: *Vertical* Temperature: 26
 Limit: FCC Part 15_ClassB_3M Power: AC 120V 60Hz Humidity: 47 %
 EUT: Wireless Charging Head Distance: 3m
 M/N: QLA-WCH-2
 Mode: TX
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	49.3998	45.49	-13.39	32.10	40.00	-7.90	QP		
2		54.2500	44.94	-13.64	31.30	40.00	-8.70	QP		
3		91.1099	45.46	-16.66	28.80	43.50	-14.70	QP		
4		105.6599	39.37	-15.97	23.40	43.50	-20.10	QP		
5		158.0399	39.93	-18.23	21.70	43.50	-21.80	QP		
6		352.0400	33.23	-11.13	22.10	46.00	-23.90	QP		


5. 20dB Bandwidth

5.1 Measurement Procedure

Maximum 20dB RF Bandwidth, FCC Rule 15.35:

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RBW was chosen so that the display was a result of the hopping channel modulation. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. Use the spectrum 20dB down delta function to measure the bandwidth.

5.2 Test SET-UP (Block Diagram of Configuration)




5.3 Measurement Results

Refer to attached data chart.

RBW:	300Hz	VBW:	1KHz
Test By:	Sance	Spectrum Detector:	PK
Temperature :	24 °C	Test Date :	August 26, 2019
Test Result:	PASS	Humidity :	50 %

Channel frequency (KHz)	20dB Down BW(Hz)
127	886

Test Channel



6. Antenna Application

6.1 Antenna requirement

According to of FCC part 15C section 15.203 and 15.240:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

6.2 Measurement Results

The antenna is induction coil antenna that no antenna other than furnished by the responsible party shall be used with the device, and the best case gain of the antenna is 0dBi, So, the antenna is consider meet the requirement.

7. Test Equipment List

Description	Manufacturer	Model Number	Serial Number	Characteristics	Calibration Date	Calibration Due Date
Test Receiver	Rohde & Schwarz	ESCI7	100837	9KHz~7GHz	Mar. 13, 2019	Mar. 12, 2020
Antenna	Schwarzbeck	VULB9162	9162-010	30MHz~7GHz	Mar. 14, 2019	Mar. 13, 2020
Cable	Huber+Suhner	CBL2-NN-1M	22390001	9KHz~7GHz	Mar. 13, 2019	Mar. 12, 2020
Cable	Huber+Suhner	CIL02	N/A	9KHz~7GHz	Mar. 13, 2019	Mar. 12, 2020
RF Cable	Huber+Suhner	SF-104	MY16559/4	9KHz~25GHz	Apr. 25, 2019	Apr. 24, 2020
Power Amplifier	HP	HP 8447D	1145A00203	100KHz~1.3GHz	Mar. 13, 2019	Mar. 12, 2020
Horn Antenna	Schwarzbeck	BBHA9170	9170-242	15GHz~40GHz	Mar. 13, 2019	Mar. 12, 2020
Horn Antenna	Com-Power	AH-118	071078	1GHz~18GHz	Mar. 14, 2019	Mar. 13, 2020
RF Cable	Huber+Suhner	SF-104	N/A	9KHz~40GHz	Apr. 24, 2019	Apr. 23, 2020
Loop antenna	Daze	ZA30900A	0708	9KHz~30MHz	Apr. 24, 2019	Apr. 23, 2020
Spectrum Analyzer	Rohde & Schwarz	FSU26	200409/026	20Hz~26.5GHz	Apr. 24, 2019	Apr. 23, 2020
Spectrum Analyzer	Rohde & Schwarz	FSV40	101003	10Hz~40GHz	April. 05, 2019	April. 04, 2020
Pre-Amplifier	EMCI	EMC 184045	980102	18GHz~40GHz	Nov. 02, 2018	Nov. 01, 2019
Pre-Amplifier	Agilent	8449B	3008A02964	1GHz~26.5GHz	Apr. 24, 2019	Apr. 23, 2020
L.I.S.N.	Rohde & Schwarz	ENV 216	101317	9KHz~30MHz	Mar. 13, 2019	Mar. 12, 2020
Temporary antenna connector	TESCOM	SS402	N/A	9KHz-25GHz	N/A	N/A
Power Meter	Anritsu	ML2495A	1139001	100k-65GHz	Nov. 03, 2018	Nov. 02, 2019
Power Sensor	Anritsu	MA2411B	100345	300M-40GHz	Nov. 03, 2018	Nov. 02, 2019

---End---