

**FCC RF EXPOSURE REPORT**

EUT	Amplifier
Model No.	M102
FCC ID:	2AUGD-M102
Frequency band (Operating)	<input type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 2.422GHz ~ 2.452GHz <input type="checkbox"/> WLAN: 5.180GHz ~ 5.240GHz <input type="checkbox"/> WLAN: 5.260GHz ~ 5.320GHz <input type="checkbox"/> WLAN: 5.500GHz ~ 5.700GHz <input checked="" type="checkbox"/> BLE: 2.402GHz ~ 2.480GHz <input checked="" type="checkbox"/> Bluetooth: 2.402GHz ~ 2.480GHz
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation)
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A



TEST RESULTS

No non-compliance noted.

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{3770}$

- Where E = Field strength in Volts / meter
- P = Power in Watts
- G = Numeric antenna gain
- d = Distance in meters
- S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

P (mW) = P (W) / 1000 and
 d (cm) = d (m) /100

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

- Where d = Distance in cm
- P = Power in mW
- G = Numeric antenna gain
- S = Power density in mW / cm²

Maximum Permissible Exposure

Test Mode	Frequency band (MHz)	Measured power(dBm)	Tuneuptoleran ce(dBm)	Max.TuneupP ower(dBm)	Peak output power(mW)	Antenna Gain (dBi)	Antenna gain (Numeric)	Distance (cm)	Power density (mW/cm2)	Limit (mW/cm2)
Bluetooth EDR	2402-2480	7.35	7.35±1	8.35	6.835967668	2	1.58	20	0.002156021	1