

**FCC TEST REPORT**

For

**ARTIKA FOR LIVING INC****Adeline Vanity 18inch 3CCT****Test Model: 18VAN-ADC-BL**

**Additional Model No.: 18VAN-ADC-XXXXXX("XXXXXX" can be A to Z and/or 0 to 9 and/or blank (commercial code))**

**Prepared for** : ARTIKA FOR LIVING INC  
**Address** : 1756 50th avenue, Lachine, Qc, Canada H8T 2V5

**Prepared by** : Shenzhen LCS Compliance Testing Laboratory Ltd.  
101, 201 Bldg A & 301 Bldg C, Juji Industrial Park  
**Address** : Yabianxueziwei, Shajing Street, Baoan District,  
Shenzhen, 518000, China

**Tel** : +(86) 0755-82591330  
**Fax** : +(86) 0755-82591332  
**Web** : www.lcs-cert.com  
**Mail** : webmaster@lcs-cert.com

**Date of receipt of test sample** : July 02, 2024  
**Number of tested samples** : 1  
**Serial number** : Prototype  
**Sample No.** : B240624032001  
**Date of Test** : July 02, 2024 to July 05, 2024  
**Date of Report** : July 08, 2024





### TEST REPORT

**Report No.** ..... : **LCSA06184207E**

**Date of Issue**..... : July 08, 2024

**Testing Laboratory Name** ..... : **Shenzhen LCS Compliance Testing Laboratory Ltd.**

**Address**..... : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park  
Yabianxueziwei, Shajing Street, Baoan District,  
Shenzhen, 518000, China

**Testing Location/ Procedure** ..... : Full application of Harmonised standards ■  
Partial application of Harmonised standards □  
Other standard testing method □

**Applicant's Name**..... : **ARTIKA FOR LIVING INC**

**Address**..... : 1756 50th avenue, Lachine, Qc, Canada H8T 2V5

#### Test Specification

**Standard** ..... : FCC 47 CFR Part 15, Subpart B  
ANSI C63.4-2014

**Test Report Form No.** ..... : TRF-4-E-010 A/0

**TRF Originator** ..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

**Master TRF** ..... : Dated 2011-03

#### Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test Item Description.** ..... : **Adeline Vanity 18inch 3CCT**

**Trade Mark**..... : Artika

**Test Model** ..... : 18VAN-ADC-BL

**Result**..... : **Positive**

**Compiled by:**

**Supervised by:**

**Approved by:**

Emma wang / File Administrator

Cary Luo/ Technique principal

Gavin Liang / Manager





# TEST REPORT

<b>Test Report No.:</b> LCSA06184207E	<u>July 08, 2024</u> Date of issue
---------------------------------------	---------------------------------------

<b>Test Model</b> .....	: <b>18VAN-ADC-BL</b>
<b>EUT</b> .....	: Adeline Vanity 18inch 3CCT
<b>Applicant</b> .....	: <b>ARTIKA FOR LIVING INC</b>
<b>Address</b> .....	: 1756 50th avenue, Lachine, Qc, Canada H8T 2V5
<b>Telephone</b> .....	: /
<b>Fax</b> .....	: /
<b>Manufacturer</b> .....	: <b>ZHONGSHAN C5 LIGHTING CO. LTD</b>
<b>Address</b> .....	: 1# Henglong Road, Tongyi Industrial Area, Cao San, Guzhen, Zhongshan, Guangdong, China.
<b>Telephone</b> .....	: /
<b>Fax</b> .....	: /
<b>Factory</b> .....	: <b>ZHONGSHAN C5 LIGHTING CO. LTD</b>
<b>Address</b> .....	: 1# Henglong Road, Tongyi Industrial Area, Cao San, Guzhen, Zhongshan, Guangdong, China.
<b>Telephone</b> .....	: /
<b>Fax</b> .....	: /

<b>Test Result</b>	<b>Positive</b>
--------------------	-----------------

The test report merely corresponds to the test sample.  
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.





## Revision History

Report Version	Issue Date	Revision Content	Revised By
000	July 08, 2024	Initial Issue	/





# TABLE OF CONTENTS

Test Report Description	Page
<b>1. SUMMARY OF STANDARDS AND RESULTS</b> .....	<b>6</b>
1.1 Description of Standards and Results .....	6
1.2 Description of Test Modes .....	7
<b>2. GENERAL INFORMATION</b> .....	<b>8</b>
2.1 Description of Device (EUT).....	8
2.2 Support equipment List .....	8
2.3 Description of Test Facility .....	8
2.4 Measurement Uncertainty .....	8
<b>3. MEASURING DEVICES AND TEST EQUIPMENT</b> .....	<b>9</b>
<b>4. EMISSION TEST RESULTS (EMI)</b> .....	<b>10</b>
4.1 Conducted emissions on AC mains .....	10
4.2 Radiated emissions (Below 1GHz) .....	13
<b>5. TEST SETUP PHOTOS</b> .....	<b>16</b>
<b>6. EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS)</b> .....	<b>17</b>





## 1. SUMMARY OF STANDARDS AND RESULTS

### 1.1 Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

Description of Test Item	Standard	Limits	Result
Conducted emissions on AC mains	FCC 47 CFR Part 15, Subpart B ANSI C63.4-2014	15.107, Class B	Pass
Radiated emissions (Below 1GHz)	FCC 47 CFR Part 15, Subpart B ANSI C63.4-2014	15.109, Class B	Pass





## 1.2 Description of Test Modes

No	Title	Description
TM1	Working(AC 120V/60Hz)	Record





## 2. GENERAL INFORMATION

### 2.1 Description of Device (EUT)

EUT	: Adeline Vanity 18inch 3CCT
Test Model	: 18VAN-ADC-BL
Additional Model No.	: 18VAN-ADC-XXXXXX("XXXXXX" can be A to Z and/or 0 to 9 and/or blank (commercial code))
Model Declaration	: PCB board, structure and internal of these model(s) are the same, So no additional models were tested.
Power Supply	: 120V~, 60Hz, 13W, 3000-4000-5000K
Highest Internal Frequency	: 1.705-108MHz
Classification of Equipment	: Class B

Highest internal frequency (Fx)	Highest measured frequency
$F_x \leq 1.705\text{MHz}$	30MHz
$1.705\text{MHz} < F_x \leq 108\text{MHz}$	1GHz
$108\text{MHz} < F_x \leq 500\text{MHz}$	2GHz
$500\text{MHz} < F_x \leq 1000\text{MHz}$	5GHz
$F_x > 1\text{GHz}$	5 x Fx up to a maximum of 40GHz

### 2.2 Support equipment List

The EUT was tested as an independent device.

### 2.3 Description of Test Facility

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

NVLAP Accreditation Code is 600167-0.  
 FCC Designation Number is CN5024.  
 CAB identifier is CN0071.  
 CNAS Registration Number is L4595.  
 Test Firm Registration Number: 254912.

### 2.4 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emission (150kHz to 30MHz)	$\pm 2.35$ dB
Radiated Emission (30MHz to 1000MHz)	$\pm 3.48$ dB
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	







### 3. MEASURING DEVICES AND TEST EQUIPMENT

Conducted emissions on AC mains					
Equipment	Manufacturer	Model No	Serial No.	Cal Date	Due Date
EMI Test Software	Farad	EZ	/	/	/
Artificial Mains	R&S	ENV216	101288	2024-06-06	2025-06-05
Pulse Limiter	R&S	ESH3-Z2	102750-NB	2023-08-15	2024-08-14
EMI Test Receiver	R&S	ESR3	102312	2024-03-02	2025-03-01

Radiated emissions (Below 1GHz)					
Equipment	Manufacturer	Model No	Serial No.	Cal Date	Due Date
EMI Test Software	Farad	EZ	/	/	/
EMI Test Software	AUDIX	E3	/	/	/
By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2021-09-12	2024-09-11
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2021-09-05	2024-09-04
EMI Test Receiver	R&S	ESR3	102311	2023-08-15	2024-08-14
Broadband Preamp	/	BP-01M18G	P190501	2024-06-06	2025-06-05
EMI Test Receiver	R&S	ESCI7	101173	2023-10-25	2024-10-24
By-log Antenna	SchwarzZBECK	VULB9163	01428	2023-09-05	2024-09-04





## 4. EMISSION TEST RESULTS (EMI)


### 4.1 Conducted emissions on AC mains

Test Requirement:	15.107, Class B		
Test Limit:	<b>Frequency of emission (MHz)</b>	<b>Conducted limit (dB<math>\mu</math>V)</b>	
		<b>Quasi-peak</b>	<b>Average</b>
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
	*Decreases with the logarithm of the frequency.		
Test Method:	ANSI C63.4-2014		
Procedure:	An initial pre-scan was performed with peak detector. Quasi-Peak or Average measurement were performed at the frequencies with maximized peak emission were detected. Remark: Level= Read Level+ Cable Loss+ LISN Factor		

#### 4.1.1 E.U.T. Operation:

Operating Environment:			
Temperature:	24 °C	Humidity:	53.7 %
Pre test mode:	TM1		
Final test mode:	TM1		


#### 4.1.2 Test Setup Diagram:





### 4.1.3 Test Data:

TM1 / Line: Line




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	*	0.1500	31.98	19.63	51.61	66.00	-14.39	QP	
2		0.1500	10.26	19.63	29.89	56.00	-26.11	AVG	
3		0.2626	4.82	19.63	24.45	51.35	-26.90	AVG	
4		0.3076	18.78	19.63	38.41	60.04	-21.63	QP	
5		0.4786	0.51	19.64	20.15	46.36	-26.21	AVG	
6		0.5550	9.63	19.65	29.28	56.00	-26.72	QP	
7		1.2750	-3.41	19.66	16.25	46.00	-29.75	AVG	
8		1.3965	6.74	19.66	26.40	56.00	-29.60	QP	
9		3.5386	7.82	19.70	27.52	56.00	-28.48	QP	
10		3.9751	-2.22	19.70	17.48	46.00	-28.52	AVG	
11		21.0796	19.04	20.15	39.19	60.00	-20.81	QP	
12		23.1226	7.26	20.07	27.33	50.00	-22.67	AVG	





TM1 / Line: Neutral



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1771	7.80	19.63	27.43	54.62	-27.19	AVG	
2	*	0.1905	29.14	19.63	48.77	64.01	-15.24	QP	
3		0.4516	0.92	19.64	20.56	46.85	-26.29	AVG	
4		0.5550	8.89	19.65	28.54	56.00	-27.46	QP	
5		1.1310	-3.23	19.65	16.42	46.00	-29.58	AVG	
6		1.2839	6.28	19.66	25.94	56.00	-30.06	QP	
7		4.2991	7.69	19.80	27.49	56.00	-28.51	QP	
8		4.5376	-1.78	19.80	18.02	46.00	-27.98	AVG	
9		8.1780	8.34	19.84	28.18	60.00	-31.82	QP	
10		9.3840	-1.13	19.85	18.72	50.00	-31.28	AVG	
11		24.9990	20.41	20.03	40.44	60.00	-19.56	QP	
12		29.2290	12.39	20.09	32.48	50.00	-17.52	AVG	

\*\*\*Note: 1) Pre-scan all modes and recorded the worst case results in this report.

2) Margin= Reading level + Correct factor-Limit

Correct Factor=Lish Factor+Cable Factor+Insertion loss of Pulse Limitter






### 4.2 Radiated emissions (Below 1GHz)

Test Requirement:	15.109, Class B				
Test Limit:	Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:				
	Frequency of emission (MHz)	Field strength @3m		Field strength @10m	
		(uV/m)	(dBuV/m)	(uV/m)	(dBuV/m)
	30 – 88	100	40	30	29.5
	88 – 216	150	43.5	45	33.1
216 – 960	200	46	60	35.6	
Above 960	500	54	150	43.5	
Test Method:	ANSI C63.4-2014				
Procedure:	An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by BiConiLog antenna with 2 orthogonal polarities. Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor				

#### 4.2.1 E.U.T. Operation:

Operating Environment:			
Temperature:	22.3 °C	Humidity:	53 %
Pre test mode:	TM1		
Final test mode:	TM1		


#### 4.2.2 Test Setup Diagram:





### 4.2.3 Test Data:

TM1 / Polarization: Horizontal




	Freq	Reading	CabLos	Antfac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	47.99	6.36	0.58	12.13	19.07	40.00	-20.93	QP
2	62.00	7.35	0.66	12.01	20.02	40.00	-19.98	QP
3	110.96	9.76	0.86	11.32	21.94	43.50	-21.56	QP
4	195.14	8.54	1.19	10.56	20.29	43.50	-23.21	QP
5	316.59	5.54	1.33	13.57	20.44	46.00	-25.56	QP
6	490.74	8.41	1.49	16.60	26.50	46.00	-19.50	QP

- Note: 1. All readings are Quasi-peak values.  
 2. Measured= Reading + Antenna Factor + Cable Loss  
 3. The emission that are 20db below the official limit are not reported





TM1 / Polarization: Vertical



	Freq	Reading	CabLos	Antfac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	43.66	7.25	0.55	11.43	19.23	40.00	-20.77	QP
2	55.41	9.39	0.63	12.54	22.56	40.00	-17.44	QP
3	62.00	11.07	0.66	12.01	23.74	40.00	-16.26	QP
4	100.23	8.63	0.80	10.72	20.15	43.50	-23.35	QP
5	194.45	8.50	1.18	10.53	20.21	43.50	-23.29	QP
6	601.43	10.31	1.50	19.28	31.09	46.00	-14.91	QP

- Note: 1. All readings are Quasi-peak values.  
 2. Measured= Reading + Antenna Factor + Cable Loss  
 3. The emission that are 20db below the official limit are not reported

Note:1).Pre-Scan all mode, Thus record worse case mode result in this report.

2) Margin= Reading level + Correct factor – Limit

Correct Factor=Antenna Factor+Cable Factor- Pre-amplifier Factor





## 5. TEST SETUP PHOTOS

Refer to Appendix - Test Setup Photos for LCSA06184207E.docx

## 6. EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS)

Refer to Appendix - EUT Photos for LCSA06184207E.docx

--- End of Report ---

