



FCC Part 15, Subpart B, Class B

ARTIKA FOR LIVING INC

Altitude Flush Mount chrome

Test Model: FM-AD5C-C1CR

Additional Model No.: FM-AD5C-XXXXXXXXXXXX("XXXXXXXXXXXX" can be A to Z and/or 0 to 9 and or/blank(commerical code))

Prepared for : ARTIKA FOR LIVING INC
Address : 1756 50th avenue, Lachine, Qc, CanadaH8T 2V5

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : October 16, 2023
Number of tested samples : 2
Sample No. : A09013252
Serial number : Prototype
Date of Test : October 16, 2023 ~ October 20, 2023
Date of Report : October 20, 2023





FCC Part 15, Subpart B, Class B
FCC 47 CFR Part 15 Subpart B, Class B, ANSI C63.4 -2014

Report Reference No. : LCSA09013252EA

Date Of Issue : October 20, 2023

Testing Laboratory Name : Shenzhen LCS Compliance Testing Laboratory Ltd.

Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park
Yabianxueziwei, Shajing Street, Baoan District, Shenzhen,
518000, China

Testing Location/ Procedure... : Full application of Harmonised standards ■
Partial application of Harmonised standards □
Other standard testing method □

Applicant's Name..... : ARTIKA FOR LIVING INC

Address : 1756 50th avenue, Lachine, Qc, CanadaH8T 2V5

Test Specification

Standard..... : FCC 47 CFR Part 15 Subpart B, Class B, ANSI C63.4
-2014

Test Report Form No..... : LCSEMC-1.0

TRF Originator..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF..... : Dated 2011-03

SHENZHEN LCS COMPLIANCE TESTING LABORATORY LTD. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long
as the SHENZHEN LCS COMPLIANCE TESTING LABORATORY LTD. is acknowledged as
copyright owner and source of the material. SHENZHEN LCS COMPLIANCE TESTING
LABORATORY LTD. takes no responsibility for and will not assume liability for damages
resulting from the reader's interpretation of the reproduced material due to its placement and
context.

Test Item Description..... : Altitude Flush Mount chrome

Test Model : FM-AD5C-C1CR

Trade Mark : ARTIKA

Ratings : Input: AC 120V, 60Hz, 33W

Result : Positive

Compiled by:

Vera Deng

Vera Deng/ Administrator

Supervised by:

Cary Luo

Cary Luo/ Technique principal

Approved by:

Gavin Liang

Gavin Liang/ Manager





FCC -- TEST REPORT

Test Report No. : LCSA09013252EA	<u>October 20, 2023</u> Date of issue
---	--

<p>Test Model : FM-AD5C-C1CR</p> <p>EUT..... : Altitude Flush Mount chrome</p>
<p>Applicant..... : ARTIKA FOR LIVING INC</p> <p>Address..... : 1756 50th avenue, Lachine, Qc, CanadaH8T 2V5</p> <p>Telephone..... : /</p> <p>Fax..... : /</p>
<p>Manufacturer..... : Ningbo Shenghe Lighting Co.,LTD.</p> <p>Address..... : No.311 Penglai Road, Xiangshan Economic development Zone, Ningbo, Zhejiang, 315700</p> <p>Telephone..... : /</p> <p>Fax..... : /</p>
<p>Factory 1..... : Ningbo Shenghe Lighting Co.,LTD.</p> <p>Address..... : No.311 Penglai Road, Xiangshan Economic development Zone, Ningbo, Zhejiang, 315700</p> <p>Telephone..... : /</p> <p>Fax..... : /</p>
<p>Factory 2..... : SHININGMOON LIGHTING (CAMBODIA) CO.,LTD</p> <p>Address..... : D3 Y Seven Industrial Park III, National Road No. 4, Sangkrous Cheat Village, TrapangKorng Commune, Samrong Toung District, KS, Cambodia</p> <p>Telephone..... : /</p> <p>Fax..... : /</p>

Test Result according to the standards on page 6: **Positive**

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.





Revision History

Report Version	Issue Date	Revision Content	Revised By
000	October 20, 2023	Initial Issue	---





TABLE OF CONTENTS

Test Report Description	Page
1. SUMMARY OF STANDARDS AND RESULTS	6
1.1. Description of Standards and Results	6
2. GENERAL INFORMATION	7
2.1. Description of Device (EUT)	7
2.2. Support Equipment List.....	7
2.3 External I/O Cable.....	7
2.4. Description of Test Facility	8
2.5. Statement of the Measurement Uncertainty	8
2.6. Measurement Uncertainty.....	8
3. TEST RESULTS	9
3.1. POWER LINE CONDUCTED EMISSION MEASUREMENT	9
3.2. Radiated emission Measurement	13
4. TEST SETUP PHOTOGRAPHS OF EUT	17
5. EXTERIOR PHOTOGRAPHS OF THE EUT	17
6. INTERIOR PHOTOGRAPHS OF THE EUT.....	17





1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION			
Description of Test Item	Standard	Limits	Results
Conducted disturbance at mains terminals	FCC 47 CFR Part 15 Subpart B, Class B, ANSI C63.4 -2014	Class B	PASS
Radiated disturbance	FCC 47 CFR Part 15 Subpart B, Class B, ANSI C63.4 -2014	Class B	PASS
N/A is an abbreviation for Not Applicable.			

Test mode:		
Mode 1	Lighting	Record





2. GENERAL INFORMATION

2.1. Description of Device (EUT)

- EUT : Altitude Flush Mount chrome
- Trade Mark : ARTIKA
- Test Model : FM-AD5C-C1CR
- Additional Model No. : FM-AD5C-XXXXXXXXXXXX("XXXXXXXXXXXX" can be A to Z and/or 0 to 9 and or/blank(commerical code))
- Model Declaration : PCB board, structure and internal of these model(s) are the same, So no additional models were tested
- Power Supply : Input: AC 120V, 60Hz, 33W
- Highest internal frequency (Fx) : Fx ≤ 108 MHz

Highest internal frequency (Fx)	Highest measured frequency
Fx ≤ 108 MHz	1 GHz
108 MHz < Fx ≤ 500 MHz	2 GHz
500 MHz < Fx ≤ 1 GHz	5 GHz
Fx > 1 GHz	5 × Fx up to a maximum of 6 GHz

NOTE 1 For FM and TV broadcast receivers, Fx is determined from the highest frequency generated or used excluding the local oscillator and tuned frequencies.
Where Fx is unknown, the radiated emission measurements shall be performed up to 6 GHz.

2.2. Support Equipment List

Manufacturer	Description	Model	Serial Number	Certificate
---	---	---	---	---

2.3 External I/O Cable

I/O Port Description	Quantity	Cable
---	---	---





2.4. Description of Test Facility

Site Description

EMC Lab. : NVLAP Accreditation Code is 600167-0.
 FCC Designation Number is CN5024.
 CAB identifier is CN0071.
 CNAS Registration Number is L4595.
 FCC Test Firm Registration Number: 254912.

2.5. Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

2.6. Measurement Uncertainty

Test	Parameters	Expanded Uncertainty (Ulab)	Expanded Uncertainty (Ucisp)
Conducted Emission	Level accuracy (9kHz to 150kHz) (150kHz to 30MHz)	± 2.63 dB ± 2.35 dB	± 3.8 dB ± 3.4 dB
Radiated Emission	Level accuracy (30MHz to 1000MHz)	± 3.48 dB	± 5.3 dB
Radiated Emission	Level accuracy (above 1000MHz)	± 3.90 dB	± 5.2 dB

(1) Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus.

(2) The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor of k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.





3. TEST RESULTS


3.1. POWER LINE CONDUCTED EMISSION MEASUREMENT

3.1.1. Test Equipment

The following test equipments are used during the power line conducted measurement:

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	EMI Test Software	Farad	EZ	/	N/A	N/A
2	EMI Test Receiver	R&S	ESR3	102312	2023-02-25	2024-02-24
3	Artificial Mains	R&S	ENV216	101288	2023-06-09	2024-06-08
4	Pulse Limiter	R&S	ESH3-Z2	102750-NB	2023-08-15	2024-08-14
5	Impedance Stabilization Network	TESEQ	ISN T800	45130	2022-10-29	2023-10-28

3.1.2. Block Diagram of Test Setup



3.1.3. Test Standard

Power Line Conducted Emission Limits (Class B)

Frequency (MHz)			Limit (dB μ V)	
			Quasi-peak Level	Average Level
0.15	~	0.50	66.0 ~ 56.0 *	56.0 ~ 46.0 *
0.50	~	5.00	56.0	46.0
5.00	~	30.00	60.0	50.0

NOTE1-The lower limit shall apply at the transition frequencies.

NOTE2-The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.





3.1.4.EUT Configuration on Test

The following equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner, which tends to maximize its emission characteristics in a normal application.

3.1.5.Operating Condition of EUT

3.1.5.1.Setup the EUT as shown on Section 3.1.2

3.1.5.2.Turn on the power of all equipments.

3.1.5.3.Let the EUT work in measuring Lighting and measure it.

3.1.6.Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC/ANSI C63.4-2014 on Conducted Emission Measurement.

The bandwidth of the test receiver is set at 9kHz.

The frequency range from 150kHz to 30MHz is investigated

3.1.7.Test Results


PASS.

The test result please refer to the next page.





Test Model	FM-AD5C-C1CR	Test Mode	Lighting
Environmental Conditions	23.5°C, 53.6% RH	Test Engineer	Joker Hu
Pol	Line	Test Voltage	AC 120V/60Hz




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector
1		0.1573	38.48	19.63	58.11	65.61	-7.50	QP
2	*	0.1951	27.90	19.63	47.53	53.82	-6.29	AVG
3		0.3436	27.60	19.63	47.23	59.12	-11.89	QP
4		0.3886	14.27	19.63	33.90	48.09	-14.19	AVG
5		0.8161	18.02	19.64	37.66	56.00	-18.34	QP
6		0.8836	2.23	19.64	21.87	46.00	-24.13	AVG
7		2.0401	8.49	19.68	28.17	56.00	-27.83	QP
8		2.2246	-2.80	19.68	16.88	46.00	-29.12	AVG
9		8.9161	8.88	19.81	28.69	60.00	-31.31	QP
10		9.4651	-2.37	19.83	17.46	50.00	-32.54	AVG
11		21.2461	14.32	20.14	34.46	60.00	-25.54	QP
12		22.2046	1.26	20.09	21.35	50.00	-28.65	AVG





Test Model	FM-AD5C-C1CR	Test Mode	Lighting
Environmental Conditions	23.5°C, 53.6% RH	Test Engineer	Joker Hu
Pol	Neutral	Test Voltage	AC 120V/60Hz



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Margin dB	Detector
1		0.1906	37.17	19.63	56.80	64.01	-7.21	QP
2	*	0.1951	27.12	19.63	46.75	53.82	-7.07	AVG
3		0.5146	19.47	19.65	39.12	56.00	-16.88	QP
4		0.6361	2.61	19.66	22.27	46.00	-23.73	AVG
5		1.2796	15.18	19.66	34.84	56.00	-21.16	QP
6		1.5316	0.56	19.67	20.23	46.00	-25.77	AVG
7		2.8231	10.14	19.72	29.86	56.00	-26.14	QP
8		3.5656	-1.46	19.78	18.32	46.00	-27.68	AVG
9		8.9026	13.95	19.85	33.80	60.00	-26.20	QP
10		9.4336	2.83	19.85	22.68	50.00	-27.32	AVG
11		20.8905	16.89	20.15	37.04	60.00	-22.96	QP
12		21.2911	4.75	20.13	24.88	50.00	-25.12	AVG

***Note: 1) Pre-scan all modes and recorded the worst case results in this report.

2) Margin= Reading level + Correct factor – Limit

Correct Factor= Lism Factor+Cable Factor






3.2. Radiated emission Measurement

3.2.1. Test Equipment

The following test equipments are used during the radiated emission measurement:

Item	Test equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	EMI Test Software	AUDIX	E3	/	N/A	N/A
2	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2021-09-12	2024-09-11
3	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2021-09-05	2024-09-04
4	EMI Test Receiver	R&S	ESPI	101940	2023-08-15	2024-08-14
5	Broadband Preamplifier	/	BP-01M18G	P190501	2023-06-09	2024-06-08
6	EMI Test Software	Farad	EZ	/	N/A	N/A
7	MXA Signal Analyzer	Agilent	N9020A	MY50510140	2022-10-29	2023-10-28
8	EMI Test Receiver	R&S	ESPI	101940	2023-08-15	2024-08-14

3.2.2. Block Diagram of Test Setup





3.2.3. Radiated Emission Limit (Class B)

Limits for Radiated Disturbance Below 1GHz

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
30 ~ 88	3	100	40
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46
960 ~ 1000	3	500	54

Remark: (1) Emission level (dB)μV = 20 log Emission level μV/m
(2) The smaller limit shall apply at the cross point between two frequency bands.
(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

Limits for Radiated Emission Above 1GHz

Frequency (MHz)	Distance (Meters)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)
Above 1000	3	74	54

***Note: The lower limit applies at the transition frequency.

3.2.4. EUT Configuration on Measurement

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

3.2.5. Operating Condition of EUT

3.2.5.1. Setup the EUT as shown in Section 3.2.2.

3.2.5.2. Let the EUT work in test Lighting and measure it.

3.2.6. Test Procedure

EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated by-log antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna is set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4-2014 on radiated emission measurement.

The bandwidth of the EMI test receiver is set at 120kHz, 300kHz.

The frequency range from 30MHz to 1000MHz is checked.

3.2.7. Radiated Emission Noise Measurement Result


PASS.

The scanning waveforms please refer to the next page.





Test Model	FM-AD5C-C1CR	Test Mode	Lighting
Environmental Conditions	23.8°C, 52.3% RH	Detector Function	Quasi-peak
Pol	Vertical	Distance	3m
Test Engineer	Joker Hu	Test Voltage	AC 120V/60Hz




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	44.5868	41.28	-16.94	24.34	40.00	-15.66	QP
2	69.8449	45.35	-19.46	25.89	40.00	-14.11	QP
3	178.7584	47.05	-18.79	28.26	43.50	-15.24	QP
4	245.0900	43.43	-15.84	27.59	46.00	-18.41	QP
5	356.6758	43.24	-14.83	28.41	46.00	-17.59	QP
6	839.1818	37.30	-9.01	28.29	46.00	-17.71	QP





Test Model	FM-AD5C-C1CR	Test Mode	Lighting
Environmental Conditions	23.8°C, 52.3% RH	Detector Function	Quasi-peak
Pol	Horizontal	Distance	3m
Test Engineer	Joker Hu	Test Voltage	AC 120V/60Hz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	52.7600	37.84	-17.54	20.30	40.00	-19.70	QP
2	68.8721	46.34	-19.39	26.95	40.00	-13.05	QP
3	133.1510	46.23	-20.67	25.56	43.50	-17.94	QP
4	229.2930	52.52	-16.55	35.97	46.00	-10.03	QP
5	356.6758	46.53	-14.83	31.70	46.00	-14.30	QP
6	839.1818	42.57	-9.01	33.56	46.00	-12.44	QP

Note: 1). Pre-Scan all mode, Thus record worse case mode result in this report.

2) Margin = Reading level + Correct factor - Limit

Correct Factor = Antenna Factor + Cable Factor - Pre-amplifier Factor





4. TEST SETUP PHOTOGRAPHS OF EUT

Please refer to separated files for Test Setup Photos of the EUT.

5. EXTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

6. INTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF TEST REPORT-----

