



**FCC Part15 Subpart B**

**TEST REPORT**

*For*

**LED Pendant Lamp**

**MODEL NUMBER: PDT-3CC**

**FCC ID: 2AUHG-PDT-3CC**

**REPORT NUMBER: 4790025665-F02-00**

**ISSUE DATE: August 06, 2021**

*Prepared for*

**Artika For Living Inc.  
1756, 50th Avenue Montreal (Lachine), Quebec Canada, H8T 2V5**

*Prepared by*

**UL-CCIC Company Limited  
Electronic Building, Parage Electronic Industrial Park, No. 8 Nanyun Er Road,  
Guangzhou Science Park, Guangzhou, 510670 China  
Website: [www.ul.com](http://www.ul.com)**

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products. This report does not imply that the product(s) has met the criteria for certification.

Form No.:TRF-GZEMC-002\_V1.1  
Form Issued: 2019-12-06  
Form Revised: 2020-01-13



## Revision History

Rev.	Issue Date	Revisions	Revised By
--	08/06/2021	Initial Issue	--



Summary of Test Results				
Standard	Test Item	Limit	Result	Remark
FCC PART 15, Subpart B	Conducted Disturbance	Class B	PASS	
	Radiated Disturbance below 1 GHz	Class B	PASS	
	Radiated Disturbance above 1 GHz	Class B	N/A	NOTE (1) NOTE (2)

Note:

(1) "N/A" denotes test is not applicable in this Test Report

(2) If the highest frequency of the internal sources of the EUT is less than 108 MHz, the measurement shall only be made up to 1 GHz. If the highest frequency of the internal sources of the EUT is between 108 MHz and 500 MHz, the measurement shall only be made up to 2 GHz. If the highest frequency of the internal sources of the EUT is between 500 MHz and 1 GHz, measurement shall only be made up to 5 GHz. If the highest frequency of the internal sources of the EUT is above 1 GHz, the measurement shall be made up to 5 times the highest frequency or 40 GHz, whichever is less.

(2) The highest frequency of the internal sources of the EUT is less than 108 MHz.



## CONTENTS

<b>1. ATTESTATION OF TEST RESULTS .....</b>	<b>5</b>
<b>2. TEST METHODOLOGY .....</b>	<b>6</b>
<b>3. FACILITIES AND ACCREDITATION .....</b>	<b>6</b>
<b>4. CALIBRATION AND UNCERTAINTY .....</b>	<b>6</b>
4.1. <i>Measuring Instrument Calibration .....</i>	<i>6</i>
4.2. <i>Measurement Uncertainty .....</i>	<i>6</i>
<b>5. EQUIPMENT UNDER TEST .....</b>	<b>7</b>
5.1. <i>Description of EUT .....</i>	<i>7</i>
5.2. <i>Test Mode .....</i>	<i>7</i>
5.3. <i>EUT Accessory .....</i>	<i>7</i>
5.4. <i>Block Diagram Showing the Configuration of System Tested .....</i>	<i>8</i>
<b>6. MEASURING EQUIPMENT AND SOFTWARE USED .....</b>	<b>9</b>
<b>7. EMISSION TEST .....</b>	<b>10</b>
7.1. <i>Conducted Disturbance Measurement .....</i>	<i>10</i>
7.1.1. <i>Limits of conducted disturbance voltage .....</i>	<i>10</i>
7.1.2. <i>Test Procedure .....</i>	<i>10</i>
7.1.3. <i>Test Setup .....</i>	<i>11</i>
7.1.4. <i>Test Environment .....</i>	<i>11</i>
7.1.5. <i>Test Mode .....</i>	<i>11</i>
7.1.6. <i>Test Results .....</i>	<i>12</i>
7.2. <i>Radiated Disturbance Measurement .....</i>	<i>14</i>
7.2.1. <i>Limits of radiated disturbance measurement .....</i>	<i>14</i>
7.2.2. <i>Test Procedure .....</i>	<i>15</i>
7.2.3. <i>Test Setup .....</i>	<i>15</i>
7.2.4. <i>Test Environment .....</i>	<i>16</i>
7.2.5. <i>Test Mode .....</i>	<i>16</i>
7.2.6. <i>Test Results – below 1GHz .....</i>	<i>17</i>
<b>Appendix I: Photographs of Test Configuration .....</b>	<b>19</b>
<b>Appendix II: Photographs of the EUT .....</b>	<b>20</b>



## 1. ATTESTATION OF TEST RESULTS

### Applicant Information

Company Name: Artika For Living Inc.  
Address: 1756, 50th Avenue Montreal (Lachine), Quebec Canada, H8T 2V5

### Manufacturer Information

Company Name: DongGuan City Rising Stars Lighting Co., LTD  
Address: BaoXi Road No., 8, BaoTang Village HouJie Town  
Dongguan, Guangdong, 523191, CN

### EUT Information

Product Name: LED Pendant Lamp  
Model name: PDT-3CC  
Brand name: N/A  
Sample Status: Normal  
Sample ID: 210714005-2  
Sample Received Date: July 15, 2021  
Date of Tested: July 15, 2021~ July 20, 2021

APPLICABLE STANDARDS	
STANDARDS	TEST RESULTS
FCC PART 15, Subpart B	PASS*

\*=Decision rule for statement(s) of conformity is based on IEC Guide 115:2007 Clause 4.4.3 Procedure 2" Accuracy Method"

Prepared By:

Ryan Pang  
Project Engineer

Approved By:

Yam Shan  
Project Engineer



## 2. TEST METHODOLOGY

All tests were performed in accordance with the standard FCC Part15 Subpart B and ANSI C63.4-2014.

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<b>A2LA (Certificate No.: 4338.01)</b> Shenzhen STS Test Services Co., Ltd. has been assessed and proved to be in compliance with A2LA. <b>CNAS (Registration No.: L7649)</b> Shenzhen STS Test Services Co., Ltd. has been assessed and proved to be in compliance with CNAS.
---------------------------	---

Note: All tests measurement facilities use to collect the measurement data are located at A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. Measuring Instrument Calibration

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

### 4.2. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Measurement Frequency Range	K	U(dB)
Conducted disturbance at mains terminals ports	0.15MHz ~ 30MHz	2	2.80 dB
Radiated disturbance Test	30MHz ~ 1000MHz	2	4.39 dB
Radiated disturbance Test	1GHz ~ 6 GHz	2	5.10 dB
Radiated disturbance Test	6GHz ~ 18GHz	2	5.48 dB

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



## 5. EQUIPMENT UNDER TEST

### 5.1. Description of EUT

EUT Name	LED Pendant Lamp
EUT Description	The devices a LED Pendant Lamp
Model	PDT-3CC
Model Difference	N/A
Rated Input	AC 120V 60Hz
Test Model	Lighting mode
Test Power Supply	AC 120V 60Hz

### 5.2. Test Mode


Test Mode	Description
Mode 1	Lighting mode

### 5.3. EUT Accessory

Item	Accessory	Brand Name	Model Name	Description
1	N/A	N/A	N/A	N/A



#### 5.4. Block Diagram Showing the Configuration of System Tested



The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

##### Necessary accessories

Item	Equipment	Mfr/Brand	Model/Type No.	Length	Note
N/A	N/A	N/A	N/A	N/A	N/A

##### Support units

Item	Equipment	Mfr/Brand	Model/Type No.	Length	Note
N/A	N/A	N/A	N/A	N/A	N/A





## 6. MEASURING EQUIPMENT AND SOFTWARE USED

Conducted Disturbance						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	EMI Test Receiver	R&S	ESCI	101427	2020.10.12	2021.10.11
<input checked="" type="checkbox"/>	LISN	R&S	ENV216	101242	2020.10.12	2021.10.11
Software						
Used	Description	Manufacturer	Name	Version		
<input checked="" type="checkbox"/>	Test Software for Conducted Emissions	Farad	EZ-EMC	Ver. UL-3A1		
Radiated Disturbance						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	EMI Test Receiver	R&S	ESCI	101427	2020.10.12	2021.10.11
<input checked="" type="checkbox"/>	Bi-log Antenna	TESEQ	CBL6111D	34678	2020.10.12	2021.10.11
<input checked="" type="checkbox"/>	Pre-amplifier(0.1M-3GHz)	EM	EM330	060665	2020.10.12	2021.10.11
<input checked="" type="checkbox"/>	Spectrum Analyzer	Agilent	N9020A	MY491000 60	2020.10.12	2021.10.11
Software						
Used	Description	Manufacturer	Name	Version		
<input checked="" type="checkbox"/>	Test Software for Radiated Emissions	Farad	EZ-EMC	Ver. UL-3A1		



## 7. EMISSION TEST

### 7.1. Conducted Disturbance Measurement

#### 7.1.1. Limits of conducted disturbance voltage

FREQUENCY (MHz)	<input type="checkbox"/> Class A (dB $\mu$ V)		<input checked="" type="checkbox"/> Class B (dB $\mu$ V)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 -5.0	73.00	60.00	56.00	46.00
5.0 -30.0	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.
- (3) The test result calculated as following:  
Measurement Value = Reading Level + Correct Factor  
Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor  
Margin Level = Measurement Value - Limit Value


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

#### 7.1.2. Test Procedure

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item:EUT Test Photos.

### 7.1.3. Test Setup



For the actual test configuration, please refer to Appendix I: Photographs of the Test Configuration.

### 7.1.4. Test Environment

Temperature:	26.5°C
Humidity:	54%
ATM pressure:	101kPa

### 7.1.5. Test Mode


Pre-test Mode:	Mode 1
Final Test Mode:	Mode 1

Note: According to pre-test results, the final test mode is each independent function's worst case and only shown in the report.




### 7.1.6. Test Results

Test Mode:	Mode 1
Test Voltage:	AC 120V/60Hz





Test Mode:	Mode 1
Test Voltage:	AC 120V/60Hz

**Phase: Neutral**

No.	Frequency (MHz)	Reading (dBuV)	Correct dB	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1500	37.29	20.29	57.58	66.00	-8.42	QP
2	0.1500	15.13	20.29	35.42	56.00	-20.58	AVG
3	0.4940	24.63	20.49	45.12	56.10	-10.98	QP
4	0.4940	10.38	20.49	30.87	46.10	-15.23	AVG
5	0.8660	22.98	20.33	43.31	56.00	-12.69	QP
6	0.8660	8.84	20.33	29.17	46.00	-16.83	AVG
7	4.1540	24.41	20.52	44.93	56.00	-11.07	QP
8	4.1540	10.62	20.52	31.14	46.00	-14.86	AVG
9	8.1780	28.42	20.71	49.13	60.00	-10.87	QP
10	8.1780	15.06	20.71	35.77	50.00	-14.23	AVG
11	29.9140	30.77	23.18	53.95	60.00	-6.05	QP
12	29.9140	18.58	23.18	41.76	50.00	-8.24	AVG

Remark

Result = Reading +Correct

Margin = Result – Limit



## 7.2. Radiated Disturbance Measurement

### 7.2.1. Limits of radiated disturbance measurement

Below 1 GHz

Measurement Method and Applied Limits:

ANSI C63.4:

Frequency (MHz)	<input type="checkbox"/> Class A		<input checked="" type="checkbox"/> Class B
	Field strength (dBuV/m) (at 10m)	Field strength (dBuV/m) (at 3m)	Field strength (dBuV/m) (at 3m)
30 - 88	39	49.5	40
88 - 216	43.5	54	43.5
216 - 960	46.4	56.9	46
Above 960	49.5	60	54

Above 1 GHz

Measurement Method and Applied Limits:

ANSI C63.4:

Frequency (MHz)	<input type="checkbox"/> Class A				<input type="checkbox"/> Class B	
	(dBuV/m) (at 3m)		(dBuV/m) (at 10m)		(dBuV/m) (at 3m)	
	Peak	Average	Peak	Average	Peak	Average
Above 1000	80	60	69.5	49.5	74	54

#### Frequency Range of Radiated Disturbance Measurement

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 - 108	1000
108 - 500	2000
500 - 1000	5000
Above 1000	5 <sup>th</sup> harmonic of the highest frequency or 40 GHz, whichever is lower

NOTE:


- (1) The limit for radiated test was performed according to FCC Part 15, Subpart B;
- (2) The tighter limit applies at the band edges;
- (3) Emission level (dBuV/m) = 20log Emission level (uV/m),  
3m Emission level = 10m Emission level + 20log(10m/3m);
- (4) The test result calculated as following:  
Measurement Value = Reading Level + Correct Factor,  
Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use),  
Margin Level = Measurement Value - Limit Value.

### 7.2.2. Test Procedure


- The measuring distance of at 3m shall be used for measurements at frequency up to 1GHz.
- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For the actual test configuration, please refer to the related Item:EUT Test Photos.

### 7.2.3. Test Setup

(a) Radiated Disturbance Test Set-Up Frequency 30MHz - 1GHz



(b) Radiated Disturbance Test Set-Up Frequency above 1GHz



For the actual test configuration, please refer to Appendix I: Photographs of the Test Configuration.

#### 7.2.4. Test Environment

Radiated Disturbance - below 1 GHz		Radiated Disturbance - above 1 GHz	
Temperature:	23.3°C	Temperature:	N/A
Humidity:	52%	Humidity:	N/A
ATM pressure:	101kPa	ATM pressure:	N/A

#### 7.2.5. Test Mode

Radiated Disturbance - below 1 GHz		Radiated Disturbance - above 1 GHz	
Pre-test Mode:	Mode 1	Pre-test Mode:	N/A
Final Test Mode:	Mode 1	Final Test Mode:	N/A

Note: According to pre-test results, the final test mode is each independent function's worst case and only shown in the report.






### 7.2.6. Test Results – below 1GHz

Test Mode:	Mode 1
Test Voltage:	AC 120V/60Hz

#### Polarization: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	34.3963	48.71	-13.48	35.23	40.00	-4.77	QP
2	48.1625	55.34	-20.72	34.62	40.00	-5.38	QP
3	92.1388	53.06	-21.22	31.84	43.50	-11.66	QP
4	187.0956	47.81	-21.34	26.47	43.50	-17.03	QP
5	299.3158	44.92	-16.27	28.65	46.00	-17.35	QP
6	531.9634	36.40	-9.93	26.47	46.00	-19.53	QP


Remark

Result = Reading +Correct

Margin = Result – Limit



Test Mode:	Mode 1
Test Voltage:	AC 120V/60Hz

**Polarization: Horizontal**

No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	61.1316	48.02	-25.91	22.11	40.00	-17.89	QP
2	93.1132	43.00	-21.05	21.95	43.50	-21.55	QP
3	149.4857	42.79	-18.12	24.67	43.50	-18.83	QP
4	208.5803	51.94	-21.39	30.55	43.50	-12.95	QP
5	327.8873	47.68	-15.12	32.56	46.00	-13.44	QP
6	665.8035	34.18	-8.27	25.91	46.00	-20.09	QP

Remark

Result = Reading + Correct


Margin = Result - Limit

## Appendix I: Photographs of Test Configuration


### Conducted Disturbance





### Radiated Disturbance below 1GHz





## Appendix II: Photographs of the EUT




















UL-CCIC Company Ltd. Suzhou Branch

Form No.:TRF-GZEMC-002\_V1.1  
Form Issued: 2019-12-06  
Form Revised: 2020-01-13