

## **RF Exposure evaluation**

Test report
On Behalf of

Shenzhen Vitek Electronics Co., Ltd.

For

8 inch Tablet PC Model No.: VK800, XK80, XK80-XXX1, VK800-XXX1

FCC ID: 2AUIK-VK800

**Prepared for:** Shenzhen Vitek Electronics Co.,Ltd.

Room 402-408, Building 8, He Tang Zhi Yuan, Huan Cheng Nan Road, Bantian, Shenzhen,

China

Prepared By: Shenzhen HUAK Testing Technology Co., Ltd.

1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street,

Bao'an District, Shenzhen City, China

Date of Test: Sep. 20, 2019 ~ Sep. 27, 2019

Date of Report: Sep. 27, 2019

Report Number: HK1909232397-5E



## 1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$ 50 mm are determined by: [(max power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[ $\sqrt{f(GHz)}$ ] $\leq$ 3.0 for 1-g SAR and  $\leq$  7.5 for 10-g extremity SAR,

Where:

Result= $P/D*\sqrt{F}$ 

F= the RF channel transmit frequency in GHz

P=Maximum turn-up power in mw

D=Min. test separation distance in mm

## 2. Test Result of RF Exposure Evaluation

2.4G

	Output	Tune Up	Max Tune	Min test	Result	exclusion	SAR Test
	power	Power	Up power	separation		thresholds for	Exclusion
	(dBm)	(dBm)	dBm/mW	distance		1-g SAR	
				mm			
2.4 WiFi	8.49	7.5±1	8.5/ 7.08	5	2.199	3.0	Pass
5.2 WiFi	8.36	7.5±1	8.5/ 7.08	5	2.199	3.0	Pass
BLE	-0.021	-1±1	0/ 1.0	5	0.315	3.0	Pass
BT EDR	3.56	3±1	4/ 2.51	5	0.791	3.0	Pass

Note:

PK Output power= conducted power.

Conducted power see the test report HK1909232397-1E/-2E/-3E/-4E, antenna gain=1dBi

Note: WiFi and BT functions can be used at the same time, so the maximum test exclusion threshold is 2.199+0.791=2.99

Per KDB 447498 D01, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 2.99, which is <= 3, SAR testing is not required.

Note: Exclusion Thresholds Results=[(max. power of channel, including tune-up tolerance, <math>mW)/(min. test separation distance, mm)] •  $[\sqrt{f_{(GHz)}}]$ 

f(GHz) is the RF channel transmit frequency in GHz

Distance=5mm.....End of Report.....