



Test Report No.: W7L-P21060015SA01



RF EXPOSURE REPORT

Product: Wyze Switch

Model Name: WLPS1

FCC ID: 2AUIUWLPS1

Applicant: Wyze Labs, Inc.

Address: 5808 Lake Washington Blvd NE Ste 300 Kirkland WA 98033

Manufacturer: LEEDARSON LIGHTING CO.,LTD.

Address: Xingtai Industrial Park, Economic Development Zone of Changtai County, Zhangzhou City Fujian, China

Prepared by: BV 7Layers Communications Technology (Shenzhen) Co. Ltd

Lab Location: No.B102, Dazhu Chuangxin Mansion, North of Beihuan Avenue, North Area, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, China

TEL: +86 755 8869 6566

FAX: +86 755 8869 6577

E-MAIL: customerservice.dg@cn.bureauveritas.com

Report No.: W7L-P21060015SA01

Received Date: Jun. 17, 2021

Test Date: Jun. 17, 2021 ~ Jul. 26, 2021

Issued Date: Jul. 27, 2021

This report should not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

RF EXPOSURE REPORT.....	1
RELEASE CONTROL RECORD	3
1 CERTIFICATION	4
2 GENERAL INFORMATION	5
2.1 GENERAL DESCRIPTION OF EUT	5
3 RF EXPOSURE	6
3.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)	6
3.2 MPE CALCULATION FORMULA	6
3.3 CLASSIFICATION	6
3.4 CONDUCTED POWER	7
3.5 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	8
3.6 CONCLUSION OF SIMULTANEOUS TRANSMITTER	9



BUREAU
VERITAS

Test Report No.: W7L-P21060015SA01

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
W7L-P21060015SA01	Original release	Jul. 27, 2021



Test Report No.: W7L-P21060015SA01

1 CERTIFICATION

PRODUCT: Wyze Switch
BRAND NAME: WYZE
MODEL NAME: WLPS1
APPLICANT: Wyze Labs, Inc.
TESTED: Jun. 17, 2021 ~ Jul. 26, 2021
TEST SAMPLE: Identical Prototype
STANDARDS: **FCC Part 2 (Section 2.1091)**
FCC OET Bulletin 65, Supplement C (01-01)
KDB 447498 D01 General RF Exposure Guidance v06
IEEE C95.1

The above equipment has been tested by **BV 7Layers Communications Technology (Shenzhen) Co. Ltd** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Simon, **DATE:** Jul. 27, 2021
(Simon Wang / Engineer)

APPROVED BY : Luke Lu, **DATE:** Jul. 27, 2021
(Luke Lu / Manager)



2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Wyze Switch	
MODEL NAME	WLPS1	
NOMINAL VOLTAGE	120Vac	
OPERATING TEMPERATURE RANGE	0-40°C (32~104°F) °C	
MODULATION TYPE	BT_LE	GFSK
	WLAN	DSSS, OFDM
OPERATING FREQUENCY	BT_LE	2402MHz ~ 2480MHz
	WLAN	2412 ~ 2462MHz for 11b/g/n(HT20)
HW VERSION	V1	
SW VERSION	V1.2.5	
I/O PORTS	Refer to user's manual	
CABLE SUPPLIED	N/A	

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

3 RF EXPOSURE

3.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

3.2 MPE CALCULATION FORMULA

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

3.3 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.



3.4 CONDUCTED POWER

WIFI 2.4G

802.11b 11b

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	14.90	N/A
6	2437	15.14	N/A
11	2462	15.17	N/A

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	13.40	N/A
6	2437	13.37	N/A
11	2462	13.41	N/A

802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	13.44	N/A
6	2437	13.38	N/A
11	2462	13.25	N/A

BLE

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
0	2402	5.83	N/A
19	2440	6.66	N/A
39	2480	7.62	N/A



3.5 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

WIFI&BLE

Band	Frequency (MHz)	Operating Mode	Antenna Gain (dBi)	Tune-up Power (dBm)	Tune-up Power (mW)	Power Density (mW/cm ²)	limit (mW/cm ²)	PASS / FAIL
BLE	2402-2480	1M	1.23	11.50	14.13	0.004	1.00	PASS
WIFI 2.4G	2412-2462	11b	1.23	23.00	199.53	0.053	1.00	PASS



3.6 CONCLUSION OF SIMULTANEOUS TRANSMITTER

Both of the WLAN and plug-in device can transmit simultaneously, the formula of calculated the MPE is:

$$\text{CPD1/LPD1} + \text{CPD2/LPD2} + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

Therefore the worst-case situation is $0.004/1.00 + 0.053/1.00 = 0.057$, which is less than "1", This confirmed that the device comply with FCC 1.1310 MPE limit.

--END--