

FCC 22H 24E 27L, §2.1091 – RF Exposure

FCC ID: 2AUVX-NT07E

Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: f is frequency in MHz

* = Power density limit is applicable at frequencies greater than 100 MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

* = Plane-wave equivalent power density

MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=20cm

Test Result of RF Exposure Evaluation

	Tune up Produce power	Maximum peak output power (dBm)	Output power to antenn a (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm ²)	Limit (mW / cm ²)	Result
GSM850	33±1	34	2511.89	1.390 (1.43dBi)	0.694945	1	Pass
GSM1900	30±1	31	1258.93	1.390 (1.43dBi)	0.348298	1	Pass

	Tune up Produce power	Maximum peak output power (dBm)	Output power to antenn a (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm ²)	Limit (mW / cm ²)	Result
LTE BADN 2	20±1	21	125.89	1.390 (1.43dBi)	0.03483	1	Pass
LTE BADN 4	21±1	22	158.49	1.390 (1.43dBi)	0.04385	1	Pass
LTE BADN 5	21±1	22	158.49	1.390 (1.43dBi)	0.04385	1	Pass
LTE BADN 12	21±1	22	158.49	1.390 (1.43dBi)	0.04385	1	Pass
LTE BADN 13	21±1	22	158.49	1.390 (1.43dBi)	0.04385	1	Pass
LTE BADN 25	21±1	22	158.49	1.390 (1.43dBi)	0.04385	1	Pass