telefication bv The Netherlands Chamber of Commerce 51565536 www.telefication.com



FCC RF exposure report

Product name : Rootzone Sensor

Applicant : Rockwool BV

FCC ID : 2AUKP-RZ002

ISED ID : 25447-RZ002

Test report No.: 200701990 005 Ver 1.00

laboratory certification approvals



Laboratory information

Accreditation

Telefication complies with the accreditation criteria for test laboratories as laid down in ISO/IEC 17025:2017. The accreditation covers the quality system of the laboratory as well as the specific activities as described in the authorized annex bearing the accreditation number L021 and is granted on 30 November 1990 by the Dutch Council For Accreditation (RvA: Raad voor Accreditatie).

Telefication is designated by the FCC as an Accredited Test Firm for compliance testing of equipment subject to Certification under Parts 15 & 18. The Designation number is: NL0001.

Telefication is a Wireless Device Testing laboratory recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements.

Telefication is a registered Conformity Assessment body (CAB) under the Japan-EC MRA (Agreement on Mutual Recognition between Japan and the European Community). The registration number is: 201.

Documentation

The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 10 years at Telefication Netherlands.

Testing Location

Test Site	Kiwa Telefication BV	
Test Site location	Wilmersdorf 50	
	7327 AC Apeldoorn	
	The Netherlands	
	Tel. +31 88998 3393	
Test Site FCC	NL0001	



Revision History

Version	Date	Remarks	Ву
V0.50	31-03-2021	Release version	K.K.
v1.00	04-06-2021	Release version	RvB



Table of Contents

Revision I	History	. 2
1 Gene	eral Description	. 4
1.1	Applicant	.4
1.2	Manufacturer	.4
1.3	Tested Equipment Under Test (EUT)	.4
1.4	SAR Measurement Evaluation	.5
1.4.1	Maximum Output Power	.5
1.4.2	SAR Testing Exclusions, Mobile use	.5
1.5	Summary	5



1 General Description

1.1 Applicant

Client name: Rockwool BV

Address: Industrieweg 15, Roermond, The Netherlands

Zip code: 6045 JG

E-mail: <u>Edwin.dilling@grodan.com</u>

Contact name: Mr. E. Dilling

1.2 Manufacturer

Client name: Rockwool BV

Address: Industrieweg 15, Roermond, The Netherlands

Zip code: 6045 JG

E-mail: <u>Edwin.dilling@grodan.com</u>

Contact name: Mr. E. Dilling

1.3 Tested Equipment Under Test (EUT)

Product name: Rootzone Sensor

Brand name: ROCKWOOL, Grodan, GroSens

Product type: GS21RZ03

Model(s): -Software version: -Hardware version: --



1.4 SAR Measurement Evaluation

1.4.1 Maximum Output Power

The maximum radiated power including tune-up tolerance is shown as below.

Mode	Output power (dBm)		
LoRa	1.22		
BLE	3.05		

1.4.2 SAR Testing Exclusions, Mobile use

Calculation method of RF Safety Distance:

$$PD = \frac{Pout * G}{4\pi r^2}$$

Where:

PD = Power Density in mW/cm^2 Pout = Output power in mW G = Gain of antenna

R = Distance between observation point and centre of the radiator in cm

Antenna

Technology	LoRa/BLE
Antenna type	PCB Antenna
Antenna gain	-4.9 dBi/0 dBi

Calculation results

Technology	Frequency	Max	Antenna	Distance	Power	Limit
	(MHz)	power	gain	(cm)	density	(m W/
		(mW)	(numeric)		(mW/	cm^2)
					cm^2)	
LoRa	908.7	1.32	.32	20	0.021	1
BLE	2440	2.01	1	20	0.105	1

1.5 Summary

Since the SAR testing for all device orientations apply SAR test exclusion per KDB 447498, SAR testing for this device is not required.