



# TEST REPORT

**APPLICANT** : Rhino Mobility LLC

**PRODUCT NAME** : Tablet

**MODEL NAME** : C6D

**BRAND NAME** : RHINO

**FCC ID** : 2AUOUC6D

**STANDARD(S)** : 47 CFR Part 2  
47 CFR Part 22 Subpart H  
47 CFR Part 24 Subpart E  
47 CFR Part 27 Subpart L

**RECEIPT DATE** : 2023-04-20

**TEST DATE** : 2023-04-24 to 2023-05-22

**ISSUE DATE** : 2023-09-27



Edited by: Peng Mi  
Peng Mi(Rapporteur)

Approved by: Shen Junsheng  
ShenJunsheng (Supervisor)

**NOTE:** This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





# DIRECTORY

- 1. Technical Information ..... 3**
- 1.1. Applicant and Manufacturer Information ..... 3**
- 1.2. Equipment Under Test (EUT) Description ..... 3**
- 1.3. Maximum E.R.P./E.I.R.P. and Emission Designator ..... 5**
- 1.4. Test Standards and Results ..... 6**
- 1.5. Environmental Conditions ..... 7**
- 2. 47 CFR Part 2, Part 22H, 24E&27L Requirements ..... 8**
- 2.1. Conducted RF Output Power ..... 8**
- 2.2. Peak to Average Ratio ..... 12**
- 2.3. Occupied Bandwidth ..... 16**
- 2.4. Frequency Stability ..... 21**
- 2.5. Conducted Out of Band Emissions ..... 24**
- 2.6. Band Edge ..... 28**
- 2.7. Determining E.R.P. and/or E.I.R.P. from conducted RF output power measurements ..... 31**
- 2.8. Radiated Out of Band Emissions ..... 35**
- Annex A Test Uncertainty ..... 56**
- Annex B Testing Laboratory Information ..... 57**

Change History		
Version	Date	Reason for change
1.0	2023-09-27	First edition





# 1. Technical Information

Note: Provide by applicant.

## 1.1. Applicant and Manufacturer Information

<b>Applicant:</b>	Rhino Mobility LLC
<b>Applicant Address:</b>	8 The Green, Suite A, Dover, Delaware,19901, USA
<b>Manufacturer:</b>	Rhino Mobility LLC
<b>Manufacturer Address:</b>	8 The Green, Suite A, Dover, Delaware,19901, USA

## 1.2. Equipment Under Test (EUT) Description

<b>Product Name:</b>	Tablet	
<b>Sample No.:</b>	28#	
<b>Hardware Version:</b>	Q6010_MB_V1.0	
<b>Software Version:</b>	C6D(001)_20230904	
<b>Modulation Type:</b>	WCDMA Mode with QPSK Modulation HSDPA Mode with QPSK Modulation HSUPA Mode with QPSK Modulation HSPA+ Mode with 16QAM Modulation	
<b>Operating Frequency Range:</b>	WCDMA Band V	Tx: 824MHz-849MHz
		Rx: 869MHz-894MHz
	WCDMA Band IV	Tx: 1710MHz-1755MHz
		Rx: 2110MHz-2155MHz
	WCDMA Band II	Tx: 1850MHz-1910MHz
		Rx: 1930MHz-1990MHz
<b>Antenna Type:</b>	PIFA Antenna	
<b>Antenna Gain:</b>	WCDMA Band V:	-1.13dBi
	WCDMA Band IV:	-1.33dBi
	WCDMA Band II:	-0.04dBi



<b>Accessory Information:</b>	Battery	
	Brand Name:	N/A
	Model No.:	BPC6
	Serial No.:	N/A
	Capacity:	3950mAh
	Rated Voltage:	3.87V
	Charge Limit:	4.45V
	Manufacturer:	Phenix New Energy (Huizhou) Co., Ltd.
	Adaptor	
	Brand Name:	RHINO
	Model No.:	TPA-10S120150UU01
	Serial No.:	N/A
	Rated Output:	3.6V-6.0V=3.0A; 6.0V-9.0V=2.0A; 9.0V-12.0V=1.5A;
	Rated Input:	100-240V~50/60Hz, 0.6A
	Manufacturer:	Shenzhen Tianyin Electronics Co., Ltd.
	USB Cable 1	
	Model No.:	188.123022001-09
	Manufacturer:	YibinRuirun Electronics Co., Ltd.
	USB Cable 2	
	Model No.:	188.123022002-09
	Manufacturer:	YibinRuirun Electronics Co., Ltd.
	USB Cable 3	
	Model No.:	USB TYPE A TO C 2.0 Cable 2.0m
	Manufacturer:	HUIZHOU WASHIN ELECTRONICTS CO.,LTD.
USB Cable 4		
Model No.:	USB TYPE A TO C 2.0 Cable 1.0m	
Manufacturer:	HUIZHOU WASHIN ELECTRONICTS CO.,LTD.	

**Note 1:** This is a variant report of original report (Report No.: SZ23020326W02, FCC ID: 2AUOUC6).Based on the similarity between before, only changed product name, model name, SW version which disabled voice and GSM functions, the others are the same as before. The changes do not affect the test results.

**Note 2:** The transmitter (Tx) frequency arrangement of the WCDMA Band V used by the EUT can be represented with the formula  $F(n)=826.4+0.2*(n-4132)$ ,  $4132 \leq n \leq 4233$ ; the lowest, middle and highest channel numbers (ARFCHs) used and tested in this report are separately 4132





(826.4MHz), 4182(836.4MHz) and 4233 (846.6MHz).

**Note 3:** The transmitter (Tx) frequency arrangement of the WCDMA IV band used by the EUT can be represented with the formula  $F(n)=1712.4+0.2*(n-1312)$ ,  $1312 \leq n \leq 1513$ ; the lowest, middle and highest channel numbers (ARFCHs) used and tested in this report are separately 1312 (1712.4MHz), 1413 (1732.6MHz) and 1513 (1752.6MHz).

**Note 4:** The transmitter (Tx) frequency arrangement of the WCDMA Band II used by the EUT can be represented with the formula  $F(n)=1852.4+0.2*(n-9262)$ ,  $9262 \leq n \leq 9538$ ; the lowest, middle and highest channel numbers (ARFCHs) used and tested in this report are separately 9262 (1852.4MHz), 9400 (1880MHz) and 9538 (1907.6MHz).

**Note 5:** All test modes and data rates were considered and evaluated respectively by performing full test. Test modes are chosen to be reported as the worst case below:

WCDMA mode for WCDMA band V;

WCDMA mode for WCDMA band IV;

WCDMA mode for WCDMA band II;

**Note 6:** For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

### 1.3. Maximum E.R.P./E.I.R.P. and Emission Designator

Test Mode	Maximum E.R.P./E.I.R.P. (W)	Emission Designator
WCDMA Band V	0.101	4M15F9W
WCDMA Band IV	0.167	4M16F9W
WCDMA Band II	0.221	4M17F9W



## 1.4. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 2, Part 22, Part 24 and Part 27 for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 2 (10-1-12 Edition)	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	47 CFR Part 22 (10-1-12 Edition)	Public Mobile Services
3	47 CFR Part 24 (10-1-12 Edition)	Personal Communications Services
4	47 CFR Part 27 (10-1-12 Edition)	Miscellaneous Wireless Communications Services

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result	Method determination /Remark
1	2.1046	Conducted RF Output Power	Apr. 24,2023	Chen Hao	PASS <sub>Note1</sub>	No deviation
2	24.232(d)	Peak -Average Ratio	Apr. 24,2023	Li Huaijie	PASS <sub>Note1</sub>	No deviation
3	2.1049	Occupied Bandwidth	Apr. 24,2023	Li Huaijie	PASS <sub>Note1</sub>	No deviation
4	2.1055, 22.355, 24.235, 27.54	Frequency Stability	Apr. 24,2023	Li Huaijie	PASS <sub>Note1</sub>	No deviation
5	2.1051, 22.917(a), 24.238(a), 27.53(h)	Conducted Out of Band Emissions	Apr. 24,2023	Li Huaijie	PASS <sub>Note1</sub>	No deviation
6	2.1051, 22.917(a), 24.238(a), 27.53(h)	Band Edge	Apr. 24,2023	Li Huaijie	PASS <sub>Note1</sub>	No deviation
7	22.913(a), 24.232(c), 27.50(d)	Transmitter Radiated Power (E.I.P.R./E.R.P.)	Apr. 24,2023	Li Huaijie	PASS <sub>Note1</sub>	No deviation
8	2.1053, 22.917(a), 24.238(a),	Radiated Out of Band Emissions	May22,2023	Lin Jiayong	PASS <sub>Note1</sub>	No deviation





27.53(h)					
<p><b>Note 1:</b> The test results of these test items in this report refer to the test report(Report No.: SZ23020326W02).</p> <p><b>Note 2:</b> The tests were performed according to the method of measurements prescribed in KDB971168 D01 v03r01 and ANSI/TIA-603-E-2016.</p> <p><b>Note 3:</b> The path loss during the RF test is calibrated to correct the results by the offset setting in the test equipments. The ref offset 24.5dB contains two parts that cable loss 14.5dB and Attenuator 10dB.</p> <p><b>Note 4:</b> Additions to, deviation, or exclusions from the method shall be judged in the"method determination" column of add,deviate or exclude from the specific method shall be explained in the "Remark" of the above table.</p> <p><b>Note 5:</b> When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.</p>					

### 1.5. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106



## 2.47 CFR Part 2, Part 22H, 24E&27L Requirements


### 2.1. Conducted RF Output Power

#### 2.1.1. Requirement

According to FCC section 2.1046(a), for transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in FCC section 2.1033(c)(8).

#### 2.1.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.





**2.1.3. Test Results**

WCDMA Band V	Average Power (dBm)		
<b>TX Channel</b>	<b>4132</b>	<b>4182</b>	<b>4233</b>
<b>Frequency (MHz)</b>	<b>826.4</b>	<b>836.4</b>	<b>846.6</b>
RMC 12.2Kbps	23.25	23.32	23.29
HSDPA Subtest-1	22.25	22.11	22.24
HSDPA Subtest-2	22.29	22.18	22.19
HSDPA Subtest-3	21.72	21.61	21.66
HSDPA Subtest-4	21.73	21.58	21.69
DC-HSDPA Subtest-1	22.36	22.02	22.36
DC-HSDPA Subtest-2	22.31	22.20	22.13
DC-HSDPA Subtest-3	21.80	21.73	21.54
DC-HSDPA Subtest-4	21.68	21.53	21.73
HSUPA Subtest-1	22.26	22.17	22.14
HSUPA Subtest-2	21.75	21.70	21.68
HSUPA Subtest-3	22.22	22.13	22.10
HSUPA Subtest-4	22.24	22.14	22.32
HSUPA Subtest-5	22.23	22.15	22.31
HSPA+ (16QAM) Subtest-1	20.71	20.72	20.76





WCDMA Band IV	Average Power (dBm)		
	1312	1413	1513
<b>TX Channel</b>	<b>1712.4</b>	<b>1732.6</b>	<b>1752.6</b>
<b>Frequency (MHz)</b>	<b>1712.4</b>	<b>1732.6</b>	<b>1752.6</b>
RMC 12.2Kbps	23.51	23.57	23.55
HSDPA Subtest-1	22.54	22.60	22.64
HSDPA Subtest-2	22.64	22.57	22.68
HSDPA Subtest-3	22.21	21.99	22.14
HSDPA Subtest-4	22.24	21.94	22.13
DC-HSDPA Subtest-1	22.51	22.48	22.62
DC-HSDPA Subtest-2	22.60	22.52	22.75
DC-HSDPA Subtest-3	22.32	22.07	22.18
DC-HSDPA Subtest-4	22.30	21.88	22.17
HSUPA Subtest-1	21.57	22.64	22.77
HSUPA Subtest-2	21.56	22.14	22.21
HSUPA Subtest-3	21.56	22.60	22.65
HSUPA Subtest-4	22.54	22.63	22.68
HSUPA Subtest-5	21.45	21.43	22.70
HSPA+ (16QAM) Subtest-1	21.18	21.13	21.19





WCDMA Band II	Average Power (dBm)		
	9262	9400	9538
<b>TX Channel</b>	<b>9262</b>	<b>9400</b>	<b>9538</b>
<b>Frequency (MHz)</b>	<b>1852.4</b>	<b>1880.0</b>	<b>1907.6</b>
RMC 12.2Kbps	23.46	23.48	23.45
HSDPA Subtest-1	22.29	22.17	22.12
HSDPA Subtest-2	22.30	22.19	22.06
HSDPA Subtest-3	21.82	21.64	21.54
HSDPA Subtest-4	21.82	21.68	21.51
DC-HSDPA Subtest-1	22.19	22.15	22.16
DC-HSDPA Subtest-2	22.42	22.20	22.06
DC-HSDPA Subtest-3	21.70	21.72	21.55
DC-HSDPA Subtest-4	21.76	21.61	21.59
HSUPA Subtest-1	21.18	21.08	21.01
HSUPA Subtest-2	21.18	21.07	21.03
HSUPA Subtest-3	20.89	20.76	20.69
HSUPA Subtest-4	22.18	22.08	22.04
HSUPA Subtest-5	21.08	20.95	20.89
HSPA+ (16QAM) Subtest-1	20.82	20.70	20.64



## 2.2. Peak to Average Ratio

### 2.2.1. Requirement

According to FCC 24.232(d) and 27.50(d), the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

### 2.2.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.

### 2.2.3. Test procedure

1. For UMTS operating mode:
  - a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
  - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1%.







## 2.2.4. Test Result

WCDMA Band IV					
Mode	Channel	Frequency (MHz)	Peak to Average ratio (dB)	Limit (dB)	Verdict
WCDMA	1312	1712.4	2.80	13	PASS
	1413	1732.6	2.85		PASS
	1513	1752.6	2.90		PASS

WCDMA Band II					
Mode	Channel	Frequency (MHz)	Peak to Average ratio (dB)	Limit (dB)	Verdict
WCDMA	9262	1852.4	2.94	13	PASS
	9400	1880.0	2.97		PASS
	9538	1907.6	2.88		PASS








## 2.3. Occupied Bandwidth

### 2.3.1. Requirement

According to FCC section 2.1049, the occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission. Occupied bandwidth is also known as the 99% emission bandwidth.

### 2.3.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.







2.3.3.Test Result

WCDMA Band V				
Mode	Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26dB Bandwidth (MHz)
WCDMA	4132	826.4	4.14	4.72
	4182	836.4	4.15	4.74
	4233	846.6	4.12	4.72

WCDMA Band IV				
Mode	Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26dB Bandwidth (MHz)
WCDMA	1312	1712.4	4.14	4.72
	1413	1732.6	4.16	4.73
	1513	1752.6	4.14	4.76

WCDMA Band II				
Mode	Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26dB Bandwidth (MHz)
WCDMA	9262	1852.4	4.16	4.74
	9400	1880.0	4.17	4.73
	9538	1907.6	4.16	4.74






<h3 style="text-align: center; margin: 0;">WCDMA Band V, CH4132, 826.4MHz</h3> <div style="border: 1px solid black; padding: 5px;"> <p style="font-size: small; margin: 0;">Agilent Spectrum Analyzer - Occupied BW</p> <p style="font-size: x-small; margin: 0;">Center Freq: 826.400000 MHz    Center Freq: 826.400000 MHz    Radio Std: None              Trig: Free Run    #FGain: Low    #Atten: 16 dB    AvgJHold: &gt;10/10    Radio Device: BTS</p> <p style="font-size: x-small; margin: 0;">Center 826.4 MHz    #Res BW 100 kHz    #VBW 300 kHz    Span 10 MHz    Sweep 1 ms</p> <table style="width:100%; font-size: x-small; border-collapse: collapse;"> <tr> <td style="width:33%;">Occupied Bandwidth</td> <td style="width:33%;">Total Power</td> <td style="width:33%;">32.0 dBm</td> </tr> <tr> <td><b>4.1416 MHz</b></td> <td></td> <td></td> </tr> <tr> <td>Transmit Freq Error</td> <td>-5.054 kHz</td> <td>OBW Power 99.00 %</td> </tr> <tr> <td>x dB Bandwidth</td> <td>4.719 MHz</td> <td>x dB -26.00 dB</td> </tr> </table> <p style="font-size: x-small; margin: 0;">MSG: File &lt;4132.state&gt; recalled    STATUS</p> </div>	Occupied Bandwidth	Total Power	32.0 dBm	<b>4.1416 MHz</b>			Transmit Freq Error	-5.054 kHz	OBW Power 99.00 %	x dB Bandwidth	4.719 MHz	x dB -26.00 dB	<h3 style="text-align: center; margin: 0;">WCDMA Band V, CH4182, 836.4MHz</h3> <div style="border: 1px solid black; padding: 5px;"> <p style="font-size: small; margin: 0;">Agilent Spectrum Analyzer - Occupied BW</p> <p style="font-size: x-small; margin: 0;">Center Freq: 836.400000 MHz    Center Freq: 836.400000 MHz    Radio Std: None              Trig: Free Run    #FGain: Low    #Atten: 16 dB    AvgJHold: &gt;10/10    Radio Device: BTS</p> <p style="font-size: x-small; margin: 0;">Center 836.4 MHz    #Res BW 100 kHz    #VBW 300 kHz    Span 10 MHz    Sweep 1 ms</p> <table style="width:100%; font-size: x-small; border-collapse: collapse;"> <tr> <td style="width:33%;">Occupied Bandwidth</td> <td style="width:33%;">Total Power</td> <td style="width:33%;">32.0 dBm</td> </tr> <tr> <td><b>4.1483 MHz</b></td> <td></td> <td></td> </tr> <tr> <td>Transmit Freq Error</td> <td>12.908 kHz</td> <td>OBW Power 99.00 %</td> </tr> <tr> <td>x dB Bandwidth</td> <td>4.741 MHz</td> <td>x dB -26.00 dB</td> </tr> </table> <p style="font-size: x-small; margin: 0;">MSG: File &lt;4182.state&gt; recalled    STATUS</p> </div>	Occupied Bandwidth	Total Power	32.0 dBm	<b>4.1483 MHz</b>			Transmit Freq Error	12.908 kHz	OBW Power 99.00 %	x dB Bandwidth	4.741 MHz	x dB -26.00 dB
Occupied Bandwidth	Total Power	32.0 dBm																							
<b>4.1416 MHz</b>																									
Transmit Freq Error	-5.054 kHz	OBW Power 99.00 %																							
x dB Bandwidth	4.719 MHz	x dB -26.00 dB																							
Occupied Bandwidth	Total Power	32.0 dBm																							
<b>4.1483 MHz</b>																									
Transmit Freq Error	12.908 kHz	OBW Power 99.00 %																							
x dB Bandwidth	4.741 MHz	x dB -26.00 dB																							
<h3 style="text-align: center; margin: 0;">WCDMA Band V, CH4233, 846.6MHz</h3> <div style="border: 1px solid black; padding: 5px;"> <p style="font-size: small; margin: 0;">Agilent Spectrum Analyzer - Occupied BW</p> <p style="font-size: x-small; margin: 0;">Center Freq: 846.600000 MHz    Center Freq: 846.600000 MHz    Radio Std: None              Trig: Free Run    #FGain: Low    #Atten: 16 dB    AvgJHold: &gt;10/10    Radio Device: BTS</p> <p style="font-size: x-small; margin: 0;">Center 846.6 MHz    #Res BW 100 kHz    #VBW 300 kHz    Span 10 MHz    Sweep 1 ms</p> <table style="width:100%; font-size: x-small; border-collapse: collapse;"> <tr> <td style="width:33%;">Occupied Bandwidth</td> <td style="width:33%;">Total Power</td> <td style="width:33%;">31.9 dBm</td> </tr> <tr> <td><b>4.1247 MHz</b></td> <td></td> <td></td> </tr> <tr> <td>Transmit Freq Error</td> <td>6.213 kHz</td> <td>OBW Power 99.00 %</td> </tr> <tr> <td>x dB Bandwidth</td> <td>4.716 MHz</td> <td>x dB -26.00 dB</td> </tr> </table> <p style="font-size: x-small; margin: 0;">MSG: File &lt;4233.state&gt; recalled    STATUS</p> </div>	Occupied Bandwidth	Total Power	31.9 dBm	<b>4.1247 MHz</b>			Transmit Freq Error	6.213 kHz	OBW Power 99.00 %	x dB Bandwidth	4.716 MHz	x dB -26.00 dB													
Occupied Bandwidth	Total Power	31.9 dBm																							
<b>4.1247 MHz</b>																									
Transmit Freq Error	6.213 kHz	OBW Power 99.00 %																							
x dB Bandwidth	4.716 MHz	x dB -26.00 dB																							









### WCDMA Band II, CH9262, 1852.4MHz



### WCDMA Band II, CH9400, 1880.0MHz



### WCDMA Band II, CH9538, 1907.6MHz



## 2.4. Frequency Stability

### 2.4.1. Requirement


According to FCC section 22.355, 24.235 and 27.54 the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. According to FCC section 2.1055, the test conditions are:

- (a) The temperature is varied from  $-30^{\circ}\text{C}$  to  $+50^{\circ}\text{C}$  at intervals of not more than  $10^{\circ}\text{C}$ .
- (b) For hand carried battery powered equipment, the primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacture. The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided.

**Note:** The operating temperature of EUT is from  $0^{\circ}\text{C}$  to  $40^{\circ}\text{C}$ , which are specified by the applicant.

### 2.4.2. Test Description

Test Setup:



The EUT, which is powered by the DC Power Supply directly, is located in the Temperature Chamber. The EUT is commanded by the System Simulator (SS) to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS via a Common Antenna.



**2.4.3. Test Result**

The nominal, highest and lowest extreme voltages are separately 3.87V, 4.45V and 3.65V, which are specified by the applicant; the normal temperature here used is 20°C.

<b>WCDMA Band V, CH4182, 836.4MHz</b>					
<b>Limit =±2.5ppm</b>					
<b>Voltage (%)</b>	<b>Power (VDC)</b>	<b>Temp (°C)</b>	<b>Fre. Dev. (Hz)</b>	<b>Deviation (ppm)</b>	<b>Result</b>
Normal	3.87	+20(Ref)	7	0.008	PASS
Normal		0	15	0.018	
Normal		+10	15	0.018	
Normal		+20	0	0.000	
Normal		+30	19	0.023	
Normal		+40	23	<b>0.027</b>	
High		4.45	+20	-15	
BATT.ENDPOINT	3.65	+20	14	0.017	

<b>WCDMA Band IV, CH1413, 1732.6MHz</b>					
<b>Limit =Within Authorized Band</b>					
<b>Voltage (%)</b>	<b>Power (VDC)</b>	<b>Temp (°C)</b>	<b>Fre. Dev. (Hz)</b>	<b>Deviation (ppm)</b>	<b>Result</b>
Normal	3.87	+20(Ref)	14	0.008	PASS
Normal		0	13	0.008	
Normal		+10	18	0.010	
Normal		+20	17	0.010	
Normal		+30	-19	-0.011	
Normal		+40	-6	-0.003	
High		4.45	+20	20	
BATT.ENDPOINT	3.65	+20	14	0.008	





<b>WCDMA Band II, CH9400, 1880.0MHz</b>					
<b>Limit =Within Authorized Band</b>					
<b>Voltage (%)</b>	<b>Power (VDC)</b>	<b>Temp (°C)</b>	<b>Fre. Dev. (Hz)</b>	<b>Deviation (ppm)</b>	<b>Result</b>
Normal	3.87	+20(Ref)	19	<b>0.010</b>	PASS
Normal		0	6	0.003	
Normal		+10	18	0.010	
Normal		+20	18	0.010	
Normal		+30	-15	-0.008	
Normal		+40	10	0.005	
High		4.45	+20	18	
BATT.ENDPOINT	3.65	+20	-23	-0.012	




## 2.5. Conducted Out of Band Emissions

### 2.5.1. Requirement

According to FCC section 22.917(a), 24.238(a) and 27.53(h) the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43+10*\log(P)$ dB. This calculated to be -13dBm. The measurement frequency range is from 30MHz to the 10<sup>th</sup> harmonic of the fundamental frequency.

### 2.5.2. Test Description

Test Setup:




The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.








2.5.3. Test Result






**WCDMA Band IV, CH1312, 1712.4MHz**



**WCDMA Band IV, CH1413, 1732.6MHz**




**WCDMA Band IV, CH1513, 1752.6MHz**







**WCDMA Band II, CH9262, 1852.4MHz**



**WCDMA Band II, CH9400, 1880.0MHz**



**WCDMA Band II, CH9538, 1907.6MHz**




## 2.6. Band Edge

### 2.6.1. Requirement

According to FCC section 22.917(a), 24.238(a) and 27.53(h) the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43+10*\log(P)$ dB.

### 2.6.2. Test Description

Test Setup:




The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.






2.6.3. Test Result

The lowest and highest channels are tested to verify the band edge emissions.







## 2.7. Determining E.R.P. and/or E.I.R.P. from conducted RF output power measurements

### 2.7.1. Requirement

According to FCC section 22.913, the Effective Radiated Power (E.R.P.) of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

According to FCC section 24.232, the broadband PCS mobile station is limited to 2 Watts e.i.r.p. peak power.

According to FCC section 27.50, mobile, and portable (hand-held) stations is limited to 1 Watts e.i.r.p. peak power.

### 2.7.2. Test Description

The test setups refer to section 2.1.3

The relevant equation for determining the maximum E.R.P. or E.I.R.P. from the measured RF output power is given in Equation (1) as follows:

$$\text{E.R.P. or E.I.R.P.} = P_{\text{Meas}} + G_{\text{T}}$$

Where:

E.R.P. or E.I.R.P. effective radiated power or equivalent isotropically radiated power, respectively (expressed in the same units as  $P_{\text{Meas}}$ , e.g., dBm or dBW)

$P_{\text{Meas}}$  measured transmitter output power or PSD, in dBm or dBW

$G_{\text{T}}$  gain of the transmitting antenna, in dBd (E.R.P.) or dBi (E.I.R.P.)

For devices utilizing multiple antennas, see ANSI C63.25-2015 6.4 for guidance with respect to determining the effective array transmit antenna gain term to be used in the above equation.

The following equations demonstrate the mathematical relationship between E.R.P. and E.I.R.P.:

a)  $\text{E.R.P.} = \text{E.I.R.P.} - 2.15$ , where E.R.P. and E.I.R.P. are expressed in consistent units.

b)  $\text{E.I.R.P.} = \text{E.R.P.} + 2.15$ , where E.R.P. and E.I.R.P. are expressed in consistent units.





2.7.3.Test Result

WCDMA Band V							
Band	Channel	Frequency (MHz)	Measured E.R.P.		Limit		Verdict
			dBm	W	dBm	W	
WCDMA	4132	826.4	19.97	0.099	38.5	7	PASS
	4182	836.4	20.04	0.101			PASS
	4233	846.6	20.01	0.100			PASS
HSDPA	4132	826.4	19.01	0.080	38.5	7	PASS
	4182	836.4	18.90	0.078			PASS
	4233	846.6	18.96	0.079			PASS
DC-HSDPA	4132	826.4	19.08	0.081	38.5	7	PASS
	4182	836.4	18.92	0.078			PASS
	4233	846.6	19.08	0.081			PASS
HSUPA	4132	826.4	18.98	0.079	38.5	7	PASS
	4182	836.4	18.89	0.077			PASS
	4233	846.6	19.04	0.080			PASS
HSPA+	4132	826.4	17.43	0.055	38.5	7	PASS
	4182	836.4	17.44	0.055			PASS
	4233	846.6	17.48	0.056			PASS

**Note 1:** For the HSDPA and HSUPA mode, all the subtests were tested and just the worst data were recorded in this report.







WCDMA Band IV							
Band	Channel	Frequency (MHz)	Measured E.I.R.P.		Limit		Verdict
			dBm	W	dBm	W	
WCDMA	1312	1712.4	22.18	0.165	30	1	PASS
	1413	1732.6	22.24	0.167			PASS
	1513	1752.6	22.22	0.167			PASS
HSDPA	1312	1712.4	21.31	0.135	30	1	PASS
	1413	1732.6	21.27	0.134			PASS
	1513	1752.6	21.35	0.136			PASS
DC-HSDPA	1312	1712.4	21.27	0.134	30	1	PASS
	1413	1732.6	21.19	0.132			PASS
	1513	1752.6	21.42	0.139			PASS
HSUPA	1312	1712.4	21.21	0.132	30	1	PASS
	1413	1732.6	21.31	0.135			PASS
	1513	1752.6	21.44	0.139			PASS
HSPA+	1312	1712.4	19.85	0.097	30	1	PASS
	1413	1732.6	19.80	0.095			PASS
	1513	1752.6	19.86	0.097			PASS

**Note 1:** For the HSDPA and HSUPA mode, all the subtests were tested and just the worst data were recorded in this report.



WCDMA Band II							
Band	Channel	Frequency (MHz)	Measured E.I.R.P.		Limit		Verdict
			dBm	W	dBm	W	
WCDMA	9262	1852.4	23.42	0.220	33	2	PASS
	9400	1880.0	23.44	0.221			PASS
	9538	1907.6	23.41	0.219			PASS
HSDPA	9262	1852.4	22.26	0.168	33	2	PASS
	9400	1880.0	22.15	0.164			PASS
	9538	1907.6	22.08	0.161			PASS
DC-HSDPA	9262	1852.4	22.38	0.173	33	2	PASS
	9400	1880.0	22.16	0.164			PASS
	9538	1907.6	22.12	0.163			PASS
HSUPA	9262	1852.4	22.14	0.164	33	2	PASS
	9400	1880.0	22.04	0.160			PASS
	9538	1907.6	22.00	0.158			PASS
HSPA+	9262	1852.4	20.78	0.120	33	2	PASS
	9400	1880.0	20.66	0.116			PASS
	9538	1907.6	20.60	0.115			PASS

**Note 1:** For the HSDPA and HSUPA mode, all the subtests were tested and just the worst data were recorded in this report.




## 2.8. Radiated Out of Band Emissions

### 2.8.1. Requirement


The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43+10*\log(P)$ dB. This calculated to be -13dBm. The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency.

### 2.8.2. Test Description



(For the test frequency from 30MHz to 1GHz)





(For the test frequency above 1GHz)

The EUT is located in a 3m Full-Anechoic Chamber, the cable loss, air loss and so on of the site as factors are pre-calibrated using the "Substitution" method, and calculated to correct the reading. A call is established between the EUT and the SS via a Common Antenna. The EUT is commanded by the SS to operate at the maximum and minimum output power and only the test result of the maximum output power was recorded.

In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground and the Turn Table is actuated to turn from 0° to 360° to determine the maximum value of the radiated power. The emission levels at both horizontal and vertical polarizations should be tested. The Filters consists of Notch Filters and High Pass Filter.

**Note:** When doing measurements above 1GHz, the EUT has been within the 3dB cone width of the horn antenna during horizontal antenna.

### 2.8.3. Test Procedure

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video bandwidth is set to 3MHz for peak measurements.





#### 2.8.4. Test Result

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. The lowest, middle and highest channels are tested to verify the out of band emissions.

The substitution corrections are obtained as described below:

$$A_{\text{SUBST}} = P_{\text{SUBST\_TX}} - P_{\text{SUBST\_RX}} - L_{\text{SUBST\_CABLES}} + G_{\text{SUBST\_TX\_ANT}}$$

$$A_{\text{TOT}} = L_{\text{CABLES}} + A_{\text{SUBST}}$$

Where  $A_{\text{SUBST}}$  is the final substitution correction including receive antenna gain.

$P_{\text{SUBST\_TX}}$  is signal generator level,

$P_{\text{SUBST\_RX}}$  is receiver level,

$L_{\text{SUBST\_CABLES}}$  is cable losses including TX cable,

$G_{\text{SUBST\_TX\_ANT}}$  is substitution antenna gain.

$A_{\text{TOT}}$  is total correction factor including cable loss and substitution correction

During the test, the data of  $A_{\text{TOT}}$  was added in the test spectrum analyze, so spectrum analyze reading is the final values which contain the data of  $A_{\text{TOT}}$ .

**Note1:** The power of the EUT transmitting frequency should be ignored.

**Note2:** All test mode and condition mentioned were considered and evaluated respectively by performing full test, only the worst data were recorded and reported.


**Note3:** All spurious emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

**Note4:** N/A means the frequency is the basic frequency or the base station frequency, they are no need to verdict.

**Note5:** The amplitude of emissions(18GHz to 10th harmonics) which are attenuated more than 20 dB below the limit are not be reported.




WCDMA Band V(WCDMA), Low Channel



Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	42.6230	-65.6	-13.00	Horizontal	PASS
2	60.1000	-66.62	-13.00	Horizontal	PASS
3	109.6200	-71.27	-13.00	Horizontal	PASS
4	234.8750	-73.35	-13.00	Horizontal	PASS
5	828.1380	-41.36	-13.00	Horizontal	N/A
6	871.8320	-44.53	-13.00	Horizontal	N/A




Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	2000.3330	-56.29	-13.00	Horizontal	PASS
2	2991.9970	-58.38	-13.00	Horizontal	PASS
3	6275.5460	-48.06	-13.00	Horizontal	PASS
4	9061.0100	-45.59	-13.00	Horizontal	PASS
5	12069.0120	-42.1	-13.00	Horizontal	PASS
6	15324.5540	-40.98	-13.00	Horizontal	PASS




WCDMA Band V(WCDMA), Low Channel



Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	39.7100	-66.11	-13.00	Vertical	PASS
2	106.7070	-64.11	-13.00	Vertical	PASS
3	252.3520	-75.83	-13.00	Vertical	PASS
4	360.1300	-71.86	-13.00	Vertical	PASS
5	828.1380	-45.34	-13.00	Vertical	N/A
6	871.8320	-47.1	-13.00	Vertical	N/A




Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	2146.3820	-60.01	-13.00	Vertical	PASS
2	4125.1880	-57.07	-13.00	Vertical	PASS
3	6275.5460	-49.58	-13.00	Vertical	PASS
4	9443.5740	-45.19	-13.00	Vertical	PASS
5	11976.4960	-42.33	-13.00	Vertical	PASS
6	14206.8680	-40.42	-13.00	Vertical	PASS




WCDMA Band V(WCDMA), Mid Channel



Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	39.7100	-65.69	-13.00	Horizontal	PASS
2	60.1000	-66.4	-13.00	Horizontal	PASS
3	108.6490	-71.08	-13.00	Horizontal	PASS
4	360.1300	-68.94	-13.00	Horizontal	PASS
5	836.8770	-41.03	-13.00	Horizontal	N/A
6	879.6000	-42.92	-13.00	Horizontal	N/A




Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	2001.6670	-56.43	-13.00	Horizontal	PASS
2	3822.6370	-56.81	-13.00	Horizontal	PASS
3	6275.5460	-49.68	-13.00	Horizontal	PASS
4	8978.4960	-46.73	-13.00	Horizontal	PASS
5	12096.5160	-42.63	-13.00	Horizontal	PASS
6	15347.0580	-40.35	-13.00	Horizontal	PASS






WCDMA Band V(WCDMA), Mid Channel



Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	40.6810	-66.5	-13.00	Vertical	PASS
2	112.5330	-63.58	-13.00	Vertical	PASS
3	360.1300	-71.35	-13.00	Vertical	PASS
4	536.8470	-74.25	-13.00	Vertical	PASS
5	836.8770	-45.39	-13.00	Vertical	N/A
6	880.5710	-45.83	-13.00	Vertical	N/A




Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	1671.5570	-59.37	-13.00	Vertical	PASS
2	2279.7600	-58.49	-13.00	Vertical	PASS
3	3447.5750	-58.53	-13.00	Vertical	PASS
4	6515.5860	-50.58	-13.00	Vertical	PASS
5	9516.0860	-45.36	-13.00	Vertical	PASS
6	14194.3660	-40.78	-13.00	Vertical	PASS




WCDMA Band V(WCDMA), High Channel



Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	41.6520	-64.48	-13.00	Horizontal	PASS
2	58.1580	-65.92	-13.00	Horizontal	PASS
3	106.7070	-71.24	-13.00	Horizontal	PASS
4	360.1300	-69.13	-13.00	Horizontal	PASS
5	847.5580	-41.35	-13.00	Horizontal	N/A
6	892.2220	-43.32	-13.00	Horizontal	N/A




Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	2016.3390	-55.79	-13.00	Horizontal	PASS
2	3627.6050	-56.42	-13.00	Horizontal	PASS
3	6275.5460	-49.06	-13.00	Horizontal	PASS
4	9246.0410	-46.84	-13.00	Horizontal	PASS
5	12064.0110	-42.04	-13.00	Horizontal	PASS
6	15999.6670	-40.89	-13.00	Horizontal	PASS




WCDMA Band V(WCDMA), High Channel



Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	39.7100	-66.67	-13.00	Vertical	PASS
2	105.7360	-63.63	-13.00	Vertical	PASS
3	360.1300	-71.6	-13.00	Vertical	PASS
4	578.5990	-75.11	-13.00	Vertical	PASS
5	847.5580	-48.8	-13.00	Vertical	PASS
6	890.2800	-46.17	-13.00	Vertical	PASS




Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	1396.1320	-61.09	-13.00	Vertical	PASS
2	2314.4380	-58.96	-13.00	Vertical	PASS
3	3820.1370	-57.25	-13.00	Vertical	PASS
4	6275.5460	-49.91	-13.00	Vertical	PASS
5	10388.7310	-44.36	-13.00	Vertical	PASS
6	14204.3670	-40.7	-13.00	Vertical	PASS




WCDMA Band IV(WCDMA), Low Channel



Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	40.6810	-64.75	-13.00	Horizontal	PASS
2	60.1000	-67.54	-13.00	Horizontal	PASS
3	107.6780	-70.4	-13.00	Horizontal	PASS
4	234.8750	-73.01	-13.00	Horizontal	PASS
5	360.1300	-69.31	-13.00	Horizontal	PASS
6	760.1700	-70.32	-13.00	Horizontal	PASS




Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	1711.5710	-27.59	-13.00	Horizontal	PASS
2	2113.0380	-39.33	-13.00	Horizontal	PASS
3	2573.8580	-52.5	-13.00	Horizontal	PASS
4	6275.5460	-49.15	-13.00	Horizontal	PASS
5	9953.6590	-45.02	-13.00	Horizontal	PASS
6	14656.9430	-41.34	-13.00	Horizontal	PASS




WCDMA Band IV(WCDMA), Low Channel



Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	32.9130	-60.72	-13.00	Vertical	PASS
2	107.6780	-62.92	-13.00	Vertical	PASS
3	252.3520	-77.02	-13.00	Vertical	PASS
4	360.1300	-70.94	-13.00	Vertical	PASS
5	484.4140	-74.57	-13.00	Vertical	PASS
6	759.1990	-71.86	-13.00	Vertical	PASS




Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	1711.5710	-28.57	-13.00	Vertical	PASS
2	2112.3710	-46.94	-13.00	Vertical	PASS
3	2573.8580	-52.24	-13.00	Vertical	PASS
4	6275.5460	-49.69	-13.00	Vertical	PASS
5	9943.6570	-44.48	-13.00	Vertical	PASS
6	14711.9520	-40.63	-13.00	Vertical	PASS




WCDMA Band IV(WCDMA), Mid Channel



Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	40.6810	-65.02	-13.00	Horizontal	PASS
2	60.1000	-66.92	-13.00	Horizontal	PASS
3	110.5910	-70	-13.00	Horizontal	PASS
4	232.9330	-72.47	-13.00	Horizontal	PASS
5	360.1300	-68.62	-13.00	Horizontal	PASS
6	760.1700	-70.23	-13.00	Horizontal	PASS




Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	1741.5810	-27	-13.00	Horizontal	PASS
2	2141.7140	-37.43	-13.00	Horizontal	PASS
3	4982.8300	-53.16	-13.00	Horizontal	PASS
4	8498.4160	-48.09	-13.00	Horizontal	PASS
5	11571.4290	-42.45	-13.00	Horizontal	PASS
6	15327.0550	-39.92	-13.00	Horizontal	PASS




WCDMA Band IV(WCDMA), Mid Channel



Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	40.6810	-65.8	-13.00	Vertical	PASS
2	88.2580	-65.67	-13.00	Vertical	PASS
3	107.6780	-63.28	-13.00	Vertical	PASS
4	197.9780	-77.45	-13.00	Vertical	PASS
5	360.1300	-72.36	-13.00	Vertical	PASS
6	604.8150	-72.98	-13.00	Vertical	PASS




Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	1740.9140	-29.4	-13.00	Vertical	PASS
2	2139.7130	-46.1	-13.00	Vertical	PASS
3	4107.6850	-56.14	-13.00	Vertical	PASS
4	6275.5460	-49.93	-13.00	Vertical	PASS
5	9958.6600	-44.14	-13.00	Vertical	PASS
6	14414.4020	-40.45	-13.00	Vertical	PASS




WCDMA Band IV(WCDMA), High Channel



Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	40.6810	-62.79	-13.00	Horizontal	PASS
2	60.1000	-66.66	-13.00	Horizontal	PASS
3	108.6490	-70.32	-13.00	Horizontal	PASS
4	230.9910	-73.36	-13.00	Horizontal	PASS
5	360.1300	-69.41	-13.00	Horizontal	PASS
6	760.1700	-70.53	-13.00	Horizontal	PASS




Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	1753.5850	-27.67	-13.00	Horizontal	PASS
2	2152.3840	-38.16	-13.00	Horizontal	PASS
3	2699.2330	-51.12	-13.00	Horizontal	PASS
4	6275.5460	-49.19	-13.00	Horizontal	PASS
5	10671.2790	-43.48	-13.00	Horizontal	PASS
6	14656.9430	-41.25	-13.00	Horizontal	PASS






WCDMA Band IV(WCDMA), High Channel



Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	40.6810	-66.77	-13.00	Vertical	PASS
2	88.2580	-65.83	-13.00	Vertical	PASS
3	107.6780	-63.86	-13.00	Vertical	PASS
4	360.1300	-72.24	-13.00	Vertical	PASS
5	507.7180	-74.83	-13.00	Vertical	PASS
6	872.8030	-70.74	-13.00	Vertical	PASS




Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	1751.5840	-28.58	-13.00	Vertical	PASS
2	2152.3840	-47.31	-13.00	Vertical	PASS
3	2699.9000	-52.35	-13.00	Vertical	PASS
4	5085.3480	-54.26	-13.00	Vertical	PASS
5	7490.7480	-48.6	-13.00	Vertical	PASS
6	14414.4020	-40.69	-13.00	Vertical	PASS




WCDMA Band II(WCDMA), Low Channel



Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	40.6810	-65.24	-13.00	Horizontal	PASS
2	59.1290	-66.85	-13.00	Horizontal	PASS
3	108.6490	-70.59	-13.00	Horizontal	PASS
4	230.9910	-72.94	-13.00	Horizontal	PASS
5	360.1300	-70.14	-13.00	Horizontal	PASS
6	840.7610	-70.49	-13.00	Horizontal	PASS




Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	1851.6170	-25.55	-13.00	Horizontal	PASS
2	1932.3110	-29.53	-13.00	Horizontal	PASS
3	4407.7350	-54.51	-13.00	Horizontal	PASS
4	6275.5460	-49.22	-13.00	Horizontal	PASS
5	9871.1450	-45.17	-13.00	Horizontal	PASS
6	13646.7740	-39.97	-13.00	Horizontal	PASS




WCDMA Band II(WCDMA), Low Channel



Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	41.6520	-67.58	-13.00	Vertical	PASS
2	106.7070	-63.51	-13.00	Vertical	PASS
3	197.9780	-77.55	-13.00	Vertical	PASS
4	360.1300	-72.77	-13.00	Vertical	PASS
5	585.3950	-73.28	-13.00	Vertical	PASS
6	917.4670	-70.55	-13.00	Vertical	PASS




Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	1852.9510	-28.88	-13.00	Vertical	PASS
2	1931.6440	-39	-13.00	Vertical	PASS
3	3822.6370	-56.15	-13.00	Vertical	PASS
4	6275.5460	-50.56	-13.00	Vertical	PASS
5	9906.1510	-44.99	-13.00	Vertical	PASS
6	14419.4030	-40.63	-13.00	Vertical	PASS




WCDMA Band II(WCDMA), Mid Channel



Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	41.6520	-65.04	-13.00	Horizontal	PASS
2	59.1290	-68.11	-13.00	Horizontal	PASS
3	114.4740	-71.28	-13.00	Horizontal	PASS
4	233.9040	-72.08	-13.00	Horizontal	PASS
5	360.1300	-70.42	-13.00	Horizontal	PASS
6	760.1700	-70.07	-13.00	Horizontal	PASS




Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	1880.9600	-24.45	-13.00	Horizontal	PASS
2	1960.9870	-30.14	-13.00	Horizontal	PASS
3	2994.6650	-59.43	-13.00	Horizontal	PASS
4	5795.4660	-53.11	-13.00	Horizontal	PASS
5	7548.2580	-47.68	-13.00	Horizontal	PASS
6	14679.4470	-40.86	-13.00	Horizontal	PASS




WCDMA Band II(WCDMA), Mid Channel



Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	34.8550	-63.44	-13.00	Vertical	PASS
2	87.2870	-67.09	-13.00	Vertical	PASS
3	113.5040	-64.39	-13.00	Vertical	PASS
4	312.5530	-74.86	-13.00	Vertical	PASS
5	514.5150	-75.01	-13.00	Vertical	PASS
6	785.4150	-71.12	-13.00	Vertical	PASS




Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	1881.6270	-30.12	-13.00	Vertical	PASS
2	1960.9870	-38.08	-13.00	Vertical	PASS
3	4105.1840	-56.34	-13.00	Vertical	PASS
4	6275.5460	-49.83	-13.00	Vertical	PASS
5	9948.6580	-44.78	-13.00	Vertical	PASS
6	14201.8670	-40.68	-13.00	Vertical	PASS




WCDMA Band II(WCDMA), High Channel



Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	40.6810	-64.33	-13.00	Horizontal	PASS
2	61.0710	-66.23	-13.00	Horizontal	PASS
3	107.6780	-69.45	-13.00	Horizontal	PASS
4	231.9620	-71.74	-13.00	Horizontal	PASS
5	360.1300	-69.17	-13.00	Horizontal	PASS
6	760.1700	-70.43	-13.00	Horizontal	PASS




Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	1908.3030	-23.66	-13.00	Horizontal	PASS
2	1986.3290	-31.29	-13.00	Horizontal	PASS
3	2619.8730	-51.16	-13.00	Horizontal	PASS
4	6275.5460	-49.03	-13.00	Horizontal	PASS
5	9453.5760	-44.78	-13.00	Horizontal	PASS
6	14674.4460	-40.66	-13.00	Horizontal	PASS




WCDMA Band II(WCDMA), High Channel



Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	31.9420	-62.12	-13.00	Vertical	PASS
2	86.3160	-67.19	-13.00	Vertical	PASS
3	113.5040	-64.79	-13.00	Vertical	PASS
4	360.1300	-72.44	-13.00	Vertical	PASS
5	618.4080	-73.24	-13.00	Vertical	PASS
6	832.0220	-70.91	-13.00	Vertical	PASS



Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	1906.9690	-28.95	-13.00	Vertical	PASS
2	1987.6630	-38.66	-13.00	Vertical	PASS
3	3827.6380	-57.3	-13.00	Vertical	PASS
4	6275.5460	-50.45	-13.00	Vertical	PASS
5	9531.0890	-44.52	-13.00	Vertical	PASS
6	14286.8810	-41.18	-13.00	Vertical	PASS





## Annex A Test Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test Items	Uncertainty
Output Power	$\pm 2.22\text{dB}$
Bandwidth	$\pm 5\%$
Conducted Spurious Emission	$\pm 2.77\text{dB}$
Radiated Emission	$\pm 2.95\text{dB}$

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .







## Annex B Testing Laboratory Information

### 1. Identification of the Responsible Testing Laboratory

<b>Laboratory Name:</b>	ShenzhenMorlab Communications Technology Co., Ltd.
<b>Laboratory Address:</b>	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
<b>Telephone:</b>	+86 755 36698555
<b>Facsimile:</b>	+86 755 36698525

### 2. Identification of the Responsible Testing Location

<b>Name:</b>	ShenzhenMorlab Communications Technology Co., Ltd.
<b>Address:</b>	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

### 3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.





#### 4. Test Equipments Utilized

##### 4.1 Conducted Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY51511149	N9020A	Agilent	2022.07.04	2023.07.03
Communication Test Station	6200995016	MT8820C	Anritsu	2022.10.11	2023.10.10
Temperature Chamber	S022177101 00089002	KMT-36LF 1A0	KOMEG	2022.11.18	2023.11.17

##### 4.2 List of Software Used

Description	Manufacturer	Software Version
MORLAB EMCR V1.2	MORLAB	V1.2



**4.3 Radiated Test Equipments**

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
System Simulator	152038	CMW500	R&S	2022.10.11	2023.10.10
Receiver	MY54130016	N9038A	Agilent	2022.07.07	2023.07.06
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2022.05.25	2025.05.24
Test Antenna - Horn	9120D-963	BBHA 9120D	Schwarzbeck	2022.05.23	2025.05.24
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2022.07.08	2023.07.07
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2022.07.08	2023.07.07
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2022.07.08	2023.07.07
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-K K-0.5	Qualwave	2022.07.08	2023.07.07
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-K KF-2	Qualwave	2022.07.08	2023.07.07
Preamplifier (10MHz-6GHz)	46732	S10M100L38 02	LUCIX CORP.	2022.07.08	2023.07.07
Preamplifier (2GHz-18GHz)	61171/61172	S020180L32 03	LUCIX CORP.	2022.07.08	2023.07.07
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-40C-S	Decentest	2022.07.23	2023.07.22
Notch Filter	N/A	WRCGV-W Band V	Wainwright	2022.07.08	2023.07.07
Notch Filter	N/A	WRCGV-W Band II	Wainwright	2022.07.08	2023.07.07
Notch Filter	N/A	WRCGV-W Band IV	Wainwright	2022.07.08	2023.07.07
Anechoic Chamber	N/A	9m*6m*6m	CRT	2022.05.10	2025.05.09

END OF REPORT

