

# FCC SAR TEST REPORT

**Product Name:** Handheld Smart Terminal

**Trade Mark:**  or RHINO

**Model No.:** T5se

**Add. Model No.:** N/A

**Report Number:** 220412018SAR-1

**Test Standards:** FCC 47 CFR Part 2 §2.1093  
ANSI/IEEE C95.1-1992  
IEEE Std 1528-2013

**FCC ID:** 2AUOUT5SE

**Test Result:** PASS

**Date of Issue:** August 11, 2022

Prepared for:

**Rhino Mobility LLC**  
**8 The Green, Suite A, Dover, Delaware,19901, USA**


Prepared by:

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**  
**Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and**  
**technology park, Longhua district, Shenzhen, China**

**TEL: +86-755-2823 0888**

**FAX: +86-755-2823 0886**

Prepared by:



Curry Xue  
Test Engineer

Reviewed by:



Henry Lu  
Team Leader

Approved by:



Kevin Liang  
Assistant Manager

Date:

August 11, 2022

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

**Version**

<b>Version No.</b>	<b>Date</b>	<b>Description</b>
V1.0	August 11, 2022	Original Report

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: [info@uttlab.com](mailto:info@uttlab.com)<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

## CONTENTS

<b>1. GENERAL INFORMATION .....</b>	<b>5</b>
1.1. STATEMENT OF COMPLIANCE .....	5
1.2. CLIENT INFORMATION .....	6
1.3. EUT INFORMATION .....	6
1.3.1. GENERAL DESCRIPTION OF EUT .....	6
1.3.2. DESCRIPTION OF ACCESSORIES .....	7
1.3.3. EUT TX FREQUENCY BANDS .....	8
1.3.4. WIRELESS TECHNOLOGIES .....	9
1.4. MAXIMUM CONDUCTED POWER .....	10
1.5. OTHER INFORMATION .....	10
1.6. TEST LOCATION .....	11
1.7. TEST FACILITY .....	11
1.8. GUIDANCE STANDARD .....	11
<b>2. SPECIFIC ABSORPTION RATE (SAR) .....</b>	<b>12</b>
2.1. INTRODUCTION .....	12
2.2. SAR DEFINITION .....	12
2.3. SAR LIMITS .....	12
<b>3. SAR MEASUREMENT SYSTEM .....</b>	<b>13</b>
3.1. SPEAG DASY SYSTEM .....	13
3.1.1. ROBOT .....	13
3.1.2. PROBE .....	14
3.1.3. DATA ACQUISITION ELECTRONICS (DAE) .....	14
3.1.4. PHANTOM .....	15
3.1.5. DEVICE HOLDER .....	16
3.1.6. SYSTEM VALIDATION DIPOLES .....	16
3.2. SAR SCAN PROCEDURE .....	17
3.2.1. SAR REFERENCE MEASUREMENT (DRIFT) .....	17
3.2.2. AREA SCAN .....	17
3.2.3. ZOOM SCAN .....	18
3.2.4. SAR DRIFT MEASUREMENT .....	18
3.3. EQUIPMENT LIST .....	19
3.4. MEASUREMENT UNCERTAINTY .....	20
3.5. TISSUE DIELECTRIC PARAMETER MEASUREMENT & SYSTEM VERIFICATION .....	22
3.5.1. TISSUE SIMULATING LIQUIDS .....	22
3.5.2. SYSTEM CHECK DESCRIPTION .....	24
3.5.3. TISSUE VERIFICATION .....	24
3.5.4. SYSTEM VERIFICATION .....	25
<b>4. SAR MEASUREMENT EVALUATION .....</b>	<b>26</b>
4.1. EUT CONFIGURATION AND SETTING .....	26
4.1.1. WCDMA CONFIGURATION AND TESTING .....	26
4.1.2. LTE CONFIGURATION AND TESTING .....	28
4.1.3. WLAN CONFIGURATION AND TESTING .....	30
4.2. EUT TESTING POSITION .....	32
4.2.1. HEAD EXPOSURE CONDITIONS .....	32
4.2.2. BODY-WORN ACCESSORY EXPOSURE CONDITIONS .....	34
4.2.3. HOTSPOT ACCESSORY EXPOSURE CONDITIONS .....	35
4.3. MEASURED CONDUCTED POWER RESULT .....	36
4.3.1. CONDUCTED POWER OF WCDMA BANDS .....	36
4.3.2. CONDUCTED POWER OF LTE BANDS .....	36
4.3.3. CONDUCTED POWER OF WLAN .....	52
4.3.4. CONDUCTED POWER OF BT .....	53
4.4. SAR TESTING RESULTS .....	54

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

- 4.4.1. SAR TEST REDUCTION CONSIDERATIONS.....54
- 4.4.2. SAR RESULTS FOR HEAD EXPOSURE CONDITION .....57
- 4.4.3. SAR RESULTS FOR BODY-WORN EXPOSURE CONDITION (SEPARATION DISTANCE IS 1.0 CM).....63
- 4.4.4. SAR RESULTS FOR HOTSPOT EXPOSURE CONDITION (SEPARATION DISTANCE IS 1.0 CM) .....68
- 4.5. SAR MEASUREMENT VARIABILITY .....77
  - 4.5.1. REPEATED MEASUREMENT.....77
  - 4.5.2. DUT HOLDER PERTURBATIONS .....78
- 4.6. SIMULTANEOUS MULTI-BAND TRANSMISSION EVALUATION .....79
  - 4.6.1. SIMULTANEOUS TRANSMISSION SAR TEST EXCLUSION CONSIDERATIONS .....79
  - 4.6.2. SIMULTANEOUS TRANSMISSION POSSIBILITIES .....80
  - 4.6.3. MAX. STANDALONE SAR .....81
  - 4.6.4. SUM OF SAR.....82

- Appendix A. SAR Plots of System Verification
- Appendix B. SAR Plots of SAR Measurement
- Appendix C. Calibration Certificate for Probe and Dipole
- Appendix D. Photographs of EUT and Setup

# 1. GENERAL INFORMATION

## 1.1. STATEMENT OF COMPLIANCE

The maximum results of Specific Absorption Rate (SAR) found during testing for the EUT are as follows:


Equipment Class	Mode	Highest Reported Head SAR <sub>1g</sub> (W/kg)	Highest Reported Body-worn SAR <sub>1g</sub> (1.0 cm Gap) (W/kg)	Highest Reported Hotspot SAR <sub>1g</sub> (1.0 cm Gap) (W/kg)
PCE	WCDMA Band II	0.414	0.782	0.782
	WCDMA Band IV	0.444	0.946	0.946
	WCDMA Band V	0.344	0.387	0.387
	LTE Band 2	0.634	0.974	0.974
	LTE Band 5	0.399	0.423	0.423
	LTE Band 7	0.744	1.107	1.107
	LTE Band 12(17)	0.385	0.464	0.464
	LTE Band 13	0.403	0.434	0.434
	LTE Band 14	0.343	0.345	0.345
	LTE Band 25	0.761	0.959	0.959
	LTE Band 26	0.381	0.390	0.390
	LTE Band 30	0.481	<b>1.148</b>	<b>1.159</b>
	LTE Band 41	0.385	0.662	0.662
	LTE Band 66(4)	0.519	1.048	1.048
LTE Band 71	0.379	0.421	0.421	
DTS	2.4G WLAN	0.540	0.139	0.139
NII	5.2-5.3G WLAN	0.553	0.178	0.178
	5.8G WLAN	<b>0.768</b>	0.242	0.242
DSS	Bluetooth	0.174	0.052	N/A
DXX	NFC	N/A	N/A	N/A
<b>Max SAR</b>		<b>0.768</b>	<b>1.113</b>	<b>1.159</b>
<b>Highest Simultaneous Transmission SAR</b>		<b>Head (W/kg)</b>	<b>Body-worn (W/kg)</b>	<b>Hotspot (W/kg)</b>
<b>PCE + DTS</b>		1.301	1.287	1.287
<b>PCE + NII</b>		1.529	1.390	1.390
<b>PCE + DSS</b>		0.935	1.200	N/A

## 1.2. CLIENT INFORMATION

<b>Applicant:</b>	Rhino Mobility LLC
<b>Address of Applicant:</b>	8 The Green, Suite A, Dover, Delaware,19901, USA
<b>Manufacturer:</b>	Rhino Mobility LLC
<b>Address of Manufacturer:</b>	8 The Green, Suite A, Dover, Delaware,19901, USA

## 1.3. EUT INFORMATION

### 1.3.1. General Description of EUT

<b>Product Name:</b>	Handheld Smart Terminal
<b>Trade Mark:</b>	 or RHINO
<b>Model No.:</b>	T5se
<b>Add. Model No.:</b>	N/A
<b>FCC ID:</b>	2AUOUT5SE
<b>DUT Stage:</b>	Identical Prototype
<b>IMEI Code:</b>	354657110011334, 354657110010013, 354657110011375
<b>Software Version:</b>	T5se(001)_20220624 (Provided by the customer)
<b>Hardware Version:</b>	AL_Z06_MB_V12 (Provided by the customer)
<b>Sample Received Date:</b>	April 13, 2022
<b>Sample Tested Date:</b>	May 5, 2022 to July 11, 2022
Note: The T5se have two LCD modules from different vendors. This report has evaluated and pre-testing of two batches of LCD modules, with only the worst data recorded in the report.	

### 1.3.2. Description of Accessories

Adapter	
<b>Model No.:</b>	XY-PP018U1
<b>Input:</b>	100-240 V~50/60 Hz 0.5A
<b>Output:</b>	3.6-6.0 V $\equiv$ 3.0A, 6.0-9.0 V $\equiv$ 2.0A, 9.0-12.0 V $\equiv$ 1.5A
<b>AC Cable:</b>	N/A
<b>DC Cable:</b>	N/A

Internal Battery	
<b>Model No.:</b>	BPT5se
<b>Battery Type:</b>	Lithium-ion Rechargeable Battery
<b>Rated Voltage:</b>	3.85 Vdc
<b>Limited Charge Voltage:</b>	4.4 Vdc
<b>Rated Capacity:</b>	3000 mAh

External Battery Pack	
<b>Model No.:</b>	T5SE-EBAT-3K-BLK
<b>Battery Type:</b>	Lithium-ion Rechargeable Battery
<b>Rated Voltage:</b>	3.85 Vdc
<b>Limited Charge Voltage:</b>	4.4 Vdc
<b>Rated Capacity:</b>	3030 mAh

Cable	
<b>Description:</b>	USB Type-C Plug Cable
<b>Cable Type:</b>	Shielded without ferrite
<b>Length:</b>	1 Meter

### 1.3.3. EUT Tx Frequency Bands

RF Type	Band(s)	Tx Frequency Range (Unit: MHz)
WCDMA	WCDMA Band II:	1852.4 - 1907.6
	WCDMA Band IV:	1712.4 - 1752.6
	WCDMA Band V:	826.4 - 846.6
LTE	LTE Band 2:	1850.7 - 1909.3 (1.4M), 1851.5 - 1908.5 (3M), 1852.5 - 1907.5 (5M), 1855 - 1905 (10M), 1857.5 - 1902.5 (15M), 1860 - 1900 (20M)
	LTE Band 4:	1710.7 - 1754.3 (1.4M), 1711.5 - 1753.5 (3M), 1712.5 - 1752.5 (5M), 1715 - 1750 (10M), 1717.5 - 1747.5 (15M), 1720 - 1745 (20M)
	LTE Band 5:	824.7 - 848.3 (1.4M), 825.5 - 847.5 (3M), 826.5 - 846.5 (5M), 829 - 844 (10M)
	LTE Band 7:	2502.5 - 2567.5 (5M), 2505 - 2565 (10M), 2507.5 - 2562.5 (15M), 2510 - 2560 (20M)
	LTE Band 12:	699.7 - 715.3 (1.4M), 700.5 - 714.5 (3M), 701.5 - 713.5 (5M), 704 - 711 (10M)
	LTE Band 13:	779.5 - 784.5 (5M), 782 (10M)
	LTE Band 14:	790.5 - 795.5 (5M), 793 (10M)
	LTE Band 17:	706.5 - 713.5 (5M), 709 - 711 (10M)
	LTE Band 25:	1850.7 - 1914.3 (1.4M), 1851.5 - 1913.5 (3M), 1852.5 - 1912.5 (5M), 1855 - 1910 (10M), 1857.5 - 1907.5 (15M), 1860 - 1905 (20M)
	LTE Band 26:	814.7 - 848.3 (1.4M), 815.5 - 847.5 (3M), 816.5 - 846.5 (5M), 819 - 844 (10M), 821.5 - 841.5 (15M)
	LTE Band 30:	2307.5 - 2312.5 (5M), 2310 (10M)
	LTE Band 41:	2498.5 - 2687.5 (5M), 2501 - 2685 (10M), 2503.5 - 2682.5 (15M), 2506 - 2680 (20M)
	LTE Band 66:	1710.7 - 1779.3 (1.4M), 1711.5 - 1778.5 (3M), 1712.5 - 1777.5 (5M), 1715 - 1775 (10M), 1717.5 - 1772.5 (15M), 1720 - 1770 (20M)
LTE Band 71:	665.5 - 695.5 (5M), 668 - 693 (10M), 670.5 - 690.5 (15M), 673 - 688 (20M)	
WLAN	2.4 GHz:	2412 - 2462
	U-NII-1:	5180 - 5240
	U-NII-2A:	5260 - 5320
	U-NII-3:	5745 - 5825
Bluetooth	2.4 GHz:	2402 - 2480
NFC	13.553 - 13.567 MHz	13.56

**Note 1:**

According to 201504 FCC TCB workshop RF exposure slides, for overlapping bands, only larger band was tested.

1. The maximum output power, including tolerance, for the smaller band is = the larger band to qualify for the SAR test exclusion.
2. The channel bandwidth and other operating parameters for the smaller band is fully supported by the larger band.
  - Band 66 (1710 - 1780 MHz) SAR can support band 4 (1710 - 1755 MHz).
  - Band 12 (699 - 716 MHz) SAR can support band 17 (704 - 716 MHz).



### 1.3.4. Wireless Technologies

<b>WCDMA</b>	RMC HSDPA HSUPA HSPA+
<b>LTE</b>	QPSK 16QAM 64QAM DL CA VoLTE
<b>2.4G WLAN</b>	802.11b 802.11g 802.11n (HT20/HT40)
<b>5G WLAN</b>	802.11a 802.11n (HT20/HT40) 802.11ac (VHT20/VHT40/VHT80)
<b>Bluetooth</b>	BR+EDR LE
<b>Antenna Type</b>	LDS Antenna
<b>Power Reduction</b>	Not Support
<b>Dynamic Antenna</b>	Not Support
<b>Wireless Router (Hotspot)</b>	2.4G WLAN: Support 5.2G WLAN: Support 5.3G WLAN: Not Support 5.8G WLAN: Support
<b>VOIP</b>	Support Note: Since this device supports VOIP capability through 3rd party apps software, we have evaluated data mode for head and body-worn SAR.

### 1.4. MAXIMUM CONDUCTED POWER

The maximum conducted average power including tune-up tolerance is shown as below.

➤ **WCDMA**

Mode	Maximum conducted average power (dBm)		
	WCDMA Band II	WCDMA Band V	WCDMA Band IV
RMC 12.2K	20.5	23.5	21.5
HSDPA	20.0	23.5	21.0
HSUPA	19.0	22.5	20.0
HSPA+	18.5	21.5	19.00

➤ **LTE**

Band	Mode	Maximum Conducted Power (dBm)
LTE Band 2	QPSK / 16QAM / 64QAM	24.0
LTE Band 4	QPSK / 16QAM / 64QAM	24.5
LTE Band 5	QPSK / 16QAM / 64QAM	25.0
LTE Band 7	QPSK / 16QAM / 64QAM	24.5
LTE Band 12	QPSK / 16QAM / 64QAM	25.0
LTE Band 13	QPSK / 16QAM / 64QAM	25.0
LTE Band 14	QPSK / 16QAM / 64QAM	25.0
LTE Band 17	QPSK / 16QAM / 64QAM	25.0
LTE Band 25	QPSK / 16QAM / 64QAM	24.0
LTE Band 26	QPSK / 16QAM / 64QAM	24.5
LTE Band 30	QPSK / 16QAM / 64QAM	24.0
LTE Band 41	QPSK / 16QAM / 64QAM	26.0
LTE Band 66	QPSK / 16QAM / 64QAM	24.5
LTE Band 71	QPSK / 16QAM / 64QAM	25.0

➤ **2.4GHz WLAN**

Mode	Maximum Conducted Power (dBm)
802.11b	18.0
802.11g	15.5
802.11n-HT20	15.0
802.11n-HT40	15.5

➤ **5GHz WLAN**

Mode	Maximum Conducted Power (dBm)			
	U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
802.11a	14.0	14.0	--	14.5
802.11n-HT20	13.5	14.0	--	14.0
802.11n-HT40	13.0	13.5	--	13.0
802.11ac-VHT20	13.0	13.0	--	13.5
802.11ac-VHT40	12.5	13.0	--	13.0
802.11ac-VHT80	12.5	12.5	--	12.5

➤ **Bluetooth**

Mode	Modulation	Maximum Conducted Power (dBm)
BR + EDR	GFSK	11.0
	π/4-DQPSK	9.0
	8-DPSK	9.0
LE	GFSK	4.5

### 1.5. OTHER INFORMATION

None.

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

---

## 1.6. TEST LOCATION

---

### Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Telephone: +86 (0) 755 2823 0888

Fax: +86 (0) 755 2823 0886

---

---

## 1.7. TEST FACILITY

---

The test facility is recognized, certified, or accredited by the following organizations:

### Shenzhen UnionTrust Quality and Technology Co., Ltd.

#### CNAS-Lab Code: L9069

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

#### A2LA-Lab Certificate No.: 4312.01

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

#### ISED Wireless Device Testing Laboratories

CAB identifier: CN0032

#### FCC Accredited Lab.

Designation Number: CN1194

Test Firm Registration Number: 259480

---

---

## 1.8. GUIDANCE STANDARD

The tests documented in this report were performed in accordance with FCC 47 CFR Part 2 §2.1093, IEEE Std 1528-2013, ANSI/IEEE C95.1-1992, the following FCC Published RF exposure KDB procedures:

KDB 865664 D01 v01r04

KDB 865664 D02 v01r02

KDB 248227 D01 v02r02

KDB 447498 D01 v06

KDB 648474 D04 v01r03

KDB 941225 D01 v03r01

KDB 941225 D05 v02r05

KDB 941225 D05A v01r02

KDB 941225 D06 v02r01

KDB 941225 D07 v01r02

---

### Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: [info@uttlab.com](mailto:info@uttlab.com)

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

## 2. SPECIFIC ABSORPTION RATE (SAR)

### 2.1. INTRODUCTION

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling, by appropriate techniques, to produce specific absorption rates (SARs) as averaged over the whole-body, any 1 g or any 10 g of tissue (defined as a tissue volume in the shape of a cube). All SAR values are to be averaged over any six-minute period. When portable device was used within 20 cm of the user's body, SAR evaluation of the device will be required. The SAR limit in chapter 2.3.

### 2.2. SAR DEFINITION

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

### 2.3. SAR LIMITS

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0


**Note:**

- 1) Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.
- 2) At frequencies above 6.0 GHz, SAR limits are not applicable and MPE limits for power density should be applied at 5 cm or more from the transmitting device.
- 3) The SAR limit is specified in FCC 47 CFR Part 2 §2.1093, ANSI/IEEE C95.1-1992.

### 3. SAR MEASUREMENT SYSTEM

#### 3.1. SPEAG DASY SYSTEM

DASY system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY5 software defined. The DASY software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.




##### 3.1.1. Robot


The DASY system uses the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY4: CS7MB) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability  $\pm 0.02$  mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)


### 3.1.2. Probe

The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.


<b>Model</b>	EX3DV4	
<b>Construction</b>	Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
<b>Frequency</b>	10 MHz to 6 GHz Linearity: $\pm 0.2$ dB	
<b>Directivity</b>	$\pm 0.3$ dB in HSL (rotation around probe axis) $\pm 0.5$ dB in tissue material (rotation normal to probe axis)	
<b>Dynamic Range</b>	10 $\mu$ W/g to 100 mW/g Linearity: $\pm 0.2$ dB (noise: typically $< 1$ $\mu$ W/g)	
<b>Dimensions</b>	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	


<b>Model</b>	ES3DV3	
<b>Construction</b>	Symmetrical design with triangular core. Interleaved sensors. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
<b>Frequency</b>	10 MHz to 4 GHz Linearity: $\pm 0.2$ dB	
<b>Directivity</b>	$\pm 0.2$ dB in HSL (rotation around probe axis) $\pm 0.3$ dB in tissue material (rotation normal to probe axis)	
<b>Dynamic Range</b>	5 $\mu$ W/g to 100 mW/g Linearity: $\pm 0.2$ dB	
<b>Dimensions</b>	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm	

### 3.1.3. Data Acquisition Electronics (DAE)


<b>Model</b>	DAE3, DAE4	
<b>Construction</b>	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detectors for mechanical surface detection and emergency robot stop.	
<b>Measurement Range</b>	-100 to +300 mV (16-bit resolution and two range settings: 4mV, 400mV)	
<b>Input Voltage</b> <b>Offset</b>	$< 5\mu$ V (with auto zero)	
<b>Input Bias Current</b>	$< 50$ fA	
<b>Dimensions</b>	60 x 60 x 68 mm	


### 3.1.4. Phantom

<b>Model</b>	Twin SAM	
<b>Construction</b>	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.	
<b>Material</b>	Vinylester, glass fiber reinforced (VE-GF)	
<b>Shell Thickness</b>	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
<b>Dimensions</b>	Length: 1000 mm Width: 500 mm Height: adjustable feet	
<b>Filling Volume</b>	approx. 25 liters	


<b>Model</b>	ELI	
<b>Construction</b>	Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.	
<b>Material</b>	Vinylester, glass fiber reinforced (VE-GF)	
<b>Shell Thickness</b>	2.0 ± 0.2 mm (bottom plate)	
<b>Dimensions</b>	Major axis: 600 mm Minor axis: 400 mm	
<b>Filling Volume</b>	approx. 30 liters	

### 3.1.5. Device Holder

<b>Model</b>	Mounting Device	
<b>Construction</b>	In combination with the Twin SAM Phantom or ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to IEC, IEEE, FCC or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat).	
<b>Material</b>	POM	

<b>Model</b>	Laptop Extensions Kit	
<b>Construction</b>	Simple but effective and easy-to-use extension for Mounting Device that facilitates the testing of larger devices according to IEC 62209-2 (e.g., laptops, cameras, etc.). It is lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner.	
<b>Material</b>	POM, Acrylic glass, Foam	

### 3.1.6. System Validation Dipoles

<b>Model</b>	D-Serial	
<b>Construction</b>	Symmetrical dipole with 1/4 balun. Enables measurement of feed point impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions.	
<b>Frequency</b>	750 MHz to 5800 MHz	
<b>Return Loss</b>	> 20 dB	
<b>Power Capability</b>	> 100 W (f < 1GHz), > 40 W (f > 1GHz)	



### 3.2. SAR SCAN PROCEDURE

#### 3.2.1. SAR Reference Measurement (drift)

Prior to the SAR test, local SAR shall be measured at a stationary reference point where the SAR exceeds the lower detection limit of the measurement system.

#### 3.2.2. Area Scan

Measurement procedures for evaluating the SAR of wireless device start with a coarse measurement grid to determine the approximate location of the local peak SAR values. This is known as the area-scan procedure. All antennas and radiating structures that may contribute to the measured SAR or influence the SAR distribution must be included in the area scan. The area scan measurement resolution must enable the extrapolation algorithms of the SAR system to correctly identify the peak SAR location(s) for subsequent zoom scan measurements to correctly determine the 1-g SAR. Area scans are performed at a constant distance from the phantom surface, determined by the measurement frequencies. When a measured peak is closer than 1/2 the zoom scan volume dimension (x, y) from the edge of the area scan region, unless the entire peak and gram-averaging volume are both captured within the zoom scan volume, the area scan must be repeated by shifting and expanding the area scan region to ensure all peaks are away from the area scan boundary. The area scan resolutions specified in the table below must be applied to the SAR measurements.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 mm ± 1 mm	1/2 · δ · ln(2) mm ± 0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°
Maximum area scans spatial resolution: Δx <sub>Area</sub> , Δy <sub>Area</sub>	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

### 3.2.3. Zoom Scan

To evaluate the peak spatial-average SAR values with respect to 1 g or 10 g cubes, fine resolution volume scans, called zoom scans, are performed at the peak SAR locations identified during the area scan. If the cube volume within the zoom scan chosen to calculate the peak spatial-average SAR touches any boundary of the zoom-scan volume, the zoom scan shall be repeated with the center of the zoom-scan volume shifted to the new maximum SAR location. For any secondary peaks found in the area scan that are within 2 dB of the maximum peak and are not within this zoom scan, the zoom scan shall be performed for such peaks, unless the peak spatial-average SAR at the location of the maximum peak is more than 2 dB below the applicable SAR limit (i.e., 1 W/kg for a 1.6 W/kg 1 g limit, or 1.26 W/kg for a 2 W/kg 10 g limit). The zoom scan resolutions specified in the table below must be applied to the SAR measurements.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{Zoom}, \Delta y_{Zoom}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom Scan spatial resolution, normal to phantom surface	uniform grid: $\Delta Z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta Z_{Zoom}(1)$ : between 1 <sup>ST</sup> two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta Z_{Zoom}(n>1)$ : between subsequent points	≤ 1.5 · $\Delta Z_{Zoom}(n-1)$ mm	
Minimum zoom scan volume	x, y, z	≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm	
<p>Note: <math>\delta</math> is the penetration depth of a plane-wave at normal incidence to the tissue medium; see IEEE Std 1528-2013 for details.</p> <p>* When zoom scan is required and the reported SAR from the area scan based 1-g SAR estimation procedures of KDB Publication 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.</p>				

### 3.2.4. SAR Drift Measurement

The local SAR (or conducted power) shall be measured at exactly the same location as in 3.2.1 section. The absolute value of the measurement drift (the difference between the SAR measured in 3.2.1 and 3.2.4 section) shall be recorded. The SAR drift shall be kept within ± 5%.

### 3.3. EQUIPMENT LIST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Interval
System Validation Dipole	SPEAG	D750V3	1109	May 17, 2021	3 Year
System Validation Dipole	SPEAG	D835V2	4d005	Apr. 13, 2021	3 Year
System Validation Dipole	SPEAG	D1750V2	1086	April 14, 2021	3 Year
System Validation Dipole	SPEAG	D1900V2	509	April 14, 2021	3 Year
System Validation Dipole	SPEAG	D2300V2	1087	May 19, 2021	3 Year
System Validation Dipole	SPEAG	D2450V2	1014	May 19, 2021	3 Year
System Validation Dipole	SPEAG	D2600V2	1153	May 19, 2021	3 Year
System Validation Dipole	SPEAG	D5GHzV2	1280	May. 17, 2021	3 Year
Dosimetric E-Field Probe	SPEAG	ES3DV3	3090	Apr. 06, 2022	1 Year
Data Acquisition Electronics	SPEAG	DAE4	662	Mar. 24, 2022	1 Year
Dosimetric E-Field Probe	SPEAG	EX3DV4	7506	May 31, 2022	1 Year
Data Acquisition Electronics	SPEAG	DAE4	1557	Jan. 20, 2022	1 Year
Wideband Radio Communication Tester	R&S	CMW500	120932	Apr. 15, 2022	1 Year
E7515B UXM 5G Wireless Test Platform	KEYSIGHT	E7515B	MY59020226	Apr. 15, 2022	1 Year
ENA Series Network Analyzer	Agilent	8753ES	US39170317	Nov. 05, 2021	1 Year
Dielectric Assessment Kit	SPEAG	DAK-3.5	1056	N/A	N/A
USB/GPIB Interface	Agilent	82357B	N10149	N/A	N/A
Signal Generator	R&S	SMB100A	103718	Apr. 15, 2022	1 Year
POWER METER	R&S	NRP	101293	Nov. 05, 2021	1 Year
Thermometer	Shanghai Gao Zhi Precision Instrument Co., Ltd.	HB6801	18022507	Nov. 10, 2021	1 Year
Dual Directional Coupler	Agilent	778D	MY52180234	Nov. 05, 2021	1 Year
Amplifier	Mini-Circuit	ZHL42	QA1252001	Apr. 15, 2022	1 Year
DC Source	Agilent	66319B	MY43000795	Nov. 05, 2021	1 Year

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

### 3.4. MEASUREMENT UNCERTAINTY

Per KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval.

**TABLE 1 EXPOSURE ASSESSMENT UNCERTAINTY FOR HANDSET SAR**

Source of Uncertainty	Tolerance (± %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (1g) (± %)	Standard Uncertainty (10g) (± %)	Vi Veff
<b>Measurement System</b>								
Probe Calibration (< 3 GHz)	7.5	N (k=2)	2	1	1	3.75	3.75	∞
Probe Calibration (> 3 GHz)	6.3	N (k=2)	2	1	1	3.15	3.15	∞
Axial Isotropy	1.2	N (k=2)	2	0.7	0.7	0.42	0.42	∞
Hemispherical Isotropy	3.2	N (k=2)	2	0.7	0.7	1.12	1.12	∞
Boundary Effects	2	Rectangular	√3	1	1	1.15	1.15	∞
Linearity	0.9	N (k=2)	2	1	1	0.45	0.45	∞
Detection Limits	0.25	Rectangular	√3	1	1	0.14	0.14	∞
Modulation Response	2.4	Rectangular	√3	1	1	1.39	1.39	∞
Readout Electronics	0.3	Normal	1	1	1	0.30	0.30	∞
Response Time	0	Rectangular	√3	1	1	0.00	0.00	∞
Integration Time	1.7	Rectangular	√3	1	1	0.98	0.98	∞
RF Ambient – Noise	3	Rectangular	√3	1	1	1.73	1.73	∞
RF Ambient – Reflections	3	Rectangular	√3	1	1	1.73	1.73	∞
Probe Positioner	0.4	Rectangular	√3	1	1	0.23	0.23	∞
Probe Positioning	6.7	Rectangular	√3	1	1	3.87	3.87	∞
Max. SAR Evaluation	4	Rectangular	√3	1	1	2.31	2.31	∞
<b>Test Sample Related</b>								
Device Positioning	2.3 / 2.4	Normal	1	1	1	2.30	2.40	30
Device Holder	2.8 / 2.8	Normal	1	1	1	2.80	2.80	30
Power Drift	5	Rectangular	√3	1	1	2.89	2.89	∞
Power Scaling	0	Rectangular	√3	1	1	0.00	0.00	∞
<b>Phantom and Setup</b>								
Phantom Uncertainty	7.9	Rectangular	√3	1	1	4.56	4.56	∞
SAR correction	1.2 / 0.97	Rectangular	√3	1	0.84	0.69	0.47	∞
Liquid Conductivity (Meas.)	2.5	Rectangular	√3	0.78	0.71	1.13	1.02	∞
Liquid Permittivity (Meas.)	2.5	Rectangular	√3	0.26	0.26	0.38	0.38	∞
Temp. unc. - Conductivity	3.4	Rectangular	√3	0.78	0.71	1.53	1.39	∞
Temp. unc. - Permittivity	0.4	Rectangular	√3	0.23	0.26	0.05	0.06	∞
<b>Combined Standard Uncertainty (k = 1) (≤ 3 GHz)</b>						9.64	9.62	
<b>Combined Standard Uncertainty (k = 1) (&gt; 3 GHz)</b>						9.42	9.40	
<b>Max. Expanded Uncertainty (k = 2)</b>						<b>19.27</b>	<b>19.23</b>	

**TABLE 2 SYSTEM VALIDATION Measurement uncertainty**

Source of Uncertainty	Tolerance (± %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (1g) (± %)	Standard Uncertainty (10g) (± %)	Vi Veff
<b>Measurement System</b>								
Probe Calibration (< 3 GHz)	7.5	N (k=2)	2	1	1	3.75	3.75	∞
Probe Calibration (> 3 GHz)	6.3	N (k=2)	2	1	1	3.15	3.15	∞
Axial Isotropy	1.2	N (k=2)	2	0.7	0.7	0.42	0.42	∞
Hemispherical Isotropy	3.2	N (k=2)	2	0.7	0.7	1.12	1.12	∞
Boundary Effects	2	Rectangular	√3	1	1	1.15	1.15	∞
Linearity	0.9	N (k=2)	2	1	1	0.45	0.45	∞
Detection Limits	0.25	Rectangular	√3	1	1	0.14	0.14	∞
Modulation Response	2.4	Rectangular	√3	1	1	1.39	1.39	∞
Readout Electronics	0.3	Normal	1	1	1	0.30	0.30	∞
Response Time	0	Rectangular	√3	1	1	0.00	0.00	∞
Integration Time	1.7	Rectangular	√3	1	1	0.98	0.98	∞
RF Ambient – Noise	3	Rectangular	√3	1	1	1.73	1.73	∞
RF Ambient – Reflections	3	Rectangular	√3	1	1	1.73	1.73	∞
Probe Positioner	0.4	Rectangular	√3	1	1	0.23	0.23	∞
Probe Positioning	6.7	Rectangular	√3	1	1	3.87	3.87	∞
Max. SAR Evaluation	4	Rectangular	√3	1	1	2.31	2.31	∞
<b>Test Sample Related</b>								
Device Positioning	2.3 / 2.4	Normal	1	1	1	2.30	2.40	30
Device Holder	2.8 / 2.8	Normal	1	1	1	2.80	2.80	30
Power Drift	5	Rectangular	√3	1	1	2.89	2.89	∞
Power Scaling	0	Rectangular	√3	1	1	0.00	0.00	∞
<b>Phantom and Setup</b>								
Phantom Uncertainty	7.9	Rectangular	√3	1	1	4.56	4.56	∞
SAR correction	1.2 / 0.97	Rectangular	√3	1	0.84	0.69	0.47	∞
Liquid Conductivity (Meas.)	2.5	Rectangular	√3	0.78	0.71	1.13	1.02	∞
Liquid Permittivity (Meas.)	2.5	Rectangular	√3	0.26	0.26	0.38	0.38	∞
Temp. unc. - Conductivity	3.4	Rectangular	√3	0.78	0.71	1.53	1.39	∞
Temp. unc. - Permittivity	0.4	Rectangular	√3	0.23	0.26	0.05	0.06	∞
<b>Combined Standard Uncertainty (k = 1) (≤ 3 GHz)</b>						9.64	9.62	
<b>Combined Standard Uncertainty (k = 1) (&gt; 3 GHz)</b>						9.42	9.40	
<b>Max. Expanded Uncertainty (k = 2)</b>						<b>19.27</b>	<b>19.23</b>	


### 3.5. TISSUE DIELECTRIC PARAMETER MEASUREMENT & SYSTEM VERIFICATION

Per KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval.

#### 3.5.1. Tissue Simulating Liquids

The temperature of the tissue-equivalent medium used during measurement must also be within 18 °C to 25 °C and within ± 2 °C of the temperature when the tissue parameters are characterized. The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements. The parameters should be re-measured after each 3 - 4 days of use; or earlier if the dielectric parameters can become out of tolerance.

The depth of tissue-equivalent liquid in a phantom must be ≥ 15.0 cm with ≤ ± 0.5 cm variation for SAR measurements ≤ 3 GHz and ≥ 10.0 cm with ≤ ± 0.5 cm variation for measurements > 3 GHz. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in Table-3.1.



Tissue Dielectric Parameters for Head and Body				
Target Frequency (MHz)	Head		Body	
	$\epsilon_r$	$\sigma$ (S/m)	$\epsilon_r$	$\sigma$ (S/m)
750	41.9	0.89	55.5	0.96
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
1450	40.5	1.20	54.0	1.30
1640	40.3	1.29	53.8	1.40
1750	40.1	1.37	53.4	1.49
1800	40.0	1.40	53.3	1.52
1900	40.0	1.40	53.3	1.52
2000	40.0	1.40	53.3	1.52
2300	39.5	1.67	52.9	1.81
2450	39.2	1.80	52.7	1.95
2600	39.0	1.96	52.5	2.16
3500	37.9	2.91	51.3	3.31
5200	36.0	4.66	49.0	5.30
5300	35.9	4.76	48.9	5.42
5500	35.6	4.96	48.6	5.65
5600	35.5	5.07	48.5	5.77
5800	35.3	5.27	48.2	6.00

(  $\epsilon_r$  = relative permittivity,  $\sigma$  = conductivity and  $\rho = 1000 \text{ kg/m}^3$ )

The following table gives the recipes for tissue simulating liquids.

Recipes of Tissue Simulating Liquid								
Tissue Type	Bactericide	DGBE	HEC	NaCl	Sucrose	Triton X-100	Water	Diethylene Glycol Mono-hexylether
H750	0.2	-	0.2	1.4	57.0	-	41.1	-
H835	0.1	-	1.0	1.4	57.0	-	40.5	-
H900	0.1	-	1.0	1.5	56.5	-	40.9	-
H1450	-	45.5	-	0.7	-	-	53.8	-
H1640	-	45.8	-	0.5	-	-	53.7	-
H1750	-	44.5	-	0.3	-	-	55.2	-
H1800	-	44.9	-	0.2	-	-	54.9	-
H1900	-	44.9	-	0.2	-	-	54.9	-
H2000	-	50	-	-	-	-	50	-
H2300	-	44.9	-	0.1	-	-	55.0	-
H2450	-	45.0	-	0.1	-	-	54.9	-
H2600	-	45.1	-	0.1	-	-	54.8	-
H3500	-	8.0	-	0.2	-	20.0	71.8	-
H5G	-	-	-	-	-	17.2	65.52	17.3
B750	0.2	-	0.2	0.8	48.8	-	50.0	-
B835	0.2	-	0.2	0.9	48.5	-	50.2	-
B900	0.2	-	0.2	0.9	48.2	-	50.5	-
B1450	-	34.0	-	0.3	-	-	65.7	-
B1640	-	32.5	-	0.3	-	-	67.2	-
B1750	-	29.4	-	0.4	-	-	70.2	-
B1800	-	29.5	-	0.4	-	-	70.1	-
B1900	-	29.5	-	0.3	-	-	70.2	-
B2000	-	30.0	-	0.2	-	-	69.8	-
B2300	-	31.0	-	0.1	-	-	68.9	-
B2450	-	31.4	-	0.1	-	-	68.5	-
B2600	-	31.8	-	0.1	-	-	68.1	-
B3500	-	28.8	-	0.1	-	-	71.1	-
B5G	-	-	-	-	-	10.7	78.6	10.7

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886


E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

### 3.5.2. System Check Description

The system check procedure provides a simple, fast, and reliable test method that can be performed daily or before every SAR measurement. The objective here is to ascertain that the measurement system has acceptable accuracy and repeatability. This test requires a flat phantom and a radiating source. The system verification setup is shown as below.



### 3.5.3. Tissue Verification

The measuring results for tissue simulating liquid are shown as below.

Test Date	Tissue Type	Frequency (MHz)	Liquid Temp. (°C)	Measured Conductivity ( $\sigma$ )	Measured Permittivity ( $\epsilon_r$ )	Target Conductivity ( $\sigma$ )	Target Permittivity ( $\epsilon_r$ )	Conductivity Deviation (%)	Permittivity Deviation (%)
Jul. 05, 2022	Head	750	21.1	0.852	41.600	0.89	41.90	-4.27	-0.72
Jun. 28, 2022	Head	835	21.1	0.916	41.030	0.90	41.50	1.78	-1.13
Jun. 16, 2022	Head	1750	21.0	1.328	41.170	1.37	40.10	-3.07	2.67
Jun. 27, 2022	Head	1900	21.4	1.373	38.760	1.40	40.00	-1.93	-3.10
Jun. 22, 2022	Head	2300	21.2	1.671	39.190	1.67	39.50	0.06	-0.78
Jun. 20, 2022	Head	2450	21.2	1.811	38.510	1.80	39.20	0.61	-1.76
Jun. 16, 2022	Head	2600	21.2	1.978	38.030	1.96	39.00	0.92	-2.49
Jun. 24, 2022	Head	5250	20.4	4.741	36.265	4.71	35.90	0.66	1.02
Jun. 24, 2022	Head	5800	20.4	5.313	35.464	5.27	35.30	0.82	0.46

Note:

The dielectric properties of the tissue simulating liquid must be measured within 24 hours before the SAR testing and within  $\pm 5\%$  of the target values. The variation of the liquid temperature must be within  $\pm 2^\circ\text{C}$  during the test.



### 3.5.4. System Verification

The measuring result for system verification is tabulated as below.

Test Date	Tissue Type	Frequency (MHz)	1W Target SAR-1g (W/kg)	Measured SAR-1g (W/kg)	Normalized to 1W SAR-1g (W/kg)	Deviation (%)	Dipole S/N	Probe S/N	DAE S/N
Jul. 05, 2022	Head	750	8.39	0.087	8.74	4.17	1109	3090	662
Jun. 28, 2022	Head	835	9.49	0.099	9.90	4.32	4d005	3090	662
Jun. 16, 2022	Head	1750	36.40	0.354	35.40	-2.75	1086	3090	662
Jun. 27, 2022	Head	1900	39.90	0.408	40.80	2.26	509	3090	662
Jun. 22, 2022	Head	2300	47.20	0.489	48.90	3.60	1087	3090	662
Jun. 20, 2022	Head	2450	51.80	0.517	51.70	-0.19	1014	3090	662
Jun. 16, 2022	Head	2600	54.80	0.550	55.00	0.36	1153	3090	662
Jun. 24, 2022	Head	5250	79.20	8.19	81.90	3.41	1280	7506	1557
Jun. 24, 2022	Head	5800	80.60	8.50	85.00	5.46	1280	7506	1557

Note:

Comparing to the reference SAR value, the validation data should be within its specification of 10%. The result indicates the system check can meet the variation criterion and the plots can be referred to Appendix A of this report.

## 4. SAR MEASUREMENT EVALUATION

### 4.1. EUT CONFIGURATION AND SETTING

#### Connections between EUT and System Simulator

For WWAN SAR testing, the EUT was linked and controlled by base station emulator. Communication between the EUT and the emulator was established by air link. The distance between the EUT and the communicating antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of EUT. The EUT was set from the emulator to radiate maximum output power during SAR testing.

#### 4.1.1. WCDMA Configuration and Testing

##### WCDMA Handsets Head SAR

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode.

##### WCDMA Handsets Body-worn SAR

SAR for body-worn configurations is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCHn configurations supported by the handset with 12.2 kbps RMC as the primary mode.

##### Handsets with Release 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body-worn configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSDPA using the HSDPA body SAR procedures in the “Release 5 HSDPA Data Devices”, for the highest reported SAR body-worn exposure configuration in 12.2 kbps RMC. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

##### Handsets with Release 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body-worn configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSPA using the HSPA body SAR procedures in the “Release 6 HSPA Data Devices”, for the highest reported body-worn exposure SAR configuration in 12.2 kbps RMC. When VOIP is applicable for next to the ear head exposure in HSPA, the 3G SAR test reduction procedure is applied to HSPA with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body-worn measurements is tested for next to the ear head exposure.

##### Release 5 HSDPA Data Devices

The 3G SAR test reduction procedure is applied to body SAR with 12.2 kbps RMC as the primary mode. Otherwise, body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. HSDPA is configured according to the applicable UE category of a test device. The number of HS-DSCH / HS-PDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the H-set for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 4 ms and a CQI repetition factor of 2 to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors ( $\beta_c$ ,  $\beta_d$ ), and HS-DPCCH power offset parameters ( $\Delta_{ACK}$ ,  $\Delta_{NACK}$ ,  $\Delta_{CQI}$ ) are set according to values indicated in below. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the H-set.

Sub-test	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c / \beta_d$	$\beta_{hs}^{(1)}$	CM (dB) <sup>(2)</sup>	MPR
1	2 / 15	15 / 15	64	2 / 15	4 / 15	0.0	0
2	12 / 15 <sup>(3)</sup>	15 / 15 <sup>(3)</sup>	64	12 / 15 <sup>(3)</sup>	24 / 15	1.0	0
3	15 / 15	8 / 15	64	15 / 8	30 / 15	1.5	0.5
4	15 / 15	4 / 15	64	15 / 4	30 / 15	1.5	0.5

#### Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

Note 1:  $\Delta_{ACK}, \Delta_{NACK}$  and  $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs} / \beta_c = 30 / 15 \Leftrightarrow \beta_{hs} = 30 / 15 * \beta_c$ .

Note 2:  $CM = 1$  for  $\beta_c / \beta_d = 12 / 15, \beta_{hs} / \beta_c = 24 / 15$ .

Note 3: For subtest 2 the  $\beta_c / \beta_d$  ratio of 12 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 11 / 15$  and  $\beta_d = 15 / 15$ .

**Release 6 HSUPA Data Devices**

The 3G SAR test reduction procedure is applied to body SAR with 12.2 kbps RMC as the primary mode. Otherwise, body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA. When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode. Otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing. Due to inner loop power control requirements in HSPA, a communication test set is required for output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and E-DCH configurations for HSPA are configured according to the  $\beta$  values indicated in below.

Sub-test	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c / \beta_d$	$\beta_{hs}^{(1)}$	$\beta_{ec}$	$\beta_{ed}$	$\beta_{ed}$ (SF)	$\beta_{ed}$ (codes)	CM <sup>(2)</sup> (dB)	MPR (dB)	AG <sup>(4)</sup> Index	E-TFCI
1	11 / 15 <sup>(3)</sup>	15 / 15 <sup>(3)</sup>	64	11 / 15 <sup>(3)</sup>	22 / 15	209 / 225	1039 / 225	4	1	1.0	0.0	20	75
2	6 / 15	15 / 15	64	6 / 15	12 / 15	12 / 15	94 / 75	4	1	3.0	2.0	12	67
3	15 / 15	9 / 15	64	15 / 9	30 / 15	30 / 15	$\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$	4	2	2.0	1.0	15	92
4	2 / 15	15 / 15	64	2 / 15	4 / 15	2 / 15	56 / 75	4	1	3.0	2.0	17	71
5	15 / 15 <sup>(4)</sup>	15 / 15 <sup>(4)</sup>	64	15 / 15 <sup>(4)</sup>	30 / 15	24 / 15	134 / 15	4	1	1.0	0.0	21	81

Note 1:  $\Delta_{ACK}, \Delta_{NACK}$  and  $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs} / \beta_c = 30 / 15 \Leftrightarrow \beta_{hs} = 30 / 15 * \beta_c$ .

Note 2:  $CM = 1$  for  $\beta_c / \beta_d = 12 / 15, \beta_{hs} / \beta_c = 24 / 15$ . For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the  $\beta_c / \beta_d$  ratio of 11 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 10 / 15$  and  $\beta_d = 15 / 15$ .

Note 4: For subtest 5 the  $\beta_c / \beta_d$  ratio of 15 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 14 / 15$  and  $\beta_d = 15 / 15$ .

Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.

Note 6:  $\beta_{ed}$  cannot be set directly; it is set by Absolute Grant Value.

**HSPA+ SAR Guidance**

The 3G SAR test reduction procedure is applied to HSPA+ (uplink) with 12.2 kbps RMC as the primary mode. Otherwise, when SAR is required for Rel. 6 HSPA, SAR is required for Rel. 7 HSPA+. Power is measured for HSPA+ that supports uplink 16QAM according to configurations in Table C.11.1.4 of 3GPP TS 34.121-1 to determine SAR test reduction.

**DC-HSDPA SAR Guidance**

The 3G SAR test reduction procedure is applied to DC-HSDPA with 12.2 kbps RMC as the primary mode. Otherwise, when SAR is required for Rel. 5 HSDPA, SAR is required for Rel. 8 DC-HSDPA. Power is measured for DC-HSDPA according to the H-Set 12, FRC configuration in Table C.8.1.12 of 3GPP TS 34.121-1 to determine SAR test reduction. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to be acceptable.

### 4.1.2. LTE Configuration and Testing


UE power class is category 3. The LTE maximum power reduction (MPR) in accordance with 3GPP TS 36.101 is active all times during LTE operation. The allowed MPR for the maximum output power please refer to the tune up procedure.

In addition, the device is compliant with additional maximum power reduction (A-MPR) requirements defined in 3GPP TS 36.101 section 6.2.4 that was disabled for all FCC compliance testing.

A properly configured base station simulator is used for the SAR and power measurements, so spectrum plots for each RB allocation and offset configuration are not included in the SAR report to demonstrate that the tested RB allocations have been correctly established at the maximum output power conditions.

#### TDD-LTE Setup Configurations

According to KDB 941225 D05, SAR testing for TDD-LTE device must be tested using a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by the defined 3GPP TDD-LTE configurations. The TDD-LTE of this device supports frame structure type 2 defined in 3GPP TS 36.211 section 4.2, and the frame structure configuration can be referred to below.



**3GPP TS 36.211 Table 4.2-1: Configuration of Special Subframe**

Special Subframe Configuration	Normal Cyclic Prefix in Downlink		Extended Cyclic Prefix in Downlink			
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal Cyclic Prefix in Uplink	Extended Cyclic Prefix in Uplink		Normal Cyclic Prefix in Uplink	Extended Cyclic Prefix in Uplink
0	6592·Ts	2192·Ts	2560·Ts	7680·Ts	2192·Ts	2560·Ts
1	19760·Ts			20480·Ts		
2	21952·Ts			23040·Ts		
3	24144·Ts			25600·Ts		
4	26336·Ts	4384·Ts	5120·Ts	7680·Ts	4384·Ts	5120·Ts
5	6592·Ts			20480·Ts		
6	19760·Ts			23040·Ts		
7	21952·Ts			12800·Ts		
8	24144·Ts	-	-	-	-	-
9	13168·Ts	-	-	-	-	-

Uplink-Downlink Configurations and duty cycle												
Uplink-Downlink Configuration	Downlink-to-Uplink Switch-Point Periodicity	Subframe Number										Duty-Cycle
		0	1	2	3	4	5	6	7	8	9	
0	5 ms	D	S	U	U	U	D	S	U	U	U	63.33%
1	5 ms	D	S	U	U	D	D	S	U	U	D	43.33%
2	5 ms	D	S	U	D	D	D	S	U	D	D	23.33%
3	10 ms	D	S	U	U	U	D	D	D	D	D	31.67%
4	10 ms	D	S	U	U	D	D	D	D	D	D	21.67%
5	10 ms	D	S	U	D	D	D	D	D	D	D	11.67%
6	5 ms	D	S	U	U	U	D	S	U	U	D	53.33%

Considering the highest transmission duty cycle, TDD-LTE was tested using Uplink-Downlink Configuration 0 with 6 uplink subframe and 2 special subframe. The special subframe was set to special subframe configuration 7 using extended cyclic prefix uplink. Therefore, SAR testing for TDD-LTE was performed at the maximum output power with highest transmission duty cycle of 63.33%.

**LTE DL CA**

This device supports DL CA, E-UTRA CA configurations and bandwidth combination sets defined for inter-band CA as bellow table.

Table 5.6A.1-2: E-UTRA CA configurations and bandwidth combination sets defined for inter-band CA										
E-UTRA CA configuration / Bandwidth combination set										
E-UTRA CA Configuration	CA configurations	EUTRA Bands	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	20 MHz	Maximum aggregated bandwidth [MHz]	Bandwidth combination set
CA_2A-5A	CA_2A-5A	2			Yes	Yes	Yes	Yes	30	0
		5			Yes	Yes				
		2			Yes	Yes			20	1
		5			Yes	Yes				
CA_4A-5A	CA_4A-5A	4			Yes	Yes			20	0
		5			Yes	Yes				
		4			Yes	Yes	Yes	Yes	30	1
		5			Yes	Yes				
CA_25A-26A	CA_25A-26A	25		Yes	Yes	Yes	Yes	Yes	35	0
		26	Yes	Yes	Yes	Yes	Yes			
		25		Yes	Yes	Yes			20	1
		26		Yes	Yes	Yes				
		25			Yes	Yes			20	2
		26			Yes	Yes				
CA_5A-30A	CA_5A-30A	5			Yes	Yes			20	0
		30			Yes	Yes				
CA_5A-66A	CA_5A-66A	5			Yes	Yes			30	0
		66			Yes	Yes	Yes	Yes		

### 4.1.3. WLAN Configuration and Testing

In general, various vendor specific external test software and chipset based internal test modes are typically used for SAR measurement. These chipset-based test mode utilities are generally hardware and manufacturer dependent, and often include substantial flexibility to reconfigure or reprogram a device. A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement. The test frequencies established using test mode must correspond to the actual channel frequencies. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. In addition, a periodic transmission duty factor is required for current generation SAR systems to measure SAR correctly. The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

According to KDB 248227 D01, this device has installed WLAN engineering testing software which can provide continuous transmitting RF signal. During WLAN SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

#### Initial Test Configuration

An initial test configuration is determined for OFDM transmission modes in 2.4 GHz and 5 GHz bands according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band.

#### Subsequent Test Configuration

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units.

Additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. When the highest reported SAR for the initial test configuration according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg, SAR is not required for that subsequent test configuration.

#### SAR Test Configuration and Channel Selection

When multiple channel bandwidth configurations in a frequency band have the same specified maximum output power, the initial test configuration is using largest channel bandwidth, lowest order modulation, lowest data rate, and lowest order 802.11 mode (i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n). After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following.

- 1) The channel closest to mid-band frequency is selected for SAR measurement.
- 2) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

**Test Reduction for U-NII-1 (5.2 GHz) and U-NII-2A (5.3 GHz) Bands**

For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following.

- 1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is  $\leq 1.2$  W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition).
- 2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is  $\leq 1.2$  W/kg, SAR is not required for the band with lower maximum output power in that test configuration.





**4.2. EUT TESTING POSITION**

**4.2.1. Head Exposure Conditions**

RF Exposure Conditions	Test Position	Separation Distance	SAR test exclusion
Head	Right Cheek	0 cm	N/A
	Right Tilted		
	Left Cheek		
	Left Tilted		

Note:


- 1) Head exposure for voice mode of handset is limited to next to the ear exposure conditions.
- 2) Devices that are designed to transmit next to the ear must be tested using the SAM phantom.
- 3) Other head exposure conditions, for example, in-front-of the face, should be tested using a flat phantom according to the required published RF exposure KDB procedures.
- 4) When data mode operates in next to the ear configurations, either data alone or in conjunction with voice transmissions, SAR evaluation is required for such use conditions.
- 5) When device supports VoIP, SAR evaluation for head Exposure Conditions using the most appropriate wireless data mode configurations is required.





**Define two imaginary lines on the handset**

- 1) The vertical centerline passes through two points on the front side of the handset - the midpoint of the width  $w_t$  of the handset at the level of the acoustic output, and the midpoint of the width  $w_b$  of the bottom of the handset.
- 2) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- 3) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.




**4.2.2. Body-worn Accessory Exposure Conditions**

RF Exposure Conditions	Test Position	Separation Distance	SAR test exclusion
Body-worn	Front Face	0 ~ 2.5 cm	N/A
	Rear Face		

Note:

- 1) Body-worn accessories that do not contain metallic or conductive components may be tested according to worst-case exposure configurations, typically according to the smallest test separation distance required for the group of body-worn accessories with similar operating and exposure characteristics. All body-worn accessories containing metallic components are tested in conjunction with the host device.
- 2) Body-worn accessory SAR compliance is based on a single minimum test separation distance for all wireless and operating modes applicable to each body-worn accessory used by the host, and according to the relevant voice and/or data mode transmissions and operations. If a body-worn accessory supports voice only operations in its normal and expected use conditions, testing of data mode for body-worn compliance is not required.
- 3) A conservative minimum test separation distance for supporting off-the-shelf body-worn accessories that may be acquired by users of consumer handsets should be used to test for body-worn accessory SAR compliance. This distance is determined by the handset manufacturer according to the typical body-worn accessories users may acquire at the time of equipment certification, but not more than 2.5 cm, to enable users to purchase aftermarket body-worn accessories with the required minimum separation.
- 4) Devices that are designed to operate on the body of users using lanyards and straps or without requiring additional body-worn accessories must be tested for SAR compliance using a conservative minimum test separation distance  $\leq 5$  mm to support compliance.
- 5) When device supports VoIP, SAR evaluation for body-worn accessory Exposure Conditions using the most appropriate wireless data mode configurations is required.
- 6) Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories.
- 7) When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is  $> 1.2$  W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for the body-worn accessory with a headset attached to the handset.




**4.2.3. Hotspot Accessory Exposure Conditions**

RF Exposure Conditions	Test Position	Separation Distance	SAR test exclusion
Hotspot	Front Face	1 cm	Note 2/3
	Rear Face		
	Left Side		
	Right Side		
	Top Side		
	Bottom Side		

Note:

- 1) The SAR test separation distance for hotspot mode is determined according to device form factor. When the overall length and width of a device is > 9 cm x 5 cm (~3.5" x 2"), a test separation distance of 10 mm is required for hotspot mode SAR measurements. A test separation distance of 5 mm or less is required for smaller devices. The SAR test separation distance for hotspot mode is determined according to device form factor.
- 2) Hotspot mode SAR is measured for all edges and surfaces of the device with a transmitting antenna located within 25 mm from that surface or edge.
- 3) Based on the antenna location shown on appendix D of this report, the SAR testing required for hotspot mode is listed on section 4.5.1.



### 4.3. MEASURED CONDUCTED POWER RESULT

#### 4.3.1. Conducted Power of WCDMA Bands

The measuring conducted average power (Unit: dBm) is shown as below.

Band Channel	WCDMA Band II			WCDMA Band V			WCDMA Band IV			3GPP MPR (dB)
	9262	9400	9538	1312	1413	1513	4132	4182	4233	
Frequency (MHz)	1852.4	1880.0	1907.6	1712.4	1732.6	1752.6	826.4	836.4	846.6	
RMC 12.2K	19.73	19.86	19.69	22.96	22.88	22.81	20.81	20.67	20.58	-
HSDPA Subtest-1	19.51	19.58	19.54	22.81	22.78	22.75	20.59	20.60	20.54	0
HSDPA Subtest-2	18.34	18.40	18.47	21.95	21.87	21.79	19.77	19.58	19.32	0
HSDPA Subtest-3	17.74	18.04	18.01	21.47	21.40	21.32	18.89	18.73	18.69	0.5
HSDPA Subtest-4	17.88	17.83	17.77	21.46	21.36	21.31	18.91	18.74	18.66	0.5
HSUPA Subtest-1	18.44	18.56	18.53	21.92	21.85	21.75	19.41	19.04	18.94	0
HSUPA Subtest-2	18.21	18.34	18.31	21.94	21.86	21.81	19.44	19.12	19.01	2
HSUPA Subtest-3	17.69	17.83	17.81	21.44	21.36	21.29	18.78	18.59	18.49	1
HSUPA Subtest-4	18.73	18.91	18.88	21.98	21.88	21.82	19.30	19.12	19.04	2
HSUPA Subtest-5	18.21	18.32	18.29	21.48	21.39	21.31	19.28	18.99	18.97	0
HSPA+ Subtest-1	18.12	18.24	18.15	21.24	21.15	21.13	18.46	18.35	18.28	2.5

#### 4.3.2. Conducted Power of LTE Bands

The measuring conducted average power (Unit: dBm) is shown as below.

➤ **LTE Band 2**

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 18607	Mid CH 18900	High CH 19193		Low CH 18607	Mid CH 18900	High CH 19193		Low CH 18607	Mid CH 18900	High CH 19193	
			1850.7 MHz	1880.0 MHz	1909.3 MHz		1850.7 MHz	1880.0 MHz	1909.3 MHz		1850.7 MHz	1880.0 MHz	1909.3 MHz	
2 / 1.4M	1	0	23.29	23.36	23.42	0	22.42	22.94	22.49	1	21.60	22.09	21.61	2
	1	2	23.47	23.37	23.58	0	22.60	22.95	22.43	1	21.78	22.04	21.60	2
	1	5	23.42	23.50	23.54	0	22.65	22.89	22.54	1	21.84	22.06	21.59	2
	3	0	22.66	22.68	22.61	1	21.53	21.61	21.59	2	20.65	20.75	20.78	3
	3	1	22.71	22.39	22.61	1	21.63	21.51	21.53	2	20.83	20.70	20.71	3
	3	3	22.57	22.47	22.59	1	21.67	21.41	21.51	2	20.81	20.53	20.62	3
	6	0	22.61	22.51	22.64	1	21.71	21.55	21.68	2	20.79	20.60	20.85	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 18615	Mid CH 18900	High CH 19185		Low CH 18615	Mid CH 18900	High CH 19185		Low CH 18615	Mid CH 18900	High CH 19185	
			1851.5 MHz	1880.0 MHz	1908.5 MHz		1851.5 MHz	1880.0 MHz	1908.5 MHz		1851.5 MHz	1880.0 MHz	1908.5 MHz	
2 / 3M	1	0	23.47	23.60	23.66	0	22.51	23.14	22.72	1	21.69	22.31	21.89	2
	1	7	23.54	23.51	23.62	0	22.62	23.09	22.56	1	21.79	22.26	21.80	2
	1	14	23.57	23.49	23.65	0	22.52	23.12	22.66	1	21.73	22.25	21.78	2
	8	0	22.51	22.67	22.76	1	21.39	21.83	21.68	2	20.52	20.93	20.92	3
	8	3	22.47	22.50	22.58	1	21.38	21.75	21.58	2	20.47	20.99	20.71	3
	8	7	22.53	22.63	22.67	1	21.52	21.84	21.67	2	20.63	21.02	20.87	3
	15	0	22.53	22.57	22.61	1	21.66	21.69	21.57	2	20.83	20.80	20.67	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			18625 MHz	18900 MHz	19175 MHz		18625 MHz	18900 MHz	19175 MHz		18625 MHz	18900 MHz	19175 MHz	
2 / 5M	1	0	23.16	23.47	23.45	0	22.29	22.58	22.31	1	21.42	21.74	21.51	2
	1	12	23.30	23.48	23.48	0	22.40	22.45	22.34	1	21.54	21.55	21.45	2
	1	24	23.27	23.49	23.49	0	22.36	22.46	22.40	1	21.49	21.66	21.58	2
	12	0	22.39	22.63	22.66	1	21.53	21.71	21.60	2	20.72	20.88	20.65	3
	12	6	22.43	22.50	22.56	1	21.38	21.61	21.49	2	20.57	20.76	20.74	3
	12	13	22.40	22.53	22.53	1	21.46	21.63	21.57	2	20.62	20.68	20.72	3
	25	0	22.52	22.54	22.59	1	21.56	21.56	21.67	2	20.71	20.74	20.76	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			18650 MHz	18900 MHz	19150 MHz		18650 MHz	18900 MHz	19150 MHz		18650 MHz	18900 MHz	19150 MHz	
2 / 10M	1	0	23.37	23.62	23.67	0	22.93	22.57	22.68	1	22.12	21.69	21.86	2
	1	24	23.35	23.51	23.66	0	23.08	22.61	22.69	1	22.28	21.77	21.89	2
	1	49	23.38	23.50	23.71	0	23.11	22.63	22.68	1	22.31	21.87	21.90	2
	25	0	22.58	22.63	22.60	1	21.71	21.70	21.77	2	20.88	20.78	20.98	3
	25	12	22.40	22.55	22.54	1	21.64	21.62	21.65	2	20.82	20.75	20.76	3
	25	25	22.48	22.61	22.53	1	21.61	21.53	21.74	2	20.77	20.70	20.83	3
	50	0	22.58	22.71	22.59	1	21.60	21.74	21.60	2	20.68	20.97	20.79	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			18675 MHz	18900 MHz	19125 MHz		18675 MHz	18900 MHz	19125 MHz		18675 MHz	18900 MHz	19125 MHz	
2 / 15M	1	0	23.23	23.60	23.43	0	22.91	22.58	23.00	1	21.98	21.75	22.11	2
	1	37	23.36	23.48	23.53	0	23.10	22.50	22.92	1	22.21	21.61	22.15	2
	1	74	23.38	23.46	23.52	0	23.10	22.47	22.93	1	22.35	21.66	22.11	2
	36	0	22.59	22.72	22.72	1	21.65	21.64	21.65	2	20.89	20.72	20.88	3
	36	19	22.52	22.46	22.66	1	21.60	21.50	21.63	2	20.72	20.73	20.76	3
	36	39	22.54	22.63	22.74	1	21.50	21.53	21.63	2	20.60	20.71	20.82	3
	75	0	22.55	22.60	22.65	1	21.59	21.61	21.62	2	20.65	20.67	20.73	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			18700 MHz	18900 MHz	19100 MHz		18700 MHz	18900 MHz	19100 MHz		18700 MHz	18900 MHz	19100 MHz	
2 / 20M	1	0	23.32	23.57	23.62	0	22.34	22.52	22.49	1	21.44	21.63	21.74	2
	1	50	23.39	23.61	23.62	0	22.34	22.58	22.43	1	21.41	21.70	21.60	2
	1	99	23.43	23.58	23.62	0	22.37	22.56	22.54	1	21.44	21.79	21.76	2
	50	0	23.64	23.59	23.67	1	22.83	22.52	21.59	2	22.02	21.66	20.70	3
	50	25	23.63	23.57	23.73	1	22.88	22.62	21.53	2	21.93	21.86	20.74	3
	50	50	23.50	23.67	23.70	1	22.88	22.55	21.51	2	21.98	21.69	20.63	3
	100	0	22.39	22.64	22.70	1	21.38	21.71	21.68	2	20.45	20.90	20.75	3

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

➤ LTE Band 4

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 19957	Mid CH 20175	High CH 20393		Low CH 19957	Mid CH 20175	High CH 20393		Low CH 19957	Mid CH 20175	High CH 20393	
			1710.7 MHz	1732.5 MHz	1754.3 MHz		1710.7 MHz	1732.5 MHz	1754.3 MHz		1710.7 MHz	1732.5 MHz	1754.3 MHz	
4 / 1.4M	1	0	23.45	23.38	23.41	0	22.58	23.00	22.49	1	21.64	22.16	21.67	2
	1	2	23.43	23.32	23.39	0	22.64	22.85	22.52	1	21.78	21.91	21.70	2
	1	5	23.52	23.34	23.42	0	22.66	22.87	22.46	1	21.79	22.04	21.57	2
	3	0	22.45	22.58	22.54	0	21.56	21.57	21.50	1	20.71	20.65	20.58	2
	3	1	22.69	22.70	22.62	0	21.57	21.60	21.58	1	20.68	20.82	20.81	2
	3	3	22.56	22.65	22.73	0	21.61	21.67	21.54	1	20.81	20.75	20.69	2
	6	0	22.57	22.63	22.59	1	21.60	21.55	21.56	2	20.75	20.64	20.65	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 19965	Mid CH 20175	High CH 20385		Low CH 19965	Mid CH 20175	High CH 20385		Low CH 19965	Mid CH 20175	High CH 20385	
			1711.5 MHz	1732.5 MHz	1753.5 MHz		1711.5 MHz	1732.5 MHz	1753.5 MHz		1711.5 MHz	1732.5 MHz	1753.5 MHz	
4 / 3M	1	0	23.45	23.62	23.59	0	23.24	22.65	22.59	1	22.40	21.89	21.83	2
	1	7	23.45	23.53	23.76	0	23.24	22.62	22.68	1	22.46	21.84	21.80	2
	1	14	23.44	23.58	23.69	0	23.24	22.62	22.64	1	22.38	21.87	21.70	2
	8	0	22.66	22.63	22.56	1	21.78	21.57	21.59	2	21.02	20.77	20.83	3
	8	3	22.65	22.46	22.61	1	21.82	21.66	21.60	2	20.88	20.79	20.84	3
	8	7	22.58	22.58	22.60	1	21.91	21.57	21.61	2	21.04	20.75	20.82	3
	15	0	22.67	22.62	22.58	1	21.76	21.47	21.79	2	20.89	20.53	20.93	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 19975	Mid CH 20175	High CH 20375		Low CH 19975	Mid CH 20175	High CH 20375		Low CH 19975	Mid CH 20175	High CH 20375	
			1712.5 MHz	1732.5 MHz	1752.5 MHz		1712.5 MHz	1732.5 MHz	1752.5 MHz		1712.5 MHz	1732.5 MHz	1752.5 MHz	
4 / 5M	1	0	23.40	23.44	23.43	0	22.34	22.56	22.55	1	21.45	21.62	21.80	2
	1	12	23.47	23.36	23.49	0	22.35	22.42	22.49	1	21.57	21.60	21.59	2
	1	24	23.40	23.46	23.40	0	22.33	22.51	22.51	1	21.55	21.72	21.60	2
	12	0	22.61	22.64	22.59	1	21.44	21.60	21.67	2	20.50	20.78	20.89	3
	12	6	22.58	22.67	22.57	1	21.67	21.65	21.75	2	20.81	20.88	20.94	3
	12	13	22.65	22.59	22.52	1	21.54	21.53	21.60	2	20.62	20.65	20.70	3
	25	0	22.64	22.69	22.58	1	21.61	21.67	21.59	2	20.85	20.84	20.83	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20000	Mid CH 20175	High CH 20350		Low CH 20000	Mid CH 20175	High CH 20350		Low CH 20000	Mid CH 20175	High CH 20350	
			1715.0 MHz	1732.5 MHz	1750.0 MHz		1715.0 MHz	1732.5 MHz	1750.0 MHz		1715.0 MHz	1732.5 MHz	1750.0 MHz	
4 / 10M	1	0	23.58	23.58	23.61	0	22.66	23.26	22.65	1	21.75	22.35	21.78	2
	1	24	23.69	23.50	23.54	0	22.71	23.21	22.51	1	21.83	22.43	21.74	2
	1	49	23.70	23.51	23.59	0	22.70	23.18	22.56	1	21.93	22.36	21.80	2
	25	0	22.62	22.61	22.70	1	21.65	21.75	21.63	2	20.85	20.81	20.81	3
	25	12	22.72	22.61	22.59	1	21.77	21.75	21.62	2	20.93	20.94	20.84	3
	25	25	22.62	22.62	22.59	1	21.78	21.74	21.60	2	21.00	20.80	20.80	3
	50	0	22.62	22.67	22.62	1	21.67	21.71	21.75	2	20.81	20.87	20.83	3

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			20025	20175	20325		20025	20175	20325		20025	20175	20325	
4 / 15M	1	0	23.49	23.48	23.53	0	23.02	23.21	22.53	1	22.10	22.27	21.76	2
	1	37	23.43	23.40	23.47	0	22.94	23.09	22.50	1	22.06	22.25	21.60	2
	1	74	23.42	23.32	23.50	0	22.95	23.19	22.52	1	22.06	22.32	21.68	2
	36	0	22.59	22.60	22.54	1	21.59	21.54	21.51	2	20.78	20.73	20.57	3
	36	19	22.68	22.69	22.66	1	21.60	21.58	21.58	2	20.81	20.78	20.79	3
	36	39	22.60	22.60	22.62	1	21.58	21.63	21.67	2	20.69	20.74	20.88	3
	75	0	22.61	22.62	22.62	1	21.64	21.60	21.64	2	20.80	20.80	20.86	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			20050	20175	20300		20050	20175	20300		20050	20175	20300	
4 / 20M	1	0	23.49	23.50	23.67	0	22.61	22.56	22.65	1	21.71	21.64	21.75	2
	1	50	23.58	23.50	23.60	0	22.54	22.58	22.64	1	21.73	21.66	21.72	2
	1	99	23.61	23.56	23.53	0	22.58	22.63	22.63	1	21.77	21.77	21.81	2
	50	0	23.68	23.66	23.56	1	22.92	22.61	22.75	2	22.02	21.86	21.99	3
	50	25	23.78	23.55	23.66	1	22.97	22.55	22.62	2	22.08	21.78	21.69	3
	50	50	23.64	23.83	23.63	1	23.16	22.47	22.59	2	22.25	21.70	21.79	3
	100	0	22.57	22.61	22.54	1	21.73	21.74	21.42	2	20.97	20.88	20.50	3

➤ LTE Band 5

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			20407	20525	20643		20407	20525	20643		20407	20525	20643	
5 / 1.4M	1	0	24.32	24.29	24.35	0	23.43	23.85	23.31	1	22.57	22.97	22.37	2
	1	2	24.38	24.21	24.38	0	23.34	23.85	23.34	1	22.50	23.10	22.41	2
	1	5	24.39	24.29	24.39	0	23.38	23.84	23.23	1	22.59	23.00	22.42	2
	3	0	23.34	23.32	23.34	1	22.58	22.50	22.29	2	21.77	21.61	21.47	2
	3	1	23.38	23.31	23.27	1	22.42	22.38	22.25	2	21.66	21.54	21.36	2
	3	3	23.33	23.34	23.26	1	22.49	22.40	22.24	2	21.57	21.65	21.33	2
	6	0	23.45	23.43	23.37	1	22.48	22.32	22.31	2	21.66	21.55	21.54	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			20415	20525	20635		20415	20525	20635		20415	20525	20635	
5 / 3M	1	0	24.13	24.36	24.31	0	23.93	23.37	23.35	1	23.18	22.42	22.49	2
	1	7	24.19	24.35	24.36	0	23.92	23.37	23.26	1	23.01	22.46	22.45	2
	1	14	24.30	24.38	24.36	0	23.90	23.34	23.29	1	23.00	22.45	22.44	2
	8	0	23.29	23.40	23.24	1	22.53	22.37	22.16	2	21.77	21.54	21.37	3
	8	3	23.45	23.35	23.35	1	22.54	22.19	22.13	2	21.62	21.35	21.31	3
	8	7	23.42	23.36	23.23	1	22.52	22.25	22.30	2	21.64	21.40	21.47	3
	15	0	23.28	23.34	23.35	1	22.37	22.24	22.36	2	21.45	21.31	21.60	3

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			20425	20525	20625		20425	20525	20625		20425	20525	20625	
5 / 5M	1	0	24.16	24.23	24.13	0	23.21	23.18	23.04	1	22.42	22.41	22.27	2
	1	12	24.24	24.15	24.14	0	23.14	23.30	23.06	1	22.23	22.38	22.16	2
	1	24	24.24	24.21	24.13	0	23.21	23.20	23.05	1	22.30	22.41	22.28	2
	12	0	23.31	23.32	23.38	1	22.29	22.33	22.24	2	21.39	21.39	21.34	3
	12	6	23.30	23.30	23.20	1	22.25	22.37	22.14	2	21.34	21.56	21.37	3
	12	13	23.37	23.30	23.22	1	22.26	22.32	22.17	2	21.47	21.50	21.28	3
	25	0	23.41	23.28	23.24	1	22.43	22.32	22.32	2	21.68	21.47	21.53	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			20450	20525	20600		20450	20525	20600		20450	20525	20600	
5 / 10M	1	0	24.19	24.31	24.26	0	23.30	23.23	23.28	1	22.50	22.35	22.33	2
	1	24	24.27	24.32	24.24	0	23.28	23.32	23.27	1	22.35	22.53	22.39	2
	1	49	24.38	24.32	24.23	0	23.34	23.29	23.32	1	22.42	22.50	22.56	2
	25	0	24.38	24.31	24.25	1	23.64	23.00	23.28	2	22.87	22.25	22.46	3
	25	12	24.24	24.33	24.29	1	23.63	23.08	23.24	2	22.73	22.16	22.38	3
	25	25	24.55	24.39	24.51	1	23.61	23.03	23.23	2	22.86	22.20	22.45	3
	50	0	23.44	23.42	23.43	1	22.35	22.41	22.05	2	21.46	21.63	21.16	3

➤ LTE Band 7

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			20775	21100	21425		20775	21100	21425		20775	21100	21425	
7 / 5M	1	0	23.56	23.52	23.57	0	22.43	22.51	22.61	1	21.49	21.62	21.61	2
	1	12	23.56	23.62	23.59	0	22.39	22.54	22.54	1	21.55	21.61	21.68	2
	1	24	23.55	23.55	23.70	0	22.45	22.48	22.60	1	21.57	21.68	21.74	2
	12	0	22.65	22.71	22.76	1	21.60	21.63	21.76	2	20.68	20.68	20.84	3
	12	6	22.65	22.68	22.66	1	21.55	21.61	21.76	2	20.74	20.71	20.93	3
	12	13	22.63	22.68	22.65	1	21.55	21.63	21.70	2	20.66	20.81	20.76	3
	25	0	22.72	22.63	22.67	1	21.65	21.65	21.71	2	20.72	20.72	20.78	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			20800	21100	21400		20800	21100	21400		20800	21100	21400	
7 / 10M	1	0	23.47	23.68	23.61	0	22.49	22.65	22.98	1	21.68	21.82	22.09	2
	1	24	23.51	23.59	23.56	0	22.50	22.68	22.93	1	21.51	21.83	22.12	2
	1	49	23.41	23.61	23.53	0	22.41	22.67	23.00	1	21.53	21.77	22.01	2
	25	0	22.58	22.74	22.66	1	21.64	21.67	21.68	2	20.70	20.72	20.88	3
	25	12	22.78	22.71	22.66	1	21.65	21.60	21.53	2	20.67	20.72	20.67	3
	25	25	22.79	22.67	22.54	1	21.70	21.66	21.51	2	20.78	20.81	20.66	3
	50	0	22.71	22.82	22.59	1	21.72	21.69	21.71	2	20.84	20.71	20.80	3

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1



LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			20825	21100	21375		20825	21100	21375		20825	21100	21375	
7 / 15M	1	0	23.48	23.65	23.68	0	22.97	23.12	22.71	1	22.10	22.17	21.76	2
	1	37	23.48	23.62	23.67	0	23.00	23.17	22.69	1	22.15	22.33	21.70	2
	1	74	23.46	23.60	23.73	0	22.87	23.13	22.67	1	22.07	22.25	21.78	2
	36	0	22.81	22.75	22.83	1	21.64	21.73	21.75	2	20.82	20.73	20.90	3
	36	19	22.80	22.72	22.78	1	21.63	21.74	21.65	2	20.82	20.78	20.79	3
	36	39	22.80	22.75	22.75	1	21.69	21.77	21.71	2	20.73	20.88	20.78	3
	75	0	22.73	22.68	22.72	1	21.63	21.76	21.79	2	20.66	20.78	20.91	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			20850	21100	21350		20850	21100	21350		20850	21100	21350	
7 / 20M	1	0	23.58	23.69	23.64	0	22.71	22.78	23.14	1	21.90	21.91	22.33	2
	1	50	23.69	23.80	23.72	0	22.67	22.78	23.15	1	21.79	21.94	22.31	2
	1	99	23.67	23.78	23.70	0	22.71	22.76	23.15	1	21.91	21.88	22.23	2
	50	0	22.69	22.68	22.69	1	21.76	21.78	21.89	2	20.88	20.83	20.94	3
	50	25	22.67	22.73	22.67	1	21.79	21.86	21.82	2	20.93	20.87	21.02	3
	50	50	22.74	22.78	22.71	1	21.81	21.85	21.75	2	20.98	20.99	20.92	3
	100	0	22.78	22.72	22.75	1	21.73	21.78	21.69	2	20.92	20.91	20.87	3

➤ LTE Band 12

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			23017	23095	23173		23017	23095	23173		23017	23095	23173	
12 / 1.4M	1	0	24.20	24.22	24.33	0	23.74	23.26	23.28	1	22.98	22.46	22.48	2
	1	2	24.19	24.31	24.35	0	23.83	23.25	23.36	1	23.01	22.47	22.57	2
	1	5	24.29	24.33	24.39	0	23.77	23.29	23.28	1	22.92	22.40	22.47	2
	3	0	23.35	23.31	23.47	1	22.31	22.32	22.53	2	21.38	21.52	21.71	2
	3	1	23.30	23.30	23.30	1	22.42	22.35	22.45	2	21.55	21.52	21.50	2
	3	3	23.35	23.26	23.28	1	22.43	22.30	22.37	2	21.54	21.47	21.46	2
	6	0	23.31	23.30	23.36	1	22.39	22.38	22.37	2	21.45	21.47	21.49	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			23025	23095	23165		23025	23095	23165		23025	23095	23165	
12 / 3M	1	0	24.35	24.31	24.26	0	23.72	23.29	23.34	1	22.88	22.43	22.49	2
	1	7	24.17	24.31	24.35	0	23.82	23.26	23.28	1	22.88	22.37	22.45	2
	1	14	24.18	24.34	24.41	0	23.82	23.19	23.33	1	23.01	22.35	22.44	2
	8	0	23.25	23.29	23.29	1	22.42	22.22	22.26	2	21.65	21.45	21.41	3
	8	3	23.34	23.20	23.31	1	22.48	22.18	22.21	2	21.70	21.32	21.35	3
	8	7	23.29	23.19	23.25	1	22.49	22.20	22.26	2	21.73	21.45	21.41	3
	15	0	23.20	23.29	23.23	1	22.35	22.09	22.37	2	21.49	21.18	21.44	3

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			23035	23095	23155		23035	23095	23155		23035	23095	23155	
12 / 5M	1	0	24.12	24.16	24.20	0	23.01	23.16	23.04	1	22.14	22.35	22.28	2
	1	12	24.19	24.14	24.14	0	23.10	23.13	23.04	1	22.17	22.18	22.21	2
	1	24	24.23	24.25	24.11	0	23.09	23.10	23.08	1	22.22	22.33	22.30	2
	12	0	23.27	23.21	23.38	1	22.22	22.36	22.24	2	21.44	21.61	21.34	3
	12	6	23.29	23.26	23.26	1	22.15	22.31	22.18	2	21.26	21.51	21.36	3
	12	13	23.23	23.27	23.19	1	22.18	22.36	22.08	2	21.40	21.61	21.15	3
	25	0	23.24	23.23	23.19	1	22.35	22.23	22.24	2	21.54	21.46	21.33	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			23060	23095	23130		23060	23095	23130		23060	23095	23130	
12 / 10M	1	0	24.25	24.32	24.27	0	23.25	23.19	23.27	1	22.34	22.35	22.43	2
	1	24	24.30	24.22	24.33	0	23.15	23.24	23.27	1	22.20	22.37	22.50	2
	1	49	24.26	24.30	24.30	0	23.22	23.15	23.26	1	22.36	22.36	22.34	2
	25	0	24.40	24.35	24.35	1	23.46	23.08	23.15	2	22.69	22.19	22.31	3
	25	12	24.24	24.24	24.44	1	23.43	23.12	23.24	2	22.52	22.35	22.46	3
	25	25	24.33	24.23	24.47	1	23.58	23.08	23.29	2	22.74	22.33	22.52	3
	50	0	23.26	23.31	23.37	1	22.21	22.29	22.01	2	21.38	21.35	21.14	3

➤ LTE Band 13

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			23205	23230	23255		23205	23230	23255		23205	23230	23255	
13 / 5M	1	0	24.14	24.22	24.17	0	23.03	23.20	23.06	1	22.27	22.32	22.27	2
	1	12	24.18	24.12	24.16	0	23.13	23.28	22.99	1	22.35	22.40	22.19	2
	1	24	24.17	24.07	24.09	0	23.16	23.18	23.05	1	22.21	22.24	22.14	2
	12	0	23.20	23.25	23.26	1	22.15	22.34	22.19	2	21.35	21.56	21.33	3
	12	6	23.20	23.30	23.33	1	22.17	22.44	22.29	2	21.32	21.57	21.46	3
	12	13	23.20	23.23	23.35	1	22.18	22.29	22.27	2	21.29	21.38	21.46	3
	25	0	23.18	23.43	23.34	1	22.31	22.40	22.35	2	21.55	21.49	21.51	3

LTE Band / BW	RB Size	RB Offset	QPSK	3GPP MPR (dB)	16QAM	3GPP MPR (dB)	64QAM	3GPP MPR (dB)
			Mid CH		Mid CH		Mid CH	
			23230		23230		23230	
13 / 10M	1	0	24.27	0	23.69	1	22.90	2
	1	24	24.22	0	23.89	1	23.06	2
	1	49	24.16	0	23.88	1	23.04	2
	25	0	23.31	1	22.46	2	21.69	3
	25	12	23.32	1	22.38	2	21.44	3
	25	25	23.38	1	22.47	2	21.61	3
	50	0	23.35	1	22.43	2	21.54	3

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

➤ LTE Band 14

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			23305	23330	23355		23305	23330	23355		23305	23330	23355	
14 / 5M	1	0	24.15	24.06	24.05	0	23.14	23.20	22.92	1	22.20	22.32	22.10	2
	1	12	24.14	24.10	24.08	0	23.12	23.06	22.95	1	22.19	22.16	22.02	2
	1	24	24.06	24.04	24.10	0	22.98	23.05	22.98	1	22.02	22.12	21.99	2
	12	0	23.14	23.20	23.20	1	22.11	22.23	22.17	2	21.26	21.30	21.31	3
	12	6	23.18	23.22	23.20	1	22.16	22.16	22.11	2	21.24	21.18	21.19	3
	12	13	23.21	23.22	23.22	1	22.16	22.17	22.07	2	21.20	21.19	21.22	3
	25	0	23.24	23.16	23.19	1	22.32	22.20	22.23	2	21.38	21.34	21.30	3

LTE Band / BW	RB Size	RB Offset	QPSK	3GPP MPR (dB)	16QAM	3GPP MPR (dB)	64QAM	3GPP MPR (dB)
			Mid CH		Mid CH		Mid CH	
			23330		23330		23330	
14 / 10M	1	0	24.29	0	23.31	1	22.33	2
	1	24	24.36	0	23.34	1	22.43	2
	1	49	24.25	0	23.25	1	22.42	2
	25	0	23.45	1	22.33	2	21.35	3
	25	12	23.24	1	22.19	2	21.29	3
	25	25	23.28	1	22.19	2	21.21	3
	50	0	23.27	1	22.20	2	21.33	3

➤ LTE Band 17

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			23755	23790	23825		23755	23790	23825		23755	23790	23825	
17 / 5M	1	0	24.02	24.19	24.17	0	23.09	23.09	23.02	1	22.29	22.17	22.18	2
	1	12	24.10	24.17	24.08	0	23.10	23.09	23.03	1	22.29	22.25	22.19	2
	1	24	24.20	24.09	24.18	0	23.14	23.08	22.95	1	22.35	22.28	22.05	2
	12	0	23.20	23.26	23.28	1	22.11	22.30	22.25	2	21.28	21.38	21.34	3
	12	6	23.23	23.13	23.28	1	22.19	22.21	22.17	2	21.31	21.34	21.28	3
	12	13	23.28	23.13	23.16	1	22.21	22.19	22.18	2	21.37	21.43	21.41	3
	25	0	23.19	23.19	23.26	1	22.31	22.21	22.30	2	21.37	21.37	21.37	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			23780	23790	23800		23780	23790	23800		23780	23790	23800	
17 / 10M	1	0	24.17	24.32	24.39	0	23.79	23.32	23.34	1	22.99	22.43	22.41	2
	1	24	24.20	24.23	24.32	0	23.68	23.15	23.31	1	22.91	22.28	22.53	2
	1	49	24.25	24.23	24.35	0	23.76	23.24	23.26	1	22.89	22.46	22.37	2
	25	0	23.19	23.45	23.43	1	22.33	22.26	22.48	2	21.42	21.46	21.57	3
	25	12	23.20	23.17	23.26	1	22.22	22.14	22.33	2	21.42	21.28	21.48	3
	25	25	23.27	23.19	23.24	1	22.27	22.14	22.30	2	21.41	21.24	21.49	3
	50	0	23.29	23.28	23.33	1	22.35	22.32	22.32	2	21.49	21.38	21.56	3

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1