

Analysis Report

**The Equipment Under Test (EUT), is a portable 2.4GHz Transmitter (Bear Unit) for a RC bear.
The sample supplied operated on single channel, normally at 2437MHz.**

The EUT is powered by 2 x 1.5V AAA batteries. After switching on the EUT, the bear will be shaking head and talking based on the buttons pressed on the bear.

Antenna Type: Internal, Integral antenna

Antenna Gain: 0dBi

Nominal rated field strength is 97.2dB μ V/m at 3m (Peak), 74.0dB μ V/m at 3m (Average)

Maximum allowed production tolerance: +/- 3dB

According to the KDB 447498:

Based on the maximum average field strength of production tolerance was 77.0dB μ V/m at 3m in frequency 2.437GHz.

Thus, it below calculated field strength according to minimum SAR exclusion threshold level as follows:

The worst case of SAR Exclusion Threshold Level:

$$= 3.0 * (\text{min. test separation distance, mm}) / \sqrt{\text{freq. in GHz}}$$

$$= 3.0 * 5 / \sqrt{2.483.5} \text{ mW}$$

$$= 9.52 \text{ mW}$$

According to the KDB 412172 D01:

$$\text{EIRP} = [(FS * D)^2 * 1000 / 30]$$

Calculated Field Strength for 9.52mW is 105dB μ V/m @3m

Since maximum average field strength plus production tolerance <= 105dB μ V/m @3m and antenna gain is >= 0.0dBi, it is concluded that maximum Conducted Power and Field Strength are well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.