



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V04
Report Template Revision Date: 2018-07-06

RF Exposure Evaluation Report

Report No. : CQASZ20190900916E-03
Applicant: Dongguan Laisimar Electronics Technologies Co., Ltd
Address of Applicant: Room 201, No.15 Hsinmin Industrial Changan Town, Dongguan City, Guangdong Province, China.
Equipment Under Test (EUT):
Product: HP BH10 Bluetooth Headphones
Model No.: HP BH10
Brand Name: HP
FCC ID: 2AUPZ-HPBH10
Standards: 47 CFR Part 1.1307
47 CFR Part 2.1093
KDB447498D01 General RF Exposure Guidance v06
Date of Receipt: 2019-09-10
Date of Test: 2019-09-10 to 2019-09-26
Date of Issue: 2019-09-26
Test Result : **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Tested By:

Tom Chen

(Tom Chen)

Reviewed By:

Sheek Luo

(Sheek Luo)

Approved By:

Jack Ai

(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20190900916E-03	Rev.01	Initial report	2019-09-26

2 Contents

	Page
1 VERSION.....	2
2 CONTENTS.....	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT.....	4
3.3 GENERAL DESCRIPTION OF BT.....	4
3.4 GENERAL DESCRIPTION OF BLE.....	4
4 SAR EVALUATION.....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 <i>Standard Requirement</i>	5
4.1.2 <i>Limits</i>	5
4.1.3 <i>EUT RF Exposure</i>	6

3 General Information

3.1 Client Information

Applicant:	Dongguan Laisimar Electronics Technologies Co., Ltd
Address of Applicant:	Room 201, No.15 Hsinmin Industrial Changan Town, Dongguan City, Guangdong Province, China.
Manufacturer:	Dongguan Shangyuan Electronics Co, Ltd
Address of Manufacturer:	Fourth building, Comprehensive development Zone, Hengli Town, Dongguan, Guangdong, China

3.2 General Description of EUT

Product Name:	HP BH10 Bluetooth Headphones
Model No.:	HP BH10
Trade Mark:	HP
Hardware Version:	HB523_MAIN_BK3266_V1.1
Software Version:	HB523_MAIN_BK3266_V1.0
Bluetooth Version:	V5.0
Sample Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Power Supply:	lithium battery:DC3.7V, Charge by DC5.0V

3.3 General Description of BT

Operation Frequency:	2402MHz~2480MHz
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channel:	79
Transfer Rate:	1Mbps/2Mbps/3Mbps
Hopping Channel Type:	Adaptive Frequency Hopping systems
Test Software of EUT:	BK32xx RF Test-V1.8.2 (manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	1.9dBi

3.4 General Description of BLE

Operation Frequency:	2402MHz~2480MHz
Modulation Type:	GFSK
Transfer Rate:	1Mbps/2Mbps
Number of Channel:	40
Test Software of EUT:	BK32xx RF Test-V1.8.2 (manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	1.9dBi

Remark: Only one model number: HP BH10, but it comes in three colors (black, red), only the red EUT was tested.

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.1.3 EUT RF Exposure

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-1.670	-2±1	-1	0.794
Middle(2441MHz)	-2.490	-2±1	-1	0.794
Highest(2480MHz)	-2.300	-2±1	-1	0.794
π/4DQPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	0.500	0±1	1	1.259
Middle(2441MHz)	-0.290	0±1	1	1.259
Highest(2480MHz)	-0.130	0±1	1	1.259
8DPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	0.810	0±1	1	1.259
Middle(2441MHz)	-0.020	0±1	1	1.259
Highest(2480MHz)	0.210	0±1	1	1.259

Worst case: 8DPSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	0.810	0±1	1	1.259	0.39	3.0
Middle (2441MHz)	-0.020	0±1	1	1.259	0.39	
Highest (2480MHz)	0.210	0±1	1	1.259	0.40	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20190900916E-01

2) For BLE

Measurement Data

GFSK(1Mbps) mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	0.91	1±1	2	1.585
Middle(2440MHz)	0.50	1±1	2	1.585
Highest(2480MHz)	1.50	1±1	2	1.585

Worst case: GFSK(1Mbps)						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune- up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	0.91	1±1	2	1.585	0.49	3.0
Middle (2440MHz)	0.50	1±1	2	1.585	0.50	
Highest (2480MHz)	1.50	1±1	2	1.585	0.50	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20190900916E-02

BDR, EDR and BLE can not simultaneous transmitting at same time.