FCC ID: 2AUPZ-HPS10

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] [$\sqrt{f(GHZ)}$] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- f(GHZ) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BT:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-3.361	0.461	-3±1	-2	0.63	<5	0.19558	3.00	YES
	2.441	-1.64	0.685	-1±1	0	1.00	<5	0.31247	3.00	YES
	2.480	0.184	1.043	0±1	1	1.26	<5	0.39651	3.00	YES
π/4- DQPSK	2.402	-1.225	0.754	-1±1	0	1.00	<5	0.30997	3.00	YES
	2.441	0.638	1.158	0±1	1	1.26	<5	0.39338	3.00	YES
	2.480	2.499	1.778	2±1	3	2.00	<5	0.62843	3.00	YES
8DPSK	2.402	-0.625	0.866	0±1	1	1.26	<5	0.39023	3.00	YES
	2.441	1.169	1.309	1±1	2	1.58	<5	0.49524	3.00	YES
	2.480	3.046	2.017	3±1	4	2.51	<5	0.79114	3.00	YES

Conclusion:

For the max result : $0.79114W/Kg \le 3.0$ for 1g SAR, No SAR is required.

Jason chen

Signature:

Date: 2019-10-15

NAME AND TITLE (Please print or type): Jason Chen /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.