

**FCC ID: 2AUPZ-HPSS10**

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHZ})} \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f(\text{GHZ})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison


When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

BT:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	2.408	3.079	3±1	4	2.51	<5	0.77860	3.00	YES
	2.441	2.133	3.567	3±1	4	2.51	<5	0.78490	3.00	YES
	2.480	2.647	3.492	3±1	4	2.51	<5	0.79114	3.00	YES
π/4-DQPSK	2.402	4.806	3.724	4±1	5	3.16	<5	0.98020	3.00	YES
	2.441	4.582	4.228	4±1	5	3.16	<5	0.98813	3.00	YES
	2.480	5.008	4.144	4±1	5	3.16	<5	0.99599	3.00	YES

**Conclusion:**

For the max result :  $0.99599\text{W/Kg} \leq 3.0$  for 1g SAR, No SAR is required.



**Signature:**

**Date:** 2019-10-15

**NAME AND TITLE** (Please print or type): Jason Chen /Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.