

# RADIO TEST REPORT

## FCC 47 CFR PART 15 SUBPART C

Test Standard	FCC Part 15.247
Brand name	neat.
Product name	Neat Pad
Model No.	A1
Test Result	Pass
Statements of Conformity	Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.


The test Result was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were given in ANSI C63.10: 2013 and compliance standards.

The test results of this report relate only to the tested sample (EUT) identified in this report.

The test Report of full or partial shall not copy. Without written approval of Compliance Certification Services Inc. (Wugu Laboratory).

Approved by:

Tested by:



---

Kevin Tsai  
Deputy Manager

---

Dally Hong  
Engineer

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.  
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部分複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: T190902W03-RP1

Page 2 / 106  
Rev. 00

## Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	December 16, 2019	Initial Issue	ALL	Allison Chen

## Table of contents

<b>1.</b>	<b>GENERAL INFORMATION.....</b>	<b>4</b>
<b>1.1</b>	<b>EUT INFORMATION.....</b>	<b>4</b>
<b>1.2</b>	<b>EUT CHANNEL INFORMATION.....</b>	<b>5</b>
<b>1.3</b>	<b>ANTENNA INFORMATION.....</b>	<b>5</b>
<b>1.4</b>	<b>MEASUREMENT UNCERTAINTY.....</b>	<b>6</b>
<b>1.5</b>	<b>FACILITIES AND TEST LOCATION.....</b>	<b>7</b>
<b>1.6</b>	<b>INSTRUMENT CALIBRATION.....</b>	<b>8</b>
<b>1.7</b>	<b>SUPPORT AND EUT ACCESSORIES EQUIPMENT.....</b>	<b>9</b>
<b>1.8</b>	<b>TEST METHODOLOGY AND APPLIED STANDARDS.....</b>	<b>9</b>
<b>2.</b>	<b>TEST SUMMERY.....</b>	<b>10</b>
<b>3.</b>	<b>DESCRIPTION OF TEST MODES.....</b>	<b>11</b>
<b>3.1</b>	<b>THE WORST MODE OF OPERATING CONDITION.....</b>	<b>11</b>
<b>3.2</b>	<b>THE WORST MODE OF MEASUREMENT.....</b>	<b>12</b>
<b>4.</b>	<b>EUT DUTY CYCLE.....</b>	<b>13</b>
<b>5.</b>	<b>TEST RESULT.....</b>	<b>14</b>
<b>5.1</b>	<b>AC POWER LINE CONDUCTED EMISSION.....</b>	<b>14</b>
<b>5.2</b>	<b>6dB BANDWIDTH AND OCCUPIED BANDWIDTH(99%).....</b>	<b>17</b>
<b>5.3</b>	<b>OUTPUT POWER MEASUREMENT.....</b>	<b>31</b>
<b>5.4</b>	<b>POWER SPECTRAL DENSITY.....</b>	<b>34</b>
<b>5.5</b>	<b>CONDUCTED BANDEDGE AND SPURIOUS EMISSION.....</b>	<b>42</b>
<b>5.6</b>	<b>RADIATION BANDEDGE AND SPURIOUS EMISSION.....</b>	<b>61</b>
	<b>APPENDIX-A TEST PHOTO.....</b>	<b>A-1</b>
	<b>APPENDIX 1 - PHOTOGRAPHS OF EUT</b>	

# 1. GENERAL INFORMATION

## 1.1 EUT INFORMATION

Applicant	Neatframe AS Martin Linges Vei 25 Fornebu Fornebu 1364 Norway		
Manufacturer	Neatframe Limited The Charter Building Charter Place UXBRIDGE United Kingdom UB8 1JG United Kingdom Of Great Britain And Northern Ireland		
Equipment	Neat Pad		
Model Name	A1		
Model Discrepancy	N/A		
Trade Name	neat.		
Received Date	September 2, 2019		
Date of Test	October 30 ~ November 13, 2019		
Output Power(W)	<b>Mode</b>	<b>Output Power (W)</b>	
	IEEE 802.11b Mode	0.1396	
	IEEE 802.11g Mode	0.3327	
	IEEE 802.11n HT20 Mode	0.6448	
	IEEE 802.11n HT40 Mode	0.6034	
EUT Power Rating:	Power from adapter.		
Power Supply	VDC from Power Adapter PHIHONG / POE16R-1AFG I/P: 100-240Vac, 0.8A, 50-60Hz, 32-44VA O/P: 56Vdc, 0.275A		

Report No.: T190902W03-RP1

## 1.2 EUT CHANNEL INFORMATION

Frequency Range	802.11b/g/n HT20: 2412MHz ~ 2462MHz 802.11n HT40: 2422MHz ~ 2452MHz
Modulation Type	1. IEEE 802.11b Mode: DSSS(DBPSK/DQPSK/CCK) 2. IEEE 802.11g Mode: OFDM (BPSK/QPSK/16QAM/64QAM) 3. IEEE 802.11n HT20 Mode : OFDM (BPSK/QPSK/16QAM/64QAM) 4. IEEE 802.11n HT40 Mode : OFDM (BPSK/QPSK/16QAM/64QAM)
Number of channels	1. IEEE 802.11b Mode: 11 Channels 2. IEEE 802.11g Mode: 11 Channels 3. IEEE 802.11n HT20 Mode : 11 Channels 4. IEEE 802.11n HT40 Mode : 7 Channels

**Remark:**

Refer as ANSI C63.10: 2013 clause 5.6.1 Table 4 for test channels

Number of frequencies to be tested		
Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
<input type="checkbox"/> 1 MHz or less	1	Middle
<input type="checkbox"/> 1 MHz to 10 MHz	2	1 near top and 1 near bottom
<input checked="" type="checkbox"/> More than 10 MHz	3	1 near top, 1 near middle, and 1 near bottom

## 1.3 ANTENNA INFORMATION

Antenna Type	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB <input type="checkbox"/> Dipole <input type="checkbox"/> Coils <input checked="" type="checkbox"/> FPC
Antenna Gain	For b / g mode: Chain A (Ant 1): Gain: 0.86 dBi  For n HT20 / n HT40 mode: Chain A (Ant 1): Gain: 0.86 dBi Chain B (Ant 2): Gain: 0.90 dBi Power Directional Gain: 0.88 dBi
Antenna Connector	i-pex

**Notes:**

1. Power Directional Gain:  $10\text{LOG}(((10^{(Ant1/10)}+10^{(Ant2/10)}))/2))$

## 1.4 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	+/- 1.2575
Emission bandwidth, 20dB bandwidth	+/- 0.0014
RF output power, conducted	+/- 1.14
Power density, conducted	+/- 1.40
3M Semi Anechoic Chamber / 30M~200M	+/- 4.12
3M Semi Anechoic Chamber / 200M~1000M	+/- 4.68
3M Semi Anechoic Chamber / 1G~8G	+/- 5.18
3M Semi Anechoic Chamber / 8G~18G	+/- 5.47
3M Semi Anechoic Chamber / 18G~26G	+/- 3.81
3M Semi Anechoic Chamber / 26G~40G	+/- 3.87

**Remark:**

1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$
2. ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report.

## 1.5 FACILITIES AND TEST LOCATION

All measurement facilities used to collect the measurement data are located at  
No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan. (R.O.C.)

Test site	Test Engineer	Remark
AC Conduction Room	Dally Hong	-
Radiation	Dally Hong	-
RF Conducted	Jane Wang	-

**Remark:** The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

Report No.: T190902W03-RP1

## 1.6 INSTRUMENT CALIBRATION

RF Conducted Test Site					
Equipment	Manufacturer	Model	S/N	Cal Date	Cal Due
Coaxial Cable	Woken	WC12	CC003	06/28/2019	06/27/2020
Power Meter	Anritsu	ML2495A	1149001	02/12/2019	02/11/2020
Power Seneor	Anritsu	MA2491A	030982	02/12/2019	02/11/2020
Signal Analyzer	R&S	FSV 40	101073	09/25/2019	09/24/2020
Software	N/A				

3M 966 Chamber Test Site					
Equipment	Manufacturer	Model	S/N	Cal Date	Cal Due
Band Reject Filters	MICRO TRONICS	BRM 50702	120	02/26/2019	02/25/2020
Bilog Antenna	Sunol Sciences	JB3	A030105	07/26/2019	07/25/2020
Coaxial Cable	HUBER SUHNER	SUCOFLEX 104PEA	20995	02/26/2019	02/25/2020
Coaxial Cable	EMCI	EMC105	190914+25111	09/20/2019	09/19/2020
Digital Thermo-Hygro Meter	WISEWIND	1206	D07	01/30/2019	01/29/2020
double Ridged Guide Horn Antenna	ETC	MCTD 1209	DRH13M02003	10/04/2019	10/03/2020
Loop Ant	COM-POWER	AL-130	121051	03/22/2019	03/21/2020
Pre-Amplifier	EMEC	EM330	060609	02/26/2019	02/25/2020
Pre-Amplifier	HP	8449B	3008A00965	02/26/2019	02/25/2020
PSA Series Spectrum Analyzer	Agilent	E4446A	MY46180323	05/29/2019	05/28/2020
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R	N.C.R
Turn Table	CCS	CC-T-1F	N/A	N.C.R	N.C.R
Software	e3 6.11-20180413				

AC line Conduction Test Room					
Equipment	Manufacturer	Model	S/N	Cal Date	Cal Due
CABLE	EMCI	CFD300-NL	CERF	06/27/2019	06/26/2020
EMI Test Receiver	R&S	ESCI	100064	07/26/2019	07/25/2020
LISN	SCHWARZBECK	NSLK 8127	8127-541	01/31/2019	01/30/2020
LISN	SCHAFFNER	NNB 41	03/10013	02/13/2019	02/12/2020
Software	EZ-EMC(CCS-3A1-CE)				

**Remark:**

1. Each piece of equipment is scheduled for calibration once a year.
2. N.C.R. = No Calibration Request.



## 1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT

EUT Accessories Equipment					
No.	Equipment	Brand	Model	Series No.	FCC ID
	N/A				

Support Equipment					
No.	Equipment	Brand	Model	Series No.	FCC ID
1	NB(J)	TOSHIBA	PT345T-00L002	N/A	PD97260H

## 1.8 TEST METHODOLOGY AND APPLIED STANDARDS

The test methodology, setups and results comply with all requirements in accordance with ANSI C63.10:2013, FCC Part 2, FCC Part 15.247, KDB 558074 D01, KDB 662911 D01.

## 2. TEST SUMMERY

FCC Standard Section	Report Section	Test Item	Result
15.203	1.3	Antenna Requirement	Pass
15.207(a)	5.1	AC Conducted Emission	Pass
15.247(a)(2)	5.2	6 dB Bandwidth	Pass
2.1049	5.2	Occupied Bandwidth (99%)	Pass
15.247(b)(3)	5.3	Output Power Measurement	Pass
15.247(e)	5.4	Power Spectral Density	Pass
15.247(d)	5.5	Conducted Band Edge	Pass
15.247(d)	5.5	Conducted Spurious Emission	Pass
15.247(d)	5.6	Radiation Band Edge	Pass
15.247(d)	5.6	Radiation Spurious Emission	Pass

### 3. DESCRIPTION OF TEST MODES

#### 3.1 THE WORST MODE OF OPERATING CONDITION

Operation mode	IEEE 802.11b Mode: 1Mbps IEEE 802.11g Mode: 6Mbps IEEE 802.11n HT20 Mode: MCS8 IEEE 802.11n HT40 Mode: MCS8
Test Channel Frequencies	<b>IEEE 802.11b Mode:</b> 1. Lowest Channel: 2412MHz 2. Middle Channel: 2437MHz 3. Highest Channel: 2462MHz <b>IEEE 802.11g Mode:</b> 1. Lowest Channel: 2412MHz 2. Middle Channel: 2437MHz 3. Highest Channel: 2462MHz <b>IEEE 802.11n HT20 Mode:</b> 1. Lowest Channel: 2412MHz 2. Middle Channel: 2437MHz 3. Highest Channel: 2462MHz <b>IEEE 802.11n HT40 Mode:</b> 1. Lowest Channel: 2422MHz 2. Middle Channel: 2437MHz 3. Highest Channel: 2452MHz
Operation Transmitter	IEEE 802.11b Mode: 1T1R IEEE 802.11g Mode: 1T1R IEEE 802.11n HT20 Mode: 2T2R IEEE 802.11n HT40 Mode: 2T2R

**Remark:**

1. EUT pre-scanned data rate of output power for each mode, the worst data rate were recorded in this report.

Report No.: T190902W03-RP1

### 3.2 THE WORST MODE OF MEASUREMENT

AC Power Line Conducted Emission	
Test Condition	AC Power line conducted emission for line and neutral
Power supply Mode	Mode 1: EUT power by adapter.
Worst Mode	<input checked="" type="checkbox"/> Mode 1 <input type="checkbox"/> Mode 2 <input type="checkbox"/> Mode 3 <input type="checkbox"/> Mode 4

Radiated Emission Measurement Above 1G	
Test Condition	Radiated Emission Above 1G
Power supply Mode	Mode 1: EUT power by adapter.
Worst Mode	<input checked="" type="checkbox"/> Mode 1 <input type="checkbox"/> Mode 2 <input type="checkbox"/> Mode 3 <input type="checkbox"/> Mode 4
Worst Position	<input type="checkbox"/> Placed in fixed position. <input checked="" type="checkbox"/> Placed in fixed position at X-Plane (E2-Plane) <input type="checkbox"/> Placed in fixed position at Y-Plane (E1-Plane) <input type="checkbox"/> Placed in fixed position at Z-Plane (H-Plane)


Radiated Emission Measurement Below 1G	
Test Condition	Radiated Emission Below 1G
Power supply Mode	Mode 1: EUT power by adapter.
Worst Mode	<input checked="" type="checkbox"/> Mode 1 <input type="checkbox"/> Mode 2 <input type="checkbox"/> Mode 3 <input type="checkbox"/> Mode 4

*Remark:*

1. The worst mode was record in this test report.
2. EUT pre-scanned in three axis ,X,Y, Z and two polarity, for radiated measurement. The worst case(X-Plane) were recorded in this report
3. AC power line conducted emission and for below 1G radiation emission were performed the EUT transmit at the highest output power channel as worse case.

### 4. EUT DUTY CYCLE

Duty Cycle				
Configuration	Duty Cycle (%)	Duty Factor (dB) =10*log (1/Duty Cycle)	1/T (kHz)	VBW setting (kHz)
802.11b	100.00	0.00	0.00	0.01
802.11g	100.00	0.00	0.00	0.01
802.11n HT20	100.00	0.00	0.00	0.01
802.11n HT40	100.00	0.00	0.00	0.01



Report No.: T190902W03-RP1

## 5. TEST RESULT

### 5.1 AC POWER LINE CONDUCTED EMISSION

#### 5.1.1 Test Limit

According to §15.207(a),

Frequency Range (MHz)	Limits(dBµV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50


\* Decreases with the logarithm of the frequency.

#### 5.1.2 Test Procedure

Test method Refer as ANSI C63.10: 2013 clause 6.2,

1. The EUT was placed on a non-conducted table, which is 0.8m above horizontal ground plane and 0.4m above vertical ground plane.
2. EUT connected to the line impedance stabilization network (LISN)
3. Receiver set RBW of 9kHz and Detector Peak, and note as quasi-peak and average.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. Recorded Line for Neutral and Line.

#### 5.1.3 Test Setup




#### 5.1.4 Test Result

**Pass.**

Report No.: T190902W03-RP1

### Test Data


Test Mode:	Mode 1	Temp/Hum	24(°C)/ 50%RH
Phase:	Line	Test Date	2019/10/30
		Test Engineer	Dally Hong



Frequency (MHz)	Quasi Peak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	Quasi Peak result (dBuV)	Average result (dBuV)	Quasi Peak limit (dBuV)	Average limit (dBuV)	Quasi Peak margin (dB)	Average margin (dB)	Remark
0.2420	36.77	30.75	10.13	46.90	40.88	62.03	52.03	-15.13	-11.15	Pass
0.2980	31.76	22.85	10.13	41.89	32.98	60.30	50.30	-18.41	-17.32	Pass
0.5020	32.12	25.89	10.14	42.26	36.03	56.00	46.00	-13.74	-9.97	Pass
0.6020	30.16	18.58	10.15	40.31	28.73	56.00	46.00	-15.69	-17.27	Pass
1.0420	37.89	27.71	10.17	48.06	37.88	56.00	46.00	-7.94	-8.12	Pass
1.6540	35.67	25.77	10.19	45.86	35.96	56.00	46.00	-10.14	-10.04	Pass

Report No.: T190902W03-RP1

Test Mode:	Mode 1	Temp/Hum	24(°C)/ 50%RH
Phase:	Neutral	Test Date	2019/10/30
		Test Engineer	Dally Hong



Frequency (MHz)	Quasi Peak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	Quasi Peak result (dBuV)	Average result (dBuV)	Quasi Peak limit (dBuV)	Average limit (dBuV)	Quasi Peak margin (dB)	Average margin (dB)	Remark
0.1780	33.91	21.60	10.02	43.93	31.62	64.58	54.58	-20.65	-22.96	Pass
0.2380	37.11	29.02	10.02	47.13	39.04	62.17	52.17	-15.04	-13.13	Pass
0.3260	28.88	18.84	10.03	38.91	28.87	59.55	49.55	-20.64	-20.68	Pass
0.4700	31.27	23.39	10.03	41.30	33.42	56.51	46.51	-15.21	-13.09	Pass
0.6300	27.53	17.34	10.03	37.56	27.37	56.00	46.00	-18.44	-18.63	Pass
1.0420	37.53	27.51	10.04	47.57	37.55	56.00	46.00	-8.43	-8.45	Pass



Report No.: T190902W03-RP1

## 5.2 6dB BANDWIDTH AND OCCUPIED BANDWIDTH(99%)

### 5.2.1 Test Limit

According to §15.247(a)(2),

**6 dB Bandwidth** :

Limit	Shall be at least 500kHz
-------	--------------------------


**Occupied Bandwidth(99%)** : For reporting purposes only.

### 5.2.2 Test Procedure

Test method Refer as KDB 558074 D01 and ANSI C63.10: 2013 clause 6.9.2,

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW =100KHz , VBW = 300KHz and Detector = Peak, to measurement 6dB Bandwidth
4. SA set RBW = 1% ~ 5% OBW, VBW = three times the RBW and Detector = Peak, to measurement 99% Bandwidth
5. Measure and record the result of 6 dB Bandwidth and 99% Bandwidth. in the test report.

### 5.2.3 Test Setup



Report No.: T190902W03-RP1

### 5.2.4 Test Result

Test mode: IEEE 802.11b Mode / 2412-2462 MHz						
Channel	Frequency (MHz)	Chain A OBW(99%) (MHz)	Chain B OBW(99%) (MHz)	Chain A 6dB BW (MHz)	Chain B 6dB BW (MHz)	6dB limit (kHz)
Low	2412	13.6324	-	9.1304	-	≥500
Mid	2437	13.7626	-	9.1304	-	
High	2462	13.7192	-	9.5652	-	


Test mode: IEEE 802.11g Mode / 2412-2462 MHz						
Channel	Frequency (MHz)	Chain A OBW(99%) (MHz)	Chain B OBW(99%) (MHz)	Chain A 6dB BW (MHz)	Chain B 6dB BW (MHz)	6dB limit (kHz)
Low	2412	16.8017	-	16.4783	-	≥500
Mid	2437	16.6714	-	16.5217	-	
High	2462	16.5846	-	16.5652	-	

Test mode: IEEE 802.11n HT20 Mode / 2412-2462 MHz						
Channel	Frequency (MHz)	Chain A OBW(99%) (MHz)	Chain B OBW(99%) (MHz)	Chain A 6dB BW (MHz)	Chain B 6dB BW (MHz)	6dB limit (kHz)
Low	2412	17.7568	17.5832	17.6522	17.6087	≥500
Mid	2437	17.7134	17.6266	17.6522	17.6087	
High	2462	17.6700	17.5832	17.6522	17.6087	


Test mode: IEEE 802.11n HT40 Mode / 2422-2452 MHz						
Channel	Frequency (MHz)	Chain A OBW(99%) (MHz)	Chain B OBW(99%) (MHz)	Chain A 6dB BW (MHz)	Chain B 6dB BW (MHz)	6dB limit (kHz)
Low	2422	37.0477	36.3531	36.638	36.406	>500
Mid	2437	37.0477	36.3531	36.638	36.406	
High	2452	37.0477	36.3531	36.638	36.406	

## Test Data


### 6dB BANDWIDTH



Report No.: T190902W03-RP1




## Chain A




## IEEE 802.11n HT40 mode


### Low CH



### Mid CH



### High CH




Report No.: T190902W03-RP1

## Chain B


### IEEE 802.11n HT20 mode

#### Low CH




Date: 12.NOV.2019 16:56:42

#### Mid CH



Date: 12.NOV.2019 16:59:26

#### High CH




Date: 12.NOV.2019 17:04:10


Report No.: T190902W03-RP1

## IEEE 802.11n HT40 mode


### Low CH



### Mid CH



### High CH







Report No.: T190902W03-RP1

## Test Data

### BANDWIDTH (99%)


### Chain B






Report No.: T190902W03-RP1

## Chain A



Report No.: T190902W03-RP1




Report No.: T190902W03-RP1


## Chain B

### IEEE 802.11n HT20 mode


#### Low CH



#### Mid CH




#### High CH




## IEEE 802.11n HT40 mode


### Low CH



### Mid CH



### High CH



Report No.: T190902W03-RP1

## 5.3 OUTPUT POWER MEASUREMENT

### 5.3.1 Test Limit

According to §15.247(b)(3),

#### Peak output power :

For systems using digital modulation in the 2400-2483.5 MHz: 1 Watt(30 dBm), base on the use of antennas with directional gain not exceed 6 dBi. If transmitting antennas of directional gain greater than 6dBi are used the peak output power the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Limit	<input checked="" type="checkbox"/> Antenna not exceed 6 dBi : 30dBm <input type="checkbox"/> Antenna with DG greater than 6 dBi : [Limit = 30 – (DG – 6)] <input type="checkbox"/> Point-to-point operation :
-------	---


Average output power : For reporting purposes only.

### 5.3.2 Test Procedure

Test method Refer as KDB 558074 D01.

1. The EUT RF output connected to the power meter by RF cable.
2. Setting maximum power transmit of EUT.
3. The path loss was compensated to the results for each measurement.
4. Measure and record the result of Peak output power and Average output power. in the test report.

### 5.3.3 Test Setup



Report No.: T190902W03-RP1

### 5.3.4 Test Result

#### Peak output power :

1TX:

Wifi 2.4G								
Config	CH	Freq. (MHz)	power set		PK Power(dBm)		PK Total Power (W)	Limit (dBm)
			chain A	chain A	chain A	chain A		
IEEE 802.11b Data rate: 1Mbps	Low	2412	48	20.76	20.76	0.1191	30	
	Mid	2437	48	21.45	21.45	0.1396		
	High	2462	48	20.74	20.74	0.1186		
IEEE 802.11g Data rate: 6Mbps	Low	2412	59	24.91	24.91	0.3097		
	Mid	2437	57	25.22	25.22	0.3327		
	High	2462	58	25.00	25.00	0.3162		

2TX:

Wifi 2.4G									
Config	CH	Freq. (MHz)	power set		PK Power(dBm)		PK Total Power (dBm)	PK Total Power (W)	Limit (dBm)
			chainA	chainB	chainA	chainB			
IEEE 802.11n 20MHz Data rate: MCS8	Low	2412	55	55	25.27	24.89	28.09	0.6448	30
	Mid	2437	56	56	24.81	24.75	27.79	0.6012	
	High	2462	55	54	24.97	24.56	27.78	0.5998	
IEEE 802.11n 40MHz Data rate: MCS8	Low	2422	54	52	24.78	24.17	27.50	0.5618	
	Mid	2437	55	55	24.56	25.02	27.81	0.6034	
	High	2452	54	53	24.35	24.04	27.21	0.5258	



**Average output power :**

**1TX:**

Wifi 2.4G					
Config	CH	Freq. (MHz)	AV Power(dBm)		AV Total Power (dBm)
			chainA	chainB	
IEEE 802.11b Data rate: 1Mbps	Low	2412	18.05	-	18.05
	Mid	2437	18.68	-	18.68
	High	2462	18.06	-	18.06
IEEE 802.11g Data rate: 6Mbps	Low	2412	17.90	-	17.90
	Mid	2437	19.25	-	19.25
	High	2462	18.78	-	18.78

**2TX:**

Wifi 2.4G					
Config	CH	Freq. (MHz)	AV Power(dBm)		AV Total Power (dBm)
			chainA	chainB	
IEEE 802.11n 20MHz Data rate: MCS8	Low	2412	19.15	19.11	22.14
	Mid	2437	19.17	18.36	21.79
	High	2462	19.44	18.73	22.11
IEEE 802.11n 40MHz Data rate: MCS8	Low	2422	18.53	17.64	21.12
	Mid	2437	18.14	18.95	21.57
	High	2452	17.80	17.59	20.71

Report No.: T190902W03-RP1

## 5.4 POWER SPECTRAL DENSITY

### 5.4.1 Test Limit

According to §15.247(e),

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


Limit	<input checked="" type="checkbox"/> Antenna not exceed 6 dBi : 8dBm <input type="checkbox"/> Antenna with DG greater than 6 dBi : [ Limit = 8 – (DG – 6) ] <input type="checkbox"/> Point-to-point operation :
-------	---

### 5.4.2 Test Procedure

Test method Refer as KDB 558074 D01.

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 3kHz, VBW = 30kHz, Span = 1.5 times DTS Bandwidth (6 dB BW), Detector = Peak, Sweep Time = Auto and Trace = Max hold.
4. The path loss was compensated to the results for each measurement by SA.
5. Mark the maximum level.
6. Measure and record the result of power spectral density. in the test report.

### 5.4.3 Test Setup



Report No.: T190902W03-RP1

#### 5.4.4 Test Result

Test mode: IEEE 802.11b Mode / 2412-2462 MHz					
Channel	Frequency (MHz)	Chain A PPSD (dBm)	Chain B PPSD (dBm)	Total PSSD (dBm)	Limit (dBm)
Low	2412	-12.52	-	-12.52	8
Mid	2437	-11.87	-	-11.87	
High	2462	-12.47	-	-12.47	


Test mode: IEEE 802.11g Mode / 2412-2462 MHz					
Channel	Frequency (MHz)	Chain A PPSD (dBm)	Chain B PPSD (dBm)	Total PSSD (dBm)	Limit (dBm)
Low	2412	-11.63	-	-11.63	8
Mid	2437	-12.7	-	-12.7	
High	2462	-14.3	-	-14.3	

Test mode: IEEE 802.11n HT20 Mode / 2412-2462 MHz					
Channel	Frequency (MHz)	Chain A PPSD (dBm)	Chain B PPSD (dBm)	Total PSSD (dBm)	Limit (dBm)
Low	2412	-12.58	-21.53	-12.06	8
Mid	2437	-13.41	-19.3	-12.41	
High	2462	-13.43	-19.29	-12.43	


Test mode: IEEE 802.11n HT40 Mode / 2422-2452 MHz					
Channel	Frequency (MHz)	Chain A PPSD (dBm)	Chain B PPSD (dBm)	Total PSSD (dBm)	Limit (dBm)
Low	2422	-15.13	-19.23	-13.70	8
Mid	2437	-15.2	-22.48	-14.46	
High	2452	-15.32	-21.95	-14.47	

Report No.: T190902W03-RP1

## Test Data




Report No.: T190902W03-RP1




Report No.: T190902W03-RP1

## Chain A



Report No.: T190902W03-RP1



## Chain B

