



BUREAU
VERITAS

Test Report No.: RF191023W005-1



ACCREDITED

Certificate # 3939.01

FCC TEST REPORT (Part 15, Subpart C)



Applicant:	Otis High Rise Elevator (Shanghai) Co., Ltd.
Address:	Room 101, Building 3, No. 1599, Xinqiniao Road, China (Shanghai) Pilot Free Trade Zone.

Manufacturer or Supplier:	Otis High Rise Elevator (Shanghai) Co., Ltd.
Address:	Room 101, Building 3, No. 1599, Xinqiniao Road, China (Shanghai) Pilot Free Trade Zone.
Product:	4G IoT Wireless Gateway
Brand Name:	Otis ONE[®]
Model Name:	C9200-4L
FCC ID:	2AUTDC9200-4L
Date of tests:	Oct. 23, 2019 ~ Nov. 06, 2019

The tests have been carried out according to the requirements of the following standard:

- FCC Part 15, Subpart C, Section 15.247
- ANSI C63.10-2013

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Alex Chen Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department
 Date: Nov. 08, 2019	 Date: Nov. 08, 2019

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

RELEASE CONTROL RECORD 4

1 SUMMARY OF TEST RESULTS..... 5

1.1 MEASUREMENT UNCERTAINTY 5

2 GENERAL INFORMATION 6

2.1 GENERAL DESCRIPTION OF EUT 6

2.2 DESCRIPTION OF TEST MODES 7

2.2.1 CONFIGURATION OF SYSTEM UNDER TEST 8

2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL..... 8

2.3 DUTY CYCLE OF TEST SIGNAL 10

2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS 10

2.5 DESCRIPTION OF SUPPORT UNITS 10

2.6 ANTENNA REQUIREMENT11

CONCLUSION:.....11

3 TEST TYPES AND RESULTS..... 12

3.1 CONDUCTED EMISSION MEASUREMENT 12

3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 12

3.1.2 TEST INSTRUMENTS..... 12

3.1.3 TEST PROCEDURES 13

3.1.4 DEVIATION FROM TEST STANDARD 13

3.1.5 TEST SETUP 14

3.1.6 EUT OPERATING CONDITIONS 14

3.1.7 TEST RESULTS 15

3.2 RADIATED EMISSION MEASUREMENT 17

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT 17

3.2.2 TEST INSTRUMENTS..... 18

3.2.3 TEST PROCEDURES 19

3.2.4 DEVIATION FROM TEST STANDARD 19

3.2.5 TEST SETUP 20

3.2.6 EUT OPERATING CONDITIONS 21

3.2.7 TEST RESULTS 22

3.3 6 DB BANDWIDTH MEASUREMENT 32

3.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT 32

3.3.2 TEST INSTRUMENTS..... 32

3.3.3 TEST PROCEDURE..... 32



3.3.4	DEVIATION FROM TEST STANDARD	32
3.3.5	TEST SETUP	33
3.3.6	EUT OPERATING CONDITIONS	33
3.3.7	TEST RESULTS	33
3.4	CONDUCTED OUTPUT POWER.....	34
3.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	34
3.4.2	TEST SETUP	34
3.4.3	TEST INSTRUMENTS.....	34
3.4.4	TEST PROCEDURES	34
3.4.5	DEVIATION FROM TEST STANDARD	34
3.4.6	EUT OPERATING CONDITIONS	34
3.4.7	TEST RESULTS	35
3.4.7.1	MAXIMUM PEAK OUTPUT POWER	35
3.5	POWER SPECTRAL DENSITY MEASUREMENT	36
3.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	36
3.5.2	TEST SETUP	36
3.5.3	TEST INSTRUMENTS.....	36
3.5.4	TEST PROCEDURE.....	36
3.5.5	DEVIATION FROM TEST STANDARD	36
3.5.6	EUT OPERATING CONDITION	36
3.5.7	TEST RESULTS	37
3.6	OUT OF BAND EMISSION MEASUREMENT	37
3.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT	37
3.6.2	TEST SETUP	37
3.6.3	TEST INSTRUMENTS.....	37
3.6.4	TEST PROCEDURE.....	37
3.6.5	DEVIATION FROM TEST STANDARD	38
3.6.6	EUT OPERATING CONDITION	38
3.6.7	TEST RESULTS	38
4	PHOTOGRAPHS OF THE TEST CONFIGURATION	39
5	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	40



**BUREAU
VERITAS**

Test Report No.: RF191023W005-1

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF191023W005-1	Original release	Nov. 08, 2019



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)		
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT
15.207	AC Power Conducted Emission	Compliance
15.205 15.209	Radiated Emissions	Compliance
15.247(d)	Out of band Emission Measurement	See Note
15.247(a)(2)	6dB bandwidth	See Note
15.247(b)	Conducted Output power	See Note
15.247(e)	Power Spectral Density	See Note
15.203	Antenna Requirement	Compliance

Note: These items please refer to the BLE module report TCT171024E042 which The FCC ID is 2ACOE-SKB369, and the BLE module has been certified by MiCOM Labs on 11/10/2017. The host contains the BLE module.

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
AC Power Conducted emissions	±2.70dB
Radiated emissions (30MHz~1GMHz)	±4.98dB
Radiated emissions (1GMHz ~6GMHz)	±4.70dB
Radiated emissions (6GMHz ~18GMHz)	±4.60dB
Radiated emissions (18GMHz ~40GMHz)	±4.12dB
Conducted emissions	±4.01dB
Occupied Channel Bandwidth	±43.58KHz
Conducted Output power	±2.06dB
Power Spectral Density	±0.85 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.



2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	4G IoT Wireless Gateway
BRAND NAME	Otis ONE[®]
MODEL NAME	C9200-4L
NOMINAL VOLTAGE	DC 12V
MODULATION	GFSK
TRANSMISSION RATE	BT_LE: 1 Mbps
OPERATING FREQUENCY	2402-2480MHz for BT-LE(GFSK)
MAX. OUTPUT POWER	BT-LE: 1.589mW (Maximum)
ANTENNA TYPE	Fixed External antenna with 3dBi gain for ANT0 Fixed External antenna with 3dBi gain for ANT1
HW VERSION	V1.0.3
SW VERSION	V1.0.0
I/O PORTS	Refer to user's manual

NOTE:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- The EUT was powered by the following adapter:

ADAPTER	
BRAND:	ShenZhen Mass Power Electronic Limited
MODEL:	NBS18C120150D5
INPUT:	AC 100-240V, 600mA
OUTPUT:	DC 12V, 1500mA
POWER CORD:	1.2 meter
MANUFACTURER:	Dongguan NB Power Electronic Limited

- The EUT incorporates a SISO function. Physically, the EUT provides one transmitter and one receiver.

MODULATION MODE	TX/RX FUNCTION
BT_LE	1TX /1RX

- For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.



2.2 DESCRIPTION OF TEST MODES

40 channels are provided for BT-LE (GFSK):

CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photographs of the test configuration for reference.

2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.

The worst case was found when positioned on Y axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	-	-

Where **RE<1G**: Radiated Emission below 1GHz **RE≥1G**: Radiated Emission above 1GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

NOTE: No need to concern of Conducted Emission due to the EUT is powered by battery.

RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
BT-LE (Ant 0)	0 to 39	19	GFSK	1
BT-LE (Ant 1)	0 to 39	39	GFSK	1

RADIATED EMISSION TEST (ABOVE 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
BT-LE	0 to 39	0,19, 39	GFSK	1



POWER LINE CONDUCTED EMISSION TEST

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
BT-LE	0 to 39	19	GFSK	1

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	22deg. C, 54%RH	DC 12V	Star Le
RE≥1G	22deg. C, 54%RH	DC 12V	Star Le
PLCE	25deg. C, 52%RH	DC 12V	Jimmy Liu



2.3 Duty Cycle of Test Signal

The test results was recorded in Report No.: TCT171024E042 (FCC ID: 2ACOE-SKB369).

2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

558074 D01 DTS Meas Guidance v05r02

ANSI C63.10-2013

Note:

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (SDoC). The test report has been issued separately.

2.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC source	LONG WEI	PS-6403D	010934269	N/A
2	PC	HP	A6608CN	3CR83825X3	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	DC Line: Unshielded, Detachable 1.0m
2	AC Line: Unshielded, Detachable 1.5m



2.6 ANTENNA REQUIREMENT

Per FCC Part 15.203. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Conclusion:

The EUT use one Fixed External Antenna that was permanently attached and the detail information list as below:

ANT Gain (dBi)	Type	TX/RX	Frequency range
3	Fixed External Antenna 0	TX & RX	2400~2483.5GHz
3	Fixed External Antenna 1	TX & RX	2400~2483.5GHz



3 TEST TYPES AND RESULTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBµV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE: 1.The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

3.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	101900	Feb. 26,19	Feb. 25,20
EMC32 test software	Rohde&Schwarz	EMC32	NA	NA	NA
LISN network	Rohde&Schwarz	ENV216	101922	Feb. 26,19	Feb. 25,20

NOTE:

1. The test was performed in CE shielded room.

2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



3.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.


NOTE: All modes of operation were investigated and the worst-case emissions are reported.

3.1.4 DEVIATION FROM TEST STANDARD

No deviation.



3.1.5 TEST SETUP



- Note:**
- 1.Support units were connected to second LISN.
 - 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.



3.1.7 TEST RESULTS


CONDUCTED WORST-CASE DATA:

Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25deg. C, 52RH
Test Voltage	DC 12V From Adapter	Tested By	Jimmy Liu

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.154000	---	29.52	55.78	-26.26	L	ON	9.9
0.154000	43.70	---	65.78	-22.08	L	ON	9.9
0.396000	---	24.44	47.94	-23.50	L	ON	10.0
0.396000	32.76	---	57.94	-25.18	L	ON	10.0
0.844000	---	17.77	46.00	-28.23	L	ON	10.1
0.844000	27.53	---	56.00	-28.47	L	ON	10.1
1.416000	---	16.45	46.00	-29.55	L	ON	10.1
1.416000	24.35	---	56.00	-31.65	L	ON	10.1
3.328000	---	16.18	46.00	-29.82	L	ON	10.2
3.328000	26.36	---	56.00	-29.64	L	ON	10.2
3.884000	---	17.27	46.00	-28.73	L	ON	10.2
3.884000	27.89	---	56.00	-28.11	L	ON	10.2

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.

Full Spectrum






Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25deg. C, 52RH
Test Voltage	DC 12V From Adapter	Tested By	Jimmy Liu

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.150000	---	27.14	56.00	-28.86	N	ON	9.9
0.150000	40.49	---	66.00	-25.51	N	ON	9.9
0.400000	---	24.58	47.85	-23.27	N	ON	9.9
0.400000	32.73	---	57.85	-25.12	N	ON	9.9
0.784000	---	16.44	46.00	-29.56	N	ON	9.9
0.784000	24.59	---	56.00	-31.41	N	ON	9.9
2.100000	---	13.74	46.00	-32.26	N	ON	10.0
2.100000	24.26	---	56.00	-31.74	N	ON	10.0
3.280000	---	18.08	46.00	-27.92	N	ON	10.1
3.280000	27.92	---	56.00	-28.08	N	ON	10.1
3.892000	---	16.82	46.00	-29.18	N	ON	10.1
3.892000	27.12	---	56.00	-28.88	N	ON	10.1

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.

Full Spectrum





3.2 RADIATED EMISSION MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



3.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	Feb. 26,19	Feb. 25,20
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Feb. 26,19	Feb. 25,20
Horn Antenna	ETS-LINDGREN	3117	00168728	Feb. 26,19	Feb. 25,20
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K-SG/QMS-00361	15433	Nov. 21, 18	Nov. 20, 19
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	1505	Jun. 24,19	Jun. 23,20
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Feb. 26,19	Feb. 25,20
Signal Pre-Amplifier	EMSI	EMC 9135	980249	Jun. 24,19	Jun. 23,20
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	Jun. 24,19	Jun. 23,20
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Jun. 24,19	Jun. 23,20

- NOTE:**
1. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
 2. The test was performed in 3m Chamber.
 3. The FCC Site Registration No. is 525120; The Designation No. is CN1171.



3.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.


3.2.4 DEVIATION FROM TEST STANDARD

No deviation




3.2.5 TEST SETUP

< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).



**BUREAU
VERITAS**

Test Report No.: RF191023W005-1

3.2.6 EUT OPERATING CONDITIONS

- a. Set the EUT under full load condition and placed them on a testing table.
- b. Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- c. The necessary accessories enable the EUT in full functions.



3.2.7 TEST RESULTS

ANT 0

BELOW 1GHz WORST-CASE DATA:

30 MHz – 1GHz data:


BT-LE_4.0

CHANNEL	TX Channel 19	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
79.265	27.03	55.11	40	-12.97	8.06	1.2	37.34	200	360	QP
160.214	23.69	48.26	43.5	-19.81	10.5	1.66	36.73	200	360	QP
383.254	26.64	44.23	46	-19.36	16.68	2.55	36.82	200	360	QP
486.115	32.62	48.34	46	-13.38	18.32	2.94	36.98	200	360	QP
578.226	26.92	41.34	46	-19.08	19.75	3.12	37.29	200	360	QP
708.625	34.72	45.68	46	-11.28	23.03	3.56	37.55	200	360	QP

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value






CHANNEL	TX Channel 19	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
32.55	31.74	52.65	40	-8.26	15.72	0.82	37.45	100	0	QP
81.665	35.12	62.89	40	-4.88	8.35	1.21	37.33	100	0	QP
123.258	26.98	53.87	43.5	-16.52	8.7	1.46	37.05	100	0	QP
161.224	31	55.66	43.5	-12.5	10.4	1.66	36.72	100	0	QP
233.74	21.66	43.9	46	-24.34	12.42	1.96	36.62	100	0	QP
485.33	30.23	45.78	46	-15.77	18.49	2.94	36.98	100	0	QP

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value





ABOVE 1GHz TEST DATA:

Note: For higher frequency, the emission is too low to be detected.

BT-LE_4.0

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	64.62	73.01	74	-9.38	33.1	4.88	46.37	100	80	Peak
2390	39.2	47.59	54	-14.8	33.1	4.88	46.37	100	80	Average
2402	97.18	105.54			33.12	4.89	46.37	100	80	Peak
2402	89.5	97.86			33.12	4.89	46.37	100	80	Average
2483.5	52.89	61.01	74	-21.11	33.27	4.98	46.37	100	80	Peak
2483.5	40.54	48.66	54	-13.46	33.27	4.98	46.37	100	80	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	64.48	73.76	74	-9.52	32.21	4.88	46.37	100	330	Peak
2390	39.08	48.36	54	-14.92	32.21	4.88	46.37	100	330	Average
2402	97.43	106.66			32.25	4.89	46.37	100	330	Peak
2402	92.17	101.4			32.25	4.89	46.37	100	330	Average
2483.5	53.31	62.24	74	-20.69	32.46	4.98	46.37	100	330	Peak
2483.5	39.07	48	54	-14.93	32.46	4.98	46.37	100	330	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2402MHz: Fundamental frequency.



CHANNEL	TX Channel 19	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	66.46	74.85	74	-7.54	33.1	4.88	46.37	100	63	Peak
2390	38.71	47.1	54	-15.29	33.1	4.88	46.37	100	63	Average
2440	100.18	108.42			33.19	4.94	46.37	100	63	Peak
2440	91.44	99.68			33.19	4.94	46.37	100	63	Average
2483.5	52.85	60.97	74	-21.15	33.27	4.98	46.37	100	63	Peak
2483.5	38.98	47.1	54	-15.02	33.27	4.98	46.37	100	63	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	61.03	70.31	74	-12.97	32.21	4.88	46.37	100	330	Peak
2390	38.34	47.62	54	-15.66	32.21	4.88	46.37	100	330	Average
2440	99.55	108.64			32.34	4.94	46.37	100	330	Peak
2440	90.56	99.65			32.34	4.94	46.37	100	330	Average
2483.5	51.72	60.65	74	-22.28	32.46	4.98	46.37	100	330	Peak
2483.5	37.63	46.56	54	-16.37	32.46	4.98	46.37	100	330	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2440MHz: Fundamental frequency.



CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	66.45	74.84	74	-7.55	33.1	4.88	46.37	100	69	Peak
2390	39.96	48.35	54	-14.04	33.1	4.88	46.37	100	69	Average
2480	98.96	107.09			33.26	4.98	46.37	100	69	Peak
2480	92.97	101.1			33.26	4.98	46.37	100	69	Average
2483.5	56.08	64.2	74	-17.92	33.27	4.98	46.37	100	69	Peak
2483.5	39.14	47.26	54	-14.86	33.27	4.98	46.37	100	69	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	52.19	61.47	74	-21.81	32.21	4.88	46.37	100	280	Peak
2390	38.59	47.87	54	-15.41	32.21	4.88	46.37	100	280	Average
2480	95.72	104.66			32.45	4.98	46.37	100	280	Peak
2480	89.08	98.02			32.45	4.98	46.37	100	280	Average
2483.5	55.08	64.01	74	-18.92	32.46	4.98	46.37	100	280	Peak
2483.5	38.42	47.35	54	-15.58	32.46	4.98	46.37	100	280	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2480MHz: Fundamental frequency.



ANT 1

BELOW 1GHz WORST-CASE DATA:

30 MHz – 1GHz data:


BT-LE_4.0

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
80.25	28.2	56.23	40	-11.8	8.11	1.2	37.34	200	360	QP
161.26	24.96	49.53	43.5	-18.54	10.49	1.66	36.72	200	360	QP
384.22	28.78	46.33	46	-17.22	16.71	2.56	36.82	200	360	QP
487.25	33.8	49.51	46	-12.2	18.33	2.94	36.98	200	360	QP
578.226	28.17	42.59	46	-17.83	19.75	3.12	37.29	200	360	QP
710.26	35.81	46.75	46	-10.19	23.04	3.57	37.55	200	360	QP

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value






CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
32.55	31.74	52.65	40	-8.26	15.72	0.82	37.45	100	0	QP
81.665	35.12	62.89	40	-4.88	8.35	1.21	37.33	100	0	QP
123.258	26.98	53.87	43.5	-16.52	8.7	1.46	37.05	100	0	QP
161.224	31	55.66	43.5	-12.5	10.4	1.66	36.72	100	0	QP
233.74	21.66	43.9	46	-24.34	12.42	1.96	36.62	100	0	QP
485.33	30.23	45.78	46	-15.77	18.49	2.94	36.98	100	0	QP

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value





ABOVE 1GHz TEST DATA:

Note: For higher frequency, the emission is too low to be detected.

BT-LE_4.0

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	55.03	63.42	74	-18.97	33.1	4.88	46.37	100	270	Peak
2390	39.03	47.42	54	-14.97	33.1	4.88	46.37	100	270	Average
2402	83.25	91.61			33.12	4.89	46.37	100	270	Peak
2402	76.19	84.55			33.12	4.89	46.37	100	270	Average
2483.5	53.55	61.67	74	-20.45	33.27	4.98	46.37	100	270	Peak
2483.5	39.12	47.24	54	-14.88	33.27	4.98	46.37	100	270	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	52.68	61.96	74	-21.32	32.21	4.88	46.37	100	127	Peak
2390	38.99	48.27	54	-15.01	32.21	4.88	46.37	100	127	Average
2402	90.53	99.76			32.25	4.89	46.37	100	127	Peak
2402	85.9	95.13			32.25	4.89	46.37	100	127	Average
2483.5	51.99	60.92	74	-22.01	32.46	4.98	46.37	100	127	Peak
2483.5	39.19	48.12	54	-14.81	32.46	4.98	46.37	100	127	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2402MHz: Fundamental frequency.



CHANNEL	TX Channel 19	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	59.02	67.41	74	-14.98	33.1	4.88	46.37	100	270	Peak
2390	39.14	47.53	54	-14.86	33.1	4.88	46.37	100	270	Average
2440	84.17	92.41			33.19	4.94	46.37	100	270	Peak
2440	78.28	86.52			33.19	4.94	46.37	100	270	Average
2483.5	52.79	60.91	74	-21.21	33.27	4.98	46.37	100	270	Peak
2483.5	39	47.12	54	-15	33.27	4.98	46.37	100	270	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	59.23	68.51	74	-14.77	32.21	4.88	46.37	100	160	Peak
2390	38	47.28	54	-16	32.21	4.88	46.37	100	160	Average
2440	88.93	98.16			32.25	4.89	46.37	100	160	Peak
2440	83.66	92.75			32.34	4.94	46.37	100	160	Average
2483.5	52.23	61.16	74	-21.77	32.46	4.98	46.37	100	160	Peak
2483.5	38.22	47.15	54	-15.78	32.46	4.98	46.37	100	160	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2440MHz: Fundamental frequency.



CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	64.77	73.16	74	-9.23	33.1	4.88	46.37	100	270	Peak
2390	40.14	48.53	54	-13.86	33.1	4.88	46.37	100	270	Average
2480	82.04	90.17			33.26	4.98	46.37	100	270	Peak
2480	75.44	83.57			33.26	4.98	46.37	100	270	Average
2483.5	52.31	60.43	74	-21.69	33.27	4.98	46.37	100	270	Peak
2483.5	39.44	47.56	54	-14.56	33.27	4.98	46.37	100	270	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	55.48	64.76	74	-18.52	32.21	4.88	46.37	100	190	Peak
2390	39.39	48.67	54	-14.61	32.21	4.88	46.37	100	190	Average
2480	88.57	97.51			32.45	4.98	46.37	100	190	Peak
2480	81.79	90.73			32.45	4.98	46.37	100	190	Average
2483.5	52.77	61.7	74	-21.23	32.46	4.98	46.37	100	190	Peak
2483.5	38.33	47.26	54	-15.67	32.46	4.98	46.37	100	190	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2480MHz: Fundamental frequency.



3.3 6 dB BANDWIDTH MEASUREMENT

3.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

3.3.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Meter	ANRITSU	ML2495A	1506002	Feb. 26,19	Feb. 25,20
EXA Signal Analyzer	KEYSIGHT	N9010A-526	MY54510322	Feb. 26,19	Feb. 25,20
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510355	Feb. 26,19	Feb. 25,20
Power Sensor	ANRITSU	MA2411B	1339352	Feb. 26,19	Feb. 25,20

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in RF Oven room.

3.3.3 TEST PROCEDURE


1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

3.3.4 DEVIATION FROM TEST STANDARD

No deviation.



3.3.5 TEST SETUP



3.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.3.7 TEST RESULTS

The test results was recorded in Report No.: TCT171024E042 (FCC ID:2ACOE-SKB369).




3.4 CONDUCTED OUTPUT POWER

3.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm)

3.4.2 TEST SETUP



3.4.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

3.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

3.4.5 DEVIATION FROM TEST STANDARD

No deviation.

3.4.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



3.4.7 TEST RESULTS

3.4.7.1 MAXIMUM PEAK OUTPUT POWER

The test results was verify from Report No.: TCT171024E042 (FCC ID:2ACOE-SKB369).

BT-LE (GFSK)

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
0	2402	1.79	1.510	1	PASS
19	2440	1.25	1.334	1	PASS
39	2480	0.02	1.005	1	PASS




3.5 POWER SPECTRAL DENSITY MEASUREMENT

3.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm/3KHz.

3.5.2 TEST SETUP



3.5.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

3.5.4 TEST PROCEDURE

1. Set the span to 1.5 times the DTS bandwidth
2. Set the RBW = 3 kHz, VBW \geq 3 x RBW, Detector = peak.
3. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

3.5.5 DEVIATION FROM TEST STANDARD

No deviation.

3.5.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



3.5.7 TEST RESULTS


The test results was recorded in Report No.: TCT171024E042 (FCC ID:2ACOE-SKB369).

3.6 OUT OF BAND EMISSION MEASUREMENT

3.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

3.6.2 TEST SETUP



3.6.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

3.6.4 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW \geq 300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

3.6.5 DEVIATION FROM TEST STANDARD

No deviation.

3.6.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.6.7 TEST RESULTS

The test results was recorded in Report No.: TCT171024E042 (FCC ID:2ACOE-SKB369).



4 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



**BUREAU
VERITAS**

Test Report No.: RF191023W005-1

5 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---