

## RF Exposure Requirements

---

Product Description: Handheld Barcode Scanner

Model No.: HN-3378SR-000R, HN-3378XX-XXXX("XX"represents the focal distances of the lens maybe SR,MR,LR,HD,HP,WA etc., "X"represents software version,maybe 0-9, "XX"represents customer code, maybe 00-99, "R"represents RoHS Certification)

FCC ID: 2AUTE-3378

According to the KDB 447498 D01 v06 section 4.3.1, for 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

-  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

- Power and distance are rounded to the nearest mW and mm before calculation

- The result is rounded to one decimal place for comparison

### Calculation Result:

Tx frequency range: 2405-2480MHz

Min. test separation distance: 5mm

Maximum Conducted Output Power: -1.80dBm

Tune-Up output power: -1.0dBm

RF channel transmit frequency: 2402MHz

Result: 0.2

Limit: 3.0

The exclusion thresholds is  $0.2 < 3$ , so the transmitter complies with the RF exposure requirements and the SAR is not required.