



No.:
FCCSZ2024-0006-RF3

TEST REPORT

FCC ID : 2AUTE-4TS24A

NAME OF SAMPLE : Photo Printer

APPLICANT : Xiamen Hanin Co., Ltd.

CLASSIFICATION OF TEST : N/A

CVC Testing Technology (Shenzhen) Co., Ltd.



Applicant		Name: Xiamen Hanin Co., Ltd. Address: Room 305A, Angye Building, Pioneering Park, Torch High-tech Zone, Xiamen, China	
Manufacturer		Name: Xiamen Hanin Co., Ltd. Address: Room 305A, Angye Building, Pioneering Park, Torch High-tech Zone, Xiamen, China	
Equipment Under Test		Name: Photo Printer Model/Type: HCP-4TS24A Additional Models/Types: CP4100 Brand: N/A Serial NO.: N/A Sample NO.: 4-1	
Date of Receipt.	2024.01.23	Date of Testing	2024.01.24 ~ 2024.03.01
Test Specification		Test Result	
FCC Part 15, Subpart C, Section 15.225		PASS	
Evaluation of Test Result	The equipment under test was found to comply with the requirements of the standards applied. Seal of CVC Issue Date: 2024.03.01		
Tested by: Zhu Yulin Name Signature	Reviewed by: Huang Meng Name Signature	Approved by: Dong Sanbi Name Signature	
Other Aspects: NONE.			
Abbreviations: OK, Pass= passed Fail = failed N/A= not applicable EUT= equipment, sample(s) under tested			

This test report relates only to the EUT, and shall not be reproduced except in full, without written approval of CVC.



TABLE OF CONTENTS

1 SUMMARY OF TEST RESULTS	5
1.1 LIST OF TEST AND MEASUREMENT INSTRUMENTS	6
1.2 MEASUREMENT UNCERTAINTY	7
1.3 TEST LOCATION	7
2 GENERAL INFORMATION	8
2.1 GENERAL PRODUCT INFORMATION	8
2.2 ADDITIONAL MODEL/TYPE	8
2.3 OTHER INFORMATION	9
2.4 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	9
2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS	11
2.6 DESCRIPTION OF SUPPORT UNITS	11
3 TEST TYPES AND RESULTS	12
3.1 CONDUCTED EMISSION	12
3.2 RADIATED EMISSIONS	15
3.3 FREQUENCY TOLERANCE	25
3.4 20DB BANDWIDTH	27
4 PHOTOGRAPHS OF TEST SETUP	29
5 PHOTOGRAPHS OF THE EUT	30



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FCCSZ2024-0006-RF3	Original release	2024.03.01



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C Section 15.225			
FCC STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Line Conducted Emission	PASS	Meet the requirement of limit.
15.225 (a)&(b)&(c) 15.205	The field strength of Fundamental Emission	PASS	Meet the requirement of limit.
15.225 (d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit.
15.225 (e)	Frequency tolerance	PASS	Meet the requirement of limit.
15.215 (c)	20dB Bandwidth	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.



1.1 LIST OF TEST AND MEASUREMENT INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial Number	Cal. interval	Cal. Due
Antenna Port Conducted Test					
Signal&Spectrum Analyzer	Rohde&Schwarz	FSV 30	104408	1 year	2024.5.21
#3Shielding room	MORI	443	N/A	3 year	2026.5.16
Wideband radio communication tester	Rohde&Schwarz	CMW 500	168778	1 year	2024.5.25
Analog signal Generator (100kHz ~ 40GHz)	Rohde&Schwarz	SMB 100A	181934	1 year	2024.5.21
Vector signal Generator (9kHz ~ 6GHz)	Keysight	N5182B	MY57301451	1 year	2024.4.25
Vector signal Generator (9kHz ~ 6GHz)	Rohde&Schwarz	SGT 100A	111724	1 year	2024.5.21
RF control unit(BT/WiFi)	Tonscend	JS0806-2-8CH	20E8060261	1 year	2024.5.21
Temperature and humidity meter	/	C193561457	C193561457	1 year	2024.5.21
Radiation Spurious Test - 3M Chamber #2					
Signal&Spectrum Analyzer	Rohde&Schwarz	FSV 40	101898	1 year	2024.5.21
EMI Test Receiver	Rohde&Schwarz	ESR3	102693	1 year	2024.5.25
Antenna(30MHz~1001MHz)	SCHWARZBECK	VULB 9168	1133	1 year	2024.5.21
Horn antenna(1GHz-18GHz)	ETS	3117	227611	1 year	2024.3.25
Horn antenna(18GHz-40GHz)	QMS	QMS-00880	22051	1 year	2024.3.25
3m anechoic chamber	MORI	966	CS0300011	3 year	2026.5.18
Filter group(RSE-BT/WiFi)	Rohde&Schwarz	WiFi /BT Variant 1	100820	1 year	2024.5.21
Filter group(RSE-Cellular)	Rohde&Schwarz	Cellular Variant 1	100768	1 year	2024.5.21
Preamplifier(10kHz-1GHz)	Rohde&Schwarz	SCU-01F	100299	1 year	2024.5.21
Preamplifier(1GHz-18GHz)	Rohde&Schwarz	SCU-18F	100799	1 year	2024.5.21
Preamplifier(1GHz-18GHz)	Rohde&Schwarz	SCU-18F	100801	1 year	2024.5.21
Preamplifier(18Gz-40GHz)	Rohde&Schwarz	SCU-40A	101209	1 year	2024.5.21
#2 control room	MORI	433	CS0300028	3 year	2024.5.21
Temperature and humidity meter	/	C193561517	C193561517	1 year	2024.5.21
Radiation Spurious Test - 3M Chamber #1					
EMI Test Receiver	Rohde&Schwarz	ESR 26	101718	1 year	2024.5.25
Loop antenna (8.3k~30MHz)	Rohde&Schwarz	HFH2-Z2E	100951	1 year	2024.5.26
Antenna(30MHz~1000MHz)	SCHWARZBECK	VULB 9168	1132	1 year	2024.5.21
Horn antenna(1GHz-18GHz)	ETS	3117	227634	1 year	2024.3.25
Horn antenna(18GHz-40GHz)	SCHWARZBECK	BBHA 9170	01003	1 year	2024.3.25
3m anechoic chamber	MORI	966	CS0200019	3 year	2026.5.18
Attenuator	/	SJ-5dB	607684	1 year	2024.5.21
#1 control room	MORI	433	CS0300028	3 year	2026.5.16
Temperature and humidity meter	/	C193561473	CS0200071	1 year	2024.5.21



1.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

No.	Item	Measurement Uncertainty
1	Occupied Channel Bandwidth	±1.86 %
2	RF output power, conducted	±0.9 dB
3	Power Spectral Density, conducted	±0.8 dB
4	Conducted emission test	+/-2.7 dB
5	Radiated emission 9kHz-30MHz	+/-5.6 dB
	Radiated emission 30MHz-1GHz	+/-4.6 dB
	Radiated emission 1GHz-18GHz	+/-4.4 dB
	Radiated emission 18GHz-40GHz	+/-5.1 dB
6	Temperature	±0.73 °C
7	Humidity	±3.90 %
8	Supply voltages	±0.37 %
9	Time	±0.27 %
Remark: 95% Confidence Levels, k=2.		

1.3 TEST LOCATION

The tests and measurements refer to this report were performed by EMC testing Lab of CVC Testing Technology (Shenzhen) Co., Ltd.

Lab Address: No. 1301, Guanguang Road, Xinlan Community, Guanlan Street, Longhua District, Shenzhen City, Guangdong Province 518110 P.R.China

Post Code: 518110 Tel: 0755-23763060-8805
Fax: 0755-23763060 E-mail: sz-kf@cvc.org.cn
FCC(Test firm designation number: CN1363)
IC(Test firm CAB identifier number: CN0137)
CNAS(Test firm designation number: L16091)



2 GENERAL INFORMATION

2.1 GENERAL PRODUCT INFORMATION

PRODUCT	Photo Printer
BRAND	N/A
MODEL	HCP-4TS24A
ADDITIONAL MODEL (Remark 6)	CP4100
FCC ID	2AUTE-4TS24A
POWER SUPPLY	DC 24V from Adapter
MODULATION TYPE	ASK
OPERATING FREQUENCY	13.56MHz
NUMBER OF CHANNEL	1
ANTENNA TYPE (Remark 4/5)	Loop antenna
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	N/A
Remark: <ol style="list-style-type: none">For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.EUT photo refer to the report (Report NO.: FCCSZ2024-0006-EUT).Please refer to the antenna report.Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, CVC is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.the only difference is the model name.	

2.2 ADDITIONAL MODEL/TYPE

Adapter	
Brand	N/A
Model No.:	AP053U-24200
Input:	100-240V~50/60Hz 1.5A
Output:	24.0V \equiv 2.0A 48.0W
SN	KX202126000264
AC Cable:	N/A
DC Cable:	Shielded with one ferrite



2.3 OTHER INFORMATION

The EUT only have one channel.

CHANNEL	FREQUENCY (MHz)
1	13.56

2.4 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports
 The worst case was found when positioned on X axis for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE	FT	PLC	BW	
A	√	√	√	√	NFC Link

Where RE: Radiated Emission FT: Frequency tolerance
 PLC: Power Line Conducted Emission BW: 20dB Bandwidth

RADIATED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	TESTED CHANNEL	TESTED FREQUENCY (MHZ)	MODULATION TYPE	AXIS
A	1	13.56	ASK	X
	1	13.56	ASK	Y
	1	13.56	ASK	Z

FREQUENCY TOLERANCE:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	TESTED CHANNEL	TESTED FREQUENCY (MHZ)	MODULATION TYPE	AXIS
A	1	13.56	ASK	Y



POWER LINE CONDUCTED EMISSION TEST:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	TESTED CONDITION
A	NFC Link

20dB BANDWIDTH:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	TESTED CHANNEL	TESTED FREQUENCY (MHZ)	MODULATION TYPE	AXIS
A	1	13.56	ASK	Y

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE	25.5deg. C, 56%RH	DC 24V from Adapter	Liu Yuan
FT	25.5deg. C, 56%RH	DC 24V from Adapter	Zhu Yulin
PLC	25.5deg. C, 56%RH	DC 24V from Adapter	Zhu Yulin
BW	25.5deg. C, 56%RH	DC 24V from Adapter	Zhu Yulin



2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product, according to the specifications of the manufacturers. It must comply with the requirements of the following standards:

FCC PART 15, Subpart C. Section 15.225

ANSI C63.10-2020

All test items have been performed and recorded as per the above standards

2.6 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Support Equipment					
NO	Description	Brand	Model No.	Serial Number	Supplied by
1	N/A	N/A	N/A	N/A	N/A

Support Cable							
NO	Description	Quantity (Number)	Length (m)	Detachable (Yes/ No)	Shielded (Yes/ No)	Cores (Number)	Supplied by
1	N/A	N/A	N/A	N/A	N/A	N/A	N/A

3 TEST TYPES AND RESULTS

3.1 Conducted Emission

3.1.1 Limits Of Conducted Emission

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.107)

Frequency (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

NOTE: 1. The lower limit shall apply at the transition frequencies.
 NOTE: 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
 NOTE: 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.


3.1.2 Test Procedures

The basic test procedure was in accordance with ANSI C63.4:2014 (section 7).

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The test results of conducted emissions at mains ports are recorded of six worst margins for quasi-peak (mandatory) [and average (if necessary)] values against the limits at frequencies of interest unless the margin is 20 dB or greater.


Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

3.1.3 Test setup






3.1.4 Test Results





Test Mode	NFC Link	Frequency Range	150KHz ~ 30MHz
PHASE	Line (N)		



NO	Frequency (MHz)	QuasiPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr.Factor (dB)
1	0.152	48.7	---	65.9	17.2	N	10.0
2	0.377	---	24.4	48.3	23.9	N	9.9
3	1.565	30.3	---	56.0	25.7	N	10.0
4	3.127	---	21.5	46.0	24.5	N	10.1
5	8.036	34.7	---	60.0	25.3	N	10.3
6	8.277	---	21.9	50.0	28.1	N	10.3

Remark: The emission levels of other frequencies were very low against the limit.



3.2 RADIATED EMISSIONS

3.2.1 Limits

- (a) The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.
- (b) Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
- (c) Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

FREQUENCIES (MHz)	FIELD STRENGTH (Microvolts/Meter)	MEASUREMENT DISTANCE (Meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE: 1. The lower limit shall apply at the transition frequencies.
NOTE: 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

3.2.2 Measurement procedure


- a. The EUT was placed on the top of a rotating table 1.5 meters(above 1GHz) and 0.8 meters(below 1GHz) above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. For below 1GHz was used bilog antenna, and above 1GHz was used horn antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1m above the ground.
- g. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

NOTE:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz(Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The testing of the EUT was performed on all 3 orthogonal axes; the worst-case test configuration was reported on the file test setup photo.

3.2.3 Test setup

Below 30MHz Test Setup:



Below 1GHz Test Setup:






3.2.4 Test results

Result of The field strength of Fundamental Emission

Worst Test Mode	NFC	Channel	13.56M
Frequency Range	13.11MHz ~ 14.01MHz	Detector Function	Quasi-Peak (QP)




NO.	Freq. [MHz]	Reading [dBuV/m]	Factor [dB]	Level [dBuV/m]	Margin [dB]	Height [cm]	Angle[°]
1	13.113	4.41	-19.97	-15.56	56.06	100	197
2	13.311	4.67	-19.93	-15.26	55.43	100	253
3	13.459	5.44	-19.91	-14.47	64.97	100	169
4	13.560	18.49	-19.90	-1.41	85.41	100	237
5	13.769	5.77	-19.86	-14.09	54.59	100	265
6	13.881	3.73	-19.85	-16.12	56.62	100	288
7	13.966	5.01	-19.83	-14.82	55.32	100	130

Remark: 1. Conversion factor to 30m has been added to the factor.
 2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB).
 3. Factor (dB/m)=Antenna Factor (dB/m) + Cable Factor (dB).
 4. Emission level (dBuV/m) = 20 log Emission level (uV/m).



Worst Test Mode	NFC	Channel	13.56M
Frequency Range	13.11MHz ~ 14.01MHz	Detector Function	Quasi-Peak (QP)




NO.	Freq. [MHz]	Reading [dBuV/m]	Factor [dB]	Level [dBuV/m]	Margin [dB]	Height [cm]	Angle[°]
1	13.116	4.06	-19.97	-15.91	56.40	100	46
2	13.348	7.52	-19.93	-12.41	52.51	100	250
3	13.471	6.48	-19.91	-13.43	63.93	100	250
4	13.560	23.57	-19.90	3.67	80.33	100	227
5	13.686	6.99	-19.88	-12.89	63.39	100	238
6	13.771	5.97	-19.86	-13.89	54.39	100	250
7	13.870	4.36	-19.85	-15.49	55.99	100	221

Remark: 1. Conversion factor to 30m has been added to the factor.
 2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB).
 3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 4. Emission level (dBuV/m) = 20 log Emission level (uV/m).



Worst Test Mode	NFC	Channel	13.56M
Frequency Range	13.11MHz ~ 14.01MHz	Detector Function	Quasi-Peak (QP)




NO.	Freq. [MHz]	Reading [dBµV/m]	Factor [dB]	Level [dBµV/m]	Margin [dB]	Height [cm]	Angle[°]
1	13.117	4.35	-19.97	-15.62	56.11	100	159
2	13.345	8.95	-19.93	-10.98	51.09	100	0
3	13.445	9.40	-19.91	-10.51	61.01	100	0
4	13.521	8.25	-19.90	-11.65	62.15	100	0
5	13.560	26.76	-19.90	6.86	77.14	100	0
6	13.628	5.09	-19.89	-14.8	65.30	100	358
7	13.737	4.16	-19.87	-15.71	56.21	100	209

Remark: 1. Conversion factor to 30m has been added to the factor.
 2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB).
 3. Factor (dB/m)=Antenna Factor (dB/m) + Cable Factor (dB).
 4. Emission level (dBuV/m) = 20 log Emission level (uV/m).



Result of Radiated Emissions(9kHz~30MHz)

Worst Test Mode	NFC	Channel	13.56M
Frequency Range	9kHz ~ 30MHz	Detector Function	Quasi-Peak (QP)




NO.	Freq. [MHz]	Reading [dBuV/m]	Factor [dB]	Level [dBuV/m]	Margin [dB]	Height [cm]	Angle[°]
1	0.009	40.25	-59.48	-19.23	107.75	100	62
2	0.027	26.89	-59.22	-32.33	111.31	100	245
3	0.114	13.42	-59.25	-45.83	112.30	100	62
4	1.044	8.88	-19.21	-10.33	37.55	100	320
5	4.886	5.32	-19.20	-13.88	43.44	100	356
6	13.560	20.25	-19.90	0.35	29.20	100	245
7	25.183	5.50	-20.27	-14.77	44.31	100	3

Remark: 1. Conversion factor to 30m has been added to the factor.
 2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB).
 3. Factor (dB/m)=Antenna Factor (dB/m) + Cable Factor (dB).
 4. Emission level (dBuV/m) = 20 log Emission level (uV/m).



Worst Test Mode	NFC	Channel	13.56M
Frequency Range	9kHz ~ 30MHz	Detector Function	Quasi-Peak (QP)




NO.	Freq. [MHz]	Reading [dBµV/m]	Factor [dB]	Level [dBµV/m]	Margin [dB]	Height [cm]	Angle[°]
1	0.012	34.79	-59.45	-24.66	110.68	100	2
2	0.084	14.90	-59.41	-44.51	113.63	100	348
3	0.216	11.36	-59.47	-48.11	109.03	100	3
4	1.230	8.71	-19.19	-10.48	36.27	100	302
5	2.690	6.37	-19.03	-12.66	42.23	100	158
6	5.153	5.64	-19.23	-13.59	43.15	100	170
7	13.560	14.66	-19.90	-5.24	34.79	100	124

Remark: 1. Conversion factor to 30m has been added to the factor.
 2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB).
 3. Factor (dB/m)=Antenna Factor (dB/m) + Cable Factor (dB).
 4. Emission level (dBuV/m) = 20 log Emission level (uV/m).



Worst Test Mode	NFC	Channel	13.56M
Frequency Range	9kHz ~ 30MHz	Detector Function	Quasi-Peak (QP)




NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Margin [dB]	Height [cm]	Angle[°]
1	0.009	41.16	-59.48	-18.32	106.84	100	223
2	0.054	19.63	-59.11	-39.48	112.44	100	23
3	0.153	13.79	-59.66	-45.87	109.78	100	257
4	0.672	9.08	-18.91	-9.83	40.88	100	315
5	1.722	6.93	-19.12	-12.19	41.76	100	51
6	3.446	5.70	-19.03	-13.33	42.89	100	153
7	13.560	24.14	-19.90	4.24	25.31	100	189

Remark: 1. Conversion factor to 30m has been added to the factor.
 2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB).
 3. Factor (dB/m)=Antenna Factor (dB/m) + Cable Factor (dB).
 4. Emission level (dBuV/m) = 20 log Emission level (uV/m).



Result of Radiated Emissions(30MHz~1GHz)

Worst Test Mode	NFC	Channel	13.56M
Frequency Range	30MHz ~ 1GHz	Detector Function	Quasi-Peak (QP)




NO	Freq. [MHz]	Level [dBuV/m]	Reading [dBuV]	Factor [dB/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]
1	43.387	26.93	6.80	20.13	40.00	13.07	100	246
2	67.931	25.74	8.42	17.32	40.00	14.26	100	71
3	111.973	27.32	8.53	18.79	43.50	16.18	200	347
4	215.871	35.73	17.84	17.89	43.50	7.77	100	304
5	226.348	41.73	23.60	18.13	46.00	4.27	100	141
6	406.786	37.52	14.43	23.09	46.00	8.48	100	12

Remark: 1. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB).
 2. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m]
 4. Emission level (dBuV/m) = 20 log Emission level (uV/m).



Worst Test Mode	NFC	Channel	13.56M
Frequency Range	30MHz ~ 1GHz	Detector Function	Quasi-Peak (QP)



NO	Freq. [MHz]	Level [dBμV/m]	Reading [dBμV]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]
1	61.819	35.26	16.67	18.59	40.00	4.74	100	2
2	66.670	35.14	17.55	17.59	40.00	4.86	100	9
3	111.973	33.27	14.48	18.79	43.50	10.23	100	184
4	214.707	36.27	18.41	17.86	43.50	7.23	100	21
5	225.087	40.26	22.15	18.11	46.00	5.74	100	21
6	488.177	38.89	13.94	24.95	46.00	7.11	100	255

Remark: 1. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB).
 2. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]
 4. Emission level (dBuV/m) = 20 log Emission level (uV/m).

3.3 FREQUENCY TOLERANCE


3.3.1 LIMIT OF FREQUENCY TOLERANCE

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ (100ppm) of the operating frequency over a temperature variation of -20 degrees to $+ 50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

3.3.2 TEST PROCEDURES

Refer to ANSI C63.10-2020

3.3.3 TEST SETUP





3.3.4 TEST RESULTS

FREQUENCY STABILITY VERSUS TEMP.									
TEMP. (°C)	POWER SUPPLY (V)	0 MINUTE		2 MINUTE		5 MINUTE		10 MINUTE	
		Measured Frequency (MHz)	Frequency Drift (ppm)	Measured Frequency (MHz)	Frequency Drift (ppm)	Measured Frequency (MHz)	Frequency Drift (ppm)	Measured Frequency (MHz)	Frequency Drift (ppm)
50	24	13.560605	44.62	13.560607	44.76	13.560607	44.76	13.560607	44.76
40	24	13.560600	44.25	13.560609	44.91	13.560602	44.40	13.560603	44.47
30	24	13.560609	44.91	13.560607	44.76	13.560602	44.40	13.560604	44.54
20	24	13.560603	44.47	13.560610	44.99	13.560607	44.76	13.560612	45.13
10	24	13.560605	44.62	13.560607	44.76	13.560604	44.54	13.560612	45.13
0	24	13.560601	44.32	13.560604	44.54	13.560608	44.84	13.560604	44.54
-10	24	13.560607	44.76	13.560604	44.54	13.560605	44.62	13.560609	44.91
-20	24	13.560603	44.47	13.560609	44.91	13.560606	44.69	13.560610	44.99
20	27.6	13.560608	44.84	13.560603	44.47	13.560606	44.69	13.560611	45.06
	20.4	13.560604	44.54	13.560603	44.47	13.560605	44.62	13.560610	44.99

3.4 20dB BANDWIDTH

3.4.1 LIMITS OF 20dB BANDWIDTH


The 20dB bandwidth shall be specified in operating frequency band. (13.11MHz – 14.01MHz)

3.4.2 TEST PROCEDURE

- a. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- b. The resolution bandwidth of 1kHz and the video bandwidth of 3kHz were used.
- c. Measured spectrum width with power higher than 20dB below carrier.

Note: Because the measured signal is CW or CW-like adjust the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately the RBW

3.4.3 TEST SETUP






3.4.4 TEST RESULTS

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (KHz)
1	13.56	2.098

Lower & Upper Test Frequency Point (MHz)	Test Frequency (MHz)	P/F
Lower	13.5589	PASS
Upper	13.5610	PASS





4 PHOTOGRAPHS OF TEST SETUP

Please refer to the attached file (Test Photos).



5 PHOTOGRAPHS OF THE EUT

Please refer to the attached file (External Photos report and Internal Photos).

----- End of the Report -----



Important

- (1) The test report is invalid without the official stamp of CVC;
- (2) Any part photocopies of the test report are forbidden without the written permission from CVC;
- (3) The test report is invalid without the signatures of Approval and Reviewer;
- (4) The test report is invalid if altered;
- (5) Objections to the test report must be submitted to CVC within 15 days.
- (6) Generally, commission test is responsible for the tested samples only.
- (7) As for the test result “-” or “N” means “not applicable”, “/” means “not test”, “P” means “pass” and “F” means “fail”

The test data and test results given in this test report should only be used for purposes of scientific research, teaching and internal quality control when the CMA symbol is not presented.

Laboratory: CVC Testing Technology Co., Ltd.

Address: No.3, TiantaiyiRoad, KaitaiAvenue, ScienceCity, Guangzhou, China

Post Code: 510663 Tel: 020-32293888

FAX: 020-32293889 E-mail: office@cvc.org.cn