

1. RF Exposure Requirements

1.1 General Information

Client Information

Applicant: Xiamen Hanin Co.,Ltd.
Address of applicant: Room 305A, Angye Building, Pioneering Park, Torch High-tech, Zone, Xiamen, China
Manufacturer: The same as Applicant
Address of manufacturer: The same as Applicant

General Description of EUT:

Product Name: Photo Printer
Trade Name: /
Model No.: CP6000
Adding Model(s): HCP-4TS24C, CP6100
Rated Voltage: DC24V
AP053U-24200
Power Adapter Model: INPUT:AC100-240V 50/60Hz 1.5A
OUTPUT:DC24V 2.0A
FCC ID: 2AUTE-4TS24C
Equipment Type: Mobile device

Technical Characteristics of EUT:

Wi-Fi

Support Standards: 802.11b, 802.11g, 802.11n
Frequency Range: 2412-2462MHz for 802.11b/g/n(HT20)
RF Output Power: 15.43dBm (Conducted)
Type of Modulation: CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Quantity of Channels: 11 for 802.11b/g/n(HT20)
Channel Separation: 5MHz
Type of Antenna: FPC Antenna
Antenna Gain: 2.26dBi

Bluetooth 1

Bluetooth Version: V5.2 (BR/EDR/LE mode)
Frequency Range: 2402-2480MHz
RF Output Power: 8.09dBm (Conducted)
Data Rate: 1Mbps, 2Mbps, 3Mbps
Modulation: GFSK, $\pi/4$ DQPSK, 8DPSK
Quantity of Channels: 79/40
Channel Separation: 1MHz/2MHz
Type of Antenna: FPC Antenna
Antenna Gain: 2.26dBi

Bluetooth 2

Bluetooth Version:	V5.1(BR/EDR/LE mode)
Frequency Range:	2402-2480MHz
RF Output Power:	-7.15dBm (Conducted)
Data Rate:	1Mbps, 2Mbps
Modulation:	GFSK, $\pi/4$ DQPSK
Quantity of Channels:	79/40
Channel Separation:	1MHz/2MHz
Type of Antenna:	PCB Antenna
Antenna Gain:	-3.35dBi

NFC

Support Standards:	NFC
Frequency Range:	13.56MHz
Max. Field Strength:	39.68dBuV/m (at 3m)
Antenna Type:	Coil Antenna
Antenna Gain	0dBi

1.2 RF Exposure Exemption

According to §1.1307(b)(3) and KDB 447498 D04 Interim General RF Exposure Guidance v01, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

Option A: FCC Rule Part 1.1307 (b)(3)(i)(A):The available maximum time-averaged power is no more than 1mW, regardless of separation distance.

Option B: FCC Rule Part 1.1307 (b)(3)(i)(B): The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

Option C: FCC Rule Part 1.1307 (b)(3)(i)(C): The minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters.

Single RF Sources Subject to Routine Environmental Evaluation	
RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	1,920 R ²
1.34-30	3,450 R ² /f ²
30-300	3.83 R ²
300-1,500	0.0128 R ² f
1,500-100,000	19.2R ²

For Multiple RF sources: FCC Rule Part 1.1307(b)(3)(ii):

- (A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required).
- (B) In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

1.3 Calculated Result

Radio Access Technology	Prediction Frequency (MHz)	Output Power (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	Tune-Up Time-Averaged Power (dBm)	ERP (dBm)
Wi-Fi	2412	15.43	2.26	100	16.00	16.11
Bluetooth 1	2402	8.09	2.26	100	9.00	9.11
Bluetooth 2	2402	-7.15	-3.35	100	-7.00	-12.50
NFC	13.56	-55.58	0	/	-55.00	-56.29

Frequency (MHz)	Option	Min. Distance	Max. Power		Exposure Limit	Ratio	Result
		(cm)	(dBm)	(mW)	(mW)		Pass/Fail
2412	C	20.00	16.11	40.83	768.00	0.05	Pass
2402	C	20.00	9.11	8.15	768.00	0.01	Pass
2402	C	20.00	-12.50	0.06	768.00	0.01	Pass
13.56	C	20.00	-56.29	0.01	750.52	0.01	Pass

Note: 1. a. $\text{Time-Averaged Power} = \text{Output Power} * \text{Duty Cycle}$;

$\text{ERP} = \text{Time-Averaged Power} + \text{Antenna gain} - 2.15\text{dB}$;

b. $\text{EIRP} = E - 104.8 + 20\log D$; $\text{Output Power} = \text{EIRP} - \text{Antenna Gain}$;

$\text{ERP} = \text{EIRP} - 2.15\text{dB}$

2. Option A, B and C refers as clause 1.2.

3. For option B, Max (time-averaged power, effective radiated power (ERP)) converts to Max. Power. For option C, ERP converts to Max. Power;

4. For option B, P_{th} (mW) converts to Exposure Limit (mW); For option C, ERP (W) converts to Exposure Limit (mW).

5. $\text{Ratio} = \text{Tune-Up ERP (mW)} / \text{Exposure Limit (mW)}$

Mode for Simultaneous Multi-band Transmission:

Radio Access Technology	Ratio 1	Ratio 2	Ratio 3	Simultaneous Ratio	Limit	Result
						Pass/Fail
Wi-Fi + Bluetooth 2+ NFC	0.05	0.01	0.01	0.07	1	Pass

Note: Wi-Fi and Bluetooth 1 is the use the same antenna cannot simultaneous transmission.

Result: Pass