

# TEST REPORT

Reference No..... : WTX22X12243358W003  
FCC ID ..... : 2AUTE-8TT22G  
Applicant ..... : Xiamen Hanin Electronic Technology Co.,Ltd.  
Address..... : Room 305A, Angye Building, Pioneering Park,Torch High-tech,Zone,Xiamen  
Manufacturer ..... : The same as Applicant  
Address..... : The same as Applicant  
Product Name ..... : WIRELESS AI PRINTER, AI PRINTER  
Model No..... : GT1  
Standards ..... : FCC Part 15.225  
Date of Receipt sample .... : 2022-12-02  
Date of Test..... : 2022-12-02 to 2023-02-15  
Date of Issue ..... : 2023-02-16  
Test Report Form No. .... : WTX\_Part 15\_225W  
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

**Prepared By:**


**Waltek Testing Group (Shenzhen) Co., Ltd.**

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,  
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:

Approved by:



Dashan Chen



Silin Chen

## **TABLE OF CONTENTS**

<b>1. GENERAL INFORMATION .....</b>	<b>4</b>
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	4
1.2 TEST STANDARDS.....	5
1.3 TEST METHODOLOGY .....	5
1.4 TEST FACILITY .....	5
1.5 EUT SETUP AND TEST MODE .....	6
1.6 MEASUREMENT UNCERTAINTY.....	7
1.7 TEST EQUIPMENT LIST AND DETAILS .....	8
<b>2. SUMMARY OF TEST RESULTS.....</b>	<b>11</b>
<b>3. ANTENNA REQUIREMENT .....</b>	<b>12</b>
3.1 STANDARD APPLICABLE .....	12
3.2 TEST RESULT.....	12
<b>4. RADIATED EMISSIONS .....</b>	<b>13</b>
4.1 STANDARD APPLICABLE .....	13
4.2 TEST PROCEDURE .....	13
4.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	15
4.4 SUMMARY OF TEST RESULTS/PLOTS.....	16
<b>5. OUT OF BAND EMISSIONS .....</b>	<b>19</b>
5.1 STANDARD APPLICABLE .....	19
5.2 TEST PROCEDURE .....	19
5.3 SUMMARY OF TEST RESULTS/PLOTS.....	19
<b>6. FREQUENCY STABILITY .....</b>	<b>21</b>
6.1 STANDARD APPLICABLE .....	21
6.2 TEST PROCEDURE .....	21
6.3 SUMMARY OF TEST RESULTS/PLOTS.....	21
<b>7. EMISSION BANDWIDTH.....</b>	<b>22</b>
7.1 APPLICABLE STANDARD .....	22
7.2 TEST PROCEDURE .....	22
7.3 SUMMARY OF TEST RESULTS/PLOTS.....	22
<b>8. CONDUCTED EMISSIONS .....</b>	<b>24</b>
8.1 TEST PROCEDURE .....	24
8.2 BASIC TEST SETUP BLOCK DIAGRAM .....	24
8.3 TEST RECEIVER SETUP .....	24
8.4 SUMMARY OF TEST RESULTS/PLOTS.....	24
<b>APPENDIX PHOTOGRAPHS.....</b>	<b>27</b>

**Report version**

Version No.	Date of issue	Description
Rev.00	2023-02-16	Original
/	/	/

## 1. GENERAL INFORMATION

---

### 1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	WIRELESS AI PRINTER, AI PRINTER
Trade Name	HPRT, iDPRT
Model No.:	GT1
Adding Model(s):	Future 999
Rated Voltage:	DC 14V
Power Adapter 1#:	GMB36-140200-D Input:AC100-240 50/60Hz 1.5A Output:DC14V2.0A
Power Adapter 2#:	AP091G-140250 Input:AC100-240 50/60Hz 1.5A Output:DC14V2.5A
<p><i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model GT1, but the circuit and the electronic construction do not change, declared by the manufacturer.</i></p>	

Technical Characteristics of EUT	
Support Standards:	NFC
Frequency Range:	13.56MHz
Max. Field Strength:	46.85dBuV/m (at 3m)
Antenna Type:	PCB Antenna
Antenna Gain	0dBi

## 1.2 Test Standards

The tests were performed according to following standards:

**FCC Rules Part 15.225**: Operation within the band 13.110-14.010MHz.

**ANSI C63.10-2013**: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission/immunity, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

## 1.4 Test Facility

### **Address of the test laboratory**

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

### **FCC – Registration No.: 125990**

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

### **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

## 1.5 EUT Setup and Test Mode

The EUT was operated in the continuous transmitting mode that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

<b>Test Mode List</b>		
Test Mode	Description	Remark
TM1	Transmitting	13.56MHz

<b>Test Conditions</b>	
Temperature:	22~25 °C
Relative Humidity:	50~55 %.
ATM Pressure:	1019 mbar

<b>EUT Cable List and Details</b>			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
USB Cable	1.5	Unshielded	Without Ferrite
DC Cable	1.0	Unshielded	Without Ferrite
AC Cable	1.5	Unshielded	Without Ferrite

<b>Special Cable List and Details</b>			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

<b>Auxiliary Equipment List and Details</b>			
Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	TianYi 100-14IBD	PF0F4ABV
Phone	XIAOMI	MI10	/

### 1.6 Measurement Uncertainty

<b>Measurement uncertainty</b>		
Parameter	Conditions	Uncertainty
Frequency Deviation	2.3%	±5%
Conducted Emissions	Conducted	9-150kHz ±3.74dB
		0.15-30MHz ±3.34dB
Transmitter Spurious Emissions	Radiated	30-200MHz ±4.52dB
		0.2-1GHz ±5.56dB
		1-6GHz ±3.84dB
		6-18GHz ±3.92dB

## 1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
SEMT-1075	Communication Tester	Rohde & Schwarz	CMW500	148650	2022-03-22	2023-03-21
SEMT-1063	GSM Tester	Rohde & Schwarz	CMU200	114403	2022-03-22	2023-03-21
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2022-03-25	2023-03-24
SEMT-1079	Spectrum Analyzer	Agilent	N9020A	US47140102	2022-03-22	2023-03-21
SMET-1313	Spectrum Analyzer	Agilent	N9020A	MY54320548	2022-03-22	2023-03-21
SEMT-1080	Signal Generator	Agilent	83752A	3610A01453	2022-03-22	2023-03-21
SEMT-1081	Vector Signal Generator	Agilent	N5182A	MY47070202	2022-03-22	2023-03-21
SEMT-1028	Power Divider	Weinschel	1506A	PM204	2022-03-22	2023-03-21
SEMT-1082	Power Divider	RF-Lambda	RFLT4W5M18G	14110400027	2022-03-22	2023-03-21
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	/	/
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	/	/
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	/	/
SEMT-C004	Cable	Zheng DI	2M0RFC	/	/	/
SEMT-C005	Cable	Zheng DI	1M0RFC	/	/	/
SEMT-C006	Cable	Zheng DI	1M0RFC	/	/	/
<input checked="" type="checkbox"/> Chamber A: Below 1GHz						
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2022-03-22	2023-03-21
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2022-03-22	2023-03-21
SEMT-1008	Amplifier	HP	8447F	2805A03475	2022-01-07	2023-01-06
					2022-12-30	2023-12-29
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2021-03-20	2023-03-19
SEMT-1068	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2021-03-20	2023-03-19
<input checked="" type="checkbox"/> Chamber A: Above 1GHz						
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2022-03-22	2023-03-21



SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2022-03-22	2023-03-21
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2022-03-22	2023-03-21
SEMT-1042	Horn Antenna	ETS	3117	00086197	2021-03-19	2023-03-18
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2021-04-27	2023-04-26
SEMT-1216	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2022-03-25	2023-03-24
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2022-03-22	2023-03-21
<input type="checkbox"/> Chamber B:Below 1GHz						
SEMT-1068	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2021-04-09	2023-04-08
SEMT-1067	Amplifier	Agilent	8447D	2944A10179	2022-03-22	2023-03-21
SEMT-1066	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2022-03-22	2023-03-21
<input type="checkbox"/> Chamber C:Below 1GHz						
SEMT-1319	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2022-01-07	2023-01-06
					2022-12-30	2023-12-29
SEMT-1343	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2021-05-28	2023-05-27
SEMT-1333	Amplifier	HP	8447F	2944A03869	2022-03-22	2023-03-21
<input checked="" type="checkbox"/> Conducted Room 1#						
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2022-03-21	2023-03-20
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2022-03-25	2023-03-24
SEMT-1003	AC LISN	Schwarz beck	NSLK8126	8126-224	2022-03-22	2023-03-21
<input type="checkbox"/> Conducted Room 2#						
SEMT-1334	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2022-03-22	2023-03-21
SEMT-1336	LISN	Rohde & Schwarz	ENV 216	100097	2022-03-22	2023-03-21

<b>Software List</b>			
<b>Description</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Version</b>
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission)*	Farad	EZ-EMC	RA-03A1

\*Remark: indicates software version used in the compliance certification testing.

## 2. SUMMARY OF TEST RESULTS

---

FCC Rules	Description of Test Item	Result
§15.203	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.209	Radiated Emission	Compliant
§15.225(a)	Field Strength	Compliant
§15.225(b)(c)	Out of Band Emission	Compliant
§15.225(e)	Frequency Stability	Compliant
§15.207(a)	Conducted Emission	Compliant
§15.215(c)	Emission Bandwidth	Compliant

N/A: not applicable.

### **3. Antenna Requirement**

---

#### **3.1 Standard Applicable**

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

#### **3.2 Test Result**

This product has a PCB Antenna, fulfill the requirement of this section.

## 4. Radiated Emissions

---

### 4.1 Standard Applicable

According to §15.225(a), the field strength of any emissions within the band 13.553–13.567MHz shall not exceed 15,848 microvolts/meter at 30 meters.


According to §15.225(d), the field strength of any emissions which appear outside of this band shall not exceed the general radiated emission limits in §15.209.

Note: Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.


### 4.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.225(d) and FCC Part 15.209 Limit.


The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm. The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1GHz.



Frequency :9kHz-30MHz  
RBW=10KHz,  
VBW =30KHz  
Sweep time= Auto  
Trace = max hold  
Detector function = peak

Frequency :30MHz-1GHz  
RBW=120KHz,  
VBW=300KHz  
Sweep time= Auto  
Trace = max hold  
Detector function = peak, QP

Frequency :Above 1GHz  
RBW=1MHz,  
VBW=3MHz(Peak), 10Hz(AV)  
Sweep time= Auto  
Trace = max hold  
Detector function = peak, AV

### 4.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} - \text{Corr. Factor}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB $\mu$ V means the emission is 6dB $\mu$ V below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

#### 4.4 Summary of Test Results/Plots

**Note:** this EUT was tested in 3 orthogonal positions and the worst case position data was reported.


➤ Below 30MHz

Frequency	Reading	Correction Factor	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	X/Y/Z	
13.56	44.29	-2.08	42.21	124.0	-81.79	X	Peak
27.12	41.34	-2.27	39.07	69.5	-30.43	X	Peak
13.56	44.16	-2.08	42.08	124.0	-81.92	Y	Peak
27.12	41.27	-2.27	39.00	69.5	-30.50	Y	Peak
13.56	44.19	-2.08	42.11	124.0	-81.89	Z	Peak
27.12	41.23	-2.27	38.96	69.5	-30.54	Z	Peak




➤ Above 30MHz

Test Mode	TM1	Polarity:	Horizontal
-----------	-----	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	86.5028	39.13	-11.22	27.91	40.00	-12.09	-	-	peak
2	122.4039	43.62	-9.25	34.37	43.50	-9.13	-	-	peak
3	246.8148	39.03	-6.83	32.20	46.00	-13.80	-	-	peak
4	325.5957	47.63	-4.57	43.06	46.00	-2.94	-	-	peak
5	379.9141	45.48	-3.64	41.84	46.00	-4.16	-	-	peak
6	434.0650	37.46	-2.95	34.51	46.00	-11.49	-	-	peak

Test Mode	TM1	Polarity:	Vertical
-----------	-----	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	40.9881	36.05	-7.14	28.91	40.00	-11.09	-	-	peak
2	50.7637	39.22	-7.45	31.77	40.00	-8.23	-	-	peak
3	85.8983	42.12	-11.29	30.83	40.00	-9.17	-	-	peak
4	129.0146	42.69	-10.42	32.27	43.50	-11.23	-	-	peak
5	379.9141	35.21	-3.64	31.57	46.00	-14.43	-	-	peak
6	903.3093	31.62	4.04	35.66	46.00	-10.34	-	-	peak

Remark: '-' Means the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics.

## 5. OUT OF BAND EMISSIONS

---

### 5.1 Standard Applicable

According to FCC 15.225 (b), within the bands 13.410–13.553MHz and 13.567–13.710MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters. (c) Within the bands 13.110–13.410MHz and 13.710–14.010MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.


### 5.2 Test Procedure

As the radiation test, set the RBW=10kHz VBW=30kHz, observed the outside band of 13.11MHz to 14.01MHz, than mark the higher-level emission for comparing with the FCC rules.

### 5.3 Summary of Test Results/Plots

**Note:** this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Test Mode	TM1	Polarity:	/
-----------	-----	-----------	---



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	13.3179	40.62	-5.01	35.61	80.50	-44.89	-	-	peak
2	13.4369	39.96	-4.99	34.97	90.50	-55.53	-	-	peak
3	13.5543	51.80	-4.95	46.85	124.00	-77.15	-	-	peak
4	13.6301	39.30	-4.94	34.36	90.50	-56.14	-	-	peak
5	13.9840	39.67	-4.88	34.79	80.50	-45.71	-	-	peak

Remark: '-'Means' the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

## 6. Frequency Stability

---

### 6.1 Standard Applicable

According to 15.225(e), the frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  of the operating frequency over a temperature variation of  $-20$  degrees to  $+50$  degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

### 6.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure.

### 6.3 Summary of Test Results/Plots

Reference Frequency: 13.56MHz, Limit: 100ppm				
Voltage(%)	Power(VDC)	TEMP(°C)	Freq.Dev(Hz)	Deviation(ppm)
100%	14	-30	746	55.01
100%		-20	642	47.35
100%		-10	710	52.36
100%		0	821	60.55
100%		+10	843	62.17
100%		+20	705	51.99
100%		+30	695	51.25
100%		+40	681	50.22
100%		+50	753	55.53
Low		11.9	+20	812
High	16.1	+20	837	61.73

## 7. EMISSION BANDWIDTH

---

### 7.1 Applicable Standard

According to 15.215(c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

### 7.2 Test Procedure

According to the ANSI 63.10-2013, the emission bandwidth test method as follows.

Set span =  $1\sim 5 * EBW$ , centered on a transmitting channel

RBW =  $1\%\sim 5\% * EBW$ , VBW =  $3 * RBW$

Sweep = auto

Detector function = peak

Trace = max hold


All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down of the emission.

### 7.3 Summary of Test Results/Plots

Tx Frequency	20dB Emission bandwidth(Hz)
13.56MHz	246

Reference No.: WTX22X12243358W003

Please refer to the test plots as below:



Date: 20.DEC.2022 16:45:00


## 8. Conducted Emissions

### 8.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.

### 8.2 Basic Test Setup Block Diagram



### 8.3 Test Receiver Setup


During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency .....	150kHz
Stop Frequency .....	30MHz
Sweep Speed .....	Auto
IF Bandwidth.....	10kHz
Quasi-Peak Adapter Bandwidth .....	9kHz
Quasi-Peak Adapter Mode .....	Normal

### 8.4 Summary of Test Results/Plots




Test Mode	TM1(AC120V 60Hz)	Polarity:	Neutral
-----------	------------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.3500	12.40	10.23	22.63	48.96	-26.33	AVG
2	0.3580	23.46	10.23	33.69	58.77	-25.08	QP
3	0.6300	30.19	10.20	40.39	56.00	-15.61	QP
4	0.6340	16.55	10.20	26.75	46.00	-19.25	AVG
5	0.7780	13.28	10.17	23.45	46.00	-22.55	AVG
6	1.0260	21.89	10.14	32.03	56.00	-23.97	QP
7	1.2540	9.47	10.17	19.64	46.00	-26.36	AVG
8	1.2900	21.11	10.17	31.28	56.00	-24.72	QP
9	13.5620	36.48	10.27	46.75	60.00	-13.25	QP
10*	13.5620	35.76	10.27	46.03	50.00	-3.97	AVG
11	23.7220	3.21	10.38	13.59	50.00	-36.41	AVG
12	27.2140	25.92	10.40	36.32	60.00	-23.68	QP

Test Mode	TM1(AC120V 60Hz)	Polarity:	Line
-----------	------------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.3620	12.39	10.23	22.62	48.68	-26.06	AVG
2	0.3660	22.86	10.23	33.09	58.59	-25.50	QP
3	0.6260	15.54	10.20	25.74	46.00	-20.26	AVG
4	0.6300	29.22	10.20	39.42	56.00	-16.58	QP
5	0.7780	13.60	10.17	23.77	46.00	-22.23	AVG
6	1.1180	21.30	10.15	31.45	56.00	-24.55	QP
7	1.5180	9.52	10.20	19.72	46.00	-26.28	AVG
8	1.5380	20.38	10.20	30.58	56.00	-25.42	QP
9	13.5580	37.50	10.27	47.77	60.00	-12.23	QP
10*	13.5580	33.96	10.27	44.23	50.00	-5.77	AVG
11	20.4700	20.30	10.37	30.67	60.00	-29.33	QP
12	21.1540	3.41	10.37	13.78	50.00	-36.22	AVG

Note: Performed only the worst case (Power Adapter 1#: GMB36-140200-D) is recorded in this report.

## APPENDIX PHOTOGRAPHS

---

Please refer to "ANNEX"

\*\*\*\* END OF REPORT \*\*\*\*