

## RF Exposure Evaluation Report

<b>Report Reference No.</b> ..... :	<b>MTEB24030282 -H</b>	
<b>FCC ID</b> ..... :	<b>2AUTE-HDR3D2331</b>	
Compiled by ( position+printed name+signature)..:	File administrators Alisa Luo	
Supervised by ( position+printed name+signature)..:	Test Engineer Sunny Deng	
Approved by ( position+printed name+signature)..:	Manager Yvette Zhou	
Date of issue..... :	March 27, 2024	
<b>Representative Laboratory Name. : Shenzhen Most Technology Service Co., Ltd.</b>		
Address..... :	No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park, Nanshan, Shenzhen, Guangdong, China.	
<b>Applicant's name..... : Xiamen Hanin Co.,Ltd.</b>		
Address..... :	Room 305A, Angye Building, Pioneering Park, Torch High-tech Zone, Xiamen, china	
<b>Test specification/ Standard..... : 47 CFR Part 1.1307;47 CFR Part 1.1310</b>		
<b>KDB447498D01 General RF Exposure Guidance v06</b>		
TRF Originator..... :	Shenzhen Most Technology Service Co., Ltd.	
<b>Shenzhen Most Technology Service Co., Ltd. All rights reserved.</b>		
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Most Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Most Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.		
<b>Test item description</b> ..... :	Thermal Receipt Printer	
Trade Mark..... :	N/A	
Model/Type reference..... :	TP900	
Listed Models .....	TP900-i, TP901-i, TP902-i, TP903-i, TP904-i, FFSP9000+, FFSP9U00+, FFSP9U01+, FFSP9U02+, FFSP9U03+, FFSP8U04+, FFSP9X00+, FFSP9X01+, FFSP9X02+, FFSP9X03+, FFSP9X04+, POS90D, POS90H, HDR3D2331	
Modulation Type..... :	b: DSSS ,CCK ; g/n: BPSK, QPSK, QAM GFSK, $\pi/4$ DQPSK, 8DPSK	
Operation Frequency..... :	From 2412MHz~2462MHz 2402MHz to 2480MHz	
Hardware Version.....	TP900-MBA	
Software Version.....	V.TP900.1.x	
Rating..... :	DC 24V by Adapter	
Result..... :	<b>PASS</b>	

**TEST REPORT**

Equipment under Test : Thermal Receipt Printer

Model /Type : TP900

Listed Models : TP900-i, TP901-i, TP902-i, TP903-i, TP904-i,  
FFSP9000+,FFSP9U00+, FFSP9U01+, FFSP9U02+,  
FFSP9U03+, FFSP8U04+,FFSP9X00+, FFSP9X01+,  
FFSP9X02+, FFSP9X03+, FFSP9X04+,POS90D,  
POS90H,HDR3D2331

Remark : It's just that the product models are called differently

Applicant : Xiamen Hanin Co.,Ltd.

Address : Room 305A, Angye Building, Pioneering Park,Torch High-tech  
Zone, Xiamen, china

Manufacturer : Xiamen Hanin Co.,Ltd.

Address : Room 305A, Angye Building, Pioneering Park,Torch High-tech  
Zone, Xiamen, china

<b>Test Result:</b>	<b>PASS</b>
---------------------	-------------

The test report merely corresponds to the test sample.  
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## 1. Revision History

Revision	Issue Date	Revisions	Revised By
00	2024.03.27	Initial Issue	Alisa Luo

## 2. SAR Evaluation

### 2.1 RF Exposure Compliance Requirement

#### 2.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

##### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### 2.1.2 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$  Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

## 2.1.3 EUT RF Exposure

## BLE

GFSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402 MHz)	4.944	4.944 ± 1	5.944
Middle(2440MHz)	5.398	5.398 ± 1	6.398
Highest(2480MHz)	5.378	5.378 ± 1	6.378

## BLE

Worst case: GFSK						
Channel	Maximum tune-up Power (dBm)	Maximum tune-up Power (MW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
Middle(2440MHz)	6.398	4.36	3.02	0.0017	1.0	Pass

Note: 1) Refer to report MTEB24030282-R for EUT test Max Conducted average Output Power value.

Note: 2)  $P_d = (P_{out} * G) / (4 * \pi * R^2) = (4.36 * 2) / (4 * 3.1416 * 20^2) = 0.0017$

## WIFI 2.4G

802.11b			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2412MHz)	12.05	12.05 ± 1	13.05
Middle(2437MHz)	11.99	11.99 ± 1	12.99
Highest(2462MHz)	11.82	11.82 ± 1	12.82

802.11g			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2412MHz)	14.05	14.05 ± 1	15.05
Middle(2437MHz)	13.89	13.89 ± 1	14.89
Highest(2462MHz)	13.97	13.97 ± 1	14.97

802.11n(H20)			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2412MHz)	13.71	13.71 ± 1	14.71
Middle(2437MHz)	13.39	13.39 ± 1	14.39
Highest(2462MHz)	13.34	13.34 ± 1	14.34

802.11n(H40)			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2422MHz)	13.48	13.48 ± 1	14.48
Middle(2437MHz)	13.42	13.42 ± 1	14.42
Highest(2452MHz)	13.21	13.21 ± 1	14.21

WIFI 2.4G

Worst case: 802.11g						
Channel	Maximum tune-up Power (dBm)	Maximum tune-up Power (MW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
Lowest(2412MHz)	15.05	31.99	3.02	0.0127	1.0	Pass

Note: 1) Refer to report MTEB24030282-R2 for EUT test Max Conducted average Output Power value.

Note: 2)  $P_d = (P_{out} * G) / (4 * \pi * R^2) = (31.99 * 2) / (4 * 3.1416 * 20^2) = 0.0127$

BT classic

GFSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402MHz)	2.259	2.259 ± 1	3.259
Middle(2441MHz)	2.673	2.673 ± 1	3.673
Highest(2480MHz)	2.635	2.635 ± 1	3.635

π /4DQPSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402MHz)	3.142	3.142 ± 1	4.142
Middle(2441MHz)	3.469	3.469 ± 1	4.469
Highest(2480MHz)	3.511	3.511 ± 1	4.511

8DPSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402MHz)	3.328	3.328 ± 1	4.328
Middle(2441MHz)	3.795	3.795 ± 1	4.795
Highest(2480MHz)	3.774	3.774 ± 1	4.774

Worst case: 8DPSK						
Channel	Maximum tune-up Power (dBm)	Maximum tune-up Power (MW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
Middle(2441MHz)	4.795	3.02	3.02	0.0012	1.0	Pass

Note: 1) Refer to report MTEB24030282-R1 for EUT test Max Conducted average Output Power value.  
 Note: 2)  $P_d = (P_{out} * G) / (4 * \pi * R^2) = (3.02 * 2) / (4 * 3.1416 * 20^2) = 0.0012$  Note:  
 3) EUT's Bluetooth module is more than 20cm away from the human body.

.....THE END OF REPORT.....