


---

# **Mobile Printer**

# **MT800**

## ***User Manual***



**Xiamen Hanin Electronic Technology Co., Ltd.**

Add: 5F, 8#, Aide Airport Industrial Park, Huli District, Xiamen, China

Web: [www.hpert.com](http://www.hpert.com)

---

---

---

## Statement

This manual content may be altered without permission, and Xiamen Hanin Electronic Technology Co., Ltd. reserves the rights to make changes without notice in technology, spare parts, hardware and software of the products. If more information is needed about the products, please contact Xiamen Hanin Electronic Technology Co., Ltd. Without any written permission from the company, any section of this manual is prohibited to be copied or transferred in any form.

## Copyright

This manual is printed in 2019, the copyright belongs to Xiamen Hanin Electronic Technology Co., Ltd.

Printed in China

1.0 Version

## Warnings



This must be complied with in order to avoid any damage to the human body and to the equipment.



This shows the important information and tips for the printer operating.

---

---

# Important Safety Instructions

Please read this chapter carefully before using the printer!



## Using the Printer

1. Water or other liquid should not spill into the printer, also the printer should not be exposed to the rain, or else may cause printer damage.
2. Do not open the printer cover while the printer is printing, otherwise the printer may work improperly.
3. Too high(40°C) or too low(0°C) temperature will lead to the decrease of print quality.
4. too high (85%) or too low (20%) relative humidity will lead to the decrease of print quality
5. The print paper in poor quality or stored for too long time also may reduce the print quality even damage the printer.
6. Please do not open the printer cover when it is printing or just when printing is over, do not touch the print head with hand or body, overheat may cause scald.



## Storage Precautions

1. The printer should be placed in such an environment that the temperature is between -20°C and 70°C, and the relative humidity is between 5% and 90%.
  2. Normal thermal paper can't be kept too long, if you need to keep the receipt for a long period, please select long term effective thermal paper.
  3. Do not store printing paper in high temperature or direct sunlight, please keep it in a place to avoid the light.
-



## **Battery Safety Precautions**

Ignore the following instructions may cause battery overheating, fire, explosion, damage and/or performance, and reduced product life.

1. Be sure to use the specified battery and power charger provided by our company, do not disassemble the printer to replace the non-official battery, or may cause fire, explosion or damage to the printer.
  2. Do not allow water, sea water from entering or leaking into the battery. If the batteries internal safety device burn, when charging it, it may produce abnormal current and/or voltage, or abnormal chemical reaction when charging it, then may cause the battery overheating, fire and/or explosion.
  3. Do not use or place the battery nearby the stove or other high temperature places. Excessive heat maybe damage the resin shell and/or the insulation materials, thereby cause short-circuit inside the battery, then the battery may be overheated, burning and/or explosion.
  4. When charging, use a specified USB Type-C cable. Other conditions (high temperature, high pressure/high current, using the modified battery charger, etc.) excluded here may result in over-charging the battery and abnormal current and/or voltage, cause abnormal chemical reaction, and may cause the battery overheat, light and/or explosion.
  5. Do not heat the battery or put the battery into fire. This may melt insulation material and/ or damage safety devices or safety equipment, then ignite electrolytic solution, and cause the battery overheat, burning and/or explosion.
  6. Do not throw or attack the battery heavily. If internal safety device of the batteries burn, the battery charging may cause any abnormal current and/or voltage, and abnormal chemical reaction, and lead to the battery overheat, ignite, and/or explosion.
  7. The liquid in the battery is corrosive, if improper operation causes battery leak, and the liquid is spattered on the skin or clothes, please wash it with water, if spattered into the eyes, please rinse them with water thoroughly and see a doctor.
-



#### Other Precautions

The copyright for this user manual and various other manuals is property of our company. Any copying or conversion into electronic form and saving of this material without the express written permission is strictly prohibited. Use of the information contained in this manual is not subject to any patent liability. This manual has been prepared with utmost care and attention to detail but may contain certain errors and/or omissions. Our company is not legally liable for any damages resulting from the use of the information in this manual. Our company and its affiliates are not legally liable (United States excluded) for any damages, loss, costs, and/or expenses that result from the breakdown, malfunction, and/or misuse of the product due to violation or neglect of the operation and maintenance information and instructions provided by our company, as well as from the unauthorized alteration, repair, and/or modification of the product by the user and/or third party. We are not legally liable for any damages and/or issues resulting from the use of options and/or parts that are not authentic or authorized products.

#### 1. WEEE (Waste Electrical and Electric Equipment)



This mark shown on the product or its literature indicates that the corresponding item should not be discarded at the end of its working life with other household waste. To prevent possible harm to the environment or human health from uncontrolled waste disposal, please separate marked items from other types of waste and recycle them responsibly to promote the sustained reuse of material resources. Household users should contact either the retailer where they purchased this product, or their local government office for details of where and how they can conduct environmentally safe recycling of such items. Commercial users should contact their suppliers and check the terms and conditions of purchase contracts. This product should not be combined with other commercial waste for disposal.

**Caution:** This appliance is a Class A product, it might create radio interference in life. Under this condition, users could take effective measures to handle it.

---

---

# CONTENTS

1 Introduction.....	1
1.1 Introductions.....	1
1.2 The main Features.....	1
1.3 Packing List.....	1
1.4 Appearance and Component.....	2
2. General Specification.....	3
2.1 Printer Specification.....	3
2.2 Media Specification.....	4
2.3 Ribbon Specification.....	4
2.4 Dimension.....	4
3. Installation and use of printer.....	5
3.1 Open Printer Cover.....	5
3.2 Loading Ribbon.....	5
3.3 Loading Media.....	6
3.4 Removing Media.....	7
3.5 Printing Operation.....	7
3.5.1 Mobile Phone.....	7
3.5.2 Computer.....	8
3.6 Instruction for Sleep(Standby) Mode.....	8
4. Partial Component Description.....	9
4.1 Button.....	9
4.2 LED Indication and Buzzer.....	10
5. Troubleshooting.....	12
5.1 Printer Not Working.....	12
5.2 Troubles Occur During Printing.....	13
6. Clean Printer.....	14
6.1 Cleaning Head.....	14
6.2 Cleaning Sensor, Platen and Paper Path.....	14
7. Windows Driver.....	15
7.1 Manual Information.....	15
7.2 Operating System (OS) Environment.....	15
7.3 Windows Driver Preparation.....	15
7.4 Windows Driver Installation.....	16
7.5 Detailed Windows Driver Setting.....	19
7.5.1 Printing Preferences.....	19
7.5.2 Printer properties.....	26
7.6 Uninstall Windows Driver.....	28
8. Mobile Utility Tool Manual.....	30
8.1 Manual Information.....	30
8.2 Operating System(OS) Environment.....	30
8.3. Utility Tool Preparation.....	30

---

---

8.4. Using Utility Tool.....	31
8.4.1 Add Printer.....	32
8.4.2 Modify Printer.....	33
8.4.3 Delete Printer.....	39
8.4.4 Connection Test.....	40
8.4.5 Functions.....	41
8.5. Firmware Update.....	44

---



# 1 Introduction

## 1.1 Introductions

HPRT A4 Mobile Printer, print anytime and anywhere. Virtual will be transformed into reality, making mobile office a new trend. The distance between home and office will be shortened, and the working place will no longer be limited. MT800 supports ribbon with RFID authentication to ensure HPRT's original high quality consumables. HPRT, print your beautiful world.

Note: RFID is passive, not transmitted


## 1.2 The main Features

- 1.Perfectly portable for quality A4 printing.
- 2.Large capacity battery and long standby.
- 3.Humanized design, easy paper replacement.
- 4.High reliability, less anxiety.
- 5.Various interfaces, multiple choices.

## 1.3 Packing List

The printer is packaged with the following accessories.


If any of these accessories is broken or missing, please contact the dealer that you bought the product.



Printer



USB Type-C Cable




Ribbon Module




Note:The actual contents in the box are based on the packing list.

## 1.4 Appearance and Component

### Front



### Left




Note:



represents a wireless function in the figure.

### Inside



Note:

Paper out detection and Paper near end detection:

Detecting whether or not there is paper and whether the paper deviation occurs during the paper fed process.

## 2. General Specification

### 2.1 Printer Specification

**Table 2-1 General Specification**

Item		Parameter
Printing Parameter	Printing Method	Direct thermal/Thermal transfer printing
	Resolution	300DPI
	Printing Speed	MAX.15 mm/s
	Printing Width	198mm
	Printing Density	Order 3 adjustable
	Printing protocol	Dot matrix bitmap printing
Paper	Type	Thermal fax paper, A4 copy paper
	Width	210mm
	Thickness	60-90 $\mu$ m
	Ribbon Specification	Width 215mm, Length 14m, Diameter 14.5mm
Sensors		Cover open detection, Paper out detection, Paper feed positioning, Ribbon detection, Paper offset detection, TPH temperature detection
Communication Interface	Standard	USB Type C (support USB charging)
		Bluetooth 3.0/4.0 (Manufacturer installation)
Battery	Type	Rechargeable Li-ion battery
	Voltage	7.4V
	Capacity	2000mAh
Power	Input	AC 100~240V, 50/61Hz
	Output	DC 5V, 2A
Reliability	TPH life	50km
Memory	RAM	8MB
	Flash	4MB
Dimension (L $\times$ W $\times$ H, mm)		310.5 $\times$ 63.5 $\times$ 39.5
Weight		766g(contain ribbon), 694g(without ribbon)
Certificates		CCC, CE, MFI

## 2.2 Media Specification


Paper type	Paper width	Paper thickness
Thermal fax paper	210mm	60-90 $\mu$ m
A4 copy paper	210mm	60-90 $\mu$ m

## 2.3 Ribbon Specification

Ribbon	Parameter
Width	215mm
Length	14m
Diameter	14.5mm

## 2.4 Dimension


- Dimension: 310.5(L)  $\times$  63.5(W)  $\times$  39.5(H)mm
- Weight: 766g (including ribbon)



## 3. Installation and use of printer


### 3.1 Open Printer Cover

1. Press the cover open button meanwhile, then lift the printer cover upward.




### 3.2 Loading Ribbon

1. Hold the ribbon module by hands, then align it to the spacing hole and press down.




Note: To avoid errors during installing ribbon, please make sure that the arrow direction marked on the ribbon module is the same as the arrow direction marked in the printer.

2. Turn the rewind wheel to make the ribbon smooth.




3. Press down the cover by hands until you hearing the sound of “click”.



### 3.3 Loading Media

1. Make sure the ribbon is properly loaded, long touch power button, and release it after the printer is turned on.




2. Put the paper into the paper entry slot in parallel. Printer will feed a distance automatically after it detects the paper. After the paper feeding stops, it means that the paper is loaded successfully and get ready if the printer sound once.

## 3.4 Removing Media



Note: Don't pull the paper out forcefully while the printer cover is closed, or it may cause damage. Please remove the paper according to follow steps.

1. Press the open button meanwhile, then lift the printer cover upward.
2. Remove media.



## 3.5 Printing Operation

### 3.5.1 Mobile Phone

#### 1. ✕ Direct thermal printing:

After opening the printer cover and placing the special thermal bracket, please close the printer cover and put the A4 thermal paper into entry slot, then the printer will automatically feed the paper. After installing APP, you can connect the device by searching Bluetooth to print.

#### 2. ✕ Thermal transfer printing:

After installing the ribbon module, please make sure that both sides of the printer cover are closed, and put A4 copy paper/fax paper into entry slot, then the printer will automatically feed paper. After installing APP, you can connect the device by searching Bluetooth to print.

3. APP download address: the QR code can be scanned on the outer box of the package to download APP.

4. Bluetooth name: MT800-XXXX(default)

Bluetooth password: default no password, support setting and modification.


#### 5. Connection Mode:

- ① Open the APP;
- ② Click add device, please according to the prompt and turn on the Bluetooth authority, then enter the Bluetooth device list and select Mt800-XXXX;
- ③ Pair automatically and complete connection.


### 3.5.2 Computer

You can connect the computer via Bluetooth/USB, then installing printer driver.

USB connection



Bluetooth connection



## 3.6 Instruction for Sleep(Standby) Mode

In order to save power and prolong the service time, MT800 printer adopts automatic sleep and automatic wake-up technology. After the printer is turned on, if there is no operation on the printer within 5 minutes, the printer will enter standby mode. Note in particular that the printer will automatically turn off after 60 minutes of free time in the case of a Bluetooth connection.

When the printer enters standby mode, the power consumption will be greatly reduced, and there will be no effect on the use of the user. The printer will wake up automatically when receiving the print data without manual intervention to wake it up.



## 4. Partial Component Description

### 4.1 Button

#### 1.Power Button

##### ①Turn On

In the turn off state, long touch the power button about 2 seconds and the printer will be turned up;

##### ②Turn Off

In the turn on state, long touch power button about 3 seconds and the printer will be turned off;

##### ③Print Self Test


In the turn on state, continuously touch power button 3 times, the printer will print the self-check page.

#### 2.Cover Open Button

Press the cover open button meanwhile, then lift the printer cover upward.

#### 3.Reset Button

When the button fails to respond or Bluetooth fails to connect, please remove the ribbon, lightly press the Reset button with toothpick or pin for 2 seconds, then restart the printer.



## 4.2 LED Indicator and Buzzer

MT800 has two LED, front strip lamp and side pinhole lamp.

### 1. Front Strip Lamp

The front strip lamp focuses on the status of printer. The status is divided into four categories: behavior indication (red, green, white), charging indication (green), abnormal indication (red), and printing indication (white).

#### ① Abnormal status

Status	LED (Red)	Buzzer
Low-voltage	Flash	“Beep-Beep-Beep-”
TPH temperature overheated	Flash	“Beep-Beep Beep-”
Paper jar/paper loading abnormal	Slowly Flash	“Beep Beep Beep-”
Open the cover of printer	Lighting	——
Paper/Ribbon out	Slowly Flash	——

#### ② Charging status

Status	LED (Green)
Power too low	Flash
Printer charging	Lighting
Charging full	Off
Enter	Lighting 3 seconds

#### ③ Printing status

Status	LED (White)
Standby	Lighting
Wake up the printer	Lighting
Printing	Slowly Flash

## ④ Behavior status

Status	LED (Red, Green, White)
Turn on	Flash a round
Firmware upgrade	Alternating flash
Turn off	Flash a round

## 2. Side Pinhole Lamp

The side pinhole lamp is a blue monochrome lamp, focusing on the connection status of the printer.

## ① Connection status

Status	LED (Blue)
Data receiving	Flash
Bluetooth is not connected	Off
Bluetooth is connected	Lighting

## 5. Troubleshooting

Your printer is very reliable, but occasionally problems may occur. This chapter provides information on some common problems you may encounter and how to solve them. If you encounter problems that you can not resolve, contact your dealer for assistance.

### 5.1 Printer Not Working

Problem Description	Problem Reason	Solution
LED not light, printer not working	Printer no power	Please use a special charging line to charge
	Printer consumables do not match	Please replace the consumables immediately and continue printing with the official consumables
	Circuit board damage	Contact with the dealer

## 5.2 Troubles Occur During Printing

Problem Description	Problem Reason	Solution
Printing process stops printing	Battery power is too low	Please use a special charging line to charge
Paper jam occurs during printing	When the paper is automatically fed, there is a deviation, resulting in paper jam	Please open the cover, remove the jammed paper, and place the paper in parallel into the feed port
The ribbon is taken out when printing	The ribbon is loose before printing.	Please roll the ribbon to a flat state by rewind wheel
Print font missing, with white lines	Ribbon with folds, damaged	Please bring the ribbon back to roll flat and print with a good ribbon
	Uneven paper	Please print with flat paper
The printer cannot automatically absorb paper	The cover is not properly closed.	Please check that both sides of the cover are in place

## **6. Clean Printer**

### **6.1 Cleaning Head**

Printing quality might be degraded by dust, foreign substance, adhesive substance, or other pollution materials stuck in the printer head or inside the printer. When dirty, clean the print head as follows:

※ Notes:

1. Make sure to turn the printer power off prior to cleaning.
2. Open the paper cover and ribbon assembly, and remove the paper and ribbon.
3. As the print head gets very hot during printing, if intending to clean the print head, turn the printer power off and wait approximately 2~3 minutes before commencement.
4. Use the cleaning pen to clean the head. When cleaning the print head, take care not to touch the heated portion of the print head. Printer Head is susceptible to damage from static electricity, etc.
5. Take care not to allow the print head to become scratched and/or damaged in anyway.

### **6.2 Cleaning Sensor, Platen and Paper Path**

※ Clean the parts when there is a degradation of performance in printing quality or paper detection.

1. Open the paper cover and ribbon assembly, and remove the paper and ribbon.
2. Remove any dust or foreign substance using dry cloth or cotton swab.
3. Soak the cloth or cotton swab in alcohol for medical use and use it to remove adhesive foreign substances or other pollution materials.
4. After cleaning the parts, do not use the printer until the alcohol evaporates completely (1~2 min) and the printer has completely dried.

## **7. Windows Driver**

### **7.1 Manual Information**

This Windows Driver Installation Manual provides information on installation, detailed specifications, and usage of the printer's Windows Driver according to PC operating system (OS).

We maintain ongoing efforts to enhance and upgrade the functions and quality of all our products. As follows, product specifications and/or user manual content may be changed without prior notice.

### **7.2 Operating System (OS) Environment**

The following operating systems are supported for usage.

- Microsoft Windows 10 (32 bit/64 bit)
- Microsoft Windows 8 (32 bit/64 bit)
- Microsoft Windows 7 SPI (32 bit/64 bit)
- Microsoft Windows Vista SP2 (32 bit/64 bit)
- Microsoft Windows XP Professional SP3 (32 bit)
- Microsoft Windows Server 2012(64 bit)

### **7.3 Windows Driver Preparation**

Driver download URL: <http://cn.hpert.com/XiaZai.html>

The installation file name is HPRT Mobile Printer Driver vX.X.X.X.exe

As follows: HPRT Mobile Printer Driver v2.6.7.0.exe


## 7.4 Windows Driver Installation



Notes:

Under different operating system and different type of driver, the screen has slight difference. Please operate it according to the tips. Take HPRT MT800 (Windows 7) as example.

1. Double click Windows Driver.
2. Choose "English" and click "OK".



3. Choose "I accept the agreement", then click "Next".






4. Click "Next".



Note:

If printer is already connected with computer by USB port, it only needs to click "Install", then it will be installed automatically. Otherwise, proceed to the next step.

5. Choose the matched type and port (USBxxx is for USB port, COMx is for serial port, LPTx is for parallel port). Choose the type of driver, port, such as "MT800", "USB" as port. Click "Next".



6. Click "Finish", the driver is installed successfully.




7. After installation, the icon will be found in "Start" → "Devices and Printers".




## 7.5 Detailed Windows Driver Setting

### 7.5.1 Printing Preferences


1. Click "Start" → "Devices and Printers". Right click "HPRT MT800" and choose "Printing preferences".




2. According to the different needs, choose "Paper" \ "Offset" \ "Rotate" \ "Effect" \ "Copies" in "Page".




- Select “Paper Name”




- Click “Manager”, add or delete paper




- Setting “Horizontal”, “Vertical”




- Setting “Rotate”, “Effect”




- Click “Advanced”




- Save Paper




- Feed Paper




- Custom Command



- Media Type




3.Click "Watermark". Set watermark to print.






4. Click "Halftone" to set the halftone.




## 7.5.2 Printer properties


1. Click "Start" → "Devices and Printers". Right click "HPRT MT800" and choose "Printer properties".




2. Choose "General", click "Print Test Page", then it will print the current settings.



3. Click "Port" to choose another port or add port.



4. Click "Advanced" to set the available time for printing.




## 7.6 Uninstall Windows Driver


1. Double click Windows Driver.
2. Choose "English" and click "OK".



3. Choose "Uninstall printer driver". Click "Next".



4. Choose "HPRT MT800", click "Next". Then it is complete to uninstall.



5. Uninstall successfully.

## 8. Mobile Utility Tool Manual

### 8.1 Manual Information

This Manual provides information on usage of the printer's Utility Tool For Mobile according to PC operating system.

We maintain ongoing efforts to enhance and upgrade the functions and quality of all our products. As follow, product specifications and/or Utility Tool manual content may be changed without prior notice.

### 8.2 Operating System(OS) Environment

Utility Tool is applicable to the following operating system:

- Microsoft Windows 10 (32 bit/64 bit)
- Microsoft Windows 8 (32 bit/64 bit)
- Microsoft Windows 7 SPI (32 bit/64 bit)
- Microsoft Windows Vista SP2 (32 bit/64 bit)
- Microsoft Windows XP Professional SP3 (32 bit)
- Microsoft Windows Server 2012(64 bit)

### 8.3. Utility Tool Preparation


The installation file name is HPRTUtilityForMobile\_Dealer VX.X.X.X


eg : HPRTUtilityForMobile\_Dealer V2.0.0.5

## 8.4. Using Utility Tool




Warning: Under different operating system, the screen has slight difference. Please operate it according to the tips. Take Windows 7 as example.

1. Unzip the compressed package file, then open the folder, click  to open the Printer Utility For Mobile.




### 8.4.1 Add Printer

1.Click “Add Printer”.



2.Choose the right printer model and port type, then click “OK”.




3.Add printer is finish.




## 8.4.2 Modify Printer

1. Choose the printer that needs to be modified. Click on "Modify Printer".



2. Choose the printer model and port type that needs to be modified, then click "OK".




3. Modify the new printer is finish.

4. For example, when connecting via Bluetooth, you need to change the port to COM to connect. The specific actions are as follows:


- 1) Turn on the printer.
- 2) Turn on the upper device. The Bluetooth icon will show at the lower right of the screen. If the upper device is not configured with Bluetooth function, you need to insert a Bluetooth Dongle into its USB connector.




- 3) Right click the icon, choose "Add a Device".




4) Find the corresponding printer, click “Next”.




5) Add a printer to succeed as shown in the figure. The printer takes MT800-140C as an example.




6) Click "Start" → "Devices and Printers". Right click "MT800-140C" and choose "Properties".




7) In "MT800-140C Properties" dialog box, choose the "Services" window and find the corresponding port. As shown in the figure, the port of MT800-140C is COM3.




8) Open the printer utility and click “Modify Printer”.



9) Choose “Printer Model” as MT800, “Port Type” as COM, “COM Port” as COM3. Then click “OK”.




10) Modification of printer successfully.




### 8.4.3 Delete Printer

1. Choose the printer which you want to delete in the list, then click on "Delete Printer".





2. Click "OK", then the printer is deleted.



### 8.4.4 Connection Test

1. Click "Connection Test". If the connection is successful, it will appear the following window.



Note:

1. Make sure printer is connected with computer and power on.
2. Before using the following function, carry out the "Connection Test" first.




## 8.4.5 Functions

The function of Printer Utility For Mobile contains four items. Click the button and printer will execute the appropriate action.


Note:

The following screen may differ depending on the device to which you connect. Please operate it according to the actual interfaces.



1. Print Self Information: the printer will print out setting information.


2.Parameter Config: to set “Bluetooth”, “Print Density”, “Power Down Time” in the Parameter setting. When complete the above settings, please restart the printer.




Note: Power Down Time is only valid for unconnected Bluetooth.

3.Click “Command Test”, you can load file or input the text in the input on the left, then click “Send”, the printer will print the text out accordingly.

✧ Click “Text”:




✧ Click "Hex":




## 8.5. Firmware Update


1. Click "Firmware Update".



2. Select the appropriate upgrade file and click "Download".



3.The firmware upgrade was successful and please restart the printer.



#### FCC WARNING

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

To maintain compliance with FCC's RF Exposure guidelines, This equipment should be installed and operated with minimum distance between 20cm the radiator your body: Use only the supplied antenna.