



Engineering Test Report No. 2301385-01

Report Date	September 5, 2023	
Manufacturer Name	Pro1 IAQ Inc	
Manufacturer Address	2650 N Westgate Ave Ste 112 Springfield, MO 65803	
Test Item Name Model No.	Wireless Outdoor Remote Sensor, Model No.: R250W	
Date Received	August 31, 2023	
Test Dates	August 31, 2023, and September 1, 2023	
Specifications	FCC "Code of Federal Regulations" Title 47 Part 15, Subpart C, Section 15.247 Innovation, Science, and Economic Development Canada, RSS-GEN Innovation, Science, and Economic Development Canada, RSS-247	
Test Facility	Elite Electronic Engineering, Inc. 1516 Centre Circle, Downers Grove, IL 60515	FCC Reg. Number: 269750 IC Reg. Number: 2987A CAB Identifier: US0107
Signature	MARK E. LONGINOTTI	
Tested by	Mark E. Longinotti	
Signature	<i>Raymond J. Klouda</i>	
Approved by	Raymond J. Klouda, Registered Professional Engineer of Illinois – 44894	
PO Number	PO-2014	

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

This report shall not be reproduced, except in full, without the written approval of Elite Electronic Engineering Inc.

Elite Electronic Engineering Incorporated certifies that the information contained in this report was obtained under conditions which meet or exceed those specified in the FCC "Code of Federal Regulations" Title 47 Part 15, Subpart C, Section 15.247 and Innovation, Science, and Economic Development Canada, RSS-247 test specifications. The data presented in this test report pertains to the EUT on the test dates specified. Any electrical or mechanical modifications made to the EUT subsequent to the specified test date will serve to invalidate the data and void this certification. This report must not be used to claim product certification, approval, or endorsement by A2LA, NIST, or any agency of the Federal Government.

Table of Contents

1.	Report Revision History	3
2.	Introduction	4
2.1.	Scope of Tests	4
2.2.	Purpose	4
2.3.	Identification of the EUT	4
3.	Power Input	5
4.	Grounding	5
5.	Support Equipment	5
6.	Interconnect Leads	5
7.	Modifications Made to the EUT	5
8.	Modes of Operation	5
9.	Test Specifications	5
10.	Test Plan	6
11.	Deviation, Additions to, or Exclusions from Test Specifications	6
12.	Laboratory Conditions	6
13.	Summary	6
14.	Sample Calculations	7
15.	Statement of Conformity	7
16.	Certification	7
17.	Photographs of EUT	8
18.	Equipment List	10
19.	Block Diagram of Test Setup	11
20.	20dB Bandwidth	12
21.	Occupied Bandwidth (99%)	16
22.	Carrier Frequency Separation	20
23.	Number of Carrier Channels	22
24.	Average Time of Occupancy	24
25.	Maximum Peak Conducted Output Power	28
26.	Effective Isotropic Radiated Power (EIRP)	32
27.	Duty Cycle Factor Measurements	34
28.	Case Spurious Radiated Emissions	37
29.	Band-Edge Compliance	51
30.	Scope of Accreditation	57

This report shall not be reproduced, except in full,
without the written approval of Elite Electronic Engineering Inc.

1. Report Revision History

Revision	Date	Description
–	5 SEP 2023	Initial Release

2. Introduction

2.1. Scope of Tests

This document presents the results of a series of RF emissions tests that were performed on the Pro1 IAQ Inc Wireless Outdoor Remote Sensors (hereinafter referred to as the Equipment Under Test (EUT)). The EUTs were manufactured and submitted for testing by Pro1 IAQ Inc located in Springfield, MO.

2.2. Purpose

The test series was performed to determine if the EUTs meet the RF emission requirements of the FCC "Code of Federal Regulations" Title 47, Part 15, Subpart C, §15.247 for a Frequency Hopping Spread Spectrum intentional radiator, operating within the 902 – 928MHz band.

The test series was also performed to determine if the EUTs meet the RF emission requirements of the Innovation, Science, and Economic Development Canada Radio Standards Specification RSS-Gen and Innovation, Science, and Economic Development Canada Radio Standards Specification RSS-247 for a Frequency Hopping Spread Spectrum intentional radiator, operating within the 902 – 928MHz band.

Testing was performed in accordance with ANSI C63.10-2013.

2.3. Identification of the EUT

The EUTs were identified as follows:

EUT Identification	
EUT #1	
Product Description	Wireless Outdoor Remote Sensor
Model/Part No.	R250W
Serial No.	Conducted EUT #1
Size of EUT	9.5 cm x 9.5 cm x 2.5 cm
Software/Firmware Version	For all tests when hopping was enabled: WORS_FCC_APP_FULL_POWER_MODULATED_W_APP_DATA_50_CHANNELS_20230831.hex For all tests when hopping was not enabled: WORS_FCC_APP_FULL_POWER_MODULATED_W_APP_DATA_20230823.hex
Device Type	Frequency Hopping Transmission Device
Band of Operation	902 – 928MHz
Antenna Type	Note 1
Peak Conducted Output Power	13.82dBm
Rated Output Power	14dBm
20dB Bandwidth	33.37kHz
Occupied Bandwidth (99% CBW)	33.19kHz
EUT #2	
Product Description	Wireless Outdoor Remote Sensor
Model/Part No.	R250W
Serial No.	Radiated EUT #2
Size of EUT	9.5 cm x 9.5 cm x 2.5 cm
Software/Firmware Version	WORS_FCC_APP_FULL_POWER_MODULATED_W_APP_DATA_50_CHANNELS_20230831.hex
Device Type	Frequency Hopping Transmission Device

Band of Operation	902 – 928MHz
Antenna Type	Meandering "F" (Trace) Antenna
Peak EIRP	16.1dBm
Rated Output Power	14dBm
20dB Bandwidth	33.37kHz
Occupied Bandwidth (99% CBW)	33.19kHz

Note 1 – EUT #1 was modified by placing a coaxial connection at the antenna terminal of the circuit board. EUT #1 was used for all tests except for AC Power Line Conducted Emissions, Effective Isotropic Radiated Power (EIRP), and Case Spurious Radiated Emissions tests. EUT #2 was used for AC Power Line Conducted Emissions, Effective Isotropic Radiated Power (EIRP), and Case Spurious Radiated emissions tests.

3. Power Input

The EUTs obtained 3VDC from two (2) internal "AA" batteries.

4. Grounding

The EUTs were not connected to ground.

5. Support Equipment

No support equipment was used during the tests.

6. Interconnect Leads

No interconnect cables were submitted with the test items.

7. Modifications Made to the EUT

No modifications were made to the EUTs during the testing.

8. Modes of Operation

The EUTs and all peripheral equipment were energized. The units were programmed to transmit in one of the following modes:

Mode	Description
902.52MHz	Power Setting = 14dBm
914.78MHz	Power Setting = 14dBm
927.56MHz	Power Setting = 14dBm
Hopping Enabled	Power Setting = 14dBm

9. Test Specifications

The tests were performed to selected portions of, and in accordance with, the test specifications.

- Federal Communications Commission "Code of Federal Regulations", Title 47, Chapter I, Subchapter A, Part 15, Subpart C
- ANSI C63.10-2013, "American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices"
- Federal Communications Commission Office of Engineering and Technology Laboratory Division, Guidance For Compliance Measurements On Digital Transmission Systems, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating Under Section 15.247 April 2, 2019

KDB 558074 D01v05r02

- RSS-Gen Issue 5, February 2020, Amendment 2, Innovation, Science, and Economic Development Canada, "General Requirements for Compliance of Radio Apparatus"
- RSS-247 Issue 3, August 2023, "Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and License-Exempt Local Area Network (LE-LAN) Devices"

10. Test Plan

No test plan was provided. Instructions were provided by personnel from Pro1 IAQ Inc and used in conjunction with the FCC "Code of Federal Regulations" Title 47 Part 15, Subpart C, Section 15.247, Innovation, Science, and Economic Development Canada, RSS-247, and ANSI C63.4-2014 specifications.

11. Deviation, Additions to, or Exclusions from Test Specifications

There were no deviations, additions to, or exclusions from the test specifications during this test series.

12. Laboratory Conditions

The ambient parameters of the laboratory during testing were as follows:

Ambient Parameters	Value
Temperature	25°C
Relative Humidity	36%
Atmospheric Pressure	1023mb

13. Summary

The following EMC tests were performed and the results are shown below:

Test Description	Requirements	Test Method	S/N	Results
20dB Bandwidth	FCC 15.247 ISED RSS-247	ANSI C63.10:2013	Conducted EUT #1	Conforms
Occupied Bandwidth (99%)	FCC 15.247 ISED RSS-247	ANSI C63.10:2013	Conducted EUT #1	Conforms
Carrier Frequency Separation	FCC 15.247 ISED RSS-247	ANSI C63.10:2013	Conducted EUT #1	Conforms
Number of Carrier Channels	FCC 15.247 ISED RSS-247	ANSI C63.10:2013	Conducted EUT #1	Conforms
Average Time of Occupancy	FCC 15.247 ISED RSS-247	ANSI C63.10:2013	Conducted EUT #1	Conforms
Maximum Peak Conducted Output Power	FCC 15.247 ISED RSS-247	ANSI C63.10:2013	Conducted EUT #1	Conforms
Effective Isotropic Radiated Power (EIRP)	FCC 15.247 ISED RSS-247	ANSI C63.10:2013	Radiated EUT #2	Conforms
Duty Cycle Factor Measurements	FCC 15.247 ISED RSS-247	ANSI C63.10:2013	Conducted EUT #1	—
Case Spurious Radiated Emissions	FCC 15.247 ISED RSS-247	ANSI C63.10:2013	Radiated EUT #2	Conforms
Band-Edge Compliance	FCC 15.247 ISED RSS-247	ANSI C63.10:2013	Conducted EUT #1	Conforms

14. Sample Calculations

For Powerline Conducted Emissions:

The resultant voltage level (VL) is a summation in decibels (dB) of the receiver meter reading (MTR) and the cable loss factor (CF).

$$\text{Formula 1: } VL (\text{dB}\mu\text{V}) = MTR (\text{dB}\mu\text{V}) + CF (\text{dB}).$$

For Radiated Emissions:

The resultant field strength (FS) is a summation in decibels (dB) of the receiver meter reading (MTR), the antenna correction factor (AF), and the cable loss factor (CF). If an external preamplifier is used, the total is reduced by its gain (-PA). If a distance correction (DC) is required, it is added to the total.

$$\text{Formula 1: } FS (\text{dB}\mu\text{V}/\text{m}) = MTR (\text{dB}\mu\text{V}) + AF (\text{dB}/\text{m}) + CF (\text{dB}) + (-PA (\text{dB})) + DC (\text{dB})$$

To convert the Field Strength $\text{dB}\mu\text{V}/\text{m}$ term to $\mu\text{V}/\text{m}$, the $\text{dB}\mu\text{V}/\text{m}$ is first divided by 20. The Base 10 AntiLog is taken of this quotient. The result is the Field Strength value in $\mu\text{V}/\text{m}$ terms.

$$\text{Formula 2: } FS (\mu\text{V}/\text{m}) = \text{AntiLog} [(FS (\text{dB}\mu\text{V}/\text{m}))/20]$$


15. Statement of Conformity


The Pro1 IAQ Inc Wireless Outdoor Remote Sensor, Model No. R250W, did fully conform to the selected requirements of FCC "Code of Federal Regulations" Title 47 Part 15, Subpart C, Section 15.247 and Innovation, Science, and Economic Development Canada, RSS-247.

16. Certification

Elite Electronic Engineering Incorporated certifies that the information contained in this report was obtained under conditions which meet or exceed those specified in the FCC "Code of Federal Regulations" Title 47 Part 15, Subpart C, Section 15.247 and Innovation, Science, and Economic Development Canada, RSS-247 test specifications. The data presented in this test report pertains to the EUTs as received by the customer on the test date specified. Any electrical or mechanical modifications made to the EUTs subsequent to the specified test date will serve to invalidate the data and void this certification.

17. Photographs of EUT





18. Equipment List

Eq ID	Equipment Description	Manufacturer	Model No.	Serial No.	Frequency Range	Cal Date	Due Date
APW10	PREAMPLIFIER	PMI	PE2-35-120-5R0-10-12-SFF	PL11685/1241	1GHZ-20GHZ	3/10/2023	3/10/2024
CDZ3	LAB WORKSTATION	ELITE	LWS-10		WINDOWS 10	CNR	
GRE0	SIGNAL GENERATOR	AGILENT TECHNOLOGIES	E4438C	MY42083127	250KHZ-6GHZ	5/17/2023	5/17/2024
NDQ1	TUNED DIPOLE ANTENNA	EMCO	3121C-DB4	313	400-1000MHZ	9/14/2022	9/14/2024
NTA3	BILOG ANTENNA	TESEQ	6112D	32853	25-1000MHz	11/17/2022	11/17/2024
NWQ2	DOUBLE RIDGED WAVEGUIDE ANTENNA	ETS LINDGREN	3117	66659	1GHZ-18GHZ	4/27/2022	4/27/2024
RBG2	EMI ANALYZER	ROHDE & SCHWARZ	ESW44	101591	2HZ-44GHZ	4/10/2023	4/10/2024
T1EJ	10DB 25W ATTENUATOR	WEINSCHEL	46-10-34	CD6790	DC-18GHZ	1/12/2022	1/12/2024
T2SA	20DB 25W ATTENUATOR	WEINSCHEL	46-20-34	CD5015	DC-18GHZ	1/21/2022	1/21/2024
WKA1	SOFTWARE, UNIVERSAL RCV EMI	ELITE	UNIV_RCV_EMI	1	---	I/O	
XPQ3	HIGH PASS FILTER	K&L MICROWAVE	4IH30-1804/T10000-0	4	1.8GHZ-10GHZ	9/7/2021	9/7/2023


N/A: Not Applicable

I/O: Initial Only

CNR: Calibration Not Required

NOTE 1: For the purpose of this test, the equipment was calibrated over the specified frequency range, pulse rate, or modulation prior to the test or monitored by a calibrated instrument.

19. Block Diagram of Test Setup



Radiated Measurements Test Setup

20. 20dB Bandwidth

EUT Information	
Manufacturer	Pro1 IAQ Inc
Product	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit


Test Setup Details	
Setup Format	Tabletop
Height of Support (For Floor Standing only)	N/A
Measurement Method	Antenna Conducted
Type of Test Site	Tabletop
Test Site Used	N/A
Type of Antennas Used	N/A
Notes	

Measurement Uncertainty	
Measurement Type	Expanded Measurement Uncertainty
Radiated disturbance (electric field strength on an open area test site or alternative test site) (30 MHz – 1000 MHz)	4.3
Radiated disturbance (electric field strength on an open area test site or alternative test site) (1 GHz – 6 GHz)	3.1

Requirements
<u>For frequency hopping systems operating in the 902-928 MHz band:</u>
Systems using frequency hopping techniques operating in the 902 – 928MHz band are allowed a maximum 20dB bandwidth of 500kHz.

Procedure
The antenna port of the EUT was connected to the spectrum analyzer through 30dB of attenuation. With the hopping function disabled, the EUT was allowed to transmit continuously.
The frequency hopping channel was set separately to low, middle, and high hopping channels. The resolution bandwidth (RBW) was set to $\geq 1\%$ of the 20dB BW. The span was set to approximately 2 to 3 times the 20dB bandwidth.
The 'Max-Hold' function was engaged. The analyzer was allowed to scan until the envelope of the transmitter bandwidth was defined. The analyzer's display was then screenshot and saved.

Test Details	
Manufacturer	Pro1 IAQ Inc
EUT	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit
Frequency Tested	902.52MHz
Result	20dB BW = 33.37kHz
Notes	
Date Tested	August 31, 2023



20dB Bandwidth

Test Details	
Manufacturer	Pro1 IAQ Inc
EUT	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit
Frequency Tested	914.78MHz
Result	20dB BW = 33.27kHz
Notes	
Date Tested	August 31, 2023



20dB Bandwidth

Test Details	
Manufacturer	Pro1 IAQ Inc
EUT	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit
Frequency Tested	927.56MHz
Result	20dB BW = 32.77kHz
Notes	
Date Tested	August 31, 2023



20dB Bandwidth

21. Occupied Bandwidth (99%)

EUT Information	
Manufacturer	Pro1 IAQ Inc
Product	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit

Test Setup Details	
Setup Format	Tabletop
Height of Support (For Floor Standing only)	N/A
Measurement Method	Antenna Conducted
Type of Test Site	Tabletop
Test Site Used	N/A
Type of Antennas Used	N/A
Notes	

Measurement Uncertainty	
Measurement Type	Expanded Measurement Uncertainty
Radiated disturbance (electric field strength on an open area test site or alternative test site) (30 MHz – 1000 MHz)	4.3
Radiated disturbance (electric field strength on an open area test site or alternative test site) (1 GHz – 6 GHz)	3.1

Procedure
The antenna port of the EUT was connected to the spectrum analyzer through 30dB of attenuation.
The EUT was allowed to transmit continuously. The transmit channel was set separately to low, middle, and high channels. The resolution bandwidth (RBW) was set to 1% to 5% of the actual occupied bandwidth, the video bandwidth (VBW) was set 3 times greater than the RBW, and the span was set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency.
The 'Max-Hold' function was engaged. The analyzer was allowed to scan until the envelope of the transmitter bandwidth was defined. The spectrum analyzer's 99% bandwidth function was used to measure the occupied bandwidth of the EUT. The analyzer's display was plotted using a 'screen dump' utility.

Test Details	
Manufacturer	Pro1 IAQ Inc
EUT	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit
Frequency Tested	902.52MHz
Result	OBW = 33.19kHz
Notes	
Date Tested	August 31, 2023



Test Details	
Manufacturer	Pro1 IAQ Inc
EUT	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit
Frequency Tested	914.78MHz
Result	OBW = 33.18kHz
Notes	
Date Tested	August 31, 2023



Test Details	
Manufacturer	Pro1 IAQ Inc
EUT	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit
Frequency Tested	927.56MHz
Result	OBW = 33.19kHz
Notes	
Date Tested	August 31, 2023



22. Carrier Frequency Separation

EUT Information	
Manufacturer	Pro1 IAQ Inc
Product	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit


Test Setup Details	
Setup Format	Tabletop
Height of Support (For Floor Standing only)	N/A
Measurement Method	Antenna Conducted
Type of Test Site	Tabletop
Test Site Used	N/A
Type of Antennas Used	N/A
Notes	

Measurement Uncertainty		
Measurement Type		Expanded Measurement Uncertainty
Radiated disturbance (electric field strength on an open area test site or alternative test site) (30 MHz – 1000 MHz)		4.3
Radiated disturbance (electric field strength on an open area test site or alternative test site) (1 GHz – 6 GHz)		3.1

Requirement	
Channel carrier frequencies shall be separated by a minimum of 25kHz or the 20dB bandwidth, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5MHz band may have hopping channel carrier frequencies that are separated by 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.	

Procedure	
The antenna port of the EUT was connected to the spectrum analyzer through 30dB of attenuation. With the hopping function enabled, the EUT was allowed to transmit continuously.	
Span was set wide enough to capture the peaks of two adjacent channels. The resolution bandwidth was set to approximately 30% of the channel spacing. The peak detector and 'Max-Hold' function were engaged. The span was set wide enough to capture the peaks of at least two adjacent channels. When the trace had stabilized after multiple scans, the marker-delta function was used to determine the separation between the peaks of the adjacent channels. The analyzer's display was plotted using a 'screen dump' utility.	

Test Details	
Manufacturer	Pro1 IAQ Inc
EUT	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit
Frequency Tested	Hopping Enabled
Result	Separation = 500.5kHz
Notes	
Date Tested	August 31, 2023



99% bandwidth

23. Number of Carrier Channels

EUT Information	
Manufacturer	Pro1 IAQ Inc
Product	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit


Test Setup Details	
Setup Format	Tabletop
Height of Support (For Floor Standing only)	N/A
Measurement Method	Antenna Conducted
Type of Test Site	Tabletop
Test Site Used	N/A
Type of Antennas Used	N/A
Notes	

Measurement Uncertainty	
Measurement Type	Expanded Measurement Uncertainty
Radiated disturbance (electric field strength on an open area test site or alternative test site) (30 MHz – 1000 MHz)	4.3
Radiated disturbance (electric field strength on an open area test site or alternative test site) (1 GHz – 6 GHz)	3.1

Requirements
<u>FOR 902-928 MHz, 20dB BW < 250kHz</u> The system shall use at least 50 hopping frequencies.

Procedure
The antenna port of the EUT was connected to the spectrum analyzer through 30dB of attenuation. With the hopping function enabled, the EUT was allowed to transmit continuously.
The resolution bandwidth (RBW) was set to less than 30% of the channel spacing or the 20dB bandwidth, whichever is smaller. The peak detector and 'Max-Hold' function were engaged. The span was set wide enough to capture the entire frequency band of operation.
The EUT's signal was allowed to stabilize after multiple scans. The number of hopping frequencies was counted. The analyzer's display was plotted using a 'screen dump' utility.

Test Details	
Manufacturer	Pro1 IAQ Inc
EUT	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit
Frequency Tested	Hopping Enabled
Result	50 hopping frequencies
Notes	
Date Tested	August 31, 2023



Number of Hopping Frequencies

24. Average Time of Occupancy

EUT Information	
Manufacturer	Pro1 IAQ Inc
Product	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit

Test Setup Details	
Setup Format	Tabletop
Height of Support (For Floor Standing only)	N/A
Measurement Method	Antenna Conducted
Type of Test Site	Tabletop
Test Site Used	N/A
Type of Antennas Used	N/A
Notes	

Measurement Uncertainty	
Measurement Type	Expanded Measurement Uncertainty
Radiated disturbance (electric field strength on an open area test site or alternative test site) (30 MHz – 1000 MHz)	4.3
Radiated disturbance (electric field strength on an open area test site or alternative test site) (1 GHz – 6 GHz)	3.1


Requirements
<u>For 902-928 MHz, 20dB BW < 250kHz</u> The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period.

Procedure


The antenna port of the EUT was connected to the spectrum analyzer through 40dB of attenuation. With the hopping function enabled, the EUT was allowed to transmit continuously.

The spectrum analyzer was set to zero span centered on a hopping channel. The resolution bandwidth (RBW) was set \geq to the channel spacing. The sweep was set to capture the entire dwell time per hopping channel. The peak detector and 'Max-Hold' function were engaged. The analyzer's display was plotted using a 'screen dump' utility.

Test Details	
Manufacturer	Pro1 IAQ Inc
EUT	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit
Frequency Tested	Hopping Enabled
Result	On-time of single pulse = 6.48msec
Notes	
Date Tested	August 31, 2023



Test Details	
Manufacturer	Pro1 IAQ Inc
EUT	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit
Frequency Tested	Hopping Enabled
Result	1 on-channel pulse every 20 sec.
Notes	The average time of occupancy = (6.48msec/pulse) x (1 pulse) = 6.48 msec every 20sec
Date Tested	August 31, 2023



25. Maximum Peak Conducted Output Power


EUT Information	
Manufacturer	Pro1 IAQ Inc
Product	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit

Test Setup Details	
Setup Format	Tabletop
Height of Support (For Floor Standing only)	N/A
Measurement Method	Antenna Conducted
Type of Test Site	Tabletop
Test Site Used	N/A
Notes	


Requirements
<p>FOR FREQUENCY HOPPING SYSTEMS IN THE 902-928 MHz, CHANNELS ≥ 50 The output power shall not exceed 1W (30dBm).</p>

Procedure
<p>The antenna port of the EUT was connected to the spectrum analyzer through 30dB of attenuation. With the hopping function disabled, the EUT was allowed to transmit continuously. The frequency hopping channel was set separately to low, middle, and high hopping channels. The resolution bandwidth (RBW) was set to greater than the 20dB bandwidth. The span was set to approximately 5 times the 20dB bandwidth. The 'Max-Hold' function was engaged. The maximum meter reading was recorded. The peak power output was calculated for the low, middle, and high hopping frequencies.</p>


Test Details	
Manufacturer	Pro1 IAQ Inc
EUT	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit
Frequency Tested	902.52MHz
Result	Output Power = 24.1mW (13.82dBm)
Notes	
Date Tested	August 31, 2023



Test Details	
Manufacturer	Pro1 IAQ Inc
EUT	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit
Frequency Tested	914.78MHz
Result	Output Power = 22.91mW (13.6dBm)
Notes	
Date Tested	August 31, 2023



Test Details	
Manufacturer	Pro1 IAQ Inc
EUT	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit
Frequency Tested	927.56MHz
Result	Output Power = 22.23mW (13.47dBm)
Notes	
Date Tested	August 31, 2023



26. Effective Isotropic Radiated Power (EIRP)

EUT Information	
Manufacturer	Pro1 IAQ Inc
Product	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit

Test Setup Details	
Setup Format	Tabletop Floor Standing
Height of Support (For Floor Standing only)	N/A
Measurement Method	Radiated
Type of Test Site	Semi-Anechoic Chamber
Test Site Used	Room #21
Type of Antennas Used	Below 1GHz: Bilog (or equivalent) Above 1GHz: Double-ridged waveguide (or equivalent) N/A
Notes	

Measurement Uncertainty	
Measurement Type	Expanded Measurement Uncertainty
Radiated disturbance (electric field strength on an open area test site or alternative test site) (30 MHz – 1000 MHz)	4.3
Radiated disturbance (electric field strength on an open area test site or alternative test site) (1 GHz – 6 GHz)	3.1

Requirements
<u>FOR FREQUENCY HOPPING SYSTEMS IN THE 902-928 MHz, CHANNELS ≥ 50</u>
The output power shall not exceed 4W (36dBm).

Procedure
<u>FOR FREQUENCY HOPPING SYSTEMS</u> The EUT was placed on the non-conductive stand and set to transmit. A bilog antenna was placed at a test distance of 3 meters from the EUT. The resolution bandwidth (RBW) of the spectrum analyzer was set to greater than the 20dB bandwidth. The span was set to approximately 5 times the 20 dB bandwidth. The EUT was maximized for worst case emissions (or maximum output power) at the measuring antenna. The maximum meter reading was recorded. The peak power output was measured for the low, middle, and high hopping frequencies. The equivalent power was determined from the field intensity levels measured at 3 meters using the substitution method. To determine the emission power, a dipole antenna was then set in place of the EUT and connected to a calibrated signal generator. The output of the signal generator was adjusted to match the received level at the spectrum analyzer. The signal level was recorded. The reading was then corrected to compensate for cable loss (and antenna gain for all measurements above 1GHz), as required. The peak power output was calculated for low, middle, and high hopping frequencies.

Test Details	
Manufacturer	Pro1 IAQ Inc
EUT	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Radiated EUT #2
Mode	Transmit
Result	Max EIRP = 40.74mW (16.1dBm)
Notes	
Date Tested	August 31, 2023

Freq (MHz)	Ant Pol	Wide BW Meter Reading (dB μ V)	Matched Sig Gen Reading (dBm)	Equivalent Antenna Gain (dB)	Cable Loss (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
902.52	H	67.5	-2.9	2.2	2.0	-2.8	36.0	-38.8
	V	84.0	16.0	2.2	2.0	16.1	36.0	-19.9
914.79	H	67.5	-2.9	2.2	2.0	-2.8	36.0	-38.8
	V	84.0	16.0	2.2	2.0	16.1	36.0	-19.9
927.56	H	66.7	-3.8	2.2	2.1	-3.7	36.0	-39.7
	V	82.3	15.1	2.2	2.1	15.2	36.0	-20.8

27. Duty Cycle Factor Measurements


EUT Information	
Manufacturer	Pro1 IAQ Inc
Product	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit

Test Setup Details	
Setup Format	Tabletop
Height of Support (For Floor Standing only)	N/A
Measurement Method	Antenna Conducted
Type of Test Site	Elite Test Bench
Type of Antennas Used	N/A
Notes	None


Measurement Type	Expanded Measurement Uncertainty
Radiated disturbance (electric field strength on an open area test site or alternative test site) (30 MHz – 1000 MHz)	4.3
Radiated disturbance (electric field strength on an open area test site or alternative test site) (1 GHz – 6 GHz)	3.1

Procedure
<p>The duty cycle factor is used to convert peak detected readings to average readings when pulsed modulation is employed. This factor is computed from the time domain trace of the pulse modulation signal.</p> <p>With the transmitter set up to transmit for maximum pulse density, the time domain trace is displayed on the spectrum analyzer. This trace is obtained by tuning center frequency to the transmitter frequency and then setting a zero-span width with 10msec/div. The amplitude settings are adjusted so that the on/off transitions clear the 4th division from the bottom of the display. The markers are set at the beginning and end of the “on-time”. The trace is recorded.</p> <p>Next the spectrum analyzer center frequency is set to the transmitter frequency with a zero-span width and 10msec/div. This shows if the word is longer than 100msec or shorter than 100msec. If the word period is less than 100msec, the display is set to show at least one word. The on-time and off-time are then measured. The on-time is total time signal level exceeds the 4th division. Off-time is time under for the word period.</p> <p>The duty cycle is then computed as $\left(\frac{\text{On Time}}{\text{Word Period}} \right)$, where $\text{Word Period} = (\text{On Time} + \text{Off Time})$.</p>

Test Details	
Manufacturer	Pro1 IAQ Inc
EUT	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit
Frequency Tested	Hopping Enabled
Result	On Time = 6.48msec
Notes	
Date Tested	August 31, 2023



Test Details	
Manufacturer	Pro1 IAQ Inc
EUT	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit
Frequency Tested	Hopping Enabled
Result	On Time = 6.48ms, Duty cycle = 6.48msec/100msec = 6.48% Duty Cycle Correction Factor = 20 log (6.48msec/100msec) = -23.77dB
Notes	
Date Tested	August 31, 2023



28. Case Spurious Radiated Emissions

EUT Information	
Manufacturer	Pro1 IAQ Inc
Product	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit

Test Setup Details	
Setup Format	Tabletop
Height of Support (For Floor Standing only)	N/A
Type of Test Site	Semi-Anechoic Chamber
Test Site Used	Room #21
Type of Antennas Used	Below 1GHz: Bilog (or equivalent) Above 1GHz: Double-Ridged Waveguide (or equivalent) Above 18GHz: Horn (or equivalent)
Notes	N/A

Measurement Uncertainty	
Measurement Type	Expanded Measurement Uncertainty
Radiated disturbance (electric field strength on an open area test site or alternative test site) (30 MHz – 1000 MHz)	4.3
Radiated disturbance (electric field strength on an open area test site or alternative test site) (1 GHz – 6 GHz)	3.1
Radiated disturbance (electric field strength on an open area test site or alternative test site) (6 GHz – 18 GHz)	3.2
Radiated disturbance (electric field strength on an open area test site or alternative test site) (18 GHz – 26.5 GHz)	3.3
Radiated disturbance (electric field strength on an open area test site or alternative test site) (26.5 GHz – 40 GHz)	3.4

Procedure

Radiated measurements were performed in a 32ft. x 20ft. x 14ft. high shielded enclosure. The shielded enclosure prevents emissions from other sources, such as radio and TV stations from interfering with the measurements. All powerlines and signal lines entering the enclosure pass through filters on the enclosure wall. The powerline filters prevent extraneous signals from entering the enclosure on these leads.

Preliminary radiated emissions tests were performed to determine the emission characteristics of the EUT. For the preliminary test, a broadband measuring antenna was positioned at a 3-meter distance from the EUT. The entire frequency range from 30MHz to 10.0GHz was investigated using a peak detector function.

The final open field emission tests were then manually performed over the frequency range of 30MHz to 10.0GHz.

1) For all harmonics not in the restricted bands, the following procedure was used:

- a) The field strength of the fundamental was measured using a bilog antenna. The bilog antenna was positioned at a 3-meter distance from the EUT. The EUT was placed on an 80cm high non-conductive stand. A peak detector with a resolution bandwidth of 100 kHz was used on the spectrum analyzer.
- b) The field strengths of all of the harmonics not in the restricted band were then measured using a double-ridged waveguide antenna. The waveguide antenna was positioned at a 3-meter distance from the EUT. The EUT was placed on a 1.5-meter-high non-conductive stand. A peak detector with a resolution bandwidth of 100kHz was used on the spectrum analyzer.
- c) To ensure that maximum or worst-case emission levels at the fundamental and harmonics were measured, the following steps were taken when measuring the fundamental emissions and the spurious emissions:
 - i) The EUT was rotated so that all of its sides were exposed to the receiving antenna.
 - ii) Since the measuring antenna is linearly polarized, both horizontal and vertical field components were measured.
 - iii) The measuring antenna was raised and lowered for each antenna polarization to maximize the readings.
 - iv) In instances where it was necessary to use a shortened cable between the measuring antenna and the spectrum analyzer, the measuring antenna was not raised or lowered to ensure maximized readings. Instead, the EUT was rotated through all axis to ensure the maximum readings were recorded for the EUT.
- d) All harmonics not in the restricted bands must be at least 20dB below levels measured at the fundamental. However, attenuation below the general limits specified in §15.209(a) is not required.

2) For all emissions in the restricted bands, the following procedure was used:


- a) The field strengths of all emissions below 1GHz were measured using a bi-log antenna. The bi-log antenna was positioned at a 3-meter distance from the EUT. The EUT was placed on an 80cm high non-conductive stand. A peak detector with a resolution bandwidth of 100 kHz was used on the spectrum analyzer.
- b) The field strengths of all emissions above 1GHz were measured using a double-ridged waveguide antenna. The waveguide antenna was positioned at a 3-meter distance from the EUT. The EUT was placed on a 1.5-meter-high non-conductive stand. A peak detector with a resolution bandwidth of 1MHz was used on the spectrum analyzer.
- c) To ensure that maximum or worst-case emission levels were measured, the following steps were taken when taking all measurements:
 - i) The EUT was rotated so that all of its sides were exposed to the receiving antenna.
 - ii) Since the measuring antenna is linearly polarized, both horizontal and vertical field components

were measured.


- iii) The measuring antenna was raised and lowered for each antenna polarization to maximize the readings.
- iv) In instances where it was necessary to use a shortened cable between the measuring antenna and the spectrum analyzer, the measuring antenna was not raised or lowered to ensure maximized readings. Instead, the EUT was rotated through all axis to ensure the maximum readings were recorded for the EUT.
- d) For all radiated emissions measurements below 1GHz, if the peak reading is below the limits listed in §15.209(a), no further measurements are required. If, however, the peak readings exceed the limits listed in §15.209(a), then the emissions are remeasured using a quasi-peak detector.
- e) For all radiated emissions measurements above 1GHz, the peak readings must comply with the §15.35(b) limits. §15.35(b) states that when average radiated emissions measurements are specified, there also is a limit on the peak level of the radiated emissions. The limit on the peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. Therefore, all peak readings above 1GHz must be no greater than 20dB above the limits specified in §15.209(a).
- f) If the dwell time per channel of the hopping signal is less than 100msec, then the peak reading obtained with the 1MHz RBW may be further adjusted by a duty cycle correction factor derived from $20 \cdot \log(\text{dwell time}/100\text{msec})$. These readings must be no greater than the limits specified in §15.209(a).



Test Setup for Spurious Radiated Emissions, 30MHz – 1GHz – Antenna
Polarization Horizontal



Test Setup for Spurious Radiated Emissions, 30MHz – 1GHz – Antenna
Polarization Vertical



Test Setup for Spurious Radiated Emissions, Above 1GHz – Antenna Polarization
Horizontal



Test Setup for Spurious Radiated Emissions, Above 1GHz – Antenna Polarization
Vertical

Test Details										
Manufacturer	Pro1 IAQ Inc									
EUT	Wireless Outdoor Remote Sensor									
Model No.	R250W									
Serial No.	Radiated EUT #2									
Mode	Transmit									
Frequency Tested	902.52MHz									
Notes	Peak Measurements in the Restricted Bands									
Date Tested	August 31, 2023									

Freq (MHz)	Ant Pol	Meter Reading (dB μ V)	Ambient	Cable Factor (dB)	Antenna Factor (dB/m)	Pre Amp (dB)	Peak Total at 3m (dB μ V/m)	Peak Total at 3m (μ V/m)	Peak Limit at 3m (μ V/m)	Margin (dB)
2707.44	H	53.2		2.8	32.6	-39.8	48.8	275.7	5000.0	-25.2
	V	54.4		2.8	32.6	-39.8	50.0	316.6	5000.0	-24.0
3609.92	H	56.1		3.2	33.6	-39.2	53.8	487.7	5000.0	-20.2
	V	55.6		3.2	33.6	-39.2	53.3	460.4	5000.0	-20.7
4512.40	H	59.1		3.6	34.3	-39.2	57.7	769.4	5000.0	-16.3
	V	56.7		3.6	34.3	-39.2	55.3	583.7	5000.0	-18.7
5414.88	H	61.5		3.9	34.7	-39.4	60.8	1091.4	5000.0	-13.2
	V	56.3		3.9	34.7	-39.4	55.6	599.8	5000.0	-18.4
8122.32	H	50.7		4.9	36.8	-39.4	53.0	446.5	5000.0	-21.0
	V	53.1		4.9	36.8	-39.4	55.4	588.6	5000.0	-18.6
9024.80	H	53.2		4.9	36.6	-39.3	55.5	593.7	5000.0	-18.5
	V	52.6		4.9	36.6	-39.3	54.9	554.1	5000.0	-19.1

Test Details											
Manufacturer	Pro1 IAQ Inc										
EUT	Wireless Outdoor Remote Sensor										
Model No.	R250W										
Serial No.	Radiated EUT #2										
Mode	Transmit										
Frequency Tested	902.25MHz										
Notes	Average Measurements in the Restricted Bands										
Date Tested	August 31, 2023										

Freq (MHz)	Ant Pol	Meter Reading (dB μ V)	Ambient	CBL Fac (dB)	Ant Fac (dB/m)	Pre Amp (dB)	Duty Cycle Factor (dB)	Average Total at 3m (dB μ V/m)	Average Total at 3m (μ V/m)	Average Limit at 3m (μ V/m)	Margin (dB)
2707.44	H	53.20		2.8	32.6	-39.8	-23.8	25.0	17.9	500.0	-28.9
	V	54.40		2.8	32.6	-39.8	-23.8	26.2	20.5	500.0	-27.7
3609.92	H	56.10		3.2	33.6	-39.2	-23.8	30.0	31.6	500.0	-24.0
	V	55.60		3.2	33.6	-39.2	-23.8	29.5	29.8	500.0	-24.5
4512.40	H	59.10		3.6	34.3	-39.2	-23.8	34.0	49.9	500.0	-20.0
	V	56.70		3.6	34.3	-39.2	-23.8	31.6	37.8	500.0	-22.4
5414.88	H	61.50		3.9	34.7	-39.4	-23.8	37.0	70.7	500.0	-17.0
	V	56.30		3.9	34.7	-39.4	-23.8	31.8	38.9	500.0	-22.2
8122.32	H	50.70		4.9	36.8	-39.4	-23.8	29.2	28.9	500.0	-24.8
	V	53.10		4.9	36.8	-39.4	-23.8	31.6	38.1	500.0	-22.4
9024.80	H	53.20		4.9	36.6	-39.3	-23.8	31.7	38.5	500.0	-22.3
	V	52.60		4.9	36.6	-39.3	-23.8	31.1	35.9	500.0	-22.9

Test Details										
Manufacturer	Pro1 IAQ Inc									
EUT	Wireless Outdoor Remote Sensor									
Model No.	R250W									
Serial No.	Radiated EUT #2									
Mode	Transmit									
Frequency Tested	902.52MHz									
Notes	Peak Measurements in Non-Restricted Bands									
Date Tested	August 31, 2023									

Freq (MHz)	Ant Pol	Meter Reading (dB μ V)	Ambient	Cable Factor (dB)	Antenna Factor (dB/m)	Pre Amp (dB)	Peak Total at 3m (dB μ V/m)	Peak Total at 3m (μ V/m)	Peak Limit at 3m (μ V/m)	Margin (dB)
902.48	H	67.40		1.5	26.5	0.0	95.4	59001.1	NA	NA
	V	83.90		1.5	26.5	0.0	111.9	394330.2	NA	NA
1804.96	H	64.30		2.2	30.4	-40.0	56.9	700.7	39433.0	-35.0
	V	66.10		2.2	30.4	-40.0	58.7	862.0	39433.0	-33.2
6317.36	H	47.20		4.3	35.8	-39.4	47.8	246.2	39433.0	-44.1
	V	47.00		4.3	35.8	-39.4	47.6	240.6	39433.0	-44.3
7219.84	H	48.10		4.6	36.3	-39.4	49.6	302.1	39433.0	-42.3
	V	47.90		4.6	36.3	-39.4	49.4	295.2	39433.0	-42.5

Test Details										
Manufacturer	Pro1 IAQ Inc									
EUT	Wireless Outdoor Remote Sensor									
Model No.	R250W									
Serial No.	Radiated EUT #2									
Mode	Transmit									
Frequency Tested	914.79MHz									
Notes	Peak Measurements in the Restricted Bands									
Date Tested	August 31, 2023 and September 1, 2023									

Freq (MHz)	Ant Pol	Meter Reading (dB μ V)	Ambient	Cable Factor (dB)	Antenna Factor (dB/m)	Pre Amp (dB)	Peak Total at 3m (dB μ V/m)	Peak Total at 3m (μ V/m)	Peak Limit at 3m (μ V/m)	Margin (dB)
2744.31	H	53.0		2.8	32.6	-39.7	48.7	271.3	5000.0	-25.3
	V	52.5		2.8	32.6	-39.7	48.2	256.1	5000.0	-25.8
3659.08	H	56.5		3.3	33.6	-39.2	54.2	511.3	5000.0	-19.8
	V	56.2		3.3	33.6	-39.2	53.9	494.0	5000.0	-20.1
4573.85	H	56.3		3.6	34.3	-39.2	55.0	560.7	5000.0	-19.0
	V	54.0		3.6	34.3	-39.2	52.7	430.3	5000.0	-21.3
7318.16	H	51.8		4.7	36.3	-39.4	53.3	464.0	5000.0	-20.6
	V	51.3		4.7	36.3	-39.4	52.8	438.1	5000.0	-21.1
8232.93	H	50.6		4.9	36.8	-39.4	53.0	444.4	5000.0	-21.0
	V	52.1		4.9	36.8	-39.4	54.5	528.2	5000.0	-19.5
9147.70	H	50.6	Ambient	5.0	36.7	-39.3	53.0	444.9	5000.0	-21.0
	V	50.8	Ambient	5.0	36.7	-39.3	53.2	455.3	5000.0	-20.8

Test Details											
Manufacturer	Pro1 IAQ Inc										
EUT	Wireless Outdoor Remote Sensor										
Model No.	R250W										
Serial No.	Radiated EUT #2										
Mode	Transmit										
Frequency Tested	914.79MHz										
Notes	Average Measurements in the Restricted Bands										
Date Tested	August 31, 2023 and September 1, 2023										

Freq (MHz)	Ant Pol	Meter Reading (dB μ V)	Ambient	CBL Fac (dB)	Ant Fac (dB/m)	Pre Amp (dB)	Duty Cycle Factor (dB)	Average Total at 3m (dB μ V/m)	Average Total at 3m (μ V/m)	Average Limit at 3m (μ V/m)	Margin (dB)
2744.31	H	53.00		2.8	32.6	-39.7	-23.8	24.9	17.6	500.0	-29.1
	V	52.50		2.8	32.6	-39.7	-23.8	24.4	16.6	500.0	-29.6
3659.08	H	56.50		3.3	33.6	-39.2	-23.8	30.4	33.1	500.0	-23.6
	V	56.20		3.3	33.6	-39.2	-23.8	30.1	32.0	500.0	-23.9
4573.85	H	56.30		3.6	34.3	-39.2	-23.8	31.2	36.3	500.0	-22.8
	V	54.00		3.6	34.3	-39.2	-23.8	28.9	27.9	500.0	-25.1
7318.16	H	51.80		4.7	36.3	-39.4	-23.8	29.6	30.1	500.0	-24.4
	V	51.30		4.7	36.3	-39.4	-23.8	29.1	28.4	500.0	-24.9
8232.93	H	50.60		4.9	36.8	-39.4	-23.8	29.2	28.8	500.0	-24.8
	V	52.10		4.9	36.8	-39.4	-23.8	30.7	34.2	500.0	-23.3
9147.70	H	50.60	Ambient	5.0	36.7	-39.3	-23.8	29.2	28.8	500.0	-24.8
	V	50.80	Ambient	5.0	36.7	-39.3	-23.8	29.4	29.5	500.0	-24.6

Test Details										
Manufacturer	Pro1 IAQ Inc									
EUT	Wireless Outdoor Remote Sensor									
Model No.	R250W									
Serial No.	Radiated EUT #2									
Mode	Transmit									
Frequency Tested	914.79MHz									
Notes	Peak Measurements in Non-Restricted Bands									
Date Tested	August 31, 2023 and September 1, 2023									

Freq (MHz)	Ant Pol	Meter Reading (dB μ V)	Ambient	Cable Factor (dB)	Antenna Factor (dB/m)	Pre Amp (dB)	Peak Total at 3m (dB μ V/m)	Peak Total at 3m (μ V/m)	Peak Limit at 3m (μ V/m)	Margin (dB)
914.77	H	66.70		1.6	26.3	0.0	94.6	53530.3	NA	NA
	V	82.10		1.6	26.3	0.0	110.0	315209.7	NA	NA
1829.54	H	67.40		2.2	30.5	-40.0	60.2	1019.2	31521.0	-29.8
	V	66.20		2.2	30.5	-40.0	59.0	887.7	31521.0	-31.0
5488.62	H	57.90		3.9	34.8	-39.4	57.3	729.8	31521.0	-32.7
	V	54.00		3.9	34.8	-39.4	53.4	465.8	31521.0	-36.6
6403.39	H	50.80		4.3	35.7	-39.4	51.4	371.7	31521.0	-38.6
	V	48.40		4.3	35.7	-39.4	49.0	281.9	31521.0	-41.0

Test Details										
Manufacturer	Pro1 IAQ Inc									
EUT	Wireless Outdoor Remote Sensor									
Model No.	R250W									
Serial No.	Radiated EUT #2									
Mode	Transmit									
Frequency Tested	927.56MHz									
Notes	Peak Measurements in the Restricted Bands									
Date Tested	August 31, 2023 and September 1, 2023									

Freq (MHz)	Ant Pol	Meter Reading (dB μ V)	Ambient	Cable Factor (dB)	Antenna Factor (dB/m)	Pre Amp (dB)	Peak Total at 3m (dB μ V/m)	Peak Total at 3m (μ V/m)	Peak Limit at 3m (μ V/m)	Margin (dB)
2782.56	H	52.0		2.8	32.6	-39.7	47.7	243.1	5000.0	-26.3
	V	52.5		2.8	32.6	-39.7	48.2	257.5	5000.0	-25.8
3710.08	H	57.2		3.3	33.4	-39.2	54.7	542.8	5000.0	-19.3
	V	57.4		3.3	33.4	-39.2	54.9	555.4	5000.0	-19.1
4637.60	H	62.5		3.6	34.3	-39.3	61.2	1147.9	5000.0	-12.8
	V	57.4		3.6	34.3	-39.3	56.1	638.1	5000.0	-17.9
7420.16	H	51.8		4.7	36.3	-39.4	53.4	468.2	5000.0	-20.6
	V	51.8		4.7	36.3	-39.4	53.4	468.2	5000.0	-20.6
8347.68	H	51.5		4.9	36.7	-39.4	53.7	486.2	5000.0	-20.2
	V	54.9		4.9	36.7	-39.4	57.1	719.2	5000.0	-16.8

Test Details											
Manufacturer	Pro1 IAQ Inc										
EUT	Wireless Outdoor Remote Sensor										
Model No.	R250W										
Serial No.	Radiated EUT #2										
Mode	Transmit										
Frequency Tested	927.56MHz										
Notes	Average Measurements in the Restricted Bands										
Date Tested	August 31, 2023 and September 1, 2023										

Freq (MHz)	Ant Pol	Meter Reading (dB μ V)	Ambient	CBL Fac (dB)	Ant Fac (dB/m)	Pre Amp (dB)	Duty Cycle Factor (dB)	Average Total at 3m (dB μ V/m)	Average Total at 3m (μ V/m)	Average Limit at 3m (μ V/m)	Margin (dB)
2782.68	H	66.50		3.7	33.2	-39.5	-11.8	52.2	409.6	500.0	-1.7
	V	64.60		3.7	33.2	-39.5	-11.8	50.3	329.2	500.0	-3.6
3710.24	H	59.80		4.3	34.4	-38.9	-11.8	47.9	248.5	500.0	-6.1
	V	59.90		4.3	34.4	-38.9	-11.8	48.0	251.4	500.0	-6.0
4637.80	H	52.50		4.8	36.1	-38.9	-11.8	42.7	136.4	500.0	-11.3
	V	52.20		4.8	36.1	-38.9	-11.8	42.4	131.8	500.0	-11.6
7420.48	H	57.30		6.2	37.7	-39.0	-11.8	50.4	331.0	500.0	-3.6
	V	57.80		6.2	37.7	-39.0	-11.8	50.9	350.6	500.0	-3.1
8348.04	H	0.00		6.5	38.4	-39.0	-11.8	-5.9	0.5	500.0	-59.8
	V	51.10		6.5	38.4	-39.0	-11.8	45.2	182.6	500.0	-8.7

Test Details										
Manufacturer	Pro1 IAQ Inc									
EUT	Wireless Outdoor Remote Sensor									
Model No.	R250W									
Serial No.	Radiated EUT #2									
Mode	Transmit									
Frequency Tested	927.56MHz									
Notes	Peak Measurements in Non-Restricted Bands									
Date Tested	August 31, 2023 and September 1, 2023									

Freq (MHz)	Ant Pol	Meter Reading (dB μ V)	Ambient	Cable Factor (dB)	Antenna Factor (dB/m)	Pre Amp (dB)	Peak Total at 3m (dB μ V/m)	Peak Total at 3m (μ V/m)	Peak Limit at 3m (μ V/m)	Margin (dB)
927.52	H	66.40		1.6	26.7	0.0	94.6	53904.6	NA	NA
	V	82.10		1.6	26.7	0.0	110.3	328568.5	NA	NA
1855.04	H	64.90		2.3	30.7	-40.0	57.8	778.4	32856.9	-32.5
	V	66.40		2.3	30.7	-40.0	59.3	925.2	32856.9	-31.0
5565.12	H	57.60		4.0	34.9	-39.4	57.1	716.1	32856.9	-33.2
	V	51.70		4.0	34.9	-39.4	51.2	363.0	32856.9	-39.1
6492.64	H	54.40		4.4	35.6	-39.4	55.0	562.0	32856.9	-35.3
	V	50.60		4.4	35.6	-39.4	51.2	362.8	32856.9	-39.1
9275.20	H	45.30		5.0	36.7	-39.3	47.8	244.5	32856.9	-42.6
	V	45.70		5.0	36.7	-39.3	48.2	256.0	32856.9	-42.2

29. Band-Edge Compliance

EUT Information	
Manufacturer	Pro1 IAQ Inc
Product	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit


Test Setup Details	
Setup Format	Tabletop
Height of Support (For Floor Standing only)	N/A
Measurement Method	Antenna Conducted
Type of Test Site	Elite Test Bench
Type of Antennas Used	N/A
Notes	None

Measurement Uncertainty	
Measurement Type	Expanded Measurement Uncertainty
Radiated disturbance (electric field strength on an open area test site or alternative test site) (30 MHz – 1000 MHz)	4.3
Radiated disturbance (electric field strength on an open area test site or alternative test site) (1 GHz – 6 GHz)	3.1


Procedure	
1) Low Band Edge:	
a)	The antenna port of the EUT was connected to the spectrum analyzer through 30dB of attenuation.
b)	The EUT was set to transmit continuously at the channel closest to the low band-edge, hopping function disabled.
c)	To determine the band edge compliance, the following spectrum analyzer settings were used: <ul style="list-style-type: none"> o Center Frequency = 902MHz (low band-edge frequency). o Span = Wide enough to capture the peak level of the emission operating on the channel closest to the band-edge, as well as any modulation products which fall outside of the authorized band of operation. o Resolution Bandwidth (RBW) = $\geq 1\%$ of the span. o 'Max-Hold' function was engaged.
d)	The analyzer was allowed to scan until the envelope of the transmitter bandwidth was defined.
e)	The marker was set on the peak of the in-band emissions. A display line was placed 20dB down from the peak of the in-band emissions. All emissions which fall outside of the authorized band of operation must be below the 20dB down display line. (All emissions to the left of the center frequency (band-edge) must be below the display line.)
f)	The analyzer's display was then screenshot and saved.
g)	Steps (d) through (f) were repeated with the frequency hopping function enabled.
2) High Band Edge:	
a)	The antenna port of the EUT was connected to the spectrum analyzer through 30dB of attenuation.

- b) The EUT was set to transmit continuously at the channel closest to the high band-edge, hopping function disabled).
- c) To determine the band edge compliance, the following spectrum analyzer settings were used:
 - o Center Frequency = 928MHz (high band-edge frequency).
 - o Span = Wide enough to capture the peak level of the emission operating on the channel closest to the band-edge, as well as any modulation products which fall outside of the authorized band of operation.
 - o Resolution Bandwidth (RBW) = $\geq 1\%$ of the span.
 - o 'Max-Hold' function was engaged.
- d) The analyzer was allowed to scan until the envelope of the transmitter bandwidth was defined.
- e) The marker was set on the peak of the in-band emissions. A display line was placed 20dB down from the peak of the in-band emissions. All emissions which fall outside of the authorized band of operation must be below the 20dB down display line. (All emissions to the left of the center frequency (band-edge) must be below the display line.)
- f) The analyzer's display was then screenshot and saved.
- g) Steps (d) through (f) were repeated with the frequency hopping function enabled.


Test Details	
Manufacturer	Pro1 IAQ Inc
EUT	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit
Frequency Tested	902.52MHz
Notes	Low Band Edge
Date Tested	August 31, 2023




Test Details	
Manufacturer	Pro1 IAQ Inc
EUT	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit
Frequency Tested	Hopping Enabled
Notes	Low Band Edge
Date Tested	August 31, 2023



Test Details	
Manufacturer	Pro1 IAQ Inc
EUT	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit
Frequency Tested	927.56MHz
Notes	High Band Edge
Date Tested	August 31, 2023



Test Details	
Manufacturer	Pro1 IAQ Inc
EUT	Wireless Outdoor Remote Sensor
Model No.	R250W
Serial No.	Conducted EUT #1
Mode	Transmit
Frequency Tested	Hopping Enabled
Notes	High Band Edge
Date Tested	August 31, 2023



30. Scope of Accreditation

SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017

ELITE ELECTRONIC ENGINEERING, INC.
1516 Centre Circle
Downers Grove, IL 60515
Robert Bugielski (QA Manager) Phone: 630 495 9770 ext. 168
Email: rbugielski@elitetest.com
Craig Fanning (EMC Lab Manager) Phone: 630 495 9770 ext. 112
Email: cfanning@elitetest.com
Brandon Lugo (Automotive Team Leader) Phone: 630 495 9770 ext. 163
Email: blugo@elitetest.com
Richard King (FCC/Commercial Team Leader) Phone: 630 495 9770 ext. 123
Email: reking@elitetest.com
Website: www.elitetest.com

ELECTRICAL

Valid To: June 30, 2025

Certificate Number: 1786.01

In recognition of the successful completion of the A2LA Accreditation Program evaluation process, accreditation is granted to this laboratory to perform the following automotive electromagnetic compatibility and other electrical tests:

Test Technology:*Transient Immunity**(Max Voltage 60V/Max current 100A)*Test Method(s)¹:

ISO 7637-2 (including emissions); ISO 7637-3;
ISO 16750-2:2012, Sections 4.6.3 and 4.6.4;
CS-11979, Section 6.4; CS.00054, Section 5.9;
EMC-CS-2009.1 (CI220); FMC1278 (CI220, CI221, CI222);
GMW 3097, Section 3.5; SAE J1113-11; SAE J1113-12;
ECE Regulation 10.06 Annex 10

*Electrostatic Discharge (ESD)**(Up to +/-25kV)*

ISO 10605 (2001, 2008);

CS-11979 Section 7.0; CS.00054, Section 5.10;

EMC-CS-2009.1 (CI 280); FMC1278 (CI280); SAE J1113-13;

GMW 3097 Section 3.6

Conducted Emissions

CISPR 25 (2002, 2008), Sections 6.2 and 6.3;

CISPR 25 (2016), Sections 6.3 and 6.4;

CS-11979, Section 5.1; CS.00054, Sections 5.6.1 and 5.6.2;

GMW 3097, Section 3.3.2;

EMC-CS-2009.1 (CE 420); FMC1278 (CE420, CE421, CE 430, CE440)

(A2LA Cert. No. 1786.01) 08/15/2023



Page 1 of 9

5202 Presidents Court, Suite 220 | Frederick, MD 21703-8515 | Phone: 301 644 3248 | Fax: 240 454 9449 | www.A2LA.org

<u>Test Technology:</u>	<u>Test Method(s)¹:</u>
Radiated Emissions Anechoic (Up to 6GHz)	CISPR 25 (2002, 2008), Section 6.4; CISPR 25 (2016), Section 6.5; CS-11979, Section 5.3; CS.00054, Section 5.6.3; GMW 3097, Section 3.3.1; EMC-CS-2009.1 (RE 310); FMC1278 (RE310, RE320);
Vehicle Radiated Emissions	CISPR 12; CISPR 36; ICES-002; ECE Regulation 10.06 Annex 5
Bulk Current Injection (BCI) (1 to 400MHz 500mA)	ISO 11452-4; CS-11979, Section 6.1; CS.00054, Section 5.8.1; GMW 3097, Section 3.4.1; SAE J1113-4; EMC-CS-2009.1 (RI112); FMC1278 (RI112); ECE Regulation 10.06 Annex 9
Radiated Immunity Anechoic (Up to 6GHz and 200V/m) (Including Radar Pulse 600V/m)	ISO 11452-2; CS-11979, Section 6.2; CS.00054, Section 5.8.2; GMW 3097, Section 3.4.2; EMC-CS-2009.1 (RI114); FMC1278 (RI114); SAE J1113-21; ECE Regulation 10.06 Annex 9
Radiated Immunity Magnetic Field	ISO 11452-8; FMC 1278 (RI140)
Radiated Immunity Reverb (360MHz to 6GHz and 100V/m)	ISO/IEC 61000-4-21; GMW 3097, Section 3.4.3; EMC-CS-2009.1 (RI114); FMC1278 (RI114); ISO 11452-11
Radiated Immunity (Portable Transmitters) (Up to 6GHz and 20W)	ISO 11452-9; EMC-CS-2009.1 (RI115); FMC1278 (RI115); GMW 3097, Sec 3.4.4
Vehicle Radiated Immunity (ALSE)	ISO 11451-2; ECE Regulation 10.06 Annex 6
Vehicle Product Specific EMC Standards	EN 14982; EN ISO 13309; ISO 13766; EN 50498; EC Regulation No. 2015/208; EN 55012
Electrical Loads	ISO 16750-2
Stripline	ISO 11452-5
Transverse Electromagnetic (TEM) Cell	ISO 11452-3

Test Technology:
Emissions

Radiated and Conducted
(3m Semi-anechoic chamber,
up to 40 GHz)

Test Method(s)¹:

47 CFR, FCC Part 15 B (using ANSI C63.4:2014);
47 CFR, FCC Part 18 (using FCC MP-5:1986);
ICES-001; ICES-003; ICES-005;
IEC/CISPR 11, Ed. 4.1 (2004-06); AS/NZS CISPR 11 (2004);
IEC/CISPR 11 Ed 5 (2009-05) + A1 (2010);
KN 11 (2008-5) with RRL Notice No. 2008-3 (May 20, 2008);
CISPR 11; EN 55011; KS C 9811; CNS 13803 (1997, 2003);
CISPR 14-1; EN 55014-1; AS/NZS CISPR 14.1;
CISPR 16-2-1 (2008); CISPR 16-2-1; KS C 9814-1; KN 14-1;
IEC/CISPR 22 (1997);
EN 55022 (1998) + A1(2000);
EN 55022 (1998) + A1(2000) + A2(2003); EN 55022 (2006);
IEC/CISPR 22 (2008-09); AS/NZS CISPR 22 (2004);
AS/NZS CISPR 22, 3rd Edition (2006); KN 22 (up to 6 GHz);
CNS 13438 (up to 6 GHz); VCCI V-3 (up to 6 GHz);
CISPR 32; EN 55032; KS C 9832; KN 32;
ECE Regulation 10.06 Annex 7 (Broadband);
ECE Regulation 10.06 Annex 8 (Narrowband);
ECE Regulation 10.06 Annex 14 (Conducted)

Cellular Radiated Spurious Emissions

ETSI TS 151 010-1 GSM; 3GPP TS 51.010-1, Sec 12;
ETSI TS 134 124 UMTS; 3GPP TS 34.124;
ETSI TS 136 124 LTE; E-UTRA; 3GPP TS 36.124

Current Harmonics

IEC 61000-3-2; IEC 61000-3-12;
EN 61000-3-2; KN 61000-3-2;
KS C 9610-3-2; ECE Regulation 10.06 Annex 11

Flicker and Fluctuations

IEC 61000-3-3; IEC 61000-3-11;
EN 61000-3-3; KN 61000-3-3;
KS C 9610-3-3; ECE Regulation 10.06 Annex 12

Immunity

Electrostatic Discharge

IEC 61000-4-2, Ed. 1.2 (2001);
IEC 61000-4-2 (1995) + A1(1998) + A2(2000);
EN 61000-4-2 (1995); EN 61000-4-2 (2009-05);
KN 61000-4-2 (2008-5);
RRL Notice No. 2008-4 (May 20, 2008);
IEC 61000-4-2; EN 61000-4-2; KN 61000-4-2;
KS C 9610-4-2; IEEE C37.90.3 2001

Radiated Immunity

IEC 61000-4-3 (1995) + A1(1998) + A2(2000);
IEC 61000-4-3, Ed. 3.0 (2006-02);
IEC 61000-4-3, Ed. 3.2 (2010);
KN 61000-4-3 (2008-5);
RRL Notice No. 2008-4 (May 20, 2008);
IEC 61000-4-3; EN 61000-4-3; KN 61000-4-3;
KS C 9610-4-3; IEEE C37.90.2 2004

<u>Test Technology:</u>	<u>Test Method(s)¹:</u>
Immunity (cont'd)	
Electrical Fast Transient/Burst	IEC 61000-4-4, Ed. 2.0 (2004-07); IEC 61000-4-4, Ed. 2.1 (2011); IEC 61000-4-4 (1995) + A1(2000) + A2(2001); KN 61000-4-4 (2008-5); RRL Notice No. 2008-5 (May 20, 2008); IEC 61000-4-4; EN 61000-4-4; KN 61000-4-4; KS C 9610-4-4; ECE Regulation 10.06 Annex 15
Surge	IEC 61000-4-5 (1995) + A1(2000); IEC 61000-4-5, Ed 1.1 (2005-11); EN 61000-4-5 (1995) + A1(2001); KN 61000-4-5 (2008-5); RRL Notice No. 2008-4 (May 20, 2008); IEC 61000-4-5; EN 61000-4-5; KN 61000-4-5; KS C 9610-4-5; IEEE C37.90.1 2012; IEEE STD C62.41.2 2002; ECE Regulation 10.06 Annex 16
Conducted Immunity	IEC 61000-4-6 (1996) + A1(2000); IEC 61000-4-6, Ed 2.0 (2006-05); IEC 61000-4-6 Ed. 3.0 (2008); KN 61000-4-6 (2008-5); RRL Notice No. 2008-4 (May 20, 2008); EN 61000-4-6 (1996) + A1(2001); IEC 61000-4-6; EN 61000-4-6; KN 61000-4-6; KS C 9610-4-6
Power Frequency Magnetic Field Immunity (<i>Down to 3 A/m</i>)	IEC 61000-4-8 (1993) + A1(2000); IEC 61000-4-8 (2009); EN 61000-4-8 (1994) + A1(2000); KN 61000-4-8 (2008-5); RRL Notice No. 2008-4 (May 20, 2008); IEC 61000-4-8; EN 61000-4-8; KN 61000-4-8; KS C 9610-4-8
Voltage Dips, Short Interrupts, and Line Voltage Variations	IEC 61000-4-11, Ed. 2 (2004-03); KN 61000-4-11 (2008-5); RRL Notice No. 2008-4 (May 20, 2008); IEC 61000-4-11; EN 61000-4-11; KN 61000-4-11; KS C 9610-4-11
Ring Wave	IEC 61000-4-12, Ed. 2 (2006-09); EN 61000-4-12:2006; IEC 61000-4-12; EN 61000-4-12; KN 61000-4-12; IEEE STD C62.41.2 2002

Test Technology:

Generic and Product Specific EMC Standards

Test Method(s)¹:

IEC/EN 61000-6-1; AS/NZS 61000-6-1; KN 61000-6-1;
 KS C 9610-6-1; IEC/EN 61000-6-2; AS/NZS 61000-6-2;
 KN 61000-6-2; KS C 9610-6-2; IEC/EN 61000-6-3;
 AS/NZS 61000-6-3; KN 61000-6-3; KS C 9610-6-3;
 IEC/EN 61000-6-4; AS/NZS 61000-6-4; KN 61000-6-4;
 KS C 9610-6-4; EN 50130-4; EN 61326-1; EN 50121-3-2;
 EN 12895; EN 50270; EN 50491-1; EN 50491-2; EN 50491-3;
 EN 55015; EN 60730-1; EN 60945; IEC 60533;
 EN 61326-2-6; EN 61800-3; IEC/CISPR 14-2; EN 55014-2;
 AS/NZS CISPR 14.2; KN 14-2; KS C 9814-2;
 IEC/CISPR 24; AS/NZS CISPR 24; EN 55024; KN 24;
 IEC/CISPR 35; AS/NZS CISPR 35; EN 55035; KN 35;
 KS C 9835; IEC 60601-1-2; JIS T0601-1-2

TxRx EMC Requirements

EN 301 489-1; EN 301 489-3; EN 301 489-9;
 EN 301 489-17; EN 301 489-19; EN 301 489-20

European Radio Test Standards

ETSI EN 300 086-1; ETSI EN 300 086-2;
 ETSI EN 300 113-1; ETSI EN 300 113-2;
 ETSI EN 300 220-1; ETSI EN 300 220-2;
 ETSI EN 300 220-3-1; ETSI EN 300 220-3-2;
 ETSI EN 300 330-1; ETSI EN 300 330-2;
 ETSI EN 300 440-1; ETSI EN 300 440-2;
 ETSI EN 300 422-1; ETSI EN 300 422-2;
 ETSI EN 300 328; ETSI EN 301 893;
 ETSI EN 301 511; ETSI EN 301 908-1;
 ETSI EN 908-2; ETSI EN 908-13;
 ETSI EN 303 413; ETSI EN 302 502;
 EN 303 340; EN 303 345-2; EN 303 345-3; EN 303 345-4

Canadian Radio Tests

RSS-102 measurement (RF Exposure Evaluation);
 RSS-102 measurement (Nerve Stimulation);
 SPR-002; RSS-111; RSS-112; RSS-117; RSS-119; RSS-123;
 RSS-125; RSS-127; RSS-130; RSS-131; RSS-132; RSS-133;
 RSS-134; RSS-135; RSS-137; RSS-139; RSS-140; RSS-141;
 RSS-142; RSS-170; RSS-181; RSS-182; RSS-191; RSS-192;
 RSS-194; RSS-195; RSS-196; RSS-197; RSS-199; RSS-210;
 RSS-211; RSS-213; RSS-215; RSS-216; RSS-220; RSS-222;
 RSS-236; RSS-238; RSS-243; RSS-244; RSS-247; RSS-248;
 RSS-251; RSS-252; RSS-287; RSS-288; RSS-310; RSS-GEN

Mexico Radio Tests

IFT-008-2015; NOM-208-SCFI-2016

Japan Radio Tests

Radio Law No. 131, Ordinance of MPT No. 37, 1981,
 MIC Notification No. 88:2004, Table No. 22-11;
 ARIB STD-T66, Regulation 18

Taiwan Radio Tests

LP-0002 (July 15, 2020)

<u>Test Technology:</u>	<u>Test Method(s)¹:</u>
<i>Australia/New Zealand Radio Tests</i>	AS/NZS 4268; Radiocommunications (Short Range Devices) Standard (2014)
<i>Hong Kong Radio Tests</i>	HKCA 1039 Issue 6; HKCA 1042; HKCA 1033 Issue 7; HKCA 1061; HKCA 1008; HKCA 1043; HKCA 1057; HKCA 1073
<i>Korean Radio Test Standards</i>	KN 301 489-1; KN 301 489-3; KN 301 489-9; KN 301 489-17; KN 301 489-52; KS X 3124; KS X 3125; KS X 3130; KS X 3126; KS X 3129
<i>Vietnam Radio Test Standards</i>	QCVN 47:2015/BTTTT; QCVN 54:2020/BTTTT; QCVN 55:2011/BTTTT; QCVN 65:2013/BTTTT; QCVN 73:2013/BTTTT; QCVN 74:2020/BTTTT; QCVN 112:2017/BTTTT; QCVN 117:2020//BTTTT
<i>Vietnam EMC Test Standards</i>	QCVN 18:2014/BTTTT; QCVN 86:2019/BTTTT; QCVN 96:2015/BTTTT; QCVN 118:2018/BTTTT
<i>Unlicensed Radio Frequency Devices (3 Meter Semi-Anechoic Room)</i>	47 CFR FCC Part 15C, 15D, 15E, 15F, 15G, 15H (using ANSI C63.10:2013, ANSI C63.17:2013 and FCC KDB 905462 D02 (v02))
<i>Licensed Radio Service Equipment</i>	47 CFR FCC Parts 20, 22, 24, 25, 27, 30, 73, 74, 80, 87, 90, 95, 96, 97, 101 (using ANSI/TIA-603-E, TIA-102.CAAA-E, ANSI C63.26:2015)
<i>OIA (Over the Air) Performance</i> GSM, GPRS, EGPRS UMTS (W-CDMA) LTE including CAT M1 A-GPS for UMTS/GSM LTS A-GPS, A-GLONASS, SIB8/SIB16 Large Device/Laptop/Tablet Testing Integrated Device Testing WiFi 802.11 a/b/g/n/a	CTIA Test Plan for Wireless Device Over-the-Air Performance (Method for Measurement for Radiated Power and Receiver Performance) V3.8.2; CTIA Test Plan for RF Performance Evaluation of WiFi Mobile Converged Devices V2.1.0

Test Technology: Test Method(s)¹:

Electrical Measurements and Simulation

AC Voltage / Current

(1mV to 5kV) 60 Hz
 (0.1V to 250V) up to 500 MHz
 (1µA to 150A) 60 Hz

FAA AC 150/5345-10H;
 FAA AC 150/5345-43J;
 FAA AC 150/5345-44K;
 FAA AC 150/5345-46E;
 FAA AC 150/5345-47C;
 FAA EB 67D

DC Voltage / Current

(1mV to 15 kV) / (1µA to 10A)

Power Factor / Efficiency / Crest Factor

(Power to 30kW)

Resistance

(1mΩ to 4000MΩ)

Surge

(Up to 10 kV / 5 kA) (Combination Wave and Ring Wave)

On the following products and materials:

Telecommunications Terminal Equipment (TTE), Radio Equipment, Network Equipment, Information Technology Equipment (ITE), Automotive Electronic Equipment, Automotive Hybrid Electronic Devices, Maritime Navigation and Radio Communication Equipment and Systems, Vehicles, Boats and Internal Combustion Engine Driven Devices, Automotive, Aviation, and General Lighting Products, Medical Electrical Equipment, Motors, Industrial, Scientific and Medical (ISM) Radio-Frequency Equipment, Household Appliances, Electric Tools, Low-voltage Switchgear and Control gear, Programmable Controllers, Electrical Equipment for Measurement, Control and Laboratory Use, Base Materials, Power and Data Transmission Cables and Connectors

¹ When the date, edition, version, etc. is not identified in the scope of accreditation, laboratories may use the version that immediately precedes the current version for a period of one year from the date of publication of the standard measurement method, per part C., Section 1 of A2LA R101 - *General Requirements- Accreditation of ISO-IEC 17025 Laboratories*.

Testing Activities Performed in Support of FCC Certification in Accordance with 47 Code of Federal Regulations and FCC KDB 974614, Appendix A, Table A.1²

Rule Subpart/Technology	Test Method	Maximum Frequency (MHz)
<u>Unintentional Radiators</u> Part 15B	ANSI C63.4:2014	40000
<u>Industrial, Scientific, and Medical Equipment</u> Part 18	FCC MP-5 (February 1986)	40000
<u>Intentional Radiators</u> Part 15C	ANSI C63.10:2013	40000

(A2LA Cert. No. 1786.01) 08/15/2023



Page 7 of 9

Testing Activities Performed in Support of FCC Certification in Accordance with 47 Code of Federal Regulations and FCC KDB 974614, Appendix A, Table A.1²

Rule Subpart/Technology	Test Method	Maximum Frequency (MHz)
<u>Unlicensed Personal Communication Systems Devices</u>		
Part 15D	ANSI C63.17:2013	40000
<u>U-NII without DFS Intentional Radiators</u>		
Part 15E	ANSI C63.10:2013	40000
<u>U-NII with DFS Intentional Radiators</u>		
Part 15E	FCC KDB 905462 D02 (v02)	40000
<u>UWB Intentional Radiators</u>		
Part 15F	ANSI C63.10:2013	40000
<u>BPL Intentional Radiators</u>		
Part 15G	ANSI C63.10:2013	40000
<u>White Space Device Intentional Radiators</u>		
Part 15H	ANSI C63.10:2013	40000
<u>Commercial Mobile Services (FCC Licensed Radio Service Equipment)</u>		
Parts 22 (cellular), 24, 25 (below 3 GHz), and 27	ANSI/TIA-603-E; TIA-102.CAAA-E; ANSI C63.26:2015	40000
<u>General Mobile Radio Services (FCC Licensed Radio Service Equipment)</u>		
Parts 22 (non-cellular), 90 (below 3 GHz), 95, 97, and 101 (below 3 GHz)	ANSI/TIA-603-E; TIA-102.CAAA-E; ANSI C63.26:2015	40000
<u>Citizens Broadband Radio Services (FCC Licensed Radio Service Equipment)</u>		
Part 96	ANSI/TIA-603-E; TIA-102.CAAA-E; ANSI C63.26:2015	40000
<u>Maritime and Aviation Radio Services</u>		
Parts 80 and 87	ANSI/TIA-603-E; ANSI C63.26:2015	40000
<u>Microwave and Millimeter Bands Radio Services</u>		
Parts 25, 30, 74, 90 (above 3 GHz), 97 (above 3 GHz), and 101	ANSI/TIA-603-E; TIA-102.CAAA-E; ANSI C63.26:2015	40000

(A2LA Cert. No. 1786.01) 08/15/2023



Page 8 of 9

Testing Activities Performed in Support of FCC Certification in Accordance with 47 Code of Federal Regulations and FCC KDB 974614, Appendix A, Table A.1²

Rule Subpart/Technology	Test Method	Maximum Frequency (MHz)
<u>Broadcast Radio Services</u> Parts 73 and 74 (below 3 GHz)	ANSI/TIA-603-E; TIA-102.CAAA-E; ANSI C63.26:2015	40000
<u>Signal Boosters</u> Part 20 (Wideband Consumer Signal Boosters, Provider-specific signal boosters, and Industrial Signal Boosters) Section 90.219	ANSI C63.26:2015	40000

² Accreditation does not imply acceptance to the FCC equipment authorization program. Please see the FCC website (<https://apps.fcc.gov/oetcf/eas/>) for a listing of FCC approved laboratories.



Accredited Laboratory

A2LA has accredited

ELITE ELECTRONIC ENGINEERING INC.

Downers Grove, IL

for technical competence in the field of

Electrical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 *General requirements for the competence of testing and calibration laboratories*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).



Presented this 15th day of August 2023.



Mr. Trace McInturff, Vice President, Accreditation Services
For the Accreditation Council
Certificate Number 1786.01
Valid to June 30, 2025

For the tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.