



TESTING LABORATORY
CERTIFICATE #4820.01



FCC PART 15.247

TEST REPORT

For

IDEAL TECHNOLOGY COMPANY LIMITED

NO.12 Xiangrong Road, Song mu Shan Dalang Town,Dongguan City,
Guangdong, China

FCC ID: 2AUUE-2000

Report Type: Original Report	Product Name: SMART SPEAKER
Report Number:	RDG191009006-00B
Report Date:	2019-12-03
Reviewed By:	Jerry Zhang EMC Manager <i>Jerry Zhang</i>
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
DECLARATIONS.....	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	7
EQUIPMENT MODIFICATIONS	10
SUPPORT CABLE LIST AND DETAILS	10
BLOCK DIAGRAM OF TEST SETUP	11
SUMMARY OF TEST RESULTS	12
FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	13
APPLICABLE STANDARD	13
FCC §15.203 - ANTENNA REQUIREMENT.....	15
APPLICABLE STANDARD	15
ANTENNA CONNECTOR CONSTRUCTION	15
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	16
APPLICABLE STANDARD	16
EUT SETUP	16
EMI TEST RECEIVER SETUP.....	16
TEST PROCEDURE	17
CORRECTED AMPLITUDE & MARGIN CALCULATION	17
TEST EQUIPMENT LIST AND DETAILS.....	17
TEST DATA	18
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	20
APPLICABLE STANDARD	20
EUT SETUP.....	20
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	21
TEST PROCEDURE	21
CORRECTED AMPLITUDE & MARGIN CALCULATION	21
TEST EQUIPMENT LIST AND DETAILS.....	22
TEST DATA	22
FCC §15.247(a) (2)–6 dB EMISSION BANDWIDTH.....	32
APPLICABLE STANDARD	32
TEST PROCEDURE	32
TEST EQUIPMENT LIST AND DETAILS.....	32
TEST DATA	32
FCC §15.247(b) (3) - MAXIMUM PEAK CONDUCTED OUTPUT POWER.....	41
APPLICABLE STANDARD	41
TEST PROCEDURE	41
TEST EQUIPMENT LIST AND DETAILS.....	41

TEST DATA42

FCC §15.247(d)- 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....43

 APPLICABLE STANDARD43

 TEST PROCEDURE43

 TEST EQUIPMENT LIST AND DETAILS.....43

 TEST DATA44

FCC §15.247(e) - POWER SPECTRAL DENSITY50

 APPLICABLE STANDARD50

 TEST PROCEDURE50

 TEST EQUIPMENT LIST AND DETAILS.....50

 TEST DATA50

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Name:	SMART SPEAKER
EUT Model:	IA-2000-001-EN
Multiple Models:	IA-2000-***-EN (“*” indicate blank or digit from 0 to 9 or letter from “A” to “Z”)
Operation Frequency:	2412-2462 MHz(802.11b/g/n ht20), 2422-2452 MHz(802.11 n ht40) 2402-2480MHz(BLE)
Maximum Peak Output Power (Conducted):	23.04 dBm(802.11b/g/n) -2.26 dBm(BLE)
Modulation Type:	DSSS, OFDM(802.11b/g/n) GFSK(BLE)
Rated Input Voltage:	DC 15V from adapter
Adapter Information	Model: IA-5000-001-EN, IA-5000-002-EN
	Input: 100-240Vac
	Output: 15Vdc 1.6A
Serial Number:	RDG191009007-RF-S1
EUT Received Date:	2019.10.9
EUT Received Status:	Good

*Note1: This series products model: IA-2000-001-EN and IA-2000-***-EN (“*” indicate blank or digit from 0 to 9 or letter from “A” to “Z”) are electrically identical. Model IA-2000-001-EN was selected for fully testing and the detailed information can be referred to the declaration.*

Note2: This series adapter model: IA-5000-002-EN and IA-5000-001-EN are electrically identical. Model IA-5000-002-EN was selected for fully testing and the detailed information can be referred to the declaration.

Objective

This report is prepared on behalf of *IDEAL TECHNOLOGY COMPANY LIMITED* in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission’s rules.

The tests were performed in order to determine the compliance of the EUT with FCC Rules Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15C DSS submissions with FCC ID:2AUUE-2000

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices. And 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB,200M~1GHz: 5.92 dB,1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB,18G~26.5G:5.47 dB,26.5G~40G:5.63 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1°C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “△”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA, or any agency of the U.S. Government.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in Engineering Mode, which was provided by the manufacturer.

For 2.4GHz band, total 11 channels are provided:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, and 802.11n ht20 modes were test with channel 1,6,11,for 802.11n ht40 mode were test with channel 3,6,9.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.

For Bluetooth LE mode, 40 channels are provided for testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404
...
...
..	...	38	2478
19	2440	39	2480

EUT was tested with channel 0, 19 and 39.

EUT Exercise Software

The software “Xshell-6.0.0118p” was used for testing, which was provided by manufacturer. The maximum power was configured as below table, that provided by the manufacturer:


Mode	Channel	Frequency (MHz)	Data rate	Power level Setting
802.11 b	Low	2412	1Mbps	47
	Middle	2437	1Mbps	47
	High	2462	1Mbps	47
802.11 g	Low	2412	6Mbps	52
	Middle	2437	6Mbps	52
	High	2462	6Mbps	52
802.11 n20	Low	2412	MCS0	49
	Middle	2437	MCS0	49
	High	2462	MCS0	49
802.11 n40	Low	2422	MCS0	50
	Middle	2437	MCS0	50
	High	2452	MCS0	50

Bluetooth LE mode was configured by the system default setting

The maximum duty cycle as following table:


Test mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)
802.11b	100	100	100
802.11g	1.420	1.434	99.02
802.11n ht20	1.330	1.334	99.70
802.11n ht40	0.666	0.684	97.37
BLE	0.079	0.315	25.08

802.11b




AB
Date: 11.OCT.2019 21:17:56

802.11g



AB
Date: 11.OCT.2019 21:14:35


802.11n ht20



AB

Date: 11.OCT.2019 21:11:36


802.11n ht40



AB

Date: 11.OCT.2019 21:07:42

BLE



Date: 12.OCT.2019 00:24:16


Equipment Modifications

No modification was made to the EUT.

Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From	To
Adapter Cable	No	No	0.8	Adapter	EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC§15.247 (i) & §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Calculated Data:

Modes	Frequency (MHz)	Antenna Gain		Conducted output power including Tune-up Tolerance		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
Bluetooth BDR/EDR	2402-2480	0	1.00	1	1.2589	20.00	0.0003	1.0
Bluetooth LE	2402-2480	0	1.00	-2	0.6310	20.00	0.0001	1.0
Wi-Fi	2412-2462	0	1.00	24	251.19	20.00	0.0500	1.0

The Wi-Fi and Bluetooth can transmit simultaneously:

$$\sum_i \frac{S_i}{S_{Limit,i}}$$

$$= S_{BT}/S_{limit-BT} + S_{Wi-Fi}/S_{limit-Wi-Fi}$$

$$= 0.0003/1 + 0.0500/1$$

$$= 0.0503$$

$$< 1.0$$

Result: The device meet FCC MPE at 20 cm distance

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has two internal antenna arrangement, fulfill the requirement of this section. Please refer to below information and the EUT photos:

Usage	Antenna Type	input impedance (Ohm)	Antenna Gain /Frequency Range
Bluetooth	PCB	50	0 dBi/2.4~2.5GHz
Wi-Fi	FPC	50	0 dBi/2.4~2.5GHz


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207(a).

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main lisn with a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-01	2019-09-05	2020-09-05
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A
R&S	Two-line V-network	ENV 216	101614	2018-12-10	2019-12-10
R&S	EMI Test Receiver	ESPI	100120	2019-05-09	2020-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data

Environmental Conditions

Temperature:	25.9 °C
Relative Humidity:	42%
ATM Pressure:	101.2kPa
Test by:	Sern Xiang
Test Date:	2019-11-27

Test Mode: Transmitting


AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.153015	44.9	9.000	L1	11.1	20.9	65.8
0.159228	43.4	9.000	L1	11.1	22.1	65.5
0.190460	39.9	9.000	L1	10.7	24.1	64.0
0.212491	37.6	9.000	L1	10.5	25.5	63.1
0.216762	38.0	9.000	L1	10.5	24.9	62.9
0.641227	45.1	9.000	L1	9.8	10.9	56.0

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.641227	38.2	9.000	L1	9.8	7.8	46.0
0.954700	28.0	9.000	L1	9.8	18.0	46.0
1.086538	27.4	9.000	L1	9.8	18.6	46.0
1.325783	25.4	9.000	L1	9.8	20.6	46.0
1.751745	25.9	9.000	L1	9.7	20.1	46.0
2.158836	25.5	9.000	L1	9.7	20.5	46.0

AC120 V, 60 Hz, Neutral:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	49.7	9.000	N	11.2	16.3	66.0
0.156091	47.0	9.000	N	11.1	18.7	65.7
0.167350	46.3	9.000	N	10.9	18.8	65.1
0.175887	47.6	9.000	N	10.8	17.1	64.7
0.192365	46.0	9.000	N	10.7	17.9	63.9
0.214615	41.7	9.000	N	10.5	21.3	63.0

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.641227	38.0	9.000	N	9.8	8.0	46.0
0.964247	29.8	9.000	N	9.8	16.2	46.0
2.531405	29.7	9.000	N	9.8	16.3	46.0
2.909785	29.5	9.000	N	9.8	16.5	46.0
3.246355	29.2	9.000	N	9.8	16.8	46.0
4.463546	29.6	9.000	N	9.8	16.4	46.0


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission below 1GHz tests were performed in the 3 meters chamber test site A, above 1GHz tests were performed in the 3 meters chamber test site B, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiation Below 1GHz					
R&S	EMI Test Receiver	ESR3	102453	2019-06-26	2020-06-26
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Sunol Sciences	Antenna	JB3	A060611-1	2017-11-10	2020-11-10
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2019-05-06	2020-05-06
HP	Amplifier	8447D	2727A05902	2019-09-05	2020-09-05
Radiation Above 1GHz					
Agilent	Spectrum Analyzer	E4440A	SG43360054	2019-05-09	2020-05-09
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
ETS-Lindgren	Horn Antenna	3115	000 527 35	2018-10-12	2021-10-12
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2016-11-18	2019-11-18
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2019-11-18	2022-11-18
Unknown	Coaxial Cable	C-SJSJ-50	C-0800-01	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-2.4J2.4J-50	C-0700-02	2019-06-27	2020-06-27
MITEQ	Amplifier	AFS42-00101800- 25-S-42	2001271	2019-09-05	2020-09-05
Mini-Circuit	Amplifier	ZVA-213-S+	54201245	2019-09-05	2020-09-05
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2019-06-27	2020-06-27
E-Microwave	Band-stop Filters	OBSF-2400-2483.5- S	OE01601525	2019-06-16	2020-06-16
Micro-tronics	High Pass Filter	HPM50111	S/N-G217	2019-06-16	2020-06-16

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**


Test Items	Radiation Below 1GHz	Radiation Above 1GHz
Temperature:	24.8°C	21.4°C~27.4°C
Relative Humidity:	44%	45 %~51 %
ATM Pressure:	101.4 kPa	100.1 kPa~100.7 kPa
Tester:	Tyler Pan	Tyler Pan
Test Date:	2019-11-28	2019-10-15~2019-11-27

Test Result: Compliance, please Refer to the following data

Test Mode: Transmitting


1) 30MHz-1GHz(802.11b_High channel was the worst)

Horizontal:



Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
36.7900	32.46	peak	-3.38	29.08	40.00	10.92
112.4500	47.06	QP	-5.80	41.26	43.50	2.24
152.2200	43.65	QP	-5.97	37.68	43.50	5.82
193.9300	42.54	QP	-6.80	35.74	43.50	7.76
323.9100	39.76	peak	-3.37	36.39	46.00	9.61
711.9100	33.62	peak	3.19	36.81	46.00	9.19

Vertical:



Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
33.8800	30.21	QP	-1.29	28.92	40.00	11.08
71.7100	43.21	QP	-11.06	32.15	40.00	7.85
111.4800	46.58	QP	-6.03	40.55	43.50	2.95
152.2200	42.15	QP	-5.97	36.18	43.50	7.32
192.9600	43.54	QP	-6.89	36.65	43.50	6.85
323.9100	38.32	peak	-3.37	34.95	46.00	11.05

**2) 1-25GHz:
802.11b Mode:**

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	74.95	PK	H	28.12	1.81	0.00	104.88	N/A	N/A
2412.00	70.16	AV	H	28.12	1.81	0.00	100.09	N/A	N/A
2412.00	66.23	PK	V	28.12	1.81	0.00	96.16	N/A	N/A
2412.00	62.42	AV	V	28.12	1.81	0.00	92.35	N/A	N/A
2390.00	24.54	PK	H	28.08	1.80	0.00	54.42	74.00	19.58
2390.00	13.58	AV	H	28.08	1.80	0.00	43.46	54.00	10.54
4824.00	40.73	PK	H	32.95	3.19	25.62	51.25	74.00	22.75
4824.00	36.24	AV	H	32.95	3.19	25.62	46.76	54.00	7.24
7236.00	35.42	PK	H	35.81	4.77	25.64	50.36	74.00	23.64
7236.00	23.18	AV	H	35.81	4.77	25.64	38.12	54.00	15.88
Middle Channel: 2437 MHz									
2437.00	74.35	PK	H	28.17	1.82	0.00	104.34	N/A	N/A
2437.00	70.53	AV	H	28.17	1.82	0.00	100.52	N/A	N/A
2437.00	65.28	PK	V	28.17	1.82	0.00	95.27	N/A	N/A
2437.00	61.84	AV	V	28.17	1.82	0.00	91.83	N/A	N/A
4874.00	39.24	PK	H	33.05	3.26	25.65	49.90	74.00	24.10
4874.00	34.52	AV	H	33.05	3.26	25.65	45.18	54.00	8.82
7311.00	35.14	PK	H	36.01	4.64	25.71	50.08	74.00	23.92
7311.00	23.07	AV	H	36.01	4.64	25.71	38.01	54.00	15.99
High Channel: 2462 MHz									
2462.00	73.52	PK	H	28.22	1.83	0.00	103.57	N/A	N/A
2462.00	69.61	AV	H	28.22	1.83	0.00	99.66	N/A	N/A
2462.00	64.37	PK	V	28.22	1.83	0.00	94.42	N/A	N/A
2462.00	60.49	AV	V	28.22	1.83	0.00	90.54	N/A	N/A
2483.50	24.38	PK	H	28.27	1.84	0.00	54.49	74.00	19.51
2483.50	13.79	AV	H	28.27	1.84	0.00	43.90	54.00	10.10
4924.00	39.53	PK	H	33.15	3.27	25.65	50.30	74.00	23.70
4924.00	35.62	AV	H	33.15	3.27	25.65	46.39	54.00	7.61
7386.00	34.88	PK	H	36.20	4.51	25.79	49.80	74.00	24.21
7386.00	22.94	AV	H	36.20	4.51	25.79	37.86	54.00	16.14

802.11g Mode:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	75.11	PK	H	28.12	1.81	0.00	105.04	N/A	N/A
2412.00	66.13	AV	H	28.12	1.81	0.00	96.06	N/A	N/A
2412.00	66.93	PK	V	28.12	1.81	0.00	96.86	N/A	N/A
2412.00	57.51	AV	V	28.12	1.81	0.00	87.44	N/A	N/A
2390.00	37.25	PK	H	28.08	1.80	0.00	67.13	74.00	6.87
2390.00	19.40	AV	H	28.08	1.80	0.00	49.28	54.00	4.72
4824.00	36.12	PK	H	32.95	3.19	25.62	46.64	74.00	27.36
4824.00	28.45	AV	H	32.95	3.19	25.62	38.97	54.00	15.03
7236.00	35.54	PK	H	35.81	4.77	25.64	50.48	74.00	23.52
7236.00	23.50	AV	H	35.81	4.77	25.64	38.44	54.00	15.56
Middle Channel: 2437 MHz									
2437.00	74.42	PK	H	28.17	1.82	0.00	104.41	N/A	N/A
2437.00	65.48	AV	H	28.17	1.82	0.00	95.47	N/A	N/A
2437.00	66.12	PK	V	28.17	1.82	0.00	96.11	N/A	N/A
2437.00	56.84	AV	V	28.17	1.82	0.00	86.83	N/A	N/A
4874.00	35.87	PK	H	33.05	3.26	25.65	46.53	74.00	27.47
4874.00	27.54	AV	H	33.05	3.26	25.65	38.20	54.00	15.80
7311.00	35.12	PK	H	36.01	4.64	25.71	50.06	74.00	23.94
7311.00	23.14	AV	H	36.01	4.64	25.71	38.08	54.00	15.92
High Channel: 2462 MHz									
2462.00	73.70	PK	H	28.22	1.83	0.00	103.75	N/A	N/A
2462.00	65.16	AV	H	28.22	1.83	0.00	95.21	N/A	N/A
2462.00	64.52	PK	V	28.22	1.83	0.00	94.57	N/A	N/A
2462.00	55.78	AV	V	28.22	1.83	0.00	85.83	N/A	N/A
2483.50	36.90	PK	H	28.27	1.84	0.00	67.01	74.00	6.99
2483.50	17.27	AV	H	28.27	1.84	0.00	47.38	54.00	6.62
4924.00	35.12	PK	H	33.15	3.27	25.65	45.89	74.00	28.11
4924.00	26.45	AV	H	33.15	3.27	25.65	37.22	54.00	16.78
7386.00	35.16	PK	H	36.20	4.51	25.79	50.08	74.00	23.92
7386.00	22.54	AV	H	36.20	4.51	25.79	37.46	54.00	16.54

802.11n ht20 Mode:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	73.25	PK	H	28.12	1.81	0.00	103.18	N/A	N/A
2412.00	63.96	AV	H	28.12	1.81	0.00	93.89	N/A	N/A
2412.00	64.87	PK	V	28.12	1.81	0.00	94.80	N/A	N/A
2412.00	55.21	AV	V	28.12	1.81	0.00	85.14	N/A	N/A
2390.00	31.77	PK	H	28.08	1.80	0.00	61.65	74.00	12.35
2390.00	16.47	AV	H	28.08	1.80	0.00	46.35	54.00	7.65
4824.00	36.54	PK	H	32.95	3.19	25.62	47.06	74.00	26.94
4824.00	26.54	AV	H	32.95	3.19	25.62	37.06	54.00	16.94
7236.00	35.40	PK	H	35.81	4.77	25.64	50.34	74.00	23.66
7236.00	23.78	AV	H	35.81	4.77	25.64	38.72	54.00	15.28
Middle Channel: 2437 MHz									
2437.00	72.82	PK	H	28.17	1.82	0.00	102.81	N/A	N/A
2437.00	62.84	AV	H	28.17	1.82	0.00	92.83	N/A	N/A
2437.00	64.12	PK	V	28.17	1.82	0.00	94.11	N/A	N/A
2437.00	54.23	AV	V	28.17	1.82	0.00	84.22	N/A	N/A
4874.00	36.45	PK	H	33.05	3.26	25.65	47.11	74.00	26.89
4874.00	26.07	AV	H	33.05	3.26	25.65	36.73	54.00	17.27
7311.00	35.12	PK	H	36.01	4.64	25.71	50.06	74.00	23.94
7311.00	23.48	AV	H	36.01	4.64	25.71	38.42	54.00	15.58
High Channel: 2462 MHz									
2462.00	72.06	PK	H	28.22	1.83	0.00	102.11	N/A	N/A
2462.00	62.60	AV	H	28.22	1.83	0.00	92.65	N/A	N/A
2462.00	63.28	PK	V	28.22	1.83	0.00	93.33	N/A	N/A
2462.00	53.84	AV	V	28.22	1.83	0.00	83.89	N/A	N/A
2483.50	32.76	PK	H	28.27	1.84	0.00	62.87	74.00	11.13
2483.50	15.82	AV	H	28.27	1.84	0.00	45.93	54.00	8.07
4924.00	35.98	PK	H	33.15	3.27	25.65	46.75	74.00	27.25
4924.00	24.92	AV	H	33.15	3.27	25.65	35.69	54.00	18.31
7386.00	34.84	PK	H	36.20	4.51	25.79	49.76	74.00	24.24
7386.00	23.17	AV	H	36.20	4.51	25.79	38.09	54.00	15.91

802.11n ht40 Mode:




Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2422 MHz									
2422.00	72.14	PK	H	28.14	1.81	0.00	102.09	N/A	N/A
2422.00	62.18	AV	H	28.14	1.81	0.00	92.13	N/A	N/A
2422.00	63.54	PK	V	28.14	1.81	0.00	93.49	N/A	N/A
2422.00	53.39	AV	V	28.14	1.81	0.00	83.34	N/A	N/A
2390.00	35.84	PK	H	28.08	1.80	0.00	65.72	74.00	8.28
2390.00	17.75	AV	H	28.08	1.80	0.00	47.63	54.00	6.37
4844.00	35.61	PK	H	32.99	3.22	25.63	46.19	74.00	27.81
4844.00	23.27	AV	H	32.99	3.22	25.63	33.85	54.00	20.15
7266.00	34.84	PK	H	35.89	4.72	25.67	49.78	74.00	24.22
7266.00	22.80	AV	H	35.89	4.72	25.67	37.74	54.00	16.26
Middle Channel: 2437 MHz									
2437.00	71.35	PK	H	28.17	1.82	0.00	101.34	N/A	N/A
2437.00	61.82	AV	H	28.17	1.82	0.00	91.81	N/A	N/A
2437.00	62.84	PK	V	28.17	1.82	0.00	92.83	N/A	N/A
2437.00	52.87	AV	V	28.17	1.82	0.00	82.86	N/A	N/A
4874.00	35.27	PK	H	33.05	3.26	25.65	45.93	74.00	28.07
4874.00	23.16	AV	H	33.05	3.26	25.65	33.82	54.00	20.18
7311.00	34.54	PK	H	36.01	4.64	25.71	49.48	74.00	24.52
7311.00	22.78	AV	H	36.01	4.64	25.71	37.72	54.00	16.28
High Channel: 2452 MHz									
2452.00	70.52	PK	H	28.20	1.83	0.00	100.55	N/A	N/A
2452.00	61.00	AV	H	28.20	1.83	0.00	91.03	N/A	N/A
2452.00	61.50	PK	V	28.20	1.83	0.00	91.53	N/A	N/A
2452.00	51.80	AV	V	28.20	1.83	0.00	81.83	N/A	N/A
2483.50	36.34	PK	H	28.27	1.84	0.00	66.45	74.00	7.55
2483.50	20.17	AV	H	28.27	1.84	0.00	50.28	54.00	3.72
4904.00	35.16	PK	H	33.11	3.30	25.67	45.90	74.00	28.10
4904.00	22.80	AV	H	33.11	3.30	25.67	33.54	54.00	20.46
7356.00	34.25	PK	H	36.13	4.56	25.76	49.18	74.00	24.82
7356.00	22.58	AV	H	36.13	4.56	25.76	37.51	54.00	16.49

BLE Mode:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2402 MHz									
2402.00	58.36	PK	H	28.10	1.80	0.00	88.26	N/A	N/A
2402.00	57.60	AV	H	28.10	1.80	0.00	87.50	N/A	N/A
2402.00	59.91	PK	V	28.10	1.80	0.00	89.81	N/A	N/A
2402.00	59.23	AV	V	28.10	1.80	0.00	89.13	N/A	N/A
2390.00	26.41	PK	V	28.08	1.80	0.00	56.29	74.00	17.71
2390.00	13.29	AV	V	28.08	1.80	0.00	43.17	54.00	10.83
4804.00	55.07	PK	V	32.91	3.17	37.20	53.95	74.00	20.05
4804.00	53.49	AV	V	32.91	3.17	37.20	52.37	54.00	1.63
7206.00	51.26	PK	V	35.74	4.82	37.23	54.59	74.00	19.41
7206.00	48.35	AV	V	35.74	4.82	37.23	51.68	54.00	2.32
Middle Channel: 2440 MHz									
2440.00	58.09	PK	H	28.18	1.82	0.00	88.09	N/A	N/A
2440.00	57.47	AV	H	28.18	1.82	0.00	87.47	N/A	N/A
2440.00	69.69	PK	V	28.18	1.82	0.00	99.69	N/A	N/A
2440.00	58.70	AV	V	28.18	1.82	0.00	88.70	N/A	N/A
4880.00	55.27	PK	V	33.06	3.27	37.21	54.39	74.00	19.61
4880.00	53.50	AV	V	33.06	3.27	37.21	52.62	54.00	1.38
7320.00	51.67	PK	V	36.03	4.62	37.37	54.95	74.00	19.05
7320.00	47.89	AV	V	36.03	4.62	37.37	51.17	54.00	2.83
High Channel: 2480 MHz									
2480.00	58.96	PK	H	28.26	1.84	0.00	89.06	N/A	N/A
2480.00	58.11	AV	H	28.26	1.84	0.00	88.21	N/A	N/A
2480.00	60.55	PK	V	28.26	1.84	0.00	90.65	N/A	N/A
2480.00	59.67	AV	V	28.26	1.84	0.00	89.77	N/A	N/A
2483.50	26.31	PK	V	28.27	1.84	0.00	56.42	74.00	17.58
2483.50	14.57	AV	V	28.27	1.84	0.00	44.68	54.00	9.32
4960.00	55.63	PK	V	33.22	3.23	37.25	54.83	74.00	19.17
4960.00	53.89	AV	V	33.22	3.23	37.25	53.09	54.00	0.91
7440.00	52.08	PK	V	36.34	4.41	37.52	55.31	74.00	18.69
7440.00	48.54	AV	V	36.34	4.41	37.52	51.77	54.00	2.23




Test plots(BLE High channel was the worst)
Horizontal:

Fundamental
Test with Band
Rejection Filter



Vertical:

Fundamental
Test with Band
Rejection Filter



FCC §15.247(a) (2)–6 dB EMISSION BANDWIDTH


Applicable Standard

According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2019-05-09	2020-05-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/03	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	27.8°C
Relative Humidity:	63%
ATM Pressure:	100.4 kPa
Test by:	Severn Zhu
Test Date:	2019-10-11

Test Mode: Transmitting

Test Result: Compliance. Please refer to the following table and plots.

Test mode	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	10.000	≥ 0.5
	Middle	2437	10.000	≥ 0.5
	High	2462	10.000	≥ 0.5
802.11g	Low	2412	16.560	≥ 0.5
	Middle	2437	16.560	≥ 0.5
	High	2462	16.560	≥ 0.5
802.11n ht20	Low	2412	17.680	≥ 0.5
	Middle	2437	17.520	≥ 0.5
	High	2462	17.440	≥ 0.5
802.11n ht40	Low	2422	35.840	≥ 0.5
	Middle	2437	35.840	≥ 0.5
	High	2452	36.000	≥ 0.5
BLE	Low	2402	0.608	≥ 0.5
	Middle	2440	0.600	≥ 0.5
	High	2480	0.604	≥ 0.5


802.11b Low Channel



AB

Date: 11.OCT.2019 20:28:09


802.11b Middle Channel



AB

Date: 11.OCT.2019 20:30:58


802.11b High Channel



AB

Date: 11.OCT.2019 20:33:55


802.11g Low Channel



AB

Date: 11.OCT.2019 20:37:19


802.11g Middle Channel



AB

Date: 11.OCT.2019 20:39:34


802.11g High Channel



AB

Date: 11.OCT.2019 20:41:23


802.11n ht20 Low Channel



AB


Date: 11.OCT.2019 20:45:28

802.11n ht20 Middle Channel




AB
Date: 11.OCT.2019 20:47:35

802.11n ht20 High Channel



AB
Date: 11.OCT.2019 20:49:50


802.11n ht40 Low Channel



AB

Date: 11.OCT.2019 20:52:35


802.11n ht40 Middle Channel



AB

Date: 11.OCT.2019 20:54:48


802.11n ht40 High Channel



AB


Date: 11.OCT.2019 20:59:27

BLE Low Channel




Date: 11.OCT.2019 21:16:55

BLE Middle Channel



Date: 11.OCT.2019 21:17:54

BLE High Channel



Date: 11.OCT.2019 21:20:28


FCC §15.247(b) (3) - MAXIMUM PEAK CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.
4. Set the power meter to test average output power, record the result as average power.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	USB Wideband Power Sensor	U2021XA	MY5425009	2019-05-09	2020-05-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/03	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	27.8°C
Relative Humidity:	63%
ATM Pressure:	100.4 kPa
Test by:	Severn Zhu
Test Date:	2019-10-11

Test Mode: Transmitting

Test Result: Compliance. Please refer to the following table.

Test mode	Frequency (MHz)	Conducted Peak Output Power (dBm)	Limit (dBm)
802.11b	2412	17.49	30
	2437	17.29	30
	2462	16.91	30
802.11g	2412	22.83	30
	2437	23.04	30
	2462	22.72	30
802.11n ht20	2412	22.15	30
	2437	22.34	30
	2462	22.18	30
802.11n ht40	2422	22.32	30
	2437	22.42	30
	2452	22.34	30
BLE	2402	-2.26	30
	2440	-2.52	30
	2480	-2.39	30

Note: The data above was tested in conducted mode.

FCC §15.247(d)– 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

According to FCC§15.247(d):In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2019-05-09	2020-05-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/03	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data


Environmental Conditions

Temperature:	27.8°C
Relative Humidity:	63%
ATM Pressure:	100.4 kPa
Test by:	Severn Zhu
Test Date:	2019-10-11

Test mode: Transmitting

Test Result: Compliance. Please refer to following plots.


802.11b: Band Edge, Left Side



AB

Date: 11.OCT.2019 20:28:57


802.11b: Band Edge, Right Side



AB

Date: 11.OCT.2019 20:34:42


802.11g: Band Edge, Left Side



AB

Date: 11.OCT.2019 20:38:13


802.11g: Band Edge, Right Side



AB

Date: 11.OCT.2019 20:42:30


802.11n ht20 Band Edge, Left Side



AB


Date: 11.OCT.2019 20:46:30

802.11n ht20 Band Edge, Right Side




AB
Date: 11.OCT.2019 20:50:42

802.11n ht40 Band Edge, Left Side




AB
Date: 11.OCT.2019 20:53:48

802.11n ht40 Band Edge, Right Side




AB
Date: 11.OCT.2019 21:00:39

BLE Band Edge, Left Side



Date: 11.OCT.2019 21:15:17

BLE Band Edge, Right Side



Date: 11.OCT.2019 21:19:44

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set the RBW = 3 kHz, VBW = 10 kHz, Set the span to 1.5 times the DTS bandwidth.
4. Use the peak marker function to determine the maximum amplitude level.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2019-05-09	2020-05-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/03	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	27.8°C
Relative Humidity:	63%
ATM Pressure:	100.4 kPa
Test by:	Severn Zhu
Test Date:	2019-10-11


Test Result: Compliance

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots


Test mode	Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	2412	-7.85	≤8
	2437	-8.31	≤8
	2462	-8.11	≤8
802.11g	2412	-12.58	≤8
	2437	-13.23	≤8
	2462	-13.72	≤8
802.11n ht20	2412	-14.18	≤8
	2437	-14.70	≤8
	2462	-14.89	≤8
802.11n ht40	2422	-15.01	≤8
	2437	-15.19	≤8
	2452	-15.43	≤8
BLE	2402	-19.24	≤8
	2440	-19.53	≤8
	2480	-19.94	≤8

Power Spectral Density, 802.11b Low Channel



AB
 Date: 11.OCT.2019 20:28:44


Power Spectral Density, 802.11b Middle Channel



AB

Date: 11.OCT.2019 20:31:32


Power Spectral Density, 802.11b High Channel



AB

Date: 11.OCT.2019 20:34:29


Power Spectral Density, 802.11g Low Channel



AB

Date: 11.OCT.2019 20:38:00


Power Spectral Density, 802.11g Middle Channel



AB

Date: 11.OCT.2019 20:40:22


Power Spectral Density, 802.11g High Channel



AB

Date: 11.OCT.2019 20:42:14


Power Spectral Density, 802.11n ht20 Low Channel



AB

Date: 11.OCT.2019 20:46:17


Power Spectral Density, 802.11n ht20 Middle Channel



AB

Date: 11.OCT.2019 20:48:25


Power Spectral Density, 802.11n ht20 High Channel



AB

Date: 11.OCT.2019 20:50:29


Power Spectral Density, 802.11n ht40 Low Channel



AB

Date: 11.OCT.2019 20:53:35


Power Spectral Density, 802.11n ht20 Middle Channel



AB

Date: 11.OCT.2019 20:56:07


Power Spectral Density, 802.11n ht20 High Channel



AB


Date: 11.OCT.2019 21:00:26

Power Spectral Density, BLE Low Channel




Date: 11.OCT.2019 21:15:01

Power Spectral Density, BLE Middle Channel



Date: 11.OCT.2019 21:18:18

Power Spectral Density, BLE High Channel



Date: 11.OCT.2019 21:19:28

***** END OF REPORT *****