



Engineering Solutions & Electromagnetic Compatibility Services

**FCC Part 15.249 Certification Application Report**

<b>Test Lab:</b> Rhein Tech Laboratories, Inc. 360 Herndon Parkway Suite 1400 Herndon, VA 20170 E-Mail: atcbinfo@rheintech.com		<b>Applicant:</b> HomeoLux LLC 152 West 57 <sup>th</sup> St. 18 <sup>th</sup> Floor New York, NY 10019	
Tel: 703-689-0368 Fax: 703-689-2056 www.rheintech.com		Tel: 330-389-4206	
<b>FCC ID</b>	2AUWD-40B2019	<b>Test Report Date</b>	October 29, 2019
<b>Model</b>	Base	<b>RTL Work Order #</b>	2019185
<b>American National Standard Institute</b>	ANSI C63.10-2013: American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices		
<b>FCC Classification</b>	DXT – Part 15 Low Power Transceiver		
<b>FCC Rule Part(s)/ Guidance</b>	15.249: Operation within the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5875 MHz, and 24.0-24.25 GHz (10/01/2018)		
<b>Frequency Range (MHz)</b>	<b>Output Power (W)</b>	<b>Frequency Tolerance</b>	<b>Emission Designator</b>
2475	N/A	N/A	N/A

I, the undersigned, hereby declare that the equipment tested and referenced in this report conforms to the identified standard(s) as described in this test report. No modifications were made to the equipment during testing in order to achieve compliance with these standards. Furthermore, there was no deviation from, additions to, or exclusions from, the applicable parts of FCC Part 2, FCC Part 15, RSS-210, RSS-Gen, and ANSI C63.10.

Signature: 

Date: October 29, 2019

Typed/Printed Name: Desmond A. Fraser

Position: President

*This report may not be reproduced, except in full, without the written approval of Rhein Tech Laboratories, Inc. and HomeoLux LLC. The test results relate only to the item(s) tested. This replaces DRAFT R0.2.*

*These test(s) are accredited under Rhein Tech Laboratories, Inc. ISO/IEC 17025 accreditation issued by ANAB. Refer to certificate and scope of accreditation AT-1445.*

---

## Table of Contents

---

1	General Information.....	4
1.1	Scope .....	4
1.2	Description of EUT .....	4
1.3	Test Facility.....	4
1.4	Related Submittal(s)/Grant(s) .....	4
1.5	Modifications .....	4
2	Test Information .....	5
2.1	Description of Test Modes.....	5
2.2	Exercising the EUT.....	5
2.3	Test Result Summary.....	5
2.4	Test System Details .....	5
2.5	Configuration of Tested System.....	6
3	Radiated Emissions – FCC 15.209, 15.249(a) .....	7
3.1.1	Radiated Emissions Measurement Test Procedure.....	7
3.2	Radiated Emissions Test Results .....	8
3.3	Radiated Emissions Harmonics/Spurious Test Data .....	9
4	Conducted AC Emissions – FCC 15.207: Conducted Limits.....	10
4.1	Site and Test Description.....	10
4.2	Test Limits.....	10
4.3	Conducted AC Emissions Simultaneous Transmission Test Data .....	11
5	Conclusion .....	12

---

### Figure Index

---

Figure 2-1: Configuration of System Under Test .....	6
--	---

---

### Table Index

---

Table 2-1: Channels Tested .....	5
Table 2-2: Test Result Summary .....	5
Table 2-3: Equipment Under Test .....	5
Table 3-1: Radiated Emissions Test Equipment.....	8
Table 3-2: Radiated Emissions Test Data .....	8
Table 3-3: Radiated Emissions Harmonics/Spurious – 2475 MHz; Peak .....	9
Table 3-4: Radiated Emissions Harmonics/Spurious – 2475 MHz; Average .....	9
Table 4-1: Conducted Emissions Test Equipment.....	10

---

### Plot Index

---

Plot 4-1: Conducted AC Emissions – Phase .....	11
Plot 4-2: Conducted AC Emissions – Neutral .....	12

---

### Appendix Index

---

Appendix A: FCC Agency Authorization Letter.....	13
Appendix B: FCC Confidentiality Request Letter .....	14
Appendix C: Technical Operational Description.....	15
Appendix D: Schematics.....	16
Appendix E: Block Diagram .....	17
Appendix F: ID Label and Location.....	18
Appendix G: User Manual .....	19
Appendix H: External Photographs .....	20
Appendix I: Internal Photographs .....	21
Appendix J: Test Photographs .....	22

---

### Photograph Index

---

Photograph 1: Radiated Emissions Testing – Front View (Digital Emissions, <1 GHz).....	22
Photograph 2: Radiated Emissions Testing – Back View (Digital Emissions, <1 GHz) .....	23
Photograph 3: Radiated Emissions Testing – Front View (Spurious Emissions, >1 GHz).....	24
Photograph 4: Radiated Emissions Testing – Back View (Spurious Emissions, >1 GHz) .....	25
Photograph 5: Conducted Emissions Testing – Front View .....	26
Photograph 6: Conducted Emissions Testing – Back View.....	27

## 1 General Information

### 1.1 Scope

This is an original FCC certification application request.

Applicable Standards:

FCC Part 15.249: Operation within the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5875 MHz, and 24.0-24.25 GHz

### 1.2 Description of EUT

<b>Equipment Under Test/Model</b>	Base
<b>Power Supply</b>	24 VDC AC adapter
<b>Modulation Type</b>	FSK
<b>Frequency Range</b>	2475 MHz
<b>Antenna Type</b>	Trace

### 1.3 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at 360 Herndon Parkway, Suite 1400, Herndon, Virginia 20170. This site has been fully described in a report and approved by the Federal Communications Commission to perform AC line conducted and radiated emissions testing.

### 1.4 Related Submittal(s)/Grant(s)

None.

### 1.5 Modifications

None.

## 2 Test Information

### 2.1 Description of Test Modes

In accordance with FCC 15.31(m), the following frequencies were tested.

**Table 2-1: Channels Tested**

Frequency (MHz)
2475

### 2.2 Exercising the EUT

The EUT was programmed for continuous transmission at 2475 MHz. The EUT was tested in all three orthogonal planes in order to determine worst-case emissions. The carrier was also checked to verify that information was being transmitted.

### 2.3 Test Result Summary

**Table 2-2: Test Result Summary**

Test	FCC Reference	Pass/Fail or N/A
AC Power Conducted Emissions	15.207	Pass
Radiated Emissions	15.209	Pass
Field Strength of Fundamental and Harmonics	15.249(a)	Pass


### 2.4 Test System Details

The test samples were received on September 11, 2019. The FCC identifiers for all applicable equipment, plus descriptions of all cables used in the tested system, are identified in the following table.

**Table 2-3: Equipment Under Test**

Part	Manufacturer	Model	Serial Number	FCC ID	Cable Description	RTL Bar Code
Base	HomeoLux LLC	Base	B0001	2AUWD-40B2019	N/A	23463
AC Adapter	Tri-Mag, LLC	L6R30-240V1	N/A	N/A	1.4m unshielded	23464

## 2.5 Configuration of Tested System



**Figure 2-1: Configuration of System Under Test**

### 3 Radiated Emissions – FCC 15.209, 15.249(a)

Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009-0.490	2400/f (kHz)	300
0.490-1.705	2400/f (kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

As shown in 15.35(b), for frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any circumstances of modulation.

#### 3.1.1 Radiated Emissions Measurement Test Procedure

Before final measurements of radiated emissions were made on the open-field three/ten meter range, the EUT was scanned indoors at one and three meter distances. This was done in order to determine its emissions spectrum signature. The physical arrangement of the test system and associated cabling was varied in order to determine the effect on the EUT's emissions in amplitude, direction and frequency. This process was repeated during final radiated emissions measurements on the open-field range, at each frequency, in order to ensure that maximum emission amplitudes were attained.

Final radiated emissions measurements were made on the three/ten-meter, open-field test site. The EUT was placed on a nonconductive turntable 0.8 m (< 1 GHz) / 1.5 m (> 1 GHz) above the ground plane. The spectrum was examined from 9 kHz to the 10<sup>th</sup> harmonic of the highest fundamental transmitter frequency (9.16 GHz).

At each frequency, the EUT was rotated 360°, and the antenna was raised and lowered from 1 to 4 meters in order to determine the emission's maximum level. Measurements were taken using both horizontal and vertical antenna polarizations. For frequencies between 30 and 1000 MHz, the spectrum analyzer's 6 dB bandwidth was set to 120 kHz, and the analyzer was operated in the CISPR quasi-peak detection mode. For emissions above 1000 MHz, emissions are measured using the average detector function with a minimum resolution bandwidth of 1 MHz. No video filter less than 10 times the resolution bandwidth was used. The highest emission amplitudes relative to the appropriate limit were measured and recorded in this report.

**Table 3-1: Radiated Emissions Test Equipment**

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
900791	Chase	CBL6112	Antenna (30 MHz – 2 GHz)	2099	10/4/20
900772	EMCO	3161-02	Horn Antenna (2 - 4 GHz)	9804-1044	5/17/21
900321	EMCO	3161-03	Horn Antenna (4 - 8.2 GHz)	9528-1020	5/17/21
900323	EMCO	3160-07	Horn Antenna (8.2 - 12.4 GHz)	9605-1024	5/17/21
900356	EMCO	3160-08	Horn Antenna (12.4 - 18 GHz)	9607-1044	5/17/21
901218	EMCO	3160-09	Horn Antenna (18 - 26.5 GHz)	960281-003	5/5/21
901581	Rohde & Schwarz	FSU	Spectrum Analyzer	1166.1660.50	4/26/21
901729	Insulated Wire Inc.	KPS-1503- 3150-KPR	SMK RF Cables 20'	NA	8/21/20

**3.2 Radiated Emissions Test Results**

**Table 3-2: Radiated Emissions Test Data**

Emission Frequency (MHz)	Detector Type	Analyzer Level (dBuV/m) (1 MHz RBW/ 3 MHz VBW)	Site Correction Factor (dB/m)	Corrected (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2475	Average	59.3	26.8	86.1	94.0	-7.9
2475	Peak	59.8	26.8	86.6	114.0	-27.4

Note: Testing performed at 3m



### 3.3 Radiated Emissions Harmonics/Spurious Test Data

**Table 3-3: Radiated Emissions Harmonics/Spurious – 2475 MHz; Peak**

Emission Frequency (MHz)	Peak Detector (dBuV/m) (1 MHz RBW/ 3 MHz VBW)	Site Correction Factor (dB/m)	Peak Corrected (dBuV/m)	Peak Limit (dBuV/m)	Peak Margin (dB)
4950	30.6	25.1	55.7	74.0	-18.3
7425	25.9	27.8	53.7	74.0	-20.3
9900	14.7	42.3	57.0	74.0	-17.0
12375	26.7	24.2	50.9	74.0	-23.1
14850	14.5	48.5	63.0	74.0	-11.0
17325	5.7	49.5	55.2	74.0	-18.8
19800	27.2	27.2	54.4	74.0	-19.6
22275	26.8	28.5	55.3	74.0	-18.7
24750	6.3	55.8	62.1	74.0	-11.9

**Table 3-4: Radiated Emissions Harmonics/Spurious – 2475 MHz; Average**

Emission Frequency (MHz)	Average Detector (dBuV/m) (1 MHz RBW/ 3 MHz VBW)	Site Correction Factor (dB/m)	Average Corrected (dBuV/m)	Average Limit (dBuV/m)	Average Margin (dB)
4950	26.2	25.1	51.3	54.0	-2.7
7425	14.7	27.8	42.5	54.0	-11.5
9900	4.1	42.3	46.4	54.0	-7.6
12375	15.7	24.2	39.9	54.0	-14.1
14850	-6.1	48.5	42.4	54.0	-11.6
17325	-5.1	49.5	44.4	54.0	-9.6
19800	15.9	27.2	43.1	54.0	-10.9
22275	16.2	28.5	44.7	54.0	-9.3
24750	-4.7	55.8	51.1	54.0	-2.9

Note: Testing performed at 3m

Measurement uncertainty: Measurement uncertainties shown for these tests are expanded uncertainties expressed at 95% confidence level using a coverage factor k = 2. ±4.6 dB

**Result: Pass**

**Test Personnel**

Daniel W. Baltzell  
 Test Engineer



Signature

October 24, 2019  
 Date of Test

#### 4 Conducted AC Emissions – FCC 15.207: Conducted Limits

##### 4.1 Site and Test Description

The power line conducted emissions measurements were performed in a Series 81 type shielded enclosure manufactured by Ray-proof. The EUT was assembled on a wooden table 80 centimeters high. Power was fed to the EUT through a 50-ohm/50 micro-henry Line Impedance Stabilization Network (LISN). The EUT LISN was fed power through an A.C. filter box on the outside of the shielded enclosure. The filter box and EUT LISN housing are bonded to the ground plane of the shielded enclosure. A second LISN, the peripheral LISN, provides isolation for the EUT test peripherals. This peripheral LISN was also fed A.C. power. A metal power outlet box, which is bonded to the ground plane and electrically connected to the peripheral LISN, powers the EUT host peripherals.

The spectrum analyzer was connected to the AC line through an isolation transformer. The 50-ohm output of the EUT LISN was connected to the spectrum analyzer input through a Solar 100 kHz high-pass filter. The filter is used to prevent overload of the spectrum analyzer from noise below 100 kHz. Conducted emission levels were measured on each current-carrying line with the spectrum analyzer operating in the CISPR quasi-peak mode (or peak mode, if applicable).

The analyzer's 6 dB bandwidth was set to 9 kHz. Video filter less than 10 times the resolution bandwidth is not used. Average measurements are performed in linear mode using a 10 kHz resolution bandwidth, a 1 Hz video bandwidth, and by increasing the sweep time in order to obtain a calibrated measurement. The emission spectrum was scanned from 150 kHz to 30 MHz. The highest emission amplitudes relative to the appropriate limits were measured and have been recorded.

##### 4.2 Test Limits


Line-Conducted Emissions		
Limit (dB $\mu$ V)		
Frequency (MHz)	Quasi-Peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5.00	56	46
5.00 to 30.00	60	50

Table 4-1: Conducted Emissions Test Equipment


RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
901581	Rohde and Schwarz	FSU	Spectrum Analyzer (20 Hz - 50 GHz)	200106	4/26/21
900728	Solar	8130	Filter	947306	4/24/20
901084	AFJ International	LS16	16A LISN	16010020082	4/18/22

### 4.3 Conducted AC Emissions Simultaneous Transmission Test Data

Plot 4-1: Conducted AC Emissions – Phase



**Plot 4-2: Conducted AC Emissions – Neutral**



Measurement uncertainty: Measurement uncertainties shown for these tests are expanded uncertainties expressed at 95% confidence level using a coverage factor  $k = 2$ .  $\pm 3.6$  dB

**Result: Pass**

Daniel W. Baltzell  
Test Engineer

Signature

October 23, 2019  
Date of Test

**5 Conclusion**

The data in this measurement report shows that the EUT as tested, HomeoLux LLC Base, FCC ID: 2AUWD-40B2019, complies with the applicable requirements of Parts 2 and 15 of the FCC Rules and Regulations.