

## RF EXPOSURE EVALUATION

### EUT Specification

<b>EUT</b>	Beacon40 Base
<b>Model Number</b>	BYA1000001
<b>FCC ID</b>	2AUWDBYA1000001
<b>Antenna gain (Max)</b>	0dBi
<b>Operation Frequency</b>	2.4G:2408MHz-2480MHz WIFI:2412MHz-2462MHz
<b>Input Rating</b>	AC 120V 60Hz
<b>Classification Per Stipulated Test Standard</b>	§15.247(i), §2.1093
<b>Modulation</b>	2.4G:GFSK DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
<b>Max. output power</b>	16.34 dBm(0.043053W)
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

### Test Requirement:

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

## 1 Friis transmission formula: $P_d = \frac{P_{out} \cdot G}{4 \cdot \pi \cdot R^2}$

Where

$P_d$  = Power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = Numeric gain of the antenna relative to isotropic antenna

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## 2 Measurement Result

Antenna gain: 0 dBi

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm)	Limit (dBm)	Verdict
802.11b	1	2412	16.32	30	PASS
	6	2437	16.27	30	PASS
	11	2462	16.34	30	PASS
802.11g	1	2412	14.64	30	PASS
	6	2437	14.71	30	PASS
	11	2462	14.59	30	PASS
802.11n (HT20)	1	2412	14.17	30	PASS
	6	2437	14.15	30	PASS
	11	2462	14.12	30	PASS
802.11n (HT40)	3	2422	13.71	30	PASS
	6	2437	13.75	30	PASS
	9	2452	13.74	30	PASS

Operating Mode	Test Channel	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
802.11b	1	16±1	17	50.119	0	1.000	0.009971	1
	6	16±1	17	50.119	0	1.000	0.009971	1
	11	16±1	17	50.119	0	1.000	0.009971	1
802.11g	1	14±1	15	31.623	0	1.000	0.006291	1
	6	14±1	15	31.623	0	1.000	0.006291	1
	11	14±1	15	31.623	0	1.000	0.006291	1
802.11n	1	14±1	15	31.623	0	1.000	0.006291	1
	6	14±1	15	31.623	0	1.000	0.006291	1
	11	14±1	15	31.623	0	1.000	0.006291	1
802.11n	3	13±1	14	25.119	0	1.000	0.004997	1
	6	13±1	14	25.119	0	1.000	0.004997	1
	9	13±1	14	25.119	0	1.000	0.004997	1

Signature:



Sam Lv

Date: 2021-03-26