



# FCC RADIO TEST REPORT

**FCC ID** : 2AUWW-HALOWA1B  
**Equipment** : Halo Collar  
**Brand Name** : Halo  
**Model Name** : Halo Three  
**Applicant** : Protect Animals with Satellites, LLC  
5465 Legacy Dr., Suite 650, Plano, Texas  
75024, United States  
**Manufacturer** : RoyalTek Company Ltd.,  
8F, No.40, Wenhua 2nd Rd., Guishan Dist.,  
Taoyuan City 333010, Taiwan(R.O.C.)  
**Standard** : FCC Part 15 Subpart C §15.247

The product was received on Sep. 02, 2022 and testing was performed from Dec. 30, 2022 to Jan. 20, 2023. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

*Louis Wu*

Approved by: Louis Wu

**Sporton International Inc. Wensan Laboratory**

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



## Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
<b>1 General Description.....</b>	<b>5</b>
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT .....	5
1.3 Testing Location .....	5
1.4 Applicable Standards.....	6
<b>2 Test Configuration of Equipment Under Test .....</b>	<b>7</b>
2.1 Carrier Frequency Channel .....	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system .....	9
2.5 EUT Operation Test Setup .....	10
2.6 Measurement Results Explanation Example.....	10
<b>3 Test Result.....</b>	<b>11</b>
3.1 6dB and 99% Bandwidth Measurement .....	11
3.2 Output Power Measurement.....	16
3.3 Power Spectral Density Measurement .....	17
3.4 Conducted Band Edges and Spurious Emission Measurement .....	22
3.5 Radiated Band Edges and Spurious Emission Measurement .....	28
3.6 AC Conducted Emission Measurement.....	32
3.7 Antenna Requirements .....	34
<b>4 List of Measuring Equipment .....</b>	<b>35</b>
<b>5 Uncertainty of Evaluation.....</b>	<b>37</b>
<b>Appendix A. Conducted Test Results</b>	
<b>Appendix B. AC Conducted Emission Test Result</b>	
<b>Appendix C. Radiated Spurious Emission</b>	
<b>Appendix D. Radiated Spurious Emission Plots</b>	
<b>Appendix E. Duty Cycle Plots</b>	
<b>Appendix F. Setup Photographs</b>	





## Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)(3) 15.247(b)(4)	Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	0.29 dB under the limit at 4804.000 MHz
3.6	15.207	AC Conducted Emission	Pass	21.27 dB under the limit at 1.682 MHz
3.7	15.203	Antenna Requirement	Pass	-

**Declaration of Conformity:**

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.  
It's means measurement values may risk exceeding the limit of regulation standards, if measurement uncertainty is include in test results.
2. The measurement uncertainty please refer to report "Uncertainty of Evaluation".

**Comments and Explanations:**

The product specifications of the EUT presented in the report are declared by the manufacturer who shall take full responsibility for the authenticity.

**Reviewed by: Avis Chuang**

**Report Producer: Ruby Zou**



# 1 General Description

## 1.1 Product Feature of Equipment Under Test

LTE M1, Bluetooth-LE, Wi-Fi 2.4GHz 802.11b/g/n and GNSS.

Product Feature	
Antenna Type	WWAN: Loop Antenna WLAN: Chip Antenna Bluetooth-LE: Chip Antenna BDS / Galileo / GPS / Glonass: linear polarization Antenna

Antenna information		
2402 MHz ~ 2480 MHz	Peak Gain (dBi)	0.5

Remark: The EUT's information above is declared by manufacturer. Please refer to Comments and Explanations in report summary.

## 1.2 Modification of EUT

No modifications made to the EUT during the testing.

## 1.3 Testing Location

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	<b>Sporton Site No.</b> CO05-HY (TAF Code: 1190)
Remark	The AC Conducted Emission test item subcontracted to Sporton International Inc. EMC & Wireless Communications Laboratory

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	<b>Sporton Site No.</b> TH05-HY, 03CH11-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW3786



## **1.4 Applicable Standards**

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

**Remark:**

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
20	2442	-	-	



## 2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
<b>Conducted Test Cases</b>	<b>Bluetooth – LE / GFSK</b>
	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps
	Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
<b>Radiated Test Cases</b>	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps
	Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
<b>AC Conducted Emission</b>	Mode 1: LTE Cat M1 Band 5 Idle + Bluetooth Link + WLAN (2.4GHz) Link + Speaker + USB Cable (Charging from Adapter)
<b>Remark:</b> For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.	



### 2.3 Connection Diagram of Test System



### 2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8m
3.	Notebook	Dell	Latitude 3420	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Notebook	Lenovo	IdeaPad Gaming	PD9AX201NG	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	Mobile Phone	ASUS	ASUS_X00QD	N/A	N/A	N/A
6.	Adapter	Google	G9BR1	N/A	N/A	N/A
7.	Adapter	XIAOMI	MDY-03EB	N/A	N/A	N/A



## 2.5 EUT Operation Test Setup

The RF test items, utility “SSCOM3.2” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

### 3 Test Result

#### 3.1 6dB and 99% Bandwidth Measurement

##### 3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

##### 3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

##### 3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW)  $\geq 3 * RBW$ .
6. Measure and record the results in the test report.

##### 3.1.4 Test Setup






### 3.1.5 Test Result of 6dB Bandwidth


Please refer to Appendix A.

<1Mbps>





<2Mbps>






### 3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.


<1Mbps>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



<2Mbps>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

## 3.2 Output Power Measurement

### 3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna of directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


### 3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

### 3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT is connected to the power meter by RF cable and attenuator.
3. The path loss is compensated to the results for each measurement.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Measure the conducted output power and record the results in the test report.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Average Output Power

Please refer to Appendix A.



### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.


#### 3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

#### 3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth (VBW) = 10 kHz. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6 dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100 kHz is a reference level and is used as 20 dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

#### 3.3.4 Test Setup




#### 3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.




### 3.3.6 Test Result of Power Spectral Density Plots (100kHz)

<1Mbps>






<2Mbps>






### 3.3.7 Test Result of Power Spectral Density Plots (3kHz)

<1Mbps>





<2Mbps>



## 3.4 Conducted Band Edges and Spurious Emission Measurement

### 3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 30 dB down from the highest emission level within the authorized band.


### 3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

### 3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


### 3.4.4 Test Setup






### 3.4.5 Test Result of Conducted Band Edges Plots

<1Mbps>




<2Mbps>






### 3.4.6 Test Result of Conducted Spurious Emission Plots

<1Mbps>











<2Mbps>







### 3.5 Radiated Band Edges and Spurious Emission Measurement

#### 3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device is measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.




### 3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-“.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-“.
8. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW = 100 kHz for  $f < 1$  GHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold;
  - (3) Set RBW = 1 MHz, VBW = 3 MHz for  $f \geq 1$  GHz for peak measurement.  
For average measurement:
    - VBW = 10 Hz, when duty cycle is no less than 98 percent.
    - VBW  $\geq 1/T$ , when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

### 3.5.4 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



### 3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

### 3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

### 3.5.7 Duty Cycle

Please refer to Appendix E.

### 3.5.8 Test Result of Radiated Spurious Emission (30 MHz ~ 10th Harmonic)

Please refer to Appendix C and D.



### 3.6 AC Conducted Emission Measurement

#### 3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

#### 3.6.2 Measuring Instruments


Please refer to the measuring equipment list in this test report.

#### 3.6.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.



### 3.6.4 Test Setup



### 3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



## **3.7 Antenna Requirements**

### **3.7.1 Standard Applicable**

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### **3.7.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.



## 4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
LOOP Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Sep. 20, 2022	Jan. 11, 2023~Jan. 13, 2023	Sep. 19, 2023	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D & N-6-06	35414 & AT-N0602	30MHz~1GHz	Oct. 08, 2022	Jan. 11, 2023~Jan. 13, 2023	Oct. 07, 2023	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1212	1GHz ~ 18GHz	Mar. 10, 2022	Jan. 11, 2023~Jan. 13, 2023	Mar. 09, 2023	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170584	18GHz~40GHz	Dec. 14, 2022	Jan. 11, 2023~Jan. 13, 2023	Dec. 13, 2023	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Dec. 09, 2022	Jan. 11, 2023~Jan. 13, 2023	Dec. 08, 2023	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY53270080	1GHz~26.5GHz	Nov. 09, 2022	Jan. 11, 2023~Jan. 13, 2023	Nov. 08, 2023	Radiation (03CH11-HY)
Preamplifier	Jet-Power	JPA0118-55-303	17100018000 55007	1GHz~18GHz	Jun. 15, 2022	Jan. 11, 2023~Jan. 13, 2023	Jun. 14, 2023	Radiation (03CH11-HY)
Preamplifier	EMEC	EM18G40G	060801	18GHz~40GHz	Jun. 28, 2022	Jan. 11, 2023~Jan. 13, 2023	Jun. 27, 2023	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200486	10Hz~44GHz	Oct. 07, 2022	Jan. 11, 2023~Jan. 13, 2023	Oct. 06, 2023	Radiation (03CH11-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY54130085	20MHz~8.4GHz	Oct. 18, 2022	Jan. 11, 2023~Jan. 13, 2023	Oct. 17, 2023	Radiation (03CH11-HY)
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	Jan. 11, 2023~Jan. 13, 2023	N/A	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Jan. 11, 2023~Jan. 13, 2023	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Jan. 11, 2023~Jan. 13, 2023	N/A	Radiation (03CH11-HY)
Software	Audix	E3 6.2009-8-24	RK-001053	N/A	N/A	Jan. 11, 2023~Jan. 13, 2023	N/A	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2859/2	30MHz-40GHz	Mar. 10, 2022	Jan. 11, 2023~Jan. 13, 2023	Mar. 09, 2023	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4PE	9kHz-30MHz	Mar. 10, 2022	Jan. 11, 2023~Jan. 13, 2023	Mar. 09, 2023	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4PE	30MHz-18GHz	Mar. 10, 2022	Jan. 11, 2023~Jan. 13, 2023	Mar. 09, 2023	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	811852/4	30MHz-18GHz	Mar. 10, 2022	Jan. 11, 2023~Jan. 13, 2023	Mar. 09, 2023	Radiation (03CH11-HY)
Filter	Wainwright	WLK4-1000-153 0-8000-40SS	SN11	1.53G Low Pass	Sep. 12, 2022	Jan. 11, 2023~Jan. 13, 2023	Sep. 11, 2023	Radiation (03CH11-HY)
Filter	Wainwright	WHKX12-2700-3 000-18000-60SS	SN3	3GHz High Pass Filter	Sep. 12, 2022	Jan. 11, 2023~Jan. 13, 2023	Sep. 11, 2023	Radiation (03CH11-HY)
Hygrometer	TECPEL	DTM-303B	TP140325	N/A	Nov. 07, 2022	Jan. 11, 2023~Jan. 13, 2023	Nov. 06, 2023	Radiation (03CH11-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jan. 11, 2023	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Dec. 01, 2022	Jan. 11, 2023	Nov. 30, 2023	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Nov. 17, 2022	Jan. 11, 2023	Nov. 16, 2023	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 17, 2022	Jan. 11, 2023	Nov. 16, 2023	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32	N/A	N/A	N/A	Jan. 11, 2023	N/A	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	00691	N/A	Aug. 01, 2022	Jan. 11, 2023	Jul. 31, 2023	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	260260	N/A	Dec. 29, 2022	Jan. 11, 2023	Dec. 28, 2023	Conduction (CO05-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 17, 2022	Dec. 30, 2022~Jan. 20, 2023	Nov. 16, 2023	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	16I00054SNO12 (NO:113)	10MHz~6GHz	Dec. 13, 2022	Dec. 30, 2022~Jan. 20, 2023	Dec. 12, 2023	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101905	10Hz - 40GHz(amp)	Aug. 03, 2022	Dec. 30, 2022~Jan. 20, 2023	Aug. 02, 2023	Conducted (TH05-HY)



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	3.5 dB
---	--------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	6.3 dB
---	--------

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.4 dB
---	--------

### Uncertainty of Radiated Emission Measurement (6000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.8 dB
---	--------

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.3 dB
---	--------

**Appendix A. Test Result of Conducted Test Items**

Test Engineer:	Benny Ku	Temperature:	21~25	°C
Test Date:	2022/12/30~2023/1/20	Relative Humidity:	51~54	%

**TEST RESULTS DATA**  
**6dB and 99% Occupied Bandwidth**

Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.193	0.716	0.50	Pass
BLE	1Mbps	1	19	2440	1.191	0.728	0.50	Pass
BLE	1Mbps	1	39	2480	1.191	0.746	0.50	Pass

**TEST RESULTS DATA**  
**Average Power Table**

Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	8.90	30.00	0.50	9.40	36.00	Pass
BLE	1Mbps	1	19	2440	10.60	30.00	0.50	11.10	36.00	Pass
BLE	1Mbps	1	39	2480	16.90	30.00	0.50	17.40	36.00	Pass

**TEST RESULTS DATA**  
**Peak Power Density**

Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	9.00	-3.68	0.50	8.00	Pass
BLE	1Mbps	1	19	2440	10.40	-2.18	0.50	8.00	Pass
BLE	1Mbps	1	39	2480	16.34	3.79	0.50	8.00	Pass

**Note:** PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

**TEST RESULTS DATA**  
**6dB and 99% Occupied Bandwidth**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	2Mbps	1	0	2402	2.402	1.332	0.50	Pass
BLE	2Mbps	1	19	2440	2.398	1.340	0.50	Pass
BLE	2Mbps	1	39	2480	2.394	1.399	0.50	Pass

**TEST RESULTS DATA**  
**Average Power Table**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	0	2402	9.60	30.00	0.50	10.10	36.00	Pass
BLE	2Mbps	1	19	2440	10.60	30.00	0.50	11.10	36.00	Pass
BLE	2Mbps	1	39	2480	10.80	30.00	0.50	11.30	36.00	Pass

**TEST RESULTS DATA**  
**Peak Power Density**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	2Mbps	1	0	2402	8.47	-6.71	0.50	8.00	Pass
BLE	2Mbps	1	19	2440	9.32	-5.90	0.50	8.00	Pass
BLE	2Mbps	1	39	2480	9.36	-5.92	0.50	8.00	Pass

**Note:** PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.



## Appendix B. AC Conducted Emission Test Results


Test Engineer :	Calvin Wang	Temperature :	23~26°C
		Relative Humidity :	45~55%



## EUT Information

Report NO : 901415-05  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Line

Full Spectrum




## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	28.55	55.88	27.33	L1	OFF	19.9
0.152250	33.63	---	65.88	32.25	L1	OFF	19.9
0.235500	---	24.75	52.25	27.50	L1	OFF	19.9
0.235500	28.15	---	62.25	34.10	L1	OFF	19.9
0.728250	---	23.79	46.00	22.21	L1	OFF	19.9
0.728250	26.43	---	56.00	29.57	L1	OFF	19.9
1.158000	---	23.91	46.00	22.09	L1	OFF	19.9
1.158000	26.96	---	56.00	29.04	L1	OFF	19.9
1.682250	---	24.73	46.00	21.27	L1	OFF	19.9
1.682250	27.27	---	56.00	28.73	L1	OFF	19.9
7.849500	---	25.66	50.00	24.34	L1	OFF	20.1
7.849500	27.00	---	60.00	33.00	L1	OFF	20.1

# EUT Information

Report NO : 901415-05  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Neutral

Full Spectrum



## Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.170250	---	26.72	54.95	28.23	N	OFF	19.9
0.170250	32.63	---	64.95	32.32	N	OFF	19.9
0.431250	---	24.03	47.23	23.20	N	OFF	19.9
0.431250	27.34	---	57.23	29.89	N	OFF	19.9
0.465000	---	24.11	46.60	22.49	N	OFF	19.9
0.465000	27.22	---	56.60	29.38	N	OFF	19.9
1.437000	---	23.73	46.00	22.27	N	OFF	19.9
1.437000	25.61	---	56.00	30.39	N	OFF	19.9
6.211500	---	25.71	50.00	24.29	N	OFF	20.1
6.211500	27.18	---	60.00	32.82	N	OFF	20.1
11.865750	---	25.57	50.00	24.43	N	OFF	20.3
11.865750	27.19	---	60.00	32.81	N	OFF	20.3



### Appendix C. Radiated Spurious Emission

Test Engineer :	Yuan Lee, Bank Lin and Troye Hsieh	Temperature :	21.8~23.7°C
		Relative Humidity :	53.5~66.9%

<1Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency ( MHz )	Level ( dBµV/m )	Margin ( dB )	Limit Line ( dBµV/m )	Read Level ( dBµV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
BLE CH 00 2402MHz		2361.975	52.91	-21.09	74	42.52	27.35	17.25	34.21	300	327	P	H	
		2361.87	43.96	-10.04	54	33.57	27.35	17.25	34.21	300	327	A	H	
	*	2402	100.92	-	-	90.31	27.51	17.3	34.2	300	327	P	H	
	*	2402	99.93	-	-	89.32	27.51	17.3	34.2	300	327	A	H	
													H	
			2311.155	51.82	-22.18	74	41.57	27.3	17.18	34.23	250	311	P	V
			2361.87	42.5	-11.5	54	32.11	27.35	17.25	34.21	250	311	A	V
	*		2402	97.12	-	-	86.51	27.51	17.3	34.2	250	311	P	V
	*		2402	96.08	-	-	85.47	27.51	17.3	34.2	250	311	A	V
														V
BLE CH 19 2440MHz		2381.04	52.12	-21.88	74	41.63	27.42	17.28	34.21	250	322	P	H	
		2390	41.6	-12.4	54	31.05	27.46	17.29	34.2	250	322	A	H	
	*	2440	105.04	-	-	94.2	27.66	17.36	34.18	250	322	P	H	
	*	2440	103.97	-	-	93.13	27.66	17.36	34.18	250	322	A	H	
			2493.12	53.59	-20.41	74	42.52	27.79	17.44	34.16	250	322	P	H
			2489.36	42.54	-11.46	54	31.49	27.78	17.43	34.16	250	322	A	H
			2354.64	52.78	-21.22	74	42.44	27.32	17.24	34.22	100	94	P	V
			2378.32	41.52	-12.48	54	31.05	27.41	17.27	34.21	100	94	A	V
	*		2440	100.73	-	-	89.89	27.66	17.36	34.18	100	94	P	V
	*		2440	99.73	-	-	88.89	27.66	17.36	34.18	100	94	A	V
			2497.2	52.35	-21.65	74	41.27	27.79	17.45	34.16	100	94	P	V
			2499.2	42.38	-11.62	54	31.29	27.8	17.45	34.16	100	94	A	V



<b>BLE CH 39 2480MHz</b>	*	2480	112.86	-	-	101.85	27.76	17.42	34.17	309	326	P	H
	*	2480	111.77	-	-	100.76	27.76	17.42	34.17	309	326	A	H
		2483.6	64.98	-9.02	74	53.95	27.77	17.43	34.17	309	326	P	H
		2493.32	53.47	-0.53	54	42.4	27.79	17.44	34.16	309	326	A	H
													H
													H
	*	2480	108.33	-	-	97.32	27.76	17.42	34.17	200	316	P	V
	*	2480	107.22	-	-	96.21	27.76	17.42	34.17	200	316	A	V
		2483.8	59.19	-14.81	74	48.16	27.77	17.43	34.17	200	316	P	V
		2493.28	49.58	-4.42	54	38.51	27.79	17.44	34.16	200	316	A	V
													V
													V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz  
BLE (Harmonic @ 3m)

BLE	Note	Frequency ( MHz )	Level ( dBμV/m )	Margin ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
BLE CH 00 2402MHz		4804	56.31	-17.69	74	70.65	32.22	11.38	57.94	245	339	P	H	
		4804	53.21	-0.79	54	67.55	32.22	11.38	57.94	245	339	A	H	
													H	
													H	
													H	
													H	
			4804	55.39	-18.61	74	69.73	32.22	11.38	57.94	317	218	P	V
			4804	52.21	-1.79	54	66.55	32.22	11.38	57.94	317	218	A	V
														V
														V
														V
	BLE CH 19 2440MHz		4880	54.76	-19.24	74	68.49	32.62	11.65	58	398	326	P	H
		4880	51.21	-2.79	54	64.94	32.62	11.65	58	398	326	A	H	
		7320	48.79	-25.21	74	57.15	37.02	13.35	58.73	208	118	P	H	
		7320	41.77	-12.23	54	50.13	37.02	13.35	58.73	208	118	A	H	
													H	
													H	
			4880	56.49	-17.51	74	70.22	32.62	11.65	58	400	315	P	V
			4880	53.02	-0.98	54	66.75	32.62	11.65	58	400	315	A	V
			7320	49.37	-24.63	74	57.73	37.02	13.35	58.73	396	19	P	V
			7320	42.68	-11.32	54	51.04	37.02	13.35	58.73	396	19	A	V
														V
														V



BLE	Note	Frequency ( MHz )	Level ( dBµV/m )	Margin ( dB )	Limit Line ( dBµV/m )	Read Level ( dBµV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
BLE CH 39 2480MHz		4960	56.08	-17.92	74	69.2	33.02	11.92	58.06	100	293	P	H	
		4960	52.69	-1.31	54	65.81	33.02	11.92	58.06	100	293	A	H	
		7440	57.53	-16.47	74	66.05	36.44	13.75	58.71	208	77	P	H	
		7440	53.13	-0.87	54	61.65	36.44	13.75	58.71	208	77	A	H	
		9920	51.48	-22.52	92.86	56.55	38.34	16.15	59.56	100	81	P	H	
														H
			4960	56.81	-17.19	74	69.93	33.02	11.92	58.06	197	153	P	V
			4960	53.66	-0.34	54	66.78	33.02	11.92	58.06	197	153	A	V
			7440	56.22	-17.78	74	64.74	36.44	13.75	58.71	400	269	P	V
			7440	51.35	-2.65	54	59.87	36.44	13.75	58.71	400	269	A	V
			9920	49.55	-24.45	88.33	54.62	38.34	16.15	59.56	201	240	P	V
														V
<b>Remark</b>	<ol style="list-style-type: none"> <li>No other spurious found.</li> <li>All results are PASS against Peak and Average limit line.</li> </ol>													



<2Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Margin	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )	
BLE CH 00 2402MHz		2370.27	52.85	-21.15	74	42.42	27.38	17.26	34.21	294	327	P	H	
		2361.66	43.17	-10.83	54	32.78	27.35	17.25	34.21	294	327	A	H	
	*	2402	101.68	-	-	91.07	27.51	17.3	34.2	294	327	P	H	
	*	2402	99.53	-	-	88.92	27.51	17.3	34.2	294	327	A	H	
													H	
													H	
			2346.54	51.71	-22.29	74	41.4	27.3	17.23	34.22	228	315	P	V
			2362.08	42.34	-11.66	54	31.95	27.35	17.25	34.21	228	315	A	V
	*		2402	97.13	-	-	86.52	27.51	17.3	34.2	228	315	P	V
	*		2402	94.86	-	-	84.25	27.51	17.3	34.2	228	315	A	V
													V	
												V		
BLE CH 19 2440MHz		2384.24	52.55	-21.45	74	42.03	27.44	17.28	34.2	284	329	P	H	
		2387.28	42.02	-11.98	54	31.49	27.45	17.28	34.2	284	329	A	H	
	*	2440	105.87	-	-	95.03	27.66	17.36	34.18	284	329	P	H	
	*	2440	103.74	-	-	92.9	27.66	17.36	34.18	284	329	A	H	
			2491.36	53.6	-20.4	74	42.54	27.78	17.44	34.16	284	329	P	H
			2495.04	42.83	-11.17	54	31.76	27.79	17.44	34.16	284	329	A	H
			2333.68	51.86	-22.14	74	41.57	27.3	17.21	34.22	224	306	P	V
			2381.04	41.8	-12.2	54	31.31	27.42	17.28	34.21	224	306	A	V
	*		2440	100.24	-	-	89.4	27.66	17.36	34.18	224	306	P	V
	*		2440	98.03	-	-	87.19	27.66	17.36	34.18	224	306	A	V
			2494.4	51.92	-22.08	74	40.85	27.79	17.44	34.16	224	306	P	V
		2486.4	42.52	-11.48	54	31.49	27.77	17.43	34.17	224	306	A	V	



<b>BLE CH 39 2480MHz</b>	*	2480	106.44	-	-	95.43	27.76	17.42	34.17	245	321	P	H
	*	2480	104.18	-	-	93.17	27.76	17.42	34.17	245	321	A	H
		2483.56	64.47	-9.53	74	53.44	27.77	17.43	34.17	245	321	P	H
		2483.52	53.18	-0.82	54	42.15	27.77	17.43	34.17	245	321	A	H
													H
													H
	*	2480	103.49	-	-	92.48	27.76	17.42	34.17	178	312	P	V
	*	2480	101.34	-	-	90.33	27.76	17.42	34.17	178	312	A	V
		2483.52	61.87	-12.13	74	50.84	27.77	17.43	34.17	178	312	P	V
		2483.52	50.84	-3.16	54	39.81	27.77	17.43	34.17	178	312	A	V
													V
													V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												





2.4GHz 2400~2483.5MHz  
BLE (Harmonic @ 3m)

BLE	Note	Frequency ( MHz )	Level ( dBμV/m )	Margin ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)	
BLE CH 00 2402MHz		4804	58.12	-15.88	74	72.46	32.22	11.38	57.94	343	338	P	H	
		4804	53.71	-0.29	54	68.05	32.22	11.38	57.94	343	338	A	H	
													H	
													H	
													H	
													H	
			4804	57.35	-16.65	74	71.69	32.22	11.38	57.94	280	211	P	V
			4804	52.76	-1.24	54	67.1	32.22	11.38	57.94	280	211	A	V
														V
														V
														V
	BLE CH 19 2440MHz		4880	56.29	-17.71	74	70.02	32.62	11.65	58	110	294	P	H
		4880	51.57	-2.43	54	65.3	32.62	11.65	58	110	294	A	H	
		7320	52.36	-21.64	74	60.72	37.02	13.35	58.73	200	80	P	H	
		7320	44.99	-9.01	54	53.35	37.02	13.35	58.73	200	80	A	H	
													H	
													H	
			4880	57.49	-16.51	74	71.22	32.62	11.65	58	400	316	P	V
			4880	52.87	-1.13	54	66.6	32.62	11.65	58	400	316	A	V
			7320	49.2	-24.8	74	57.56	37.02	13.35	58.73	385	58	P	V
			7320	41.41	-12.59	54	49.77	37.02	13.35	58.73	385	58	A	V
														V
														V



BLE	Note	Frequency ( MHz )	Level ( dBµV/m )	Margin ( dB )	Limit Line ( dBµV/m )	Read Level ( dBµV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
<b>BLE CH 39 2480MHz</b>		4960	55.52	-18.48	74	68.64	33.02	11.92	58.06	100	297	P	H	
		4960	50.25	-3.75	54	63.37	33.02	11.92	58.06	100	297	A	H	
		7440	49.76	-24.24	74	58.28	36.44	13.75	58.71	109	50	P	H	
		7440	41.43	-12.57	54	49.95	36.44	13.75	58.71	109	50	A	H	
													H	
													H	
			4960	55.79	-18.21	74	68.91	33.02	11.92	58.06	297	228	P	V
			4960	50.68	-3.32	54	63.8	33.02	11.92	58.06	297	228	A	V
			7440	46.47	-27.53	74	54.99	36.44	13.75	58.71	255	223	P	V
			7440	37.37	-16.63	54	45.89	36.44	13.75	58.71	255	223	A	V
														V
														V
	<b>Remark</b>	<ol style="list-style-type: none"> <li>No other spurious found.</li> <li>All results are PASS against Peak and Average limit line.</li> </ol>												



**Emission above 18GHz**

**2.4GHz BLE (SHF)**

BLE	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
		( MHz )	( dB $\mu$ V/m )	( dB )	( dB $\mu$ V/m )	( dB $\mu$ V )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )	
2.4GHz BLE SHF		21696	39.07	-34.93	74	97.1	38.1	-3.27	54.76	-	-	P	H	
													H	
													H	
													H	
			21300	38.8	-35.2	74	96.88	38.33	-3.28	54.8	-	-	P	V
														V
														V
<b>Remark</b>	<ol style="list-style-type: none"> <li>No other spurious found.</li> <li>All results are PASS against limit line.</li> <li>The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only.</li> </ol>													



Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
2.4GHz BLE LF		30.27	27.64	-12.36	40	35.03	23.8	0.96	32.15	-	-	P	H
		50.52	24.47	-15.53	40	41.76	13.9	1.06	32.25	-	-	P	H
		79.95	23.62	-16.38	40	41.24	13.15	1.39	32.16	-	-	P	H
		942.6	32.78	-13.22	46	29.11	29.78	4.76	30.87	-	-	P	H
		957.3	33.19	-12.81	46	28.57	30.54	4.81	30.73	-	-	P	H
		971.3	34.17	-19.83	54	29.34	30.57	4.84	30.58	-	-	P	H
		30.27	27.64	-12.36	40	35.03	23.8	0.96	32.15	-	-	P	V
		50.52	24.47	-15.53	40	41.76	13.9	1.06	32.25	-	-	P	V
		79.95	23.62	-16.38	40	41.24	13.15	1.39	32.16	-	-	P	V
		893.6	32.27	-13.73	46	30.46	28.53	4.57	31.29	-	-	P	V
		950.3	33.8	-12.2	46	29.61	30.19	4.8	30.8	-	-	P	V
		969.9	33.86	-20.14	54	29.07	30.55	4.84	30.6	-	-	P	V
Remark	<ol style="list-style-type: none"> <li>No other spurious found.</li> <li>All results are PASS against limit line.</li> <li>The emission position marked as "-" means no suspected emission found and emission level has at least 6dB margin against limit or emission is noise floor only.</li> </ol>												



**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>Peak</b> or <b>Average</b>
H/V	<b>Horizontal</b> or <b>Vertical</b>



A calculation example for radiated spurious emission is shown as below:

BLE	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BLE CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =  
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Margin(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)  
= 55.45 (dBμV/m)
2. Margin(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 55.45(dBμV/m) – 74(dBμV/m)  
= -18.55(dB)

**For Average Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)  
= 43.54 (dBμV/m)
2. Margin(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 43.54(dBμV/m) – 54(dBμV/m)  
= -10.46(dB)

**Both peak and average measured complies with the limit line, so test result is “PASS”.**



## Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Yuan Lee, Bank Lin and Troye Hsieh	Temperature :	21.8~23.7°C
		Relative Humidity :	53.5~66.9%

### Note symbol

-L	Low channel location
-R	High channel location







<1Mbps>

2.4GHz 2400~2483.5MHz  
BLE (Band Edge @ 3m)




BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Fundamental
Peak	<p>Site : 03CH11-HY Condition : PEAK_BE_74 3m 91200_1212_220310 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_1212_220310 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Avg.	<p>Site : 03CH11-HY Condition : AVG_BE_54 3m 91200_1212_220310 HORIZONTAL : RBW:1000.000KHz VBW:0.510KHz SWT:Auto</p>	<p>Site : 03CH11-HY Condition : AVG_54 3m 91200_1212_220310 HORIZONTAL : RBW:1000.000KHz VBW:0.510KHz SWT:Auto</p>







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH00 2402MHz		
	Vertical	Fundamental
Peak	 <p>Date: 2023-01-13</p> <p>Site Condition : 03CH11-HY : PEAK_BE_74 3m 91200_1212_220310 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Date: 2023-01-13</p> <p>Site Condition : 03CH11-HY : PEAK_74 3m 91200_1212_220310 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Avg.	 <p>Date: 2023-01-13</p> <p>Site Condition : 03CH11-HY : AVG_BE_54 3m 91200_1212_220310 VERTICAL : RBW:1000.000KHz VBW:0.510KHz SWT:Auto</p>	 <p>Date: 2023-01-13</p> <p>Site Condition : 03CH11-HY : AVG_54 3m 91200_1212_220310 VERTICAL : RBW:1000.000KHz VBW:0.510KHz SWT:Auto</p>



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Horizontal	Fundamental
Peak	 <p>Date: 2023-01-13</p> <p>Site : 03CH11-HY Condition : PEAK_BE_74 3m 91200_1212_220310 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Date: 2023-01-13</p> <p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_1212_220310 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Avg.	 <p>Date: 2023-01-13</p> <p>Site : 03CH11-HY Condition : AVG_BE_54 3m 91200_1212_220310 HORIZONTAL : RBW:1000.000KHz VBW:0.510KHz SWT:Auto</p>	 <p>Date: 2023-01-13</p> <p>Site : 03CH11-HY Condition : AVG_54 3m 91200_1212_220310 HORIZONTAL : RBW:1000.000KHz VBW:0.510KHz SWT:Auto</p>



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - R		
	Horizontal	Fundamental
Peak	 <p>Site : 03CH11-HY Condition : PEAK_BE_74 3m 91200_1212_220310 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank
Avg.	 <p>Site : 03CH11-HY Condition : AVG_BE_54 3m 91200_1212_220310 HORIZONTAL : RBW:1000.000KHz VBW:0.510KHz SWT:Auto</p>	Left blank







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - L		
	Vertical	Fundamental
Peak	<p>Date: 2023-01-13</p> <p>Site : 03CH11-HY Condition : PEAK_BE_74 3m 91200_1212_220310 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>	<p>Date: 2023-01-13</p> <p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_1212_220310 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>
Avg.	<p>Date: 2023-01-13</p> <p>Site : 03CH11-HY Condition : AVG_BE_54 3m 91200_1212_220310 VERTICAL : RBW:1000.000kHz VBW:0.510kHz SWT:Auto</p>	<p>Date: 2023-01-13</p> <p>Site : 03CH11-HY Condition : AVG_54 3m 91200_1212_220310 VERTICAL : RBW:1000.000kHz VBW:0.510kHz SWT:Auto</p>







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Vertical	Fundamental
Peak	<p>Site : 03CH11-HY Condition : PEAK_BE_74 3m 91200_1212_220310 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>	Left blank
Avg.	<p>Site : 03CH11-HY Condition : AVG_BE_54 3m 91200_1212_220310 VERTICAL : RBW:1000.000kHz VBW:0.510kHz SWT:Auto</p>	Left blank



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH39 2480MHz		
	Horizontal	Fundamental
Peak	 <p>Date: 2023-01-12</p> <p>Site : 03CH11-HY Condition : PEAK_BE_74 3m 91200_1212_220310 HORIZONTAL : RBW:3000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Date: 2023-01-12</p> <p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_1212_220310 HORIZONTAL : RBW:3000.000KHz VBW:3000.000KHz SWT:Auto</p>
Avg.	 <p>Date: 2023-01-12</p> <p>Site : 03CH11-HY Condition : AVG_BE_54 3m 91200_1212_220310 HORIZONTAL : RBW:3000.000KHz VBW:0.510KHz SWT:Auto</p>	 <p>Date: 2023-01-12</p> <p>Site : 03CH11-HY Condition : AVG_54 3m 91200_1212_220310 HORIZONTAL : RBW:3000.000KHz VBW:0.510KHz SWT:Auto</p>



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH39 2480MHz		
	Vertical	Fundamental
Peak	 <p>Date: 2023-01-12</p> <p>Site : 03CH11-HY Condition : PEAK_BE_74 3m 91200_1212_220310 VERTICAL : RBW:3000.000kHz VBW:3000.000kHz SWT:Auto</p>	 <p>Date: 2023-01-12</p> <p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_1212_220310 VERTICAL : RBW:3000.000kHz VBW:3000.000kHz SWT:Auto</p>
Avg.	 <p>Date: 2023-01-12</p> <p>Site : 03CH11-HY Condition : AVG_BE_54 3m 91200_1212_220310 VERTICAL : RBW:3000.000kHz VBW:0.510kHz SWT:Auto</p>	 <p>Date: 2023-01-12</p> <p>Site : 03CH11-HY Condition : AVG_54 3m 91200_1212_220310 VERTICAL : RBW:3000.000kHz VBW:0.510kHz SWT:Auto</p>



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_1212_220310 HORIZONTAL</p>	<p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_1212_220310 VERTICAL</p>





BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH19 2440MHz	
	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_1212_220310 HORIZONTAL :</p>	<p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_1212_220310 VERTICAL :</p>



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Vertical
Peak	<p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_1212_220310 HORIZONTAL</p>	<p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_1212_220310 VERTICAL</p>







<2Mbps>

2.4GHz 2400~2483.5MHz



BLE (Band Edge @ 3m)

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Fundamental
Peak	<p>Site : 03CH11-HY Condition : PEAK_BE_74 3m 91200_1212_220310 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_1212_220310 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Avg.	<p>Site : 03CH11-HY Condition : AVG_BE_54 3m 91200_1212_220310 HORIZONTAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto</p>	<p>Site : 03CH11-HY Condition : AVG_54 3m 91200_1212_220310 HORIZONTAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto</p>





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH00 2402MHz		
	Vertical	Fundamental
Peak	 <p>Date: 2023-01-13</p> <p>Site : 03CH11-HY Condition : PEAK_BE_74 3m 91200_1212_220310 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>	 <p>Date: 2023-01-13</p> <p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_1212_220310 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>
Avg.	 <p>Date: 2023-01-13</p> <p>Site : 03CH11-HY Condition : AVG_BE_54 3m 91200_1212_220310 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto</p>	 <p>Date: 2023-01-13</p> <p>Site : 03CH11-HY Condition : AVG_54 3m 91200_1212_220310 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto</p>







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - L		
	Horizontal	Fundamental
Peak	 <p>Date: 2023-01-13</p> <p>Site : 03CH11-HY Condition : PEAK_BE_74 3m 91200_1212_220310 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Date: 2023-01-13</p> <p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_1212_220310 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Avg.	 <p>Date: 2023-01-13</p> <p>Site : 03CH11-HY Condition : AVG_BE_54 3m 91200_1212_220310 HORIZONTAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto</p>	 <p>Date: 2023-01-13</p> <p>Site : 03CH11-HY Condition : AVG_54 3m 91200_1212_220310 HORIZONTAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto</p>





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - R		
	Horizontal	Fundamental
Peak	 <p>Site : 03CH11-HY Condition : PEAK_BE_74 3m 91200_1212_220310 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank
Avg.	 <p>Site : 03CH11-HY Condition : AVG_BE_54 3m 91200_1212_220310 HORIZONTAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto</p>	Left blank



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - L		
	Vertical	Fundamental
Peak	 <p>Date: 2023-01-13</p> <p>Site : 03CH11-HY Condition : PEAK_BE_74 3m 91200_1212_220310 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>	 <p>Date: 2023-01-13</p> <p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_1212_220310 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>
Avg.	 <p>Date: 2023-01-13</p> <p>Site : 03CH11-HY Condition : AVG_BE_54 3m 91200_1212_220310 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto</p>	 <p>Date: 2023-01-13</p> <p>Site : 03CH11-HY Condition : AVG_54 3m 91200_1212_220310 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto</p>







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - R		
	Vertical	Fundamental
Peak	 <p>Site : 03CH11-HY Condition : PEAK_BE_74 3m 91200_1212_220310 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>	Left blank
Avg.	 <p>Site : 03CH11-HY Condition : AVG_BE_54 3m 91200_1212_220310 VERTICAL RBW:1000.000kHz VBW:1.000kHz SWT:Auto</p>	Left blank





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH39 2480MHz		
	Horizontal	Fundamental
Peak	<p>Date: 2023-01-11</p> <p>Site : 03CH11-HY Condition : PEAK_BE_74 3m 91200_1212_220310 HORIZONTAL : RBW:3000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Date: 2023-01-11</p> <p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_1212_220310 HORIZONTAL : RBW:3000.000KHz VBW:3000.000KHz SWT:Auto</p>
Avg.	<p>Date: 2023-01-11</p> <p>Site : 03CH11-HY Condition : AVG_BE_54 3m 91200_1212_220310 HORIZONTAL : RBW:3000.000KHz VBW:1.000KHz SWT:Auto</p>	<p>Date: 2023-01-11</p> <p>Site : 03CH11-HY Condition : AVG_54 3m 91200_1212_220310 HORIZONTAL : RBW:3000.000KHz VBW:1.000KHz SWT:Auto</p>





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH39 2480MHz		
	Vertical	Fundamental
Peak	 <p>Date: 2023-01-11</p> <p>Level (dBV/m): 140.0, 130.0, 120.0, 110.0, 100.0, 90.0, 80.0, 70.0, 60.0, 50.0, 40.0, 30.0, 20.0, 10.0</p> <p>Frequency (MHz): 2460, 2463, 2465, 2467, 2469, 2471, 2473, 2475, 2477, 2479, 2481, 2483, 2485, 2487, 2489, 2491, 2493, 2495, 2497, 2500</p> <p>Site Condition : 03CH11-HY : PEAK_BE_74 3m 91200_1212_220310 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Date: 2023-01-11</p> <p>Level (dBV/m): 140.0, 130.0, 120.0, 110.0, 100.0, 90.0, 80.0, 70.0, 60.0, 50.0, 40.0, 30.0, 20.0, 10.0</p> <p>Frequency (MHz): 1000, 1300, 1500, 1700, 1900, 2100, 2300, 2500, 2700, 3000</p> <p>Site Condition : 03CH11-HY : PEAK_74 3m 91200_1212_220310 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Avg.	 <p>Date: 2023-01-11</p> <p>Level (dBV/m): 140.0, 130.0, 120.0, 110.0, 100.0, 90.0, 80.0, 70.0, 60.0, 50.0, 40.0, 30.0, 20.0, 10.0</p> <p>Frequency (MHz): 2460, 2463, 2465, 2467, 2469, 2471, 2473, 2475, 2477, 2479, 2481, 2483, 2485, 2487, 2489, 2491, 2493, 2495, 2497, 2500</p> <p>Site Condition : 03CH11-HY : AVG_BE_54 3m 91200_1212_220310 VERTICAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto</p>	 <p>Date: 2023-01-11</p> <p>Level (dBV/m): 140.0, 130.0, 120.0, 110.0, 100.0, 90.0, 80.0, 70.0, 60.0, 50.0, 40.0, 30.0, 20.0, 10.0</p> <p>Frequency (MHz): 1000, 1300, 1500, 1700, 1900, 2100, 2300, 2500, 2700, 3000</p> <p>Site Condition : 03CH11-HY : AVG_54 3m 91200_1212_220310 VERTICAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto</p>



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
BLE CH00 2402MHz		
	Horizontal	Vertical
Peak Avg.	 <p data-bbox="391 772 837 817">Site : 03CH11-HY Condition : PEAK_74 3m 91200_1212_220310 HORIZONTAL</p>	 <p data-bbox="865 772 1311 817">Site : 03CH11-HY Condition : PEAK_74 3m 91200_1212_220310 VERTICAL</p>



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH19 2440MHz	
	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_1212_220310 HORIZONTAL :</p>	<p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_1212_220310 VERTICAL :</p>



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Vertical
Peak	<p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_1212_220310 HORIZONTAL</p>	<p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_1212_220310 VERTICAL</p>



Emission above 18GHz  
2.4GHz BLE (SHF @ 1m)

BLE	2.4GHz 2400~2483.5MHz	
	BLE SHF	
	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH11-11Y Condition : PEAK_74 1m SHF ANT_9170_00993 HORIZONTAL</p>	<p>Site : 03CH11-11Y Condition : PEAK_74 1m SHF ANT_9170_00993 VERTICAL</p>



Emission below 1GHz
2.4GHz BLE (LF)

Table with 2 columns: Horizontal and Vertical. Each column contains a spectral plot showing Level (dBuV/m) vs Frequency (MHz) for the 2.4GHz BLE LF test. The plots show a blue signal line and a red limit line. The horizontal plot is labeled 'Horizontal' and the vertical plot is labeled 'Vertical'. Both plots include site and condition information.

QP / Peak



## Appendix E. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
Bluetooth –LE for 1Mbps	84.93	2124	0.47	0.51KHz
Bluetooth –LE for 2Mbps	42.49	1064	0.94	1k

