

# FCC ID: 2AUX4-MC6-1550

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz \* = Plane-wave equivalent power density

## MPE Calculation Method

Friis transmission formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

$P_d$  = Power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = Numeric gain of the antenna relative to isotropic antenna

$\pi$  = 3.14115926

$R$  = distance between observation point and center of the radiator in cm (20cm)

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

**Measurement Result**

Operation Frequency: 2406MHz~2466MHz

Power density limited: 1mW/ cm<sup>2</sup>

Antenna Type: External Antenna;

WIFI antenna gain: 3dBi;

R=20cm


$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}= 10^{(1/10)}=2$

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power		Gain	Power density(mW/cm2 )	(mW/cm2)
		Ant A	Ant A	(dBm)	(mW)	Numeric		
2406	QPSK	15.2	15±1	16	39.810717	2	0.01584	1
2436		15.4	15±1	16	39.810717	2	0.01584	1
2466		15.5	15±1	16	39.810717	2	0.01584	1

**Conclusion:**

For the max result : 0.01584≤ 1.0 for for Max Power Density, compliance the RF Exposure.

Signature: 

Date: 2019-12-19

NAME AND TITLE (Please print or type): Alex Li/Manager

COMPANY (Please print or type): SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD./ 1/F, Building E, Fenda Science Park Sanwei, Xixiang, Bao'an District Shenzhen, Guangdong, People's Republic of China