



FCC TEST REPORT

**Test report
On Behalf of
Hangzhou Roombanker Technology Co., Ltd.
For
Smart Gateway
Model No.: DSGW-093**

FCC ID: 2AUXBDSGW-093

Prepared for : Hangzhou Roombanker Technology Co., Ltd.
A#801 Wantong center, Hangzhou, China

Prepared By : Shenzhen Tongzhou Testing Co., Ltd
1th Floor, Building 1, Haomai High-tech Park, Huating Road 387, Dalang
Street, Longhua, Shenzhen, China

Date of Test: 2022/12/8 ~ 2022/12/30

Date of Report: 2022/12/30

Report Number: TZ221203874-E8

The test report apply only to the specific sample(s) tested under stated test conditions
It is not permitted to copy extracts of these test result without the written permission of the test
laboratory.



TEST RESULT CERTIFICATION

Applicant's name.....: Hangzhou Roombanker Technology Co., Ltd.

Address: A#801 Wantong center, Hangzhou, China

Manufacture's Name: Hangzhou Roombanker Technology Co., Ltd.

Address: A#801 Wantong center, Hangzhou, China

Product description

Trade Mark.....: Dusun

Product name.....: Smart Gateway

Model and/or type reference .: DSGW-093

Standards: FCC Rules and Regulations Part 15 Subpart C Section 15.249
ANSI C63.10: 2013

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Tongzhou Testing Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Tongzhou Testing Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Date of Test.....:

Date (s) of performance of tests: 2022/12/8 ~ 2022/12/30

Date of Issue.....: 2022/12/30

Test Result: **Pass**

Testing Engineer :

Anna Hu

(Anna Hu)

Technical Manager :

Hugo Chen

(Hugo Chen)

Authorized Signatory :

Andy Zhang

(Andy Zhang)



Revision History

| Revision | Issue Date | Revisions | Revised By |
|----------|------------|---------------|------------|
| 00 | 2022/12/30 | Initial Issue | Andy Zhang |
| | | | |
| | | | |



TABLE OF CONTENTS

| | |
|--|----|
| 1. GENERAL INFORMATION..... | 5 |
| 1.1. Description of Device (EUT)..... | 5 |
| 1.2 EUT configuration..... | 6 |
| 1.3 External I/O Cable..... | 7 |
| 1.4. Description of Test Facility..... | 7 |
| 1.5. Statement of the Measurement Uncertainty | 7 |
| 1.6. Measurement Uncertainty..... | 8 |
| 1.7. Description of Test Modes | 9 |
| 2. TEST METHODOLOGY..... | 10 |
| 2.1. EUT Configuration..... | 10 |
| 2.2. EUT Exercise | 10 |
| 2.3. General Test Procedures..... | 10 |
| 3. SYSTEM TEST CONFIGURATION | 11 |
| 3.1. Justification | 11 |
| 3.2. EUT Exercise Software | 11 |
| 3.3. Special Accessories..... | 11 |
| 3.4. Block Diagram/Schematics..... | 11 |
| 3.5. Equipment Modifications..... | 11 |
| 3.6. Test Setup | 11 |
| 4. SUMMARY OF TEST RESULTS..... | 12 |
| 5. TEST RESULT..... | 13 |
| 5.1. On Time and Duty Cycle..... | 13 |
| 5.2. Radiated Emissions Measurement..... | 15 |
| 5.3. Band-edge measurements for radiated emissions | 27 |
| 5.4. Power line conducted emissions | 30 |
| 5.5. Antenna Requirements..... | 33 |
| 6. LIST OF MEASURING EQUIPMENTS | 36 |
| 7. TEST SETUP PHOTOGRAPHS OF EUT | 37 |
| 8. EXTERIOR PHOTOGRAPHS OF THE EUT | 37 |
| 9. INTERIOR PHOTOGRAPHS OF THE EUT..... | 37 |



1. GENERAL INFORMATION

1.1. Description of Device (EUT)

| | |
|------------------------------|---------------------------------|
| Product Name | : Smart Gateway |
| Model Number | : DSGW-093 |
| Model Difference Declaration | : N/A |
| Test Model | : DSGW-093 |
| Power Supply | : Input: DC 5V,2A |
| Hardware version | : 5-1-9-010070 |
| Software version | : V1.0 |
| Sample ID | : TZ221203874-1#&TZ221203874-2# |

Bluetooth

| | |
|-----------------------|------------------------------------|
| Bluetooth Version | : V5.2 |
| Frequency Range | : 2402 – 2480 MHz |
| Channel Number | : 40 Channels for BLE (DTS) |
| Modulation Technology | : GFSK for BLE (DTS) |
| Data Rates | : BLE (DTS): 1Mbps |
| Antenna Type And Gain | : Internal Antenna / -0.09dBi(Max) |

Zigbee

| | |
|-----------------------|-----------------------------------|
| Frequency Range | : 2415 – 2480 MHz |
| Channel Number | : 14 Channels |
| Modulation Technology | : O-QPSK |
| Data Rates | : 250 kbps |
| Antenna Type And Gain | : Internal Antenna / 3.79dBi(Max) |

Z-Wave

| | |
|-----------------------|---|
| Frequency Range | : 908.4 – 916 MHz |
| Channel Number | : Channel 1: 908.4MHz / Channel 2: 916MHz |
| Modulation Technology | : FSK |
| Antenna Type And Gain | : Internal Antenna / -1.8dBi(Max) |

WiFi

| | |
|------------------------------|--|
| WLAN | : Supported IEEE 802.11a/b/g/n/ac IEEE 802.11b:2412-2462MHz IEEE 802.11g:2412-2462MHz IEEE 802.11n HT20:2412-2462MHz / 5180-5240MHz / 5745-5825MHz |
| WLAN FCC Operation Frequency | : IEEE 802.11n HT40: 2422-2452MHz / 5190-5230MHz / 5755-5795MHz IEEE 802.11a: 5180-5240MHz / 5745-5825MHz IEEE 802.11ac VHT20: 5180-5240MHz/5745-5825MHz IEEE 802.11ac VHT40: 5190-5230MHz / 5755-5795MHz IEEE 802.11ac VHT80: 5210MHz / 5775MHz |
| WLAN Channel Number | : 11 Channels for 2412-2462MHz(IEEE 802.11b/g/n HT20) 7 Channels for 2422-2462MHz(IEEE 802.11n HT40) 4 Channels for 5180-5240MHz (IEEE 802.11a/ac VHT20/n HT20) 2 Channels for 5190-5230MHz (IEEE 802.11ac VHT40/n HT40) 1 Channels for 5210MHz (IEEE 802.11ac VHT80) 5 Channels for 5745-5825MHz(IEEE 802.11a/ac VHT20/n HT20) |



2 Channels for 5755-5795MHz(IEEE 802.11ac VHT40/n HT40)
 1 Channels for 5775MHz(IEEE 802.11ac VHT80)

WLAN Modulation Technology : IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK)
 IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK)
 IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
 IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK)
 IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)

Antenna Type And Gain : Internal Antenna,
 0.38dBi (Max.), for TX/RX (WLAN 2.4G Band)
 1.15dBi (Max.), for TX/RX (WLAN 5.2G Band)
 2.09dBi (Max.), for TX/RX (WLAN 5.8G Band)

UTRA

UTRA FCC Operation Frequency : WCDMA BAND II (UL: 1850 –1910 MHz/DL: 1930 – 1990 MHz)
 WCDMA BAND IV (UL: 1710 – 1755 MHz/DL: 2110 – 2155 MHz)
 WCDMA BAND V (UL: 824 – 849 MHz/DL: 869 – 894 MHz)

Channel Separation : 0.2MHz

Modulation Technology : OFDM (16QAM, QPSK)

Antenna Type And Gain : Internal Antenna
 WCDMA BAND II: 2.89dBi
 WCDMA BAND IV: 1.92dBi
 WCDMA BAND V: 1.63dBi

E-UTRA

E-UTRA FCC Operation Frequency : FDD Band 2 (UL: 1850 – 1910 MHz/DL: 1930 – 1990 MHz)
 FDD Band 4 (UL: 1710 – 1755 MHz/DL: 2110 – 2155 MHz)
 FDD Band 5 (UL: 824 – 849 MHz/DL: 869 – 894 MHz)
 FDD Band 12(UL: 699 – 716 MHz/DL: 729 – 746 MHz)
 FDD Band 13(UL: 777 – 787 MHz/DL: 746 – 756 MHz)
 FDD Band 25(UL: 1850 – 1915 MHz/DL: 1930 – 1995 MHz)
 FDD Band 26 (UL: 814 – 849 MHz/DL: 859 – 894 MHz)

Channel Separation : 0.1 MHz

Modulation Technology : OFDM (16QAM, QPSK)

Antenna Type And Gain : Internal Antenna
 FDD Band 2:2.89 dBi
 FDD Band 4:1.92 dBi
 FDD Band 5:1.63 dBi
 FDD Band 12:0.21 dBi
 FDD Band 13:1.95 dBi
 FDD Band 25:2.89 dBi
 FDD Band 26:1.63 dBi

Note 1: Antenna position refer to EUT Photos
 Note 2: The above information supplied by the applicant

1.2 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

| | | | |
|---|---------|------------|--|
| ○ | Adapter | Model: | MDY-10-EH |
| | | Input: | 100-240VAC 50/60Hz 0.7A |
| | | Output: | DC 5.0V,3.0A; DC 9.0V,3.0A; DC 12.0V,2.25A; DC 20.0V,1.35A |
| | | Lab. Code: | SZTZ-ZB-EMC-010 |



1.3 External I/O Cable

| I/O Port Description | Quantity | Cable |
|----------------------|----------|-------|
| DC port | 1 | N/A |
| RJ45 port | 1 | N/A |

1.4. Description of Test Facility

FCC

Designation Number: CN1275

Test Firm Registration Number: 167722

Shenzhen Tongzhou Testing Co.,Ltd has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA

Certificate Number: 5463.01

Shenzhen Tongzhou Testing Co.,Ltd has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

IC

ISED#: 22033

CAB identifier: CN0099

Shenzhen Tongzhou Testing Co.,Ltd has been listed by Innovation, Science and Economic Development Canada to perform electromagnetic emission measurement.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010

1.5. Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the Shenzhen Tongzhou Testing Co.,Ltd’s quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.



1.6. Measurement Uncertainty

| Test Item | Frequency Range | Uncertainty | Note |
|--------------------------|-----------------|---------------------|------|
| Radiation Uncertainty : | 9KHz~30MHz | $\pm 3.08\text{dB}$ | (1) |
| | 30MHz~1000MHz | $\pm 3.92\text{dB}$ | (1) |
| | 1GHz~40GHz | $\pm 4.28\text{dB}$ | (1) |
| Conduction Uncertainty : | 150kHz~30MHz | $\pm 2.71\text{dB}$ | (1) |

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



1.7. Description of Test Modes

The EUT has been tested under operating condition.

All test modes were tested, only the result of the worst case was recorded in the report.

Channel List & Frequency

| Channel | Frequency(MHz) | Channel | Frequency(MHz) |
|---------|----------------|---------|----------------|
| 1 | 908.4 | 2 | 916.0 |

Test Channel

| Channel | Transmitting Frequency (MHz) |
|---------|------------------------------|
| 1 | 908.4 |
| 2 | 916.0 |



2. TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Shenzhen Tongzhou Testing Co.,Ltd

2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2. EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.205, 15.207, 15.209 and 15.249 under the FCC Rules Part 15 Subpart C.

2.3. General Test Procedures

2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013



3. SYSTEM TEST CONFIGURATION

3.1. Justification

The system was configured for testing in a continuous transmits condition.

3.2. EUT Exercise Software

The system was configured for Bluetooth testing in a continuous transmits condition and change test channels by software (PuTTY 0.73Zigbee) provided by application.

3.3. Special Accessories

| No. | Equipment | Manufacturer | Model No. | Serial No. | Length | shielded/ unshielded | Notes |
|-----|-----------|--------------|-----------|------------|--------|-------------------------|-------|
| 1 | PC | ASUS | K43S | X16-96081 | / | / | / |

3.4. Block Diagram/Schematics

Please refer to the related document

3.5. Equipment Modifications

Shenzhen Tongzhou Testing Co.,Ltd has not done any modification on the EUT.

3.6. Test Setup

Please refer to the test setup photo.



4. SUMMARY OF TEST RESULTS

| Applied Standard: FCC Part 15 Subpart C | | | |
|---|-------------------------------|----------------------------------|-----------|
| FCC Rules | Description of Test | Test Sample | Result |
| / | Duty Cycle | TZ221203874-1# | Compliant |
| §15.249(a), §15.249(c), §15.249(e) | Field strength of fundamental | TZ221203874-1# | Compliant |
| §15.205, §15.249(d) | Emissions at Restricted Band | TZ221203874-1# | Compliant |
| §15.207(a) | Conducted Emissions | TZ221203874-1# TZ221203874-2# | Compliant |
| §15.203 | Antenna Requirements | N/A | Compliant |
| §15.215 | 20 dB Bandwidth | TZ221203874-1# | Compliant |



5. TEST RESULT

5.1. On Time and Duty Cycle

5.1.1. Standard Applicable

None; for reporting purpose only.


5.1.2. Measuring Instruments and Setting

Please refer to equipment's list in this report. The following table is the setting of the spectrum analyzer.

5.1.3. Test Procedures

1. Set the centre frequency of the spectrum analyzer to the transmitting frequency;
2. Set the span=0MHz, RBW=8MHz, VBW=8MHz, Sweep time=100ms;
3. Detector = peak;
4. Trace mode = Single hold.

5.1.4. Test Setup Layout



5.1.5. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

5.1.6. Test result


| Frequency(MHz) | On Time B (ms) | Period (ms) | Duty Cycle x (Linear) | Duty Cycle (%) | Duty Cycle Correction Factor (dB) | 1/B Minimum VBW(KHz) |
|----------------|----------------|-------------|-----------------------|----------------|-----------------------------------|----------------------|
| 908.4 | 100 | 100 | 1 | 100 | 0 | 0.010 |
| 916.0 | 100 | 100 | 1 | 100 | 0 | 0.010 |



On Time and Duty Cycle



908.4MHz



916.0MHz



5.2. Radiated Emissions Measurement

5.2.1. Standard Applicable

15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

| MHz | MHz | MHz | GHz |
|-------------------|---------------------|---------------|-------------|
| 0.090-0.110 | 16.42-16.423 | 399.9-410 | 4.5-5.15 |
| \1\ 0.495-0.505 | 16.69475-16.69525 | 608-614 | 5.35-5.46 |
| 2.1735-2.1905 | 16.80425-16.80475 | 960-1240 | 7.25-7.75 |
| 4.125-4.128 | 25.5-25.67 | 1300-1427 | 8.025-8.5 |
| 4.17725-4.17775 | 37.5-38.25 | 1435-1626.5 | 9.0-9.2 |
| 4.20725-4.20775 | 73-74.6 | 1645.5-1646.5 | 9.3-9.5 |
| 6.215-6.218 | 74.8-75.2 | 1660-1710 | 10.6-12.7 |
| 6.26775-6.26825 | 108-121.94 | 1718.8-1722.2 | 13.25-13.4 |
| 6.31175-6.31225 | 123-138 | 2200-2300 | 14.47-14.5 |
| 8.291-8.294 | 149.9-150.05 | 2310-2390 | 15.35-16.2 |
| 8.362-8.366 | 156.52475-156.52525 | 2483.5-2500 | 17.7-21.4 |
| 8.37625-8.38675 | 156.7-156.9 | 2690-2900 | 22.01-23.12 |
| 8.41425-8.41475 | 162.0125-167.17 | 3260-3267 | 23.6-24.0 |
| 12.29-12.293 | 167.72-173.2 | 3332-3339 | 31.2-31.8 |
| 12.51975-12.52025 | 240-285 | 3345.8-3358 | 36.43-36.5 |
| 12.57675-12.57725 | 322-335.4 | 3600-4400 | (\2) |
| 13.36-13.41 | | | |

\1\ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

\2\ Above 38.6

According to §15.249 (d): Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009~0.490 | 2400/F(KHz) | 300 |
| 0.490~1.705 | 24000/F(KHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

According to §15.249 (a): Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

| Fundamental frequency | Field strength of fundamental | | Field strength of harmonics | |
|-----------------------|-------------------------------|--------|-----------------------------|--------|
| | millivolts/meter | dBuV/m | microvolts/meter | dBuV/m |
| 902-928 MHz | 50 | 94 | 500 | 54 |
| 2400-2483.5 MHz | 50 | 94 | 500 | 54 |
| 5725-5875 MHz | 50 | 94 | 500 | 54 |
| 24.0-24.25 GHz | 250 | 108 | 2500 | 68 |

As shown in §15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b) of this section, the peak field



strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth

5.2.2. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of spectrum analyzer and receiver.

| Spectrum Parameter | Setting |
|---|---|
| Attenuation | Auto |
| Start Frequency | 1000 MHz |
| Stop Frequency | 10 th carrier harmonic |
| RB / VB (Emission in restricted band) | 1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average |
| RB / VB (Emission in non-restricted band) | 1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average |

| Receiver Parameter | Setting |
|------------------------|--|
| Attenuation | Auto |
| Start ~ Stop Frequency | 9kHz~150kHz / RB/VB 200Hz/1KHz for QP/AVG |
| Start ~ Stop Frequency | 150kHz~30MHz / RB/VB 9kHz/30KHz for QP/AVG |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB/VB 120kHz/1MHz for QP |

5.2.3. Test Procedures

1) Sequence of testing 9 kHz to 30 MHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1.3 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

Final measurement:

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.



2) Sequence of testing 30 MHz to 1 GHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

Premeasurement:

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna is polarized vertical and horizontal.

--- The antenna height changes from 1 to 3 meter.

--- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

--- The final measurement will be performed with minimum the six highest peaks.

--- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter.

--- The final measurement will be done with QP detector with an EMI receiver.

--- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.



3) Sequence of testing 1 GHz to 18 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.



4) Sequence of testing above 18 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 1 meter.
- The EUT was set into operation.

Premeasurement:


- The antenna is moved spherical over the EUT in different polarizations of the antenna.

Final measurement:


- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

5.2.4. Test Setup Layout


For radiated emissions below 30MHz



Below 30MHz



Below 1GHz



Above 1GHz

Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB);
 Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

5.2.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

6.6.6. Radiated Emissions



| | | | |
|---------------|---------|----------------|--------------------------|
| Temperature | 22.8°C | Humidity | 56% |
| Test Engineer | Anna Hu | Configurations | Low Channel/High Channel |

(i) Results of Radiated Emissions (9 kHz~30MHz)

| Freq. (MHz) | Level (dBuV) | Over Limit (dB) | Over Limit (dBuV) | Remark |
|-------------|--------------|-----------------|-------------------|----------|
| - | - | - | - | See Note |

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);
Limit line = specific limits (dBuV) + distance extrapolation factor.

PASS.

Only record the worst test result in this report.


The test data please refer to following page.



(ii) Results of Radiated Emissions (30MHz ~1GHz)

Below 1GHz (Low Channel)

Vertical



◆ QP Detector


| Suspected Data List | | | | | | | | | |
|---------------------|-------------|----------------|---------------|----------------|----------------|-------------|-------------|-----------|----------|
| NO. | Freq. [MHz] | Reading [dBµV] | Factor [dB/m] | Level [dBµV/m] | Limit [dBµV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity |
| 1 | 43.70 | 42.72 | -14.03 | 28.69 | 40.00 | 11.31 | 100 | 352 | Vertical |
| 2 | 101.7 | 42.27 | -15.42 | 26.85 | 43.50 | 16.65 | 100 | 216 | Vertical |
| 3 | 249.8 | 50.08 | -13.77 | 36.31 | 46.50 | 10.19 | 100 | 174 | Vertical |
| 4 | 451.7 | 42.37 | -9.45 | 32.92 | 46.50 | 13.58 | 100 | 20 | Vertical |
| 5 | 752.3 | 41.09 | -4.12 | 36.97 | 46.50 | 9.53 | 100 | 85 | Vertical |
| 6 | 908.4 | 101.67 | -1.09 | 100.58 | 114.0 | 13.42 | 100 | 329 | Vertical |

| Final Data List | | | | | | | | | |
|-----------------|-------------|----------------|-------------------|-------------------|----------------|-------------|-----------|----------|--|
| NO. | Freq. [MHz] | Reading [dBµV] | AV Value [dBµV/m] | AV Limit [dBµV/m] | AV Margin [dB] | Height [cm] | Angle [°] | Polarity | |
| 1 | 908.4 | 81.00 | 79.91 | 94.0 | 14.09 | 100 | 152 | Vertical | |

Average Power = 79.91 – 95.2 = -15.29 dBm

***Note:

1. Level [dBµV/m] = Reading [dBµV] + Factor [dB/m]
2. Margin [dB] = Limit [dBµV/m] - Level [dBµV/m]



| Suspected Data List | | | | | | | | | |
|---------------------|-------------|----------------|---------------|----------------|----------------|-------------|-------------|-----------|------------|
| NO. | Freq. [MHz] | Reading [dBµV] | Factor [dB/m] | Level [dBµV/m] | Limit [dBµV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity |
| 1 | 44.13 | 41.64 | -14.04 | 27.60 | 40.00 | 12.40 | 100 | 345 | Horizontal |
| 2 | 108.3 | 41.89 | -16.00 | 25.89 | 43.50 | 17.61 | 100 | 216 | Horizontal |
| 3 | 249.8 | 57.26 | -13.87 | 43.39 | 46.50 | 3.11 | 100 | 252 | Horizontal |
| 4 | 448.4 | 42.57 | -9.08 | 33.49 | 46.50 | 13.01 | 100 | 330 | Horizontal |
| 5 | 758.8 | 42.47 | -3.50 | 38.97 | 46.50 | 7.53 | 100 | 342 | Horizontal |
| 6 | 908.3 | 112.38 | -0.94 | 111.44 | 114.0 | 2.56 | 100 | 354 | Horizontal |

| Final Data List | | | | | | | | | |
|-----------------|-------------|----------------|-------------------|-------------------|----------------|-------------|-----------|------------|--|
| NO. | Freq. [MHz] | Reading [dBµV] | AV Value [dBµV/m] | AV Limit [dBµV/m] | AV Margin [dB] | Height [cm] | Angle [°] | Polarity | |
| 1 | 904.8 | 90.1 | 89.12 | 94.0 | 4.88 | 100 | 252 | Horizontal | |

Average Power = 89.12 – 95.2 = -6.08 dBm


***Note:

1. Level [dBµV/m] = Reading [dBµV] + Factor [dB/m]
2. Margin [dB] = Limit [dBµV/m] - Level [dBµV/m]



Below 1GHz (High Channel)

Vertical



◆ QP Detector


| Suspected Data List | | | | | | | | | |
|---------------------|-------------|----------------|---------------|----------------|----------------|-------------|-------------|-----------|----------|
| NO. | Freq. [MHz] | Reading [dBµV] | Factor [dB/m] | Level [dBµV/m] | Limit [dBµV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity |
| 1 | 36.09 | 43.45 | -15.24 | 28.21 | 40.00 | 11.79 | 100 | 209 | Vertical |
| 2 | 111.34 | 42.18 | -15.69 | 26.49 | 43.50 | 17.01 | 100 | 110 | Vertical |
| 3 | 249.8 | 49.09 | -13.77 | 35.32 | 46.50 | 11.18 | 100 | 154 | Vertical |
| 4 | 353.6 | 41.19 | -10.82 | 30.37 | 46.50 | 16.13 | 100 | 358 | Vertical |
| 5 | 682.2 | 41.94 | -5.58 | 36.36 | 46.50 | 10.14 | 100 | 65 | Vertical |
| 6 | 916.0 | 95.41 | -0.95 | 94.46 | 114.0 | 19.54 | 100 | 53 | Vertical |

| Final Data List | | | | | | | | |
|-----------------|-------------|----------------|-------------------|-------------------|----------------|-------------|-----------|----------|
| NO. | Freq. [MHz] | Reading [dBµV] | AV Value [dBµV/m] | AV Limit [dBµV/m] | AV Margin [dB] | Height [cm] | Angle [°] | Polarity |
| 1 | 916.0 | 73.4 | 72.45 | 94.0 | 21.55 | 100 | 53 | Vertical |

Average Power = 72.45 – 95.2 = -22.75 dBm

***Note:

1. Level [dBµV/m] = Reading [dBµV] + Factor [dB/m]
2. Margin [dB] = Limit [dBµV/m] - Level [dBµV/m]



◆ QP Detector

| Suspected Data List | | | | | | | | | |
|---------------------|-------------|----------------|---------------|----------------|----------------|-------------|-------------|-----------|------------|
| NO. | Freq. [MHz] | Reading [dBµV] | Factor [dB/m] | Level [dBµV/m] | Limit [dBµV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity |
| 1 | 44.13 | 41.49 | -14.04 | 27.45 | 40.00 | 12.55 | 100 | 321 | Horizontal |
| 2 | 106.5 | 40.87 | -16.00 | 24.87 | 43.50 | 18.63 | 100 | 105 | Horizontal |
| 3 | 249.8 | 56.32 | -13.87 | 42.45 | 46.50 | 4.05 | 100 | 74 | Horizontal |
| 4 | 448.4 | 43.47 | -9.08 | 34.39 | 46.50 | 12.11 | 100 | 239 | Horizontal |
| 5 | 652.4 | 41.44 | -4.94 | 36.50 | 46.50 | 10.00 | 100 | 299 | Horizontal |
| 6 | 916.0 | 111.40 | -0.85 | 110.55 | 114.0 | 3.45 | 100 | 314 | Horizontal |

| Final Data List | | | | | | | | |
|-----------------|-------------|----------------|-------------------|-------------------|----------------|-------------|-----------|------------|
| NO. | Freq. [MHz] | Reading [dBµV] | AV Value [dBµV/m] | AV Limit [dBµV/m] | AV Margin [dB] | Height [cm] | Angle [°] | Polarity |
| 1 | 916.0 | 90.1 | 89.25 | 94.0 | 4.75 | 100 | 265 | Horizontal |

Average Power = 89.25 – 95.2 = -5.95 dBm

***Note:

1. Level [dBµV/m] = Reading [dBµV] + Factor [dB/m]
2. Margin [dB] = Limit [dBµV/m] - Level [dBµV/m]

*(iii) Results for Radiated Emissions (1GHz – 10GHz)*

Low Channel: 908.4MHz

| Freq. MHz | Reading dBuv | Ant. Fac dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuv/m | Limit dBuv/m | Margin dB | Remark | Pol. |
|--------------|-----------------|---------------------|--------------------|--------------------|--------------------|-----------------|--------------|--------|------------|
| 1817.04 | 48.04 | 33.06 | 35.04 | 3.94 | 50.00 | 74.00 | 24.00 | Peak | Horizontal |
| 1817.59 | 48.92 | 33.06 | 35.04 | 3.94 | 50.88 | 74.00 | 23.12 | Peak | Vertical |
| 2726.15 | 47.56 | 33.06 | 35.04 | 3.94 | 49.52 | 74.00 | 24.48 | Peak | Horizontal |
| 2726.01 | 47.38 | 33.06 | 35.04 | 3.94 | 49.34 | 74.00 | 24.66 | Peak | Vertical |

Low Channel: 916MHz

| Freq. MHz | Reading dBuv | Ant. Fac dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuv/m | Limit dBuv/m | Margin dB | Remark | Pol. |
|--------------|-----------------|---------------------|--------------------|--------------------|--------------------|-----------------|--------------|--------|------------|
| 1832.01 | 48.05 | 33.26 | 35.14 | 3.98 | 50.15 | 74.00 | 23.85 | Peak | Horizontal |
| 1832.72 | 48.30 | 33.26 | 35.14 | 3.98 | 50.40 | 74.00 | 23.60 | Peak | Vertical |
| 2748.92 | 48.79 | 33.26 | 35.14 | 3.98 | 50.89 | 74.00 | 23.11 | Peak | Horizontal |
| 2748.70 | 48.79 | 33.26 | 35.14 | 3.98 | 50.89 | 74.00 | 23.11 | Peak | Vertical |

Notes:

1. Measuring frequencies from 9 KHz - 10th harmonic or 26.5GHz (which is less), No emission found between lowest internal used/generated frequency to 30MHz.
2. Radiated emissions measured in frequency range from 9 KHz ~10th harmonic or 26.5GHz (which is less) were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. $Measured = Reading + Ant. Fac - Pre. Fac. + Cab. Loss$; $Margin = Limit - Measured$


5.3. Band-edge measurements for radiated emissions

5.3.1 Standard Applicable


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

5.3.2 Test Setup Layout

For Radiated



For Conducted



5.3.3. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of Spectrum Analyzer.

5.3.4. Test Procedures

Radiated Method:

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.



3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed..
5. The distance between test antenna and EUT was 3 meter:
6. Setting test receiver/spectrum as following table states:

| Test Frequency range | Test Receiver/Spectrum Setting | Detector |
|----------------------|---|----------|
| 1GHz-40GHz | Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto | Peak |

Conducted Method:

According to KDB 558074 D01 for Antenna-port conducted measurement. Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to an EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1MHz, VBW=3MHz for peak detector and RBW=1MHz, VBW=1/B for AV detector.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.
6. Measure the conducted output power (in dBm) using the detector specified by the appropriate regulatory agency (see 12.2.2, 12.2.3, and 12.2.4 for guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
7. Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see 12.2.5 for guidance on determining the applicable antenna gain)
8. Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
9. For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
10. Convert the result ant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \sqrt{EIRP - 20 \log D + 104.77} = \sqrt{EIRP + 95.23}$$

Where:

E = electric field strength in dBμV/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

11. Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.
12. Per KDB662911 D01 section b) In cases where a combination of conducted measurements and cabinet radiated measurements are permitted to demonstrate compliance with absolute radiated out-of-band and spurious limits (e.g., KDB Publications 558074 for DTS and 789033 for U-NII), the conducted measurements must be combined with directional gain to compute the radiated levels of the out-of-band and spurious emissions as described in this section.
13. Compare the resultant electric field strength level to the applicable regulatory limit.
14. Perform radiated spurious emission test duress until all measured frequencies were complete.



5.3.5 Test Results

Pass

According to 15.205, the restrict band is far from working frequency, it consider to compliance with 15.205(a) from radiated emission result in 5.2.7 of this report

5.4. Power line conducted emissions


5.4.1 Standard Applicable

According to §15.207 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

| Frequency Range (MHz) | Limits (dB μ V) | |
|-----------------------|---------------------|----------|
| | Quasi-peak | Average |
| 0.15 to 0.50 | 66 to 56 | 56 to 46 |
| 0.50 to 5 | 56 | 46 |
| 5 to 30 | 60 | 50 |

* Decreasing linearly with the logarithm of the frequency

5.4.2 Block Diagram of Test Setup




5.4.3 Test Results

| | | | |
|---------------|---------|----------------|-----|
| Temperature | 24.5°C | Humidity | 56% |
| Test Engineer | Anna Hu | Configurations | TX |

Pass



Neutral Line



| Frequency MHz | Level dBµV | Transd dB | Limit dBµV | Margin dB | Detector | Line | PE |
|---------------|------------|-----------|------------|-----------|----------|------|-----|
| 0.348000 | 24.90 | 10.1 | 59 | 34.1 | QP | N | GND |
| 0.487500 | 26.30 | 10.0 | 56 | 29.9 | QP | N | GND |
| 1.779000 | 21.00 | 9.7 | 56 | 35.0 | QP | N | GND |
| 2.620500 | 17.50 | 9.7 | 56 | 38.5 | QP | N | GND |
| 6.670500 | 14.10 | 9.8 | 60 | 45.9 | QP | N | GND |
| 21.871500 | 20.70 | 10.2 | 60 | 39.3 | QP | N | GND |


| Frequency MHz | Level dBµV | Transd dB | Limit dBµV | Margin dB | Detector | Line | PE |
|---------------|------------|-----------|------------|-----------|----------|------|-----|
| 0.276000 | 17.90 | 10.3 | 51 | 33.0 | AV | N | GND |
| 0.568500 | 18.20 | 9.9 | 46 | 27.8 | AV | N | GND |
| 0.955500 | 15.00 | 9.8 | 46 | 31.0 | AV | N | GND |
| 2.125500 | 12.20 | 9.7 | 46 | 33.8 | AV | N | GND |
| 5.820000 | 6.70 | 9.8 | 50 | 43.3 | AV | N | GND |
| 23.838000 | 4.50 | 10.1 | 50 | 45.5 | AV | N | GND |

Note:

1. $\text{Margin(dB)} = \text{Limit(dB}\mu\text{V)} - \text{Level(dB}\mu\text{V)}$
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz), Step size: 4 kHz, Scan time: auto.
4. Pre-scan all modes and recorded the worst case results in this report



Live Line



| Frequency MHz | Level dBµV | Transd dB | Limit dBµV | Margin dB | Detector | Line | PE |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.316500 | 27.80 | 10.2 | 60 | 32.0 | QP | L1 | GND |
| 0.622500 | 29.80 | 9.9 | 56 | 26.2 | QP | L1 | GND |
| 0.960000 | 26.50 | 9.8 | 56 | 29.5 | QP | L1 | GND |
| 2.710500 | 22.80 | 9.7 | 56 | 33.2 | QP | L1 | GND |
| 5.140500 | 22.00 | 9.8 | 60 | 38.0 | QP | L1 | GND |
| 22.128000 | 22.10 | 10.2 | 60 | 37.9 | QP | L1 | GND |

| Frequency MHz | Level dBµV | Transd dB | Limit dBµV | Margin dB | Detector | Line | PE |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.357000 | 17.00 | 10.1 | 49 | 31.8 | AV | L1 | GND |
| 0.568500 | 21.20 | 9.9 | 46 | 24.8 | AV | L1 | GND |
| 1.122000 | 16.90 | 9.8 | 46 | 29.1 | AV | L1 | GND |
| 2.125500 | 13.50 | 9.7 | 46 | 32.5 | AV | L1 | GND |
| 5.793000 | 8.30 | 9.8 | 50 | 41.7 | AV | L1 | GND |
| 23.833500 | 7.00 | 10.1 | 50 | 43.0 | AV | L1 | GND |

Note:

1. Margin(dB)= Limit(dBµV) - Level(dBµV)
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz), Step size: 4 kHz, Scan time: auto.
4. Pre-scan all modes and recorded the worst case results in this report



5.5. Antenna Requirements

5.5.1. Standard Applicable

According to antenna requirement of §15.203.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

5.5.2. Antenna Connected Construction

5.5.2.1. Standard Applicable

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

5.5.2.2. Antenna Connector Construction

The directional gains of antenna used for transmitting is 0.0dBi, and the antenna is a Internal antenna connect to PCB board and no consideration of replacement. Please see EUT photo for details.

5.5.2.3. Results: Compliance.



5.6. 20 dB Spectrum Bandwidth Measurement

5.6.1. Standard Applicable


According to antenna requirement of §15.215

(c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated

5.4.2. Test Procedures

1. Set the centre frequency of the spectrum analyzer to the transmitting frequency;
2. Set the span=0MHz, RBW=100kHz, VBW=300kHz, Sweep time=100ms;
3. Detector = peak;
4. Trace mode = Single hold.

5.6.3. Test Setup Layout



5.6.4. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

5.4.5. Test Result


| Frequency(MHz) | 20 dB Bandwidth (kHz) |
|----------------|-----------------------|
| 908.4 | 317.0 |
| 916.0 | 324.0 |



20 dB Bandwidth



908.4MHz



916.0MHz



6. LIST OF MEASURING EQUIPMENTS

| Item | Test Equipment | Manufacturer | Model No. | Serial No. | Calibration Date | Calibration Due Date |
|------|----------------------|-----------------|--------------|--------------|------------------|----------------------|
| 1 | MXA Signal Analyzer | Keysight | N9020A | MY52091623 | 2022/1/13 | 2023/1/12 |
| 2 | Power Sensor | Agilent | U2021XA | MY5365004 | 2022/1/13 | 2023/1/12 |
| 3 | Power Meter | Agilent | U2531A | TW53323507 | 2022/1/13 | 2023/1/12 |
| 4 | Loop Antenna | schwarzbeck | FMZB1519B | 00023 | 2022/11/13 | 2025/11/12 |
| 5 | Wideband Antenna | schwarzbeck | VULB 9163 | 958 | 2022/11/13 | 2025/11/12 |
| 6 | Horn Antenna | schwarzbeck | BBHA 9120D | 01989 | 2022/11/13 | 2025/11/12 |
| 7 | EMI Test Receiver | R&S | ESCI | 100849/003 | 2022/1/12 | 2023/1/11 |
| 8 | Controller | MF | MF7802 | N/A | N/A | N/A |
| 9 | Amplifier | schwarzbeck | BBV 9743 | 209 | 2022/1/12 | 2023/1/11 |
| 10 | Amplifier | Tonscend | TSAMP-0518SE | -- | 2022/1/12 | 2023/1/11 |
| 11 | RF Cable(below 1GHz) | HUBER+SUHNER | RG214 | N/A | 2022/1/12 | 2023/1/11 |
| 12 | RF Cable(above 1GHz) | HUBER+SUHNER | RG214 | N/A | 2022/1/14 | 2023/1/13 |
| 12 | Artificial Mains | ROHDE & SCHWARZ | ENV 216 | 101333-IP | 2022/1/13 | 2023/1/12 |
| 14 | EMI Test Software | ROHDE & SCHWARZ | ESK1 | V1.71 | N/A | N/A |
| 15 | RE test software | Tonscend | JS32-RE | V2.0.2.0 | N/A | N/A |
| 16 | Test Software | Tonscend | JS1120-3 | V2.5.77.0418 | N/A | N/A |
| 17 | Horn Antenna | A-INFO | LB-180400-KF | J211020657 | 2022/10/12 | 2024/10/11 |
| 18 | Amplifier | CDSA | PAP-1840 | 17021 | 2022/10/10 | 2023/10/09 |
| 19 | Spectrum Analyzer | R&S | FSP40 | 100550 | 2022/1/10 | 2023/1/9 |



7. TEST SETUP PHOTOGRAPHS OF EUT

Please refer to separated files for Test Setup Photos of the EUT.

8. EXTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

9. INTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF REPORT-----