

# RF Exposure Evaluation Report

**Applicant:** Hangzhou Roombanker Technology Co., Ltd.

**Address of Applicant:** A#801 Wantong center, Hangzhou, China

## Equipment Under Test (EUT)

**Product Name:** Multi Protocol Host Gateway

**Model No.:** DSGW-291, DSGW-291-X (X:1~18)

**FCC ID:** 2AUXBDSGW-291

**Applicable standards:** FCC CFR Title 47 Part 2 (§2.1091)

**Date of sample receipt:** 27 Feb., 2023

**Date of Test:** 28 Feb., to 26 May, 2023

**Date of report issue:** 29 May, 2023

**Test Result:** PASS


**Tested by:** \_\_\_\_\_

*June Li*

**Date:** \_\_\_\_\_

*29 May, 2023*

**Reviewed by:** \_\_\_\_\_



**Date:** \_\_\_\_\_

*29 May, 2023*

**Approved by:** \_\_\_\_\_

*Manager*

**Date:** \_\_\_\_\_

*29 May, 2023*

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in above the application standard version. Test results reported herein relate only to the item(s) tested.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

## 1 Version

Version No.	Date	Description
00	29 May, 2023	Original

## 2 Contents

	Page
<b>Cover Page</b> .....	<b>1</b>
<b>1 Version</b> .....	<b>2</b>
<b>2 Contents</b> .....	<b>3</b>
<b>3 General Information</b> .....	<b>4</b>
3.1 Client Information .....	4
3.2 General Description of E.U.T. ....	4
3.3 Operating Modes .....	5
3.4 Additions to, deviations, or exclusions from the method .....	5
3.5 Laboratory Facility .....	5
3.6 Laboratory Location .....	5
<b>4 Technical Requirements Specification</b> .....	<b>6</b>
4.1 Limits .....	6
4.2 Test Procedure .....	6
4.3 Result .....	7
4.4 Conclusion .....	8

### 3 General Information

#### 3.1 Client Information

Applicant:	Hangzhou Roombanker Technology Co., Ltd.
Address:	A#801 Wantong center, Hangzhou, China
Manufacturer:	Hangzhou Roombanker Technology Co., Ltd.
Address:	A#801 Wantong center, Hangzhou, China

#### 3.2 General Description of E.U.T.

Product Name:	Multi Protocol Host Gateway
Model No.:	DSGW-291, DSGW-291-X (X:1~18)
Operation Frequency:	2.4G Wi-Fi: 2412MHz~2462MHz 5.2G Wi-Fi Band 1: 5180MHz~5240MHz 5.8G Wi-Fi Band 4: 5725MHz~5875MHz BLE: 2402MHz~2480MHz Zigbee: 2405MHz~2480MHz Z-WAVE: 908.4 MHz SUB-G:433.92 MHz LORA:902MHz-928MHz WCDMA band II: 1852.4 MHz - 1907.6 MHz WCDMA band IV: 1712.4 MHz - 1752.6 MHz WCDMA band V: 826.4 MHz - 846.6 MHz LTE band 2: 1850 MHz - 1910 MHz LTE band 4: 1710 MHz - 1755 MHz LTE band 5: 824 MHz - 849 MHz LTE band 12: 699 MHz - 716 MHz LTE band 13: 777 MHz - 787 MHz LTE band 25: 1850 MHz - 1915 MHz LTE band 26: 814 MHz - 849 MHz
Modulation technology:	802.11b: DSSS, 802.11a/g/n/ac: OFDM BLE: GFSK Zigbee: OQPSK SUB-G:ASK Z-WAVE: GFSK LORA: LORA WCDMA: RMC(QPSK), HSUPA(QPSK), HSDPA(QPSK,16QAM) LTE: QPSK, 16QAM
Antenna gain:	BLE/Zigbee: 2.41/-1dBi; 2.4G Wi-Fi:2.31 dBi; Z-wave: -2.20dBi; SUB-G:-3.45dBi; LORA: 1.23 dBi; LORA: 0.77dBi 5.2G WiFi: 2.41dBi; 5.8G WiFi: 3.64 dBi; WCDMA band II: 3.04 dBi WCDMA band IV: 1.93 dBi; WCDMA band V: 0.14 dBi; LTE band 2: 3.04 dBi LTE band 4: 1.93 dBi; LTE band 5/26: 1.05 dBi; LTE band 12: 0.39 dBi LTE band 13: 0.32 dBi; LTE band 25: 3.04 dBi
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

### 3.3 Operating Modes

Operating mode	Detail description
BLE mode	Keep the EUT in continuously transmitting in BLE mode
Zigbee mode	Keep the EUT in continuously transmitting in Zigbee mode
2.4G WIFI mode	Keep the EUT in continuously transmitting in 2.4G WIFI mode
5.2G WIFI mode	Keep the EUT in continuously transmitting in 5.2G WIFI mode
5.8G WIFI mode	Keep the EUT in continuously transmitting in 5.8G WIFI mode
Z-WAVE mode	Keep the EUT in continuously transmitting in Z-WAVE mode
Lora mode	Keep the EUT in continuously transmitting in Lora mode
SUB-G mode	Keep the EUT in continuously transmitting in SUB-G mode
WCDMA band II mode	Keep the EUT in continuously transmitting in WCDMA band II mode
WCDMA band IV mode	Keep the EUT in continuously transmitting in WCDMA band IV mode
WCDMA band V mode	Keep the EUT in continuously transmitting in WCDMA band V mode
LTE band 2 mode	Keep the EUT in continuously transmitting in LTE band 2 mode
LTE band 4 mode	Keep the EUT in continuously transmitting in LTE band 4 mode
LTE band 5 mode	Keep the EUT in continuously transmitting in LTE band 5 mode
LTE band 12 mode	Keep the EUT in continuously transmitting in LTE band 12 mode
LTE band 13 mode	Keep the EUT in continuously transmitting in LTE band 13 mode
LTE band 25 mode	Keep the EUT in continuously transmitting in LTE band 25 mode
LTE band 26 mode	Keep the EUT in continuously transmitting in LTE band 26 mode

### 3.4 Additions to, deviations, or exclusions from the method

No
----

### 3.5 Laboratory Facility

<p>The test facility is recognized, certified, or accredited by the following organizations:</p> <ul style="list-style-type: none"> <li>● <b>FCC - Designation No.: CN1211</b> JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.</li> <li>● <b>ISED – CAB identifier.: CN0021</b> The 3m Semi-anechoic chamber and 10m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.</li> <li>● <b>CNAS - Registration No.: CNAS L15527</b> JianYan Testing Group Shenzhen Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L15527.</li> <li>● <b>A2LA - Registration No.: 4346.01</b> This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <a href="https://portal.a2la.org/scopepdf/4346-01.pdf">https://portal.a2la.org/scopepdf/4346-01.pdf</a></li> </ul>
--

### 3.6 Laboratory Location

<p>JianYan Testing Group Shenzhen Co., Ltd. Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China. Tel: +86-755-23118282, Fax: +86-755-23116366 Email: info-JYTee@lets.com, Website: <a href="http://jyt.lets.com">http://jyt.lets.com</a></p>
---

## 4 Technical Requirements Specification

### 4.1 Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

### 4.2 Test Procedure

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

### 4.3 Result

Frequency (MHz)	Maximum Output power (dBm)	Maximum Output power (mW)	Antenna Gain (dBi)	Antenna Gain (numeric)	Distance (cm)	Result (mW/cm <sup>2</sup> )	Limits for General Population/Uncontrolled Exposure (mW/cm <sup>2</sup> )	Verdict
2.4G Wi-Fi								
2412	16.4	43.65	2.31	1.70	20.00	0.0148	1.0	Pass
5.2G Wi-Fi								
5240	13.22	20.989	2.41	1.74	20.00	0.007	1.0	Pass
Z-WAVE								
908.4	0.33	1.079	-2.20	0.602	20.00	0.0001	0.61	Pass
SUB-G								
433.92	0.005	1.00	-3.45	0.45	20.00	0.0001	0.29	Pass
5.8G Wi-Fi								
5785	13	19.953	3.64	2.31	20.00	0.009	1.0	Pass
Zigbee								
2440	17.782	60.007	-1	0.794	20.00	0.009	1.0	Pass
BLE								
2480	4.556	2.855	2.41	1.74	20.00	0.001	1.0	Pass
LORA								
908.5	22.07	161.065	0.77	1.19	20.00	0.038	0.61	Pass
927.5	28.06	639.735	-3.66	0.43	20.00	0.055	0.62	Pass
WCDMA								
Band II	25.0	316.228	3.04	2.01	20.00	0.127	1.0	Pass
Band IV	25.0	316.228	1.93	1.56	20.00	0.098	1.0	Pass
Band V	25.0	316.228	0.14	1.03	20.00	0.065	0.55	Pass
LTE								
Band 2	25.0	316.228	3.04	2.01	20.00	0.127	1.0	Pass
Band 4	25.0	316.228	1.93	1.56	20.00	0.098	1.0	Pass
Band 5	25.0	316.228	1.05	1.27	20.00	0.080	0.55	Pass
Band 12	25.0	316.228	0.39	1.09	20.00	0.069	0.47	Pass
Band 13	25.0	316.228	0.32	1.08	20.00	0.068	0.52	Pass
Band 25	25.0	316.228	3.04	2.01	20.00	0.127	1.0	Pass
Band 26(Part 22)	25.0	316.228	1.05	1.27	20.00	0.080	0.54	Pass
Band 26(Part 90S)	25.0	316.228	1.05	1.27	20.00	0.080	0.54	Pass

**Note:**

1. The WCDMA and LTE maximum output power reference report: R1907A0407-M1 and R1907A0407-M2V1, FCC ID: XMR201909EG95NAX, which is issued by TA Technology(Shanghai) Co., Ltd.
2. Just the worst case mode was shown in report.

**Simultaneous transmission(Worse mode):**

Mode	Ratio	Total Ratio	Limit	Verdict
LTE Band 12	0.153	0.4618	1.00	Pass
WCDMA Band II	0.127			
5.8G Wi-Fi	0.009			
5.2G Wi-Fi	0.007			
2.4G Wi-Fi	0.0148			
LORA	0.062			
	0.089			

#### 4.4 Conclusion

The device is exempt from the SAR test and satisfies RF exposure evaluation.

-----End of report-----