RF Exposure Evaluation Report

Product Name	:	Multimedia device with Bluetooth and WLAN
Model No.	:	AIVI2SBXM

FCC ID : 2AUXS-AIVI2SBXM

Applicant : Robert Bosch GmbH

Address : Robert-Bosch-Strasse 200 Hildesheim, 31139 Germany

AC-MRA		TAF
Report Version	:	V1.0
Report No.	:	21A0126R-RFUSMPEV02-A
Date of Declaration	:	Nov. 16, 2021
Date of Receipt	:	Sep. 21, 2020

Testing Laboratory 3023

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd. Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Г



1

Issued Date: Nov. 16, 2021 Report No.: 21A0126R-RFUSMPEV02-A

>	DEKI	RA
---	------	----

Product Name	ultimedia device with Bluetooth and WLAN				
Applicant	Robert Bosch GmbH				
Address	Robert-Bosch-Strasse 200 Hildesheim, 31139 Germany				
Manufacturer	Robert Bosch GmbH				
Model No.	AIVI2SBXM				
FCC ID.	2AUXS-AIVI2SBXM				
Trade Name	Bosch				
Applicable Standard	KDB 447498 D01 v06 \boxtimes Minimum test separation distance ≥ 20 cm \square For low power devices				
Test Result	Complied				
Documented By	: April Chen (Senior Project Specialist/April Chen)				
Tested By	: Ivan Chuang				
Approved By	(Senior Engineer / Ivan Chuang) : Jack Hsu (Senior Engineer / Jack Hsu)				



Revision History

Report No.	Version	Description	Issued Date
21A0126R-RFUSMPEV02-A	V1.0	Initial issue of report.	Nov. 16, 2021

1. GENERAL INFORMATION

1.1. EUT Description

Product Name	Multimedia device with Bluetooth and WLAN
Trade Name	Bosch
Model No.	AIVI2SBXM
FCC ID.	2AUXS-AIVI2SBXM
Frequency Range	802.11b/g/n-20MHz:2412MHz~2462MHz
	802.11a/n-20MHz: 5180-5320MHz, 5500-5700MHz, 5745-5825MHz
	802.11n-40MHz: 5190-5310MHz, 5510-5670MHz, 5755-5795MHz
	802.11ac-80MHz: 5210-5290MHz, 5530-5690MHz, 5775MHz
	BT : 2402-2480MHz
Channel Number	802.11b/g/n-20MHz: 11, n-40MHz: 7
	802.11a/n-20MHz: 24; 802.11n-40MHz: 11
	802.11ac-80MHz: 6
	BT : 79
Type of Modulation	DSSS/OFDM/BPSK/QPSK/16QAM/64QAM/256QAM
	FHSS: GFSK(1Mbps) / π /4DQPSK(2Mbps) / 8DPSK(3Mbps)
Channel Control	Auto
Antenna Gain	Refer to the table "Antenna List"

Antenna List

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	N/A	VPMASF-10849-AF	Metal Plate Antenna	-0.42dBi for 2.4GHz
				0.83dBi For 5.15~5.25GHz
				1.45dBi For 5.25~5.35GHz
				2.44dBi For 5.47~5.725GHz
				0.29dBi For 5.725~5.825GHz
2	MITSUBISHI	DU-7NW233AL-SAMPLE1	Metal Plate Antenna	0.94dBi for 2.4GHz
	ELECTRIC			-4.39dBi For 5.15~5.25GHz
	CORPORATION			-4.75dBi For 5.25~5.35GHz
				1.90dBi For 5.47~5.725GHz
				2.32dBi For 5.725~5.825GHz
3	Faurecia Clarion	ZM-8100	Metal Plate Antenna	-1.91dBi for 2.4GHz
	Electronics CO.,			-4.11dBi For 5.15~5.25GHz
	LTD.			-4.17dBi For 5.25~5.35GHz
				-2.35dBi For 5.47~5.725GHz
				-2.16dBi For 5.725~5.825GHz
4	Robert Bosch GmbH	N/A	Integral Antenna	1.91dBi For 2.4GHz (BT)

2. **RF Exposure Evaluation**

2.1. Standard Applicable

According to KDB 447498 D01 (7.1), A minimum test separation distance ≥ 20 cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits.

2.2. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b) LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range	Electric Field	Magnetic Field	Power Density	Average Time		
(MHz)	Strength (V/m)	Strength (A/m)	(mW/cm^2)	(Minutes)		
	(A) Limits for Occupational/ Control Exposures					
300-1500			F/300	6		
1500-100,000			5	6		
	(B) Limits for General Population/ Uncontrolled Exposures					
300-1500			F/1500	6		
1500-100,000			1	30		

F= Frequency in MHz

Friis Formula

Friis transmission formula: $Pd = (Pout*G)/(4*pi*r^2)$

Where

 $Pd = power density in mW/cm^2$

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

 \mathbf{R} = distance between observation point and center of the radiator in cm

2.3. Test Result of RF Exposure Evaluation

Product	:	Multimedia device with Bluetooth	and WLAN

Test Item : RF Exposure Evaluation

BT 2.4G Peak Gain: 1.91dBi

Band	Frequency (MHz)	Conducted Maximum Peak Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm2)	Limit (mW/cm2)	Pass/Fail
BT-3Mbps	2441	4.84	3.048	0.0009	1	Pass

WLAN 2.4G Peak Gain: 0.94dBi

Band	Frequency (MHz)	Conducted Maximum Peak Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm2)	Limit (mW/cm2)	Pass/Fail
2.4G	2462	20.19	104.472	0.0258	1	Pass

WLAN 5G Peak Gain: 2.44dBi

Band	Frequency (MHz)	Conducted Maximum Average Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm2)	Limit (mW/cm2)	Pass/Fail
5G	5320	9.97	9.931	0.0035	1	Pass

Note: The maximum conducted output power is refer to report No.: 2090718R-E3032110108, 2090718R-E3032110118, 2090718R-E3032110129 from the DEKRA.

2.4. Calculations for Multi-Transmitter

Worst Case Mode	Max Power (dBm)	Power Density (mW/cm2)	Power Density Limit (mW/cm2)	Safety Distance (cm)	Ratios	Result	Limit
BT	4.84	0.0009	1	- 20	0.0009	-0.0267	1
WLAN	20.19	0.0258	1		0.0258		

Ratios = Power Density / Power Density Limit