

FCC

RF


TEST REPORT

ISSUED BY
Shenzhen BALUN Technology Co., Ltd.



FOR
realme Buds Q2

ISSUED TO
Realme Chongqing Mobile Telecommunications Corp., Ltd.
No.178 Yulong Avenue, Yufengshan, Yubei District, Chongqing, China



Tested by:

Ye Hongji
Ye Hongji

Date

Dec. 10, 2020

Approved by:

Wei Yanqian
Wei Yanqian
(Chief Engineer)

Date

Dec. 10, 2020



Report No.: BL-SZ20B0674-602

EUT Name: realme Buds Q2

Model Name: RMA2008

Brand Name: realme

Test Standard: 47 CFR Part 15 Subpart C

FCC ID: 2AUYFRMA2008-L

Test Conclusion: Pass

Test Date: Nov. 23, 2020 ~ Dec. 03, 2020

Date of Issue: Dec. 10, 2020

NOTE: This test report of test results only related to testing samples, which can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. Any objections should be raised within thirty days from the date of issue. To validate the report, please contact us.

Revision History

| <u>Version</u> | <u>Issue Date</u> | <u>Revisions Content</u> |
|----------------|----------------------|---|
| <u>Rev. 01</u> | <u>Dec. 09, 2020</u> | <u>Initial Issue</u> |
| <u>Rev. 02</u> | <u>Dec. 10, 2020</u> | <u>Updated the add average power data</u> |
| <u>Rev. 03</u> | <u>Dec. 11, 2020</u> | <u>Corrected average power data</u> |

TABLE OF CONTENTS

- 1 ADMINISTRATIVE DATA (GENERAL INFORMATION)5
 - 1.1 Identification of the Testing Laboratory5
 - 1.2 Identification of the Responsible Testing Location5
 - 1.3 Laboratory Condition5
 - 1.4 Announce5
- 2 PRODUCT INFORMATION6
 - 2.1 Applicant Information.....6
 - 2.2 Manufacturer Information6
 - 2.3 General Description for Equipment under Test (EUT)6
 - 2.4 Technical Information6
 - 2.5 Additional Instructions7
- 3 SUMMARY OF TEST RESULTS.....8
 - 3.1 Test Standards8
 - 3.2 Verdict8
- 4 GENERAL TEST CONFIGURATIONS9
 - 4.1 Test Environments9
 - 4.2 Test Equipment List.....9
 - 4.3 Measurement Uncertainty10
 - 4.4 Description of Test Setup11
 - 4.4.1 For Antenna Port Test.....11
 - 4.4.2 For AC Power Supply Port Test11
 - 4.4.3 For Radiated Test (Below 30 MHz)12
 - 4.4.4 For Radiated Test (30 MHz-1 GHz)12
 - 4.4.5 For Radiated Test (Above 1 GHz).....13
 - 4.5 Measurement Results Explanation Example.....14
 - 4.5.1 For conducted test items:14

| | | |
|-------|--|----|
| 4.5.2 | For radiated band edges and spurious emission test:..... | 14 |
| 5 | TEST ITEMS..... | 15 |
| 5.1 | Antenna Requirements..... | 15 |
| 5.1.1 | Relevant Standards..... | 15 |
| 5.1.2 | Antenna Anti-Replacement Construction | 15 |
| 5.1.3 | Antenna Gain | 15 |
| 5.2 | Output Power | 16 |
| 5.2.1 | Test Limit..... | 16 |
| 5.2.2 | Test Setup..... | 16 |
| 5.2.3 | Test Procedure..... | 16 |
| 5.2.4 | Test Result | 17 |
| 5.3 | Occupied Bandwidth | 18 |
| 5.3.1 | Limit..... | 18 |
| 5.3.2 | Test Setup..... | 18 |
| 5.3.3 | Test Procedure..... | 18 |
| 5.3.4 | Test Result | 18 |
| 5.4 | Conducted Spurious Emission | 19 |
| 5.4.1 | Limit..... | 19 |
| 5.4.2 | Test Setup..... | 19 |
| 5.4.3 | Test Procedure..... | 19 |
| 5.4.4 | Test Result | 20 |
| 5.5 | Band Edge (Authorized-band band-edge)..... | 21 |
| 5.5.1 | Limit..... | 21 |
| 5.5.2 | Test Setup..... | 21 |
| 5.5.3 | Test Procedure..... | 21 |
| 5.5.4 | Test Result | 21 |
| 5.6 | Conducted Emission | 22 |
| 5.6.1 | Limit..... | 22 |
| 5.6.2 | Test Setup..... | 22 |
| 5.6.3 | Test Procedure..... | 22 |
| 5.6.4 | Test Result | 22 |
| 5.7 | Radiated Spurious Emission | 23 |
| 5.7.1 | Limit..... | 23 |

| | | |
|---------|--|----|
| 5.7.2 | Test Setup | 23 |
| 5.7.3 | Test Procedure | 23 |
| 5.7.4 | Test Result | 26 |
| 5.8 | Band Edge (Restricted-band band-edge)..... | 27 |
| 5.8.1 | Limit..... | 27 |
| 5.8.2 | Test Setup | 27 |
| 5.8.3 | Test Procedure | 27 |
| 1.1.1 | Test Result | 27 |
| 5.9 | Power Spectral density (PSD)..... | 28 |
| 5.9.1 | Limit..... | 28 |
| 5.9.2 | Test Setup | 28 |
| 5.9.3 | Test Procedure | 28 |
| 5.9.4 | Test Result | 28 |
| ANNEX A | TEST RESULT | 29 |
| A.1 | Output Power, E.I.R.P, Duty Cycle..... | 29 |
| A.2 | Occupied Bandwidth | 33 |
| A.3 | Conducted Spurious Emissions | 36 |
| A.4 | Band Edge (Authorized-band band-edge)..... | 41 |
| A.5 | Conducted Emissions..... | 45 |
| A.6 | Radiated Spurious Emission | 47 |
| A.7 | Band Edge (Restricted-band band-edge)..... | 61 |
| A.8 | Power Spectral Density (PSD) | 64 |
| ANNEX B | TEST SETUP PHOTOS | 66 |
| ANNEX C | EUT EXTERNAL PHOTOS | 66 |
| ANNEX D | EUT INTERNAL PHOTOS | 66 |

1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

| | |
|--------------|---|
| Company Name | Shenzhen BALUN Technology Co., Ltd. |
| Address | Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China |
| Phone Number | +86 755 6685 0100 |

1.2 Identification of the Responsible Testing Location

| | |
|---------------------------|---|
| Test Location | Shenzhen BALUN Technology Co., Ltd. |
| Address | Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China |
| Accreditation Certificate | <p>The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A-1.</p> <p>The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.</p> <p>The laboratory is a testing organization accredited by American Association for Laboratory Accreditation(A2LA) according to ISO/IEC 17025.The accreditation certificate is 4344.01.</p> <p>The laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L6791.</p> |
| Description | All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055 |

1.3 Laboratory Condition

| | |
|---------------------------|--------------------|
| Ambient Temperature | 20°C to 25°C |
| Ambient Relative Humidity | 45% to 55% |
| Ambient Pressure | 100 kPa to 102 kPa |

1.4 Announce

- (1) The test report reference to the report template version v6.9.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (7) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2 PRODUCT INFORMATION

2.1 Applicant Information

| | |
|-----------|--|
| Applicant | Realme Chongqing Mobile Telecommunications Corp., Ltd. |
| Address | No.178 Yulong Avenue, Yufengshan, Yubei District, Chongqing, China |

2.2 Manufacturer Information

| | |
|--------------|--|
| Manufacturer | Realme Chongqing Mobile Telecommunications Corp., Ltd. |
| Address | No.178 Yulong Avenue, Yufengshan, Yubei District, Chongqing, China |

2.3 General Description for Equipment under Test (EUT)

| | |
|---|----------------|
| EUT Name | realme Buds Q2 |
| Model Name Under Test | RMA2008 |
| Series Model Name | N/A |
| Description of Model name differentiation | N/A |
| Serial Number | N/A |
| Hardware Version | V1.5 |
| Software Version | 1.1.0.5 |
| Dimensions (Approx.) | N/A |

2.4 Technical Information

| | |
|-----------------------------------|------------------------|
| Network and Wireless connectivity | Bluetooth (BR+EDR+BLE) |
|-----------------------------------|------------------------|

The requirement for the following technical information of the EUT was tested in this report:

| | |
|-------------------------------------|--|
| Modulation Technology | DTS |
| Modulation Type | GFSK |
| Product Type | <input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location |
| Transfer Rate | 1 Mbps, 2 Mbps |
| Frequency Range | The frequency range used is 2400 MHz to 2483.5 MHz. |
| Number of Channel | 40 (at intervals of 2 MHz) |
| Tested Channel | 0 (2402 MHz), 19 (2440 MHz), 39 (2480 MHz) |
| Antenna Type | FPC Antenna |
| Antenna Gain | -1.43 dBi (In test items related to antenna gain, the final results reflect this figure. This value is provided by the applicant.) |
| Antenna Impedance | 50Ω |
| Antenna System (MIMO Smart Antenna) | N/A |

2.5 Additional Instructions


EUT Software Settings:

| | |
|------|--|
| Mode | <input checked="" type="checkbox"/> Special software is used. The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually. |
|------|--|

During testing. Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

| Power level setup in software | | | |
|--|-----------------|-----------------|----------|
| Test Software Version | Airoha.Tool.Kit | | |
| Support Units (Software installation media) | Description | Manufacturer | Model |
| | | Notebook | AIGO |
| Mode | Channel | Frequency (MHz) | Soft Set |
| GFSK (1 Mbps) | CH0 | 2402 | 61 |
| | CH19 | 2440 | 61 |
| | CH39 | 2480 | 60 |
| GFSK (2 Mbps) | CH0 | 2402 | 61 |
| | CH19 | 2440 | 61 |
| | CH39 | 2480 | 60 |

Run Software



3 SUMMARY OF TEST RESULTS

3.1 Test Standards

| No. | Identity | Document Title |
|-----|--|--|
| 1 | 47 CFR Part 15, Subpart C (10-1-17 Edition) | Miscellaneous Wireless Communications Services |
| 2 | KDB 558074 D01 15.247 Meas Guidance v05r02 | Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules |
| 3 | ANSI C63.10-2013 | American National Standard for Testing Unlicensed Wireless Devices |

3.2 Verdict

| No. | Description | FCC Part No. | Channel | Test Result | Verdict |
|-----|--------------------------------------|---------------------|-----------------|-------------|-----------------------|
| 1 | Antenna Requirement | 15.203 | N/A | -- | Pass ^{Note1} |
| 2 | Output Power | 15.247(b) | Low/Middle/High | ANNEX A.1 | Pass |
| 3 | Occupied Bandwidth | 15.247(a) | Low/Middle/High | ANNEX A.2 | Pass |
| 4 | Conducted Spurious Emission | 15.247(d) | Low/Middle/High | ANNEX A.3 | Pass |
| 5 | Band Edge(Authorized-band band-edge) | 15.247(d) | Low/ High | ANNEX A.4 | Pass |
| 6 | Conducted Emission | 15.207 | Low/Middle/High | ANNEX A.5 | Pass |
| 7 | Radiated Spurious Emission | 15.209 15.247(d) | Low/Middle/High | ANNEX A.6 | Pass |
| 8 | Band Edge(Restricted-band band-edge) | 15.209 15.247(d) | Low/Middle/High | ANNEX A.7 | Pass |
| 9 | Power spectral density (PSD) | 15.247(e) | Low/Middle/High | ANNEX A.8 | Pass |
| 10 | Receiver Spurious Emissions | -- | -- | N/A | N/A ^{Note2} |

Note 1: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

Note 2: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

| | | |
|----------------------------|-------------------------|----------------|
| Relative Humidity | 45% to 55% | |
| Atmospheric Pressure | 100 kPa to 102 kPa | |
| Temperature | NT (Normal Temperature) | +22°C to +25°C |
| Working Voltage of the EUT | NV (Normal Voltage) | 3.7 V |

4.2 Test Equipment List

| Description | Manufacturer | Model | Serial No. | Cal. Date | Cal. Due |
|-----------------------------------|-------------------------|-------------------|------------|------------|------------|
| Spectrum Analyzer | ROHDE&SCHWARZ | FSV-30 | 103118 | 2020.06.08 | 2021.06.07 |
| Switch Unit with OSP-B157 | ROHDE&SCHWARZ | OSP120 | 101270 | 2020.06.08 | 2021.06.07 |
| EMI Receiver | KEYSIGHT | N9038A | MY53220118 | 2020.06.09 | 2021.06.08 |
| EMI Receiver | ROHDE&SCHWARZ | ESRP | 101036 | 2020.06.09 | 2021.06.08 |
| LISN | SCHWARZBECK | NSLK 8127 | 8127-687 | 2020.06.09 | 2021.06.08 |
| Bluetooth Tester | ROHDE&SCHWARZ | CBT | 101005 | 2020.06.08 | 2021.06.07 |
| Bluetooth Signaling Unit | ROHDE&SCHWARZ | CMW270 | 100607 | 2020.06.08 | 2021.06.07 |
| Bluetooth Signaling Unit | ROHDE&SCHWARZ | CMW500 | 142028 | 2020.06.08 | 2021.06.07 |
| DC Power Supply | ROHDE&SCHWARZ | HMP2020 | 018141664 | 2020.06.08 | 2021.06.07 |
| Power Splitter | KMW | DCPD-LDC | 1305003215 | -- | -- |
| Power Sensor | ROHDE&SCHWARZ | NRP-Z21 | 103971 | 2020.06.08 | 2021.06.07 |
| Attenuator (20 dB) | KMW | ZA-S1-201 | 110617091 | -- | -- |
| Attenuator (6 dB) | KMW | ZA-S1-61 | 1305003189 | -- | -- |
| Temperature Chamber | AHK | SP20 | 1412 | 2020.06.10 | 2021.06.09 |
| Test Antenna-Loop(9 kHz-30 MHz) | SCHWARZBECK | FMZB 1519 | 1519-037 | 2019.10.29 | 2021.10.28 |
| Test Antenna-Bi-Log(30 MHz-3 GHz) | SCHWARZBECK | VULB 9163 | 9163-624 | 2019.07.02 | 2021.07.01 |
| Test Antenna-Horn(1-18 GHz) | SCHWARZBECK | BBHA 9120D | 9120D-1917 | 2019.07.02 | 2021.07.01 |
| Test Antenna-Horn (18-40 GHz) | A-INFO | LB-180400KF | J211060273 | 2019.01.06 | 2021.01.05 |
| Anechoic Chamber | RAINFORD | 9m*6m*6m | N/A | 2017.02.21 | 2022.02.20 |
| Anechoic Chamber | EMC Electronic Co., Ltd | 20.10*11.60*7.35m | N/A | 2018.08.08 | 2021.08.07 |
| Shielded Enclosure | ChangNing | CN-130701 | 130703 | -- | -- |
| Signal Generator | ROHDE&SCHWARZ | SMB100A | 177746 | 2020.06.08 | 2021.06.07 |
| Power Amplifier | OPHIR RF | 5225F | 1037 | 2020.02.19 | 2021.02.18 |
| Power Amplifier | OPHIR RF | 5273F | 1016 | 2020.02.19 | 2021.02.18 |
| Directional Coupler | Werlantone | C5982-10 | 109275 | N/A | N/A |
| Directional Coupler | Werlantone | CHP-273E | S00801z-01 | N/A | N/A |
| Sound Level Meter | B&K | NL-20 | 00844023 | 2020.10.23 | 2021.10.22 |
| Ear Simulator | B&K | 4192-L-001 | 3038758 | 2020.02.19 | 2021.02.18 |

| Description | Manufacturer | Model | Serial No. | Cal. Date | Cal. Due |
|----------------|--------------|--------|------------|------------|------------|
| Audio analyzer | B&K | UPL 16 | 100129 | 2020.02.28 | 2021.02.27 |

4.3 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.


| Measurement | Value |
|-----------------------------------|--------------|
| Occupied Channel Bandwidth | $\pm 4\%$ |
| RF output power, conducted | ± 1.4 dB |
| Power Spectral Density, conducted | ± 2.5 dB |
| Unwanted Emissions, conducted | ± 2.8 dB |
| All emissions, radiated | ± 5.4 dB |
| Temperature | ± 1 °C |
| Humidity | $\pm 4\%$ |

4.4 Description of Test Setup

4.4.1 For Antenna Port Test


Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)

For example: the measurement value is 10 dBm and the cable loss is 0.5dB, then the conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm




(Diagram 1)

4.4.2 For AC Power Supply Port Test




(Diagram 2)

4.4.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.4.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.4.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.5 Measurement Results Explanation Example

4.5.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

4.5.2 For radiated band edges and spurious emission test:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b); RSS-247, 5.4 (f)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

| Protected Method | Description |
|---|--|
| The antenna is embedded in the product. | An embedded-in antenna design is used. |

| Reference Documents | Item |
|---------------------|--|
| Photo | Please refer to the EUT Photo documents. |

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Output Power

5.2.1 Test Limit

FCC § 15.247(b)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements.

RSS-247, 5.4 (d)

For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. Except as provided in Section 5.4(5), the e.i.r.p. shall not exceed 4 W.

5.2.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

a) Maximum peak conducted output power

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

Set the RBW \geq DTS bandwidth.

Set VBW $\geq 3 \times$ RBW.

Set span $\geq 3 \times$ RBW

Sweep time = auto couple.

Detector = peak.

Trace mode = max hold.

Allow trace to fully stabilize.

Use peak marker function to determine the peak amplitude level.

b) Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set RBW \geq OBW if possible; otherwise, set RBW to the largest available value.

Set VBW \geq RBW. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

5.2.4 Test Result

Please refer to ANNEX A.1.

5.3 Occupied Bandwidth

5.3.1 Limit

FCC §15.247(a); RSS-247, 5.2 (a); RSS-GEN, 6.7

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.

5.3.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

Use the following spectrum analyzer settings:

Set RBW = 100 kHz.

Set the video bandwidth (VBW) ≥ 3 RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.4 Test Result

Please refer to ANNEX A.2.

5.4 Conducted Spurious Emission

5.4.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.4.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

- a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).
- b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).
- c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

The following procedures shall be used to demonstrate compliance to these limits. Note that these procedures can be used in either an antenna-port conducted or radiated test set-up. Radiated tests must conform to the test site requirements and utilize maximization procedures defined herein.

Reference level measurement:

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Emission level measurement:

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

5.4.4 Test Result

Please refer to ANNEX A.3.

5.5 Band Edge (Authorized-band band-edge)

5.5.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.5.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle $\geq 98\%$). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.

Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (femission) ± 0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by femission ± 0.5 MHz.

5.5.4 Test Result

Please refer to ANNEX A.4.

5.6 Conducted Emission

5.6.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

| Frequency range (MHz) | Conducted Limit (dB μ V) | |
|--------------------------|------------------------------|----------|
| | Quai-peak | Average |
| 0.15 - 0.50 | 66 to 56 | 56 to 46 |
| 0.50 - 5 | 56 | 46 |
| 0.50 - 30 | 60 | 50 |

5.6.2 Test Setup

See section 4.4.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.6.4 Test Result

Please refer to ANNEX A.5.

5.7 Radiated Spurious Emission

5.7.1 Limit

FCC §15.209&15.247(d); RSS-GEN, 8.9; RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field Strength ($\mu\text{V}/\text{m}$) | Measurement Distance (m) |
|-----------------|---|--------------------------|
| 0.009 - 0.490 | 2400/F(kHz) | 300 |
| 0.490 - 1.705 | 24000/F(kHz) | 30 |
| 1.705 - 30.0 | 30 | 30 |
| 30 - 88 | 100 | 3 |
| 88 - 216 | 150 | 3 |
| 216 - 960 | 200 | 3 |
| Above 960 | 500 | 3 |

Note:

1. Field Strength (dB $\mu\text{V}/\text{m}$) = 20*log[Field Strength ($\mu\text{V}/\text{m}$)].
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: 54dB $\mu\text{V}/\text{m}@3\text{m}$ (AV) and 74dB $\mu\text{V}/\text{m}@3\text{m}$ (PK).

5.7.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

Since the emission limits are specified in terms of radiated field strength levels, measurements performed to demonstrate compliance have traditionally relied on a radiated test configuration. Radiated measurements remain the principal method for demonstrating compliance to the specified limits; however antenna-port conducted measurements are also now acceptable to demonstrate compliance (see below for details). When radiated measurements are utilized, test site requirements and procedures for maximizing and measuring radiated emissions that are described in ANSI C63.10 shall be followed.

Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

General Procedure for conducted measurements in restricted bands:

- a) Measure the conducted output power (in dBm) using the detector specified (see guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see guidance on determining the applicable antenna gain)
- c) Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
- d) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
- e) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

- f) Compare the resultant electric field strength level to the applicable limit.
- g) Perform radiated spurious emission test.

Quasi-Peak measurement procedure

The specifications for measurements using the CISPR quasi-peak detector can be found in Publication 16 of the International Special Committee on Radio Frequency Interference (CISPR) of the International Electrotechnical Commission.

As an alternative to CISPR quasi-peak measurement, compliance can be demonstrated to the applicable emission limits using a peak detector.

Peak power measurement procedure:

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 1.
- b) VBW $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be longer for low duty cycle applications).

Table 1—RBW as a function of frequency

| Frequency | RBW |
|-------------|-------------|
| 9-150 kHz | 200-300 Hz |
| 0.15-30 MHz | 9-10 kHz |
| 30-1000 MHz | 100-120 kHz |
| > 1000 MHz | 1 MHz |

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Trace averaging across on and off times of the EUT transmissions followed by duty cycle correction:

If continuous transmission of the EUT (i.e., duty cycle ≥ 98 percent) cannot be achieved and the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent), then the following procedure shall be used:

- a) The EUT shall be configured to operate at the maximum achievable duty cycle.
- b) Measure the duty cycle, x , of the transmitter output signal as described in section 6.0.
- c) RBW = 1 MHz (unless otherwise specified).
- d) VBW $\geq 3 \times$ RBW.
- e) Detector = RMS, if $\text{span}/(\# \text{ of points in sweep}) \leq (\text{RBW}/2)$. Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- f) Averaging type = power (i.e., RMS).
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- g) Sweep time = auto.
- h) Perform a trace average of at least 100 traces.
- i) A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (RMS) mode was used in step f), then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.
 - 2) If linear voltage averaging mode was used in step f), then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.
 - 3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

NOTE: Reduction of the measured emission amplitude levels to account for operational duty factor is not permitted. Compliance is based on emission levels occurring during transmission - not on an average across on and off times of the transmitter.

Determining the applicable transmit antenna gain:

A conducted power measurement will determine the maximum output power associated with a restricted band emission; however, in order to determine the associated EIRP level, the gain of the transmitting antenna (in dBi) must be added to the measured output power (in dBm).

Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.

See KDB 662911 for guidance on calculating the additional array gain term when determining the effective antenna gain for a EUT with multiple outputs occupying the same or overlapping frequency ranges in the same band.

Radiated spurious emission test:

An additional consideration when performing conducted measurements of restricted band emissions is that unwanted emissions radiating from the EUT cabinet, control circuits, power leads, or intermediate circuit elements will likely go undetected in a conducted measurement configuration. To address this concern, a radiated test shall be performed to ensure that emissions emanating from the EUT cabinet (rather than the antenna port) also comply with the applicable limits.

For these cabinet radiated spurious emission measurements the EUT transmit antenna may be replaced with a termination matching the nominal impedance of the antenna. Procedures for performing radiated measurements are specified in ANSI C63.10. All detected emissions shall comply with the applicable limits.

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.7.4 Test Result

Please refer to ANNEX A.6.

5.8 Band Edge (Restricted-band band-edge)

5.8.1 Limit

FCC §15.209&15.247(d); RSS-GEN, 8.10; RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.8.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

For transmitters operating above 1 GHz repeat the measurement with an average detector.

1.1.1 Test Result

Please refer to ANNEX A.7.

5.9 Power Spectral density (PSD)

5.9.1 Limit

FCC §15.247(e); RSS-247, 5.2 (b)

The same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of Section 5.4(4), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

5.9.2 Test Setup

See section 4.4.1 (Diagram 1) for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.

Set the VBW $\geq 3 \text{ RBW}$.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.9.4 Test Result

Please refer to ANNEX A.7.

ANNEX A TEST RESULT

A.1 Output Power, E.I.R.P, Duty Cycle

Peak Power Test Data

| Channel | Measured Output Peak Power | | Limit | | Verdict |
|---------|----------------------------|-------|-------|------|---------|
| | GFSK (BLE 1Mbps) | | dBm | mW | |
| | dBm | mW | | | |
| Low | 9.59 | 9.10 | 30 | 1000 | Pass |
| Middle | 10.10 | 10.23 | | | Pass |
| High | 10.14 | 10.33 | | | Pass |

| Channel | Measured Output Peak Power | | Limit | | Verdict |
|---------|----------------------------|-------|-------|------|---------|
| | GFSK (BLE 2Mbps) | | dBm | mW | |
| | dBm | mW | | | |
| Low | 9.60 | 9.12 | 30 | 1000 | Pass |
| Middle | 10.02 | 10.05 | | | Pass |
| High | 10.15 | 10.35 | | | Pass |

Average Power Test Data

| Channel | Measured Output Average Power | | Limit | | Verdict |
|---------|-------------------------------|------|-------|------|---------|
| | GFSK (BLE 1Mbps) | | dBm | mW | |
| | dBm | mW | | | |
| Low | 6.88 | 4.88 | 30 | 1000 | Pass |
| Middle | 7.86 | 6.11 | | | Pass |
| High | 7.91 | 6.18 | | | Pass |

| Channel | Measured Output Average Power | | Limit | | Verdict |
|---------|-------------------------------|------|-------|------|---------|
| | GFSK (BLE 2Mbps) | | dBm | mW | |
| | dBm | mW | | | |
| Low | 3.92 | 2.47 | 30 | 1000 | Pass |
| Middle | 4.86 | 3.06 | | | Pass |
| High | 5.11 | 3.24 | | | Pass |

Test plots

GFSK (BLE 1Mbps) LOW CHANNEL



Date: 23 NOV 2020 16:38:29

GFSK (BLE 1Mbps) MIDDLE CHANNEL



Date: 23 NOV 2020 16:44:06

GFSK (BLE 1Mbps) HIGH CHANNEL



GFSK (BLE 2Mbps) LOW CHANNEL




Date: 23 NOV 2020 17:29:33

GFSK (BLE 2Mbps) MIDDLE CHANNEL



Date: 23 NOV 2020 17:32:03

GFSK (BLE 2Mbps) HIGH CHANNEL




Duty Cycle Test Data

| Band | On Time (ms) | On+Off Time (ms) | Duty Cycle (%) |
|------------------|--------------|------------------|----------------|
| GFSK (BLE 1Mbps) | 0.37869 | 0.62647 | 60.45 |
| GFSK (BLE 2Mbps) | 0.19035 | 0.62471 | 30.47 |


Test plots

GFSK (BLE 1Mbps)



Date: 23 NOV 2020 15:28:39

GFSK (BLE 2Mbps)



Date: 23 NOV 2020 17:25:18

A.2 Occupied Bandwidth

Test Data


| Test Mode | GFSK (BLE 1Mbps) | | |
|----------------|----------------------|---------------------|-----------------------------|
| Channel | 6 dB Bandwidth (kHz) | 99% Bandwidth (kHz) | 6 dB Bandwidth Limits (kHz) |
| Low Channel | 726.074 | 1028.944 | ≥500 |
| Middle Channel | 721.924 | 1033.285 | ≥500 |
| High Channel | 717.529 | 1033.285 | ≥500 |

| Test Mode | GFSK (BLE 2Mbps) | | |
|----------------|----------------------|---------------------|-----------------------------|
| Channel | 6 dB Bandwidth (kHz) | 99% Bandwidth (kHz) | 6 dB Bandwidth Limits (kHz) |
| Low Channel | 1252.197 | 2058.000 | ≥500 |
| Middle Channel | 1252.197 | 2058.000 | ≥500 |
| High Channel | 1252.197 | 2058.000 | ≥500 |

Test plots


6 dB Bandwidth

GFSK (BLE 1Mbps) LOW CHANNEL




Date: 23 NOV 2020 16:38:35

GFSK (BLE 1Mbps) MIDDLE CHANNEL



Date: 23 NOV 2020 16:44:12

GFSK (BLE 1Mbps) HIGH CHANNEL




Date: 23 NOV 2020 16:47:13

GFSK (BLE 2Mbps) LOW CHANNEL




Date: 23 NOV 2020 17:29:38

GFSK (BLE 2Mbps) MIDDLE CHANNEL



Date: 23 NOV 2020 17:32:09

GFSK (BLE 2Mbps) HIGH CHANNEL



Date: 23 NOV 2020 17:34:50

99% Bandwidth

GFSK (BLE 1Mbps) LOW CHANNEL




Date: 23 NOV 2020 16:38:41

GFSK (BLE 1Mbps) MIDDLE CHANNEL




Date: 23 NOV 2020 16:44:18

GFSK (BLE 1Mbps) HIGH CHANNEL




Date: 23 NOV 2020 16:47:19

GFSK (BLE 2Mbps) LOW CHANNEL



Date: 23 NOV 2020 17:29:45

GFSK (BLE 2Mbps) MIDDLE CHANNEL



Date: 23 NOV 2020 17:32:15

GFSK (BLE 2Mbps) HIGH CHANNEL



Date: 23 NOV 2020 17:34:57

A.3 Conducted Spurious Emissions


Test Data

| GFSK (BLE 1Mbps) | | | | |
|------------------|--|---------------|-------------------------|---------|
| Channel | Measured Max. Out of Band Emission (dBm) | Limit (dBm) | | Verdict |
| | | Carrier Level | Calculated 20 dBc Limit | |
| Low | -33.76 | 8.84 | -11.16 | Pass |
| Middle | -33.66 | 9.35 | -10.65 | Pass |
| High | -34.59 | 9.77 | -10.23 | Pass |

| GFSK (BLE 2Mbps) | | | | |
|------------------|--|---------------|-------------------------|---------|
| Channel | Measured Max. Out of Band Emission (dBm) | Limit (dBm) | | Verdict |
| | | Carrier Level | Calculated 20 dBc Limit | |
| Low | -34.93 | 8.48 | -11.52 | Pass |
| Middle | -34.85 | 8.90 | -11.10 | Pass |
| High | -34.37 | 9.08 | -10.92 | Pass |


Test Plots

GFSK (BLE 1Mbps) LOW CHANNEL, CARRIER LEVEL




Date: 23 NOV 2020 16:38:53

GFSK (BLE 1Mbps) LOW CHANNEL, SPURIOUS
30 MHz ~ 3 GHz




Date: 23 NOV 2020 16:39:32

GFSK (BLE 1Mbps) LOW CHANNEL, SPURIOUS
2 GHz ~ 25 GHz




Date: 23 NOV 2020 16:40:01

GFSK (BLE 1Mbps) MIDDLE CHANNEL,
CARRIER LEVEL




Date: 23 NOV 2020 16:44:39

GFSK (BLE 1Mbps) MIDDLE CHANNEL,
SPURIOUS 30 MHz ~ 3 GHz




Date: 23 NOV 2020 16:45:27

GFSK (BLE 1Mbps) MIDDLE CHANNEL,
SPURIOUS 2 GHz ~ 25 GHz




Date: 23 NOV 2020 16:46:06

GFSK (BLE 1Mbps) HIGH CHANNEL, CARRIER LEVEL




Date: 23 NOV 2020 16:47:32

GFSK (BLE 1Mbps) HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




Date: 23 NOV 2020 16:48:06

GFSK (BLE 1Mbps) HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




Date: 23 NOV 2020 16:48:30

GFSK (BLE 2Mbps) LOW CHANNEL, CARRIER LEVEL




Date: 23 NOV 2020 17:29:58

GFSK (BLE 2Mbps) LOW CHANNEL, SPURIOUS
30 MHz ~ 3 GHz




Date: 23 NOV 2020 17:30:39

GFSK (BLE 2Mbps) LOW CHANNEL, SPURIOUS
2 GHz ~ 25 GHz




Date: 23 NOV 2020 17:31:06

GFSK (BLE 2Mbps) MIDDLE CHANNEL,
CARRIER LEVEL




Date: 23 NOV 2020 17:32:30

GFSK (BLE 2Mbps) MIDDLE CHANNEL,
SPURIOUS 30 MHz ~ 3 GHz




Date: 23 NOV 2020 17:33:23

GFSK (BLE 2Mbps) MIDDLE CHANNEL,
SPURIOUS 2 GHz ~ 25 GHz




Date: 23 NOV 2020 17:33:50

GFSK (BLE 2Mbps) HIGH CHANNEL, CARRIER LEVEL




Date: 23 NOV.2020 17:35:15

GFSK (BLE 2Mbps) HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



Date: 23 NOV.2020 17:36:02

GFSK (BLE 2Mbps) HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



Date: 23 NOV.2020 17:36:16

A.4 Band Edge (Authorized-band band-edge)

Note: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

BLE 1Mbps

| Channel | Measured Max. Band Edge Emission (dBm) | Limit (dBm) | | Verdict |
|--------------|--|---------------|-------------------------|---------|
| | | Carrier Level | Calculated 20 dBc Limit | |
| Low Channel | -38.46 | 8.84 | -11.16 | Pass |
| High Channel | -47.61 | 9.77 | -10.23 | Pass |


BLE 2Mbps

| Channel | Measured Max. Band Edge Emission (dBm) | Limit (dBm) | | Verdict |
|--------------|--|---------------|-------------------------|---------|
| | | Carrier Level | Calculated 20 dBc Limit | |
| Low Channel | -17.39 | 8.48 | -11.52 | Pass |
| High Channel | -45.04 | 9.08 | -10.92 | Pass |

Test Plots


BLE 1Mbps

LOW CHANNEL, Carrier level




Date: 23 NOV 2020 16:38:53

LOW CHANNEL, Reference level




Date: 23 NOV 2020 16:40:14

LOW CHANNEL, Band Edge




Date: 23 NOV 2020 16:40:19

High CHANNEL, Carrier level




Date: 23 NOV 2020 16:47:32

HIGH CHANNEL, Reference level



Date: 23 NOV 2020 16:48:42


HIGH CHANNEL, Band Edge



Date: 23 NOV 2020 16:48:48


BLE 2Mbps

LOW CHANNEL, Carrier level




Date: 23 NOV 2020 17:29:58

LOW CHANNEL, Reference level




Date: 23 NOV 2020 17:31:16

LOW CHANNEL, Band Edge



Date: 23 NOV 2020 17:31:21


High CHANNEL, Carrier level




Date: 23 NOV 2020 17:35:15

HIGH CHANNEL, Reference level

HIGH CHANNEL, Band Edge



Date: 23 NOV 2020 17:36:33



Date: 23 NOV 2020 17:36:38

A.5 Conducted Emissions

Note 1: The EUT is working in the Normal link mode.


Note 2: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

Note 3: Results (dBuV) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)

Test Data and Plots

PHASE L


CE Test case_FCC_CE_FCC PART 15B_Class B



| No. | Frequency (MHz) | Results (dBuV) | Factor (dB) | Limit (dBuV) | Over Limit (dB) | Detector | Line | Verdict |
|-----|-----------------|----------------|-------------|--------------|-----------------|----------|------|---------|
| 1 | 0.172 | 43.85 | 10.40 | 64.86 | -21.01 | Peak | L | Pass |
| 1** | 0.172 | 28.73 | 10.40 | 54.86 | -26.13 | AV | L | Pass |
| 2 | 0.204 | 43.36 | 10.38 | 63.45 | -20.09 | Peak | L | Pass |
| 2** | 0.204 | 28.85 | 10.38 | 53.45 | -24.60 | AV | L | Pass |
| 3 | 0.288 | 39.57 | 10.34 | 60.58 | -21.01 | Peak | L | Pass |
| 3** | 0.288 | 27.01 | 10.34 | 50.58 | -23.57 | AV | L | Pass |
| 4 | 0.690 | 35.96 | 10.27 | 56.00 | -20.04 | Peak | L | Pass |
| 4** | 0.690 | 25.09 | 10.27 | 46.00 | -20.91 | AV | L | Pass |
| 5 | 1.922 | 37.48 | 10.25 | 56.00 | -18.52 | Peak | L | Pass |
| 5** | 1.922 | 24.85 | 10.25 | 46.00 | -21.15 | AV | L | Pass |
| 6 | 10.904 | 36.35 | 10.38 | 60.00 | -23.65 | Peak | L | Pass |
| 6** | 10.904 | 23.28 | 10.38 | 50.00 | -26.72 | AV | L | Pass |

PHASE N

CE Test case_FCC_CE_FCC PART 15B_Class B



| No. | Frequency (MHz) | Results (dBuV) | Factor (dB) | Limit (dBuV) | Over Limit (dB) | Detector | Line | Verdict |
|-----|-----------------|----------------|-------------|--------------|-----------------|----------|------|---------|
| 1 | 0.186 | 47.50 | 10.39 | 64.21 | -16.71 | Peak | N | Pass |
| 1** | 0.186 | 30.21 | 10.39 | 54.21 | -24.00 | AV | N | Pass |
| 2 | 0.278 | 42.75 | 10.34 | 60.88 | -18.13 | Peak | N | Pass |
| 2** | 0.278 | 27.52 | 10.34 | 50.88 | -23.36 | AV | N | Pass |
| 3 | 0.398 | 39.16 | 10.31 | 57.90 | -18.74 | Peak | N | Pass |
| 3** | 0.398 | 25.10 | 10.31 | 47.90 | -22.80 | AV | N | Pass |
| 4 | 0.574 | 38.78 | 10.27 | 56.00 | -17.22 | Peak | N | Pass |
| 4** | 0.574 | 26.83 | 10.27 | 46.00 | -19.17 | AV | N | Pass |
| 5 | 1.692 | 36.38 | 10.26 | 56.00 | -19.62 | Peak | N | Pass |
| 5** | 1.692 | 23.90 | 10.26 | 46.00 | -22.10 | AV | N | Pass |
| 6 | 12.612 | 37.04 | 10.38 | 60.00 | -22.96 | Peak | N | Pass |
| 6** | 12.612 | 25.53 | 10.38 | 50.00 | -24.47 | AV | N | Pass |

A.6 Radiated Spurious Emission

Note 1: The symbol of "--" in the table which means not application.

Note 2: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.


Note 3: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note 4: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and BLE 2M-High channel mode is the worst.

Note 5: Results (dBuV/m) = Original reading level of Spectrum Analyzer (dBuV/m) + Factor (dB)


Test Data and Plots

30 MHz to 1 GHz, ANT H



| No. | Frequency (MHz) | Results (dBuV/m) | Factor (dB) | Limit (dBuV/m) | Over Limit (dB) | Detector | Table (Degree) | Height (cm) | Antenna | Verdict |
|-----|-----------------|------------------|-------------|----------------|-----------------|----------|----------------|-------------|------------|---------|
| 1 | 43.334 | 9.43 | -26.84 | 30.0 | -20.57 | Peak | 360.00 | 200 | Horizontal | Pass |
| 2 | 127.946 | 12.59 | -27.34 | 33.5 | -20.91 | Peak | 191.00 | 100 | Horizontal | Pass |
| 3 | 159.948 | 11.31 | -25.82 | 33.5 | -22.19 | Peak | 255.00 | 200 | Horizontal | Pass |
| 4 | 319.958 | 13.22 | -25.31 | 36.0 | -22.78 | Peak | 360.00 | 200 | Horizontal | Pass |
| 5 | 634.886 | 19.45 | -17.17 | 36.0 | -16.55 | Peak | 166.00 | 100 | Horizontal | Pass |
| 6 | 959.270 | 24.25 | -11.56 | 36.0 | -11.75 | Peak | 266.00 | 100 | Horizontal | Pass |

30 MHz to 1 GHz, ANT V




| No. | Frequency (MHz) | Results (dBuV/m) | Factor (dB) | Limit (dBuV/m) | Over Limit (dB) | Detector | Table (Degree) | Height (cm) | Antenna | Verdict |
|-----|-----------------|------------------|-------------|----------------|-----------------|----------|----------------|-------------|----------|---------|
| 1 | 57.396 | 9.22 | -27.75 | 30.0 | -20.78 | Peak | 55.00 | 100 | Vertical | Pass |
| 2 | 155.341 | 9.91 | -25.65 | 33.5 | -23.59 | Peak | 191.00 | 100 | Vertical | Pass |
| 3 | 287.956 | 11.28 | -26.09 | 36.0 | -24.72 | Peak | 226.00 | 100 | Vertical | Pass |
| 4 | 458.633 | 16.10 | -21.34 | 36.0 | -19.90 | Peak | 171.00 | 200 | Vertical | Pass |
| 5 | 655.009 | 19.64 | -16.78 | 36.0 | -16.36 | Peak | 337.00 | 100 | Vertical | Pass |
| 6 | 940.602 | 24.47 | -11.42 | 36.0 | -11.53 | Peak | 317.00 | 100 | Vertical | Pass |

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.


Note 2: The spurious from 18GHz-25GHz is noise only, do not show on the report.

GFSK (BLE 1Mbps) LOW CHANNEL 1 GHz to 18 GHz, ANT H




| No. | Frequency (MHz) | Results (dBuV/m) | Factor (dB) | Limit (dBuV/m) | Over Limit (dB) | Detector | Table (Degree) | Height (cm) | Antenna | Verdict |
|-----|-----------------|------------------|-------------|----------------|-----------------|----------|----------------|-------------|------------|---------|
| 1 | 1308.000 | 37.01 | -17.34 | 74.0 | -36.99 | Peak | 135.00 | 150 | Horizontal | Pass |
| 1** | 1308.000 | 28.24 | -17.34 | 54.0 | -25.76 | AV | 135.00 | 150 | Horizontal | Pass |
| 2 | 2401.800 | 103.13 | -12.26 | 74.0 | 29.13 | Peak | 284.00 | 150 | Horizontal | N/A |
| 2** | 2401.800 | 101.90 | -12.26 | 54.0 | 47.90 | AV | 284.00 | 150 | Horizontal | N/A |
| 3 | 4804.400 | 49.53 | -2.78 | 74.0 | -24.47 | Peak | 314.00 | 150 | Horizontal | Pass |
| 3** | 4804.400 | 45.95 | -2.78 | 54.0 | -8.05 | AV | 314.00 | 150 | Horizontal | Pass |
| 4 | 6846.200 | 52.12 | -0.94 | 74.0 | -21.88 | Peak | 331.00 | 150 | Horizontal | Pass |
| 4** | 6846.200 | 41.87 | -0.94 | 54.0 | -12.13 | AV | 331.00 | 150 | Horizontal | Pass |
| 5 | 12605.100 | 51.79 | 1.92 | 74.0 | -22.21 | Peak | 109.00 | 150 | Horizontal | Pass |
| 5** | 12605.100 | 41.53 | 1.92 | 54.0 | -12.47 | AV | 109.00 | 150 | Horizontal | Pass |
| 6 | 17441.925 | 54.76 | 2.96 | 74.0 | -19.24 | Peak | 67.00 | 150 | Horizontal | Pass |
| 6** | 17441.925 | 45.05 | 2.96 | 54.0 | -8.95 | AV | 67.00 | 150 | Horizontal | Pass |

GFSK (BLE 1Mbps) LOW CHANNEL 1 GHz to 18 GHz, ANT V



| No. | Frequency (MHz) | Results (dBuV/m) | Factor (dB) | Limit (dBuV/m) | Over Limit (dB) | Detector | Table (Degree) | Height (cm) | Antenna | Verdict |
|-----|-----------------|------------------|-------------|----------------|-----------------|----------|----------------|-------------|----------|---------|
| 1 | 1312.600 | 38.73 | -17.27 | 74.0 | -35.27 | Peak | 121.00 | 150 | Vertical | Pass |
| 1** | 1312.600 | 33.41 | -17.27 | 54.0 | -20.59 | AV | 121.00 | 150 | Vertical | Pass |
| 2 | 2401.700 | 101.56 | -12.26 | 74.0 | 27.56 | Peak | 44.00 | 150 | Vertical | N/A |
| 2** | 2401.700 | 98.78 | -12.26 | 54.0 | 44.78 | AV | 44.00 | 150 | Vertical | N/A |
| 3 | 4804.200 | 50.68 | -2.76 | 74.0 | -23.32 | Peak | 25.00 | 150 | Vertical | Pass |
| 3** | 4804.200 | 47.32 | -2.76 | 54.0 | -6.68 | AV | 25.00 | 150 | Vertical | Pass |
| 4 | 6735.600 | 52.64 | -0.37 | 74.0 | -21.36 | Peak | 331.00 | 150 | Vertical | Pass |
| 4** | 6735.600 | 42.90 | -0.37 | 54.0 | -11.10 | AV | 331.00 | 150 | Vertical | Pass |
| 5 | 12412.188 | 50.28 | 1.43 | 74.0 | -23.72 | Peak | 17.00 | 150 | Vertical | Pass |
| 5** | 12412.188 | 41.00 | 1.43 | 54.0 | -13.00 | AV | 17.00 | 150 | Vertical | Pass |
| 6 | 17472.901 | 54.54 | 2.86 | 74.0 | -19.46 | Peak | 287.00 | 150 | Vertical | Pass |
| 6** | 17472.901 | 45.92 | 2.86 | 54.0 | -8.08 | AV | 287.00 | 150 | Vertical | Pass |


GFSK (BLE 1Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H



| No. | Frequency (MHz) | Results (dBuV/m) | Factor (dB) | Limit (dBuV/m) | Over Limit (dB) | Detector | Table (Degree) | Height (cm) | Antenna | Verdict |
|-----|-----------------|------------------|-------------|----------------|-----------------|----------|----------------|-------------|------------|---------|
| 1 | 1288.100 | 37.65 | -17.55 | 74.0 | -36.35 | Peak | 126.00 | 150 | Horizontal | Pass |
| 1** | 1288.100 | 29.47 | -17.55 | 54.0 | -24.53 | AV | 126.00 | 150 | Horizontal | Pass |
| 2 | 2439.700 | 102.61 | -12.64 | 74.0 | 28.61 | Peak | 126.00 | 150 | Horizontal | N/A |
| 2** | 2439.700 | 101.12 | -12.64 | 54.0 | 47.12 | AV | 126.00 | 150 | Horizontal | N/A |
| 3 | 4880.200 | 49.79 | -3.44 | 74.0 | -24.21 | Peak | 0.00 | 150 | Horizontal | Pass |
| 3** | 4880.200 | 46.30 | -3.44 | 54.0 | -7.70 | AV | 0.00 | 150 | Horizontal | Pass |
| 4 | 6608.600 | 52.51 | 0.14 | 74.0 | -21.49 | Peak | 167.00 | 150 | Horizontal | Pass |
| 4** | 6608.600 | 43.23 | 0.14 | 54.0 | -10.77 | AV | 167.00 | 150 | Horizontal | Pass |
| 5 | 9803.987 | 49.04 | -0.14 | 74.0 | -24.96 | Peak | 151.00 | 150 | Horizontal | Pass |
| 5** | 9803.987 | 40.44 | -0.14 | 54.0 | -13.56 | AV | 151.00 | 150 | Horizontal | Pass |
| 6 | 16973.886 | 54.87 | 1.95 | 74.0 | -19.13 | Peak | 10.00 | 150 | Horizontal | Pass |
| 6** | 16973.886 | 45.01 | 1.95 | 54.0 | -8.99 | AV | 10.00 | 150 | Horizontal | Pass |

GFSK (BLE 1Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



| No. | Frequency (MHz) | Results (dBuV/m) | Factor (dB) | Limit (dBuV/m) | Over Limit (dB) | Detector | Table (Degree) | Height (cm) | Antenna | Verdict |
|-----|-----------------|------------------|-------------|----------------|-----------------|----------|----------------|-------------|----------|---------|
| 1 | 1685.600 | 45.72 | -17.44 | 74.0 | -28.28 | Peak | 107.00 | 150 | Vertical | Pass |
| 1** | 1685.600 | 27.74 | -17.44 | 54.0 | -26.26 | AV | 107.00 | 150 | Vertical | Pass |
| 2 | 2439.700 | 100.01 | -12.64 | 74.0 | 26.01 | Peak | 44.00 | 150 | Vertical | N/A |
| 2** | 2439.700 | 99.12 | -12.64 | 54.0 | 45.12 | AV | 44.00 | 150 | Vertical | N/A |
| 3 | 4879.800 | 49.45 | -3.43 | 74.0 | -24.55 | Peak | 24.00 | 150 | Vertical | Pass |
| 3** | 4879.800 | 45.90 | -3.43 | 54.0 | -8.10 | AV | 24.00 | 150 | Vertical | Pass |
| 4 | 6739.600 | 52.25 | -0.22 | 74.0 | -21.75 | Peak | 203.00 | 150 | Vertical | Pass |
| 4** | 6739.600 | 43.05 | -0.22 | 54.0 | -10.95 | AV | 203.00 | 150 | Vertical | Pass |
| 5 | 10388.763 | 49.56 | 0.06 | 74.0 | -24.44 | Peak | 360.00 | 150 | Vertical | Pass |
| 5** | 10388.763 | 39.86 | 0.06 | 54.0 | -14.14 | AV | 360.00 | 150 | Vertical | Pass |
| 6 | 17426.698 | 54.74 | 3.56 | 74.0 | -19.26 | Peak | -3.00 | 150 | Vertical | Pass |
| 6** | 17426.698 | 45.50 | 3.56 | 54.0 | -8.50 | AV | -3.00 | 150 | Vertical | Pass |

GFSK (BLE 1Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT H


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



| No. | Frequency (MHz) | Results (dBuV/m) | Factor (dB) | Limit (dBuV/m) | Over Limit (dB) | Detector | Table (Degree) | Height (cm) | Antenna | Verdict |
|-----|-----------------|------------------|-------------|----------------|-----------------|----------|----------------|-------------|------------|---------|
| 1 | 1310.700 | 38.39 | -17.29 | 74.0 | -35.61 | Peak | 81.00 | 150 | Horizontal | Pass |
| 1** | 1310.700 | 28.23 | -17.29 | 54.0 | -25.77 | AV | 81.00 | 150 | Horizontal | Pass |
| 2 | 2479.700 | 101.75 | -12.43 | 74.0 | 27.75 | Peak | 194.00 | 150 | Horizontal | N/A |
| 2** | 2479.700 | 98.39 | -12.43 | 54.0 | 44.39 | AV | 194.00 | 150 | Horizontal | N/A |
| 3 | 4959.800 | 52.36 | -3.30 | 74.0 | -21.64 | Peak | 360.00 | 150 | Horizontal | Pass |
| 3** | 4959.800 | 49.33 | -3.30 | 54.0 | -4.67 | AV | 360.00 | 150 | Horizontal | Pass |
| 4 | 7441.025 | 49.88 | -4.30 | 74.0 | -24.12 | Peak | 207.00 | 150 | Horizontal | Pass |
| 4** | 7441.025 | 43.65 | -4.30 | 54.0 | -10.35 | AV | 207.00 | 150 | Horizontal | Pass |
| 5 | 9919.275 | 52.28 | -1.06 | 74.0 | -21.72 | Peak | 71.00 | 150 | Horizontal | Pass |
| 5** | 9919.275 | 48.56 | -1.06 | 54.0 | -5.44 | AV | 71.00 | 150 | Horizontal | Pass |
| 6 | 12398.963 | 51.62 | 1.58 | 74.0 | -22.38 | Peak | 242.00 | 150 | Horizontal | Pass |
| 6** | 12398.963 | 47.98 | 1.58 | 54.0 | -6.02 | AV | 242.00 | 150 | Horizontal | Pass |

GFSK (BLE 1Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT V


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



| No. | Frequency (MHz) | Results (dBuV/m) | Factor (dB) | Limit (dBuV/m) | Over Limit (dB) | Detector | Table (Degree) | Height (cm) | Antenna | Verdict |
|-----|-----------------|------------------|-------------|----------------|-----------------|----------|----------------|-------------|----------|---------|
| 1 | 1312.700 | 37.36 | -17.27 | 74.0 | -36.64 | Peak | 98.00 | 150 | Vertical | Pass |
| 1** | 1312.700 | 33.29 | -17.27 | 54.0 | -20.71 | AV | 98.00 | 150 | Vertical | Pass |
| 2 | 2479.700 | 98.58 | -12.43 | 74.0 | 24.58 | Peak | 47.00 | 150 | Vertical | N/A |
| 2** | 2479.700 | 96.21 | -12.43 | 54.0 | 42.21 | AV | 47.00 | 150 | Vertical | N/A |
| 3 | 4960.800 | 50.20 | -3.24 | 74.0 | -23.80 | Peak | 78.00 | 150 | Vertical | Pass |
| 3** | 4960.800 | 49.47 | -3.24 | 54.0 | -4.53 | AV | 78.00 | 150 | Vertical | Pass |
| 4 | 6833.800 | 52.77 | -1.10 | 74.0 | -21.23 | Peak | 203.00 | 150 | Vertical | Pass |
| 4** | 6833.800 | 41.49 | -1.10 | 54.0 | -12.51 | AV | 203.00 | 150 | Vertical | Pass |
| 5 | 9919.275 | 50.37 | -1.06 | 74.0 | -23.63 | Peak | 26.00 | 150 | Vertical | Pass |
| 5** | 9919.275 | 47.67 | -1.06 | 54.0 | -6.33 | AV | 26.00 | 150 | Vertical | Pass |
| 6 | 17424.599 | 54.74 | 3.63 | 74.0 | -19.26 | Peak | -1.00 | 150 | Vertical | Pass |
| 6** | 17424.599 | 46.23 | 3.63 | 54.0 | -7.77 | AV | -1.00 | 150 | Vertical | Pass |

GFSK (BLE 2Mbps) LOW CHANNEL 1 GHz to 18 GHz, ANT H


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



| No. | Frequency (MHz) | Results (dBuV/m) | Factor (dB) | Limit (dBuV/m) | Over Limit (dB) | Detector | Table (Degree) | Height (cm) | Antenna | Verdict |
|-----|-----------------|------------------|-------------|----------------|-----------------|----------|----------------|-------------|------------|---------|
| 1 | 1875.000 | 38.42 | -16.42 | 74.0 | -35.58 | Peak | 69.00 | 150 | Horizontal | Pass |
| 1** | 1875.000 | 33.01 | -16.42 | 54.0 | -20.99 | AV | 69.00 | 150 | Horizontal | Pass |
| 2 | 2401.500 | 103.01 | -12.26 | 74.0 | 29.01 | Peak | 211.00 | 150 | Horizontal | N/A |
| 2** | 2401.500 | 100.39 | -12.26 | 54.0 | 46.39 | AV | 211.00 | 150 | Horizontal | N/A |
| 3 | 4803.200 | 48.76 | -2.68 | 74.0 | -25.24 | Peak | 308.00 | 150 | Horizontal | Pass |
| 3** | 4803.200 | 43.84 | -2.68 | 54.0 | -10.16 | AV | 308.00 | 150 | Horizontal | Pass |
| 4 | 6979.200 | 52.82 | 0.87 | 74.0 | -21.18 | Peak | 161.00 | 150 | Horizontal | Pass |
| 4** | 6979.200 | 44.24 | 0.87 | 54.0 | -9.76 | AV | 161.00 | 150 | Horizontal | Pass |
| 5 | 12263.262 | 50.93 | 1.22 | 74.0 | -23.07 | Peak | 361.00 | 150 | Horizontal | Pass |
| 5** | 12263.262 | 41.10 | 1.22 | 54.0 | -12.90 | AV | 361.00 | 150 | Horizontal | Pass |
| 6 | 17469.749 | 54.34 | 2.91 | 74.0 | -19.66 | Peak | 108.00 | 150 | Horizontal | Pass |
| 6** | 17469.749 | 45.52 | 2.91 | 54.0 | -8.48 | AV | 108.00 | 150 | Horizontal | Pass |

GFSK (BLE 2Mbps) LOW CHANNEL 1 GHz to 18 GHz, ANT V


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



| No. | Frequency (MHz) | Results (dBuV/m) | Factor (dB) | Limit (dBuV/m) | Over Limit (dB) | Detector | Table (Degree) | Height (cm) | Antenna | Verdict |
|-----|-----------------|------------------|-------------|----------------|-----------------|----------|----------------|-------------|----------|---------|
| 1 | 1310.900 | 37.26 | -17.28 | 74.0 | -36.74 | Peak | 334.00 | 150 | Vertical | Pass |
| 1** | 1310.900 | 28.67 | -17.28 | 54.0 | -25.33 | AV | 334.00 | 150 | Vertical | Pass |
| 2 | 2401.500 | 101.09 | -12.26 | 74.0 | 27.09 | Peak | 53.00 | 150 | Vertical | N/A |
| 2** | 2401.500 | 96.25 | -12.26 | 54.0 | 42.25 | AV | 53.00 | 150 | Vertical | N/A |
| 3 | 4803.400 | 49.11 | -2.69 | 74.0 | -24.89 | Peak | 306.00 | 150 | Vertical | Pass |
| 3** | 4803.400 | 44.03 | -2.69 | 54.0 | -9.97 | AV | 306.00 | 150 | Vertical | Pass |
| 4 | 6268.800 | 52.54 | -0.37 | 74.0 | -21.46 | Peak | 66.00 | 150 | Vertical | Pass |
| 4** | 6268.800 | 43.45 | -0.37 | 54.0 | -10.55 | AV | 66.00 | 150 | Vertical | Pass |
| 5 | 12275.912 | 50.63 | 1.65 | 74.0 | -23.37 | Peak | 151.00 | 150 | Vertical | Pass |
| 5** | 12275.912 | 41.23 | 1.65 | 54.0 | -12.77 | AV | 151.00 | 150 | Vertical | Pass |
| 6 | 17435.625 | 54.69 | 3.23 | 74.0 | -19.31 | Peak | 63.00 | 150 | Vertical | Pass |
| 6** | 17435.625 | 45.48 | 3.23 | 54.0 | -8.52 | AV | 63.00 | 150 | Vertical | Pass |


GFSK (BLE 2Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H

RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



| No. | Frequency (MHz) | Results (dBuV/m) | Factor (dB) | Limit (dBuV/m) | Over Limit (dB) | Detector | Table (Degree) | Height (cm) | Antenna | Verdict |
|-----|-----------------|------------------|-------------|----------------|-----------------|----------|----------------|-------------|------------|---------|
| 1 | 1352.100 | 38.21 | -17.41 | 74.0 | -35.79 | Peak | 119.00 | 150 | Horizontal | Pass |
| 1** | 1352.100 | 28.40 | -17.41 | 54.0 | -25.60 | AV | 119.00 | 150 | Horizontal | Pass |
| 2 | 2440.500 | 102.42 | -12.75 | 74.0 | 28.42 | Peak | 119.00 | 150 | Horizontal | N/A |
| 2** | 2440.500 | 99.58 | -12.75 | 54.0 | 45.58 | AV | 119.00 | 150 | Horizontal | N/A |
| 3 | 4879.200 | 49.31 | -3.42 | 74.0 | -24.69 | Peak | 310.00 | 150 | Horizontal | Pass |
| 3** | 4879.200 | 44.15 | -3.42 | 54.0 | -9.85 | AV | 310.00 | 150 | Horizontal | Pass |
| 4 | 6971.200 | 53.26 | 0.68 | 74.0 | -20.74 | Peak | 328.00 | 150 | Horizontal | Pass |
| 4** | 6971.200 | 45.47 | 0.68 | 54.0 | -8.53 | AV | 328.00 | 150 | Horizontal | Pass |
| 5 | 12604.812 | 50.64 | 1.92 | 74.0 | -23.36 | Peak | 361.00 | 150 | Horizontal | Pass |
| 5** | 12604.812 | 41.97 | 1.92 | 54.0 | -12.03 | AV | 361.00 | 150 | Horizontal | Pass |
| 6 | 17884.500 | 54.71 | 3.61 | 74.0 | -19.29 | Peak | -3.00 | 150 | Horizontal | Pass |
| 6** | 17884.500 | 46.10 | 3.61 | 54.0 | -7.90 | AV | -3.00 | 150 | Horizontal | Pass |


GFSK (BLE 2Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V



| No. | Frequency (MHz) | Results (dBuV/m) | Factor (dB) | Limit (dBuV/m) | Over Limit (dB) | Detector | Table (Degree) | Height (cm) | Antenna | Verdict |
|-----|-----------------|------------------|-------------|----------------|-----------------|----------|----------------|-------------|----------|---------|
| 1 | 1312.700 | 37.35 | -17.27 | 74.0 | -36.65 | Peak | 103.00 | 150 | Vertical | Pass |
| 1** | 1312.700 | 32.46 | -17.27 | 54.0 | -21.54 | AV | 103.00 | 150 | Vertical | Pass |
| 2 | 2439.500 | 99.84 | -12.64 | 74.0 | 25.84 | Peak | 49.00 | 150 | Vertical | N/A |
| 2** | 2439.500 | 95.21 | -12.64 | 54.0 | 41.21 | AV | 49.00 | 150 | Vertical | N/A |
| 3 | 4880.200 | 49.03 | -3.44 | 74.0 | -24.97 | Peak | 24.00 | 150 | Vertical | Pass |
| 3** | 4880.200 | 44.85 | -3.44 | 54.0 | -9.15 | AV | 24.00 | 150 | Vertical | Pass |
| 4 | 6985.600 | 52.93 | 0.51 | 74.0 | -21.07 | Peak | 346.00 | 150 | Vertical | Pass |
| 4** | 6985.600 | 43.78 | 0.51 | 54.0 | -10.22 | AV | 346.00 | 150 | Vertical | Pass |
| 5 | 12609.412 | 50.40 | 1.89 | 74.0 | -23.60 | Peak | 92.00 | 150 | Vertical | Pass |
| 5** | 12609.412 | 42.21 | 1.89 | 54.0 | -11.79 | AV | 92.00 | 150 | Vertical | Pass |
| 6 | 17467.912 | 54.93 | 2.90 | 74.0 | -19.07 | Peak | 190.00 | 150 | Vertical | Pass |
| 6** | 17467.912 | 45.80 | 2.90 | 54.0 | -8.20 | AV | 190.00 | 150 | Vertical | Pass |

GFSK (BLE 2Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT H


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



| No. | Frequency (MHz) | Results (dBuV/m) | Factor (dB) | Limit (dBuV/m) | Over Limit (dB) | Detector | Table (Degree) | Height (cm) | Antenna | Verdict |
|-----|-----------------|------------------|-------------|----------------|-----------------|----------|----------------|-------------|------------|---------|
| 1 | 1846.600 | 38.63 | -16.62 | 74.0 | -35.37 | Peak | 97.00 | 150 | Horizontal | Pass |
| 1** | 1846.600 | 29.07 | -16.62 | 54.0 | -24.93 | AV | 97.00 | 150 | Horizontal | Pass |
| 2 | 2479.500 | 101.23 | -12.44 | 74.0 | 27.23 | Peak | 237.00 | 150 | Horizontal | N/A |
| 2** | 2479.500 | 97.27 | -12.44 | 54.0 | 43.27 | AV | 237.00 | 150 | Horizontal | N/A |
| 3 | 4961.200 | 51.20 | -3.22 | 74.0 | -22.80 | Peak | 360.00 | 150 | Horizontal | Pass |
| 3** | 4961.200 | 47.61 | -3.22 | 54.0 | -6.39 | AV | 360.00 | 150 | Horizontal | Pass |
| 4 | 6624.200 | 52.66 | -0.30 | 74.0 | -21.34 | Peak | 46.00 | 150 | Horizontal | Pass |
| 4** | 6624.200 | 43.29 | -0.30 | 54.0 | -10.71 | AV | 46.00 | 150 | Horizontal | Pass |
| 5 | 9918.125 | 51.27 | -1.04 | 74.0 | -22.73 | Peak | 184.00 | 150 | Horizontal | Pass |
| 5** | 9918.125 | 48.39 | -1.04 | 54.0 | -5.61 | AV | 184.00 | 150 | Horizontal | Pass |
| 6 | 17415.150 | 54.98 | 3.64 | 74.0 | -19.02 | Peak | -3.00 | 150 | Horizontal | Pass |
| 6** | 17415.150 | 44.51 | 3.64 | 54.0 | -9.49 | AV | -3.00 | 150 | Horizontal | Pass |

GFSK (BLE 2Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT V

RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



| No. | Frequency (MHz) | Results (dBuV/m) | Factor (dB) | Limit (dBuV/m) | Over Limit (dB) | Detector | Table (Degree) | Height (cm) | Antenna | Verdict |
|-----|-----------------|------------------|-------------|----------------|-----------------|----------|----------------|-------------|----------|---------|
| 1 | 1296.200 | 37.48 | -17.40 | 74.0 | -36.52 | Peak | 64.00 | 150 | Vertical | Pass |
| 1** | 1296.200 | 28.16 | -17.40 | 54.0 | -25.84 | AV | 64.00 | 150 | Vertical | Pass |
| 2 | 2479.400 | 98.40 | -12.44 | 74.0 | 24.40 | Peak | 48.00 | 150 | Vertical | N/A |
| 2** | 2479.400 | 92.86 | -12.44 | 54.0 | 38.86 | AV | 48.00 | 150 | Vertical | N/A |
| 3 | 4961.200 | 50.60 | -3.22 | 74.0 | -23.40 | Peak | 84.00 | 150 | Vertical | Pass |
| 3** | 4961.200 | 45.70 | -3.22 | 54.0 | -8.30 | AV | 84.00 | 150 | Vertical | Pass |
| 4 | 6681.000 | 52.09 | -0.52 | 74.0 | -21.91 | Peak | 293.00 | 150 | Vertical | Pass |
| 4** | 6681.000 | 43.89 | -0.52 | 54.0 | -10.11 | AV | 293.00 | 150 | Vertical | Pass |
| 5 | 9921.863 | 49.02 | -1.09 | 74.0 | -24.98 | Peak | 24.00 | 150 | Vertical | Pass |
| 5** | 9921.863 | 42.65 | -1.09 | 54.0 | -11.35 | AV | 24.00 | 150 | Vertical | Pass |
| 6 | 17467.386 | 54.37 | 2.90 | 74.0 | -19.63 | Peak | 222.00 | 150 | Vertical | Pass |
| 6** | 17467.386 | 46.27 | 2.90 | 54.0 | -7.73 | AV | 222.00 | 150 | Vertical | Pass |

A.7 Band Edge (Restricted-band band-edge)

Note 1: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note 2: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.


Note 3: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note 4: The Level (dBuV/m) has been corrected by factor.


| Test Mode | Test Channel | Frequency (MHz) | Level (dBuV/m) | Factor (dB) | Limit Line (dBuV/m) | Margin (dB) | Remark | Verdict |
|---------------------|--------------|-----------------|----------------|-------------|---------------------|-------------|---------|---------|
| GFSK (BLE 1Mbps) | Low | 2390 | 54.526 | 32.61 | 74 | 19.474 | PEAK | Pass |
| | | 2390 | 44.563 | 32.61 | 54 | 9.437 | AVERAGE | Pass |
| GFSK (BLE 1Mbps) | HIGH | 2483.5 | 54.189 | 32.54 | 74 | 19.811 | PEAK | Pass |
| | | 2483.5 | 44.738 | 32.54 | 54 | 9.262 | AVERAGE | Pass |
| GFSK (BLE 2Mbps) | Low | 2390 | 53.897 | 32.61 | 74 | 20.103 | PEAK | Pass |
| | | 2390 | N/A | N/A | 54 | N/A | AVERAGE | Pass |
| GFSK (BLE 2Mbps) | HIGH | 2483.5 | 54.825 | 32.54 | 74 | 19.175 | PEAK | Pass |
| | | 2483.5 | 47.151 | 32.54 | 54 | 6.849 | AVERAGE | Pass |

BLE 1Mbps


LOW CHANNEL, PEAK




LOW CHANNEL, AV



HIGH CHANNEL, PEAK




HIGH CHANNEL, AV




BLE 2Mbps

LOW CHANNEL, PEAK




HIGH CHANNEL, PEAK



HIGH CHANNEL, AV

HIGH CHANNEL, AV



A.8 Power Spectral Density (PSD)

Test Data

BLE 1Mbps

| Channel | Spectral power density (dBm/3kHz) | Limit (dBm/3kHz) | Verdict |
|----------------|-----------------------------------|------------------|---------|
| Low Channel | -6.04 | 8 | Pass |
| Middle Channel | -5.45 | 8 | Pass |
| High Channel | -5.02 | 8 | Pass |


BLE 2Mbps

| Channel | Spectral power density (dBm/3kHz) | Limit (dBm/3kHz) | Verdict |
|----------------|-----------------------------------|------------------|---------|
| Low Channel | -8.30 | 8 | Pass |
| Middle Channel | -7.75 | 8 | Pass |
| High Channel | -7.64 | 8 | Pass |

Test plots


BLE 1Mbps

GFSK (BLE) LOW CHANNEL




Date: 23.NOV.2020 16:40:31

GFSK (BLE) MIDDLE CHANNEL



Date: 23.NOV.2020 16:46:20


GFSK (BLE) HIGH CHANNEL



Date: 23.NOV.2020 16:48:58


BLE 2Mbps

GFSK (BLE) LOW CHANNEL




Date: 23.NOV.2020 17:31:32

GFSK (BLE) MIDDLE CHANNEL



Date: 23.NOV.2020 17:34:02

GFSK (BLE) HIGH CHANNEL



Date: 23.NOV.2020 17:36:49

ANNEX B TEST SETUP PHOTOS

Please refer the document "BL-SZ20B0674-AR-1.PDF".

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document "BL-SZ20B0674-AW-1&AW-2.PDF".

ANNEX D EUT INTERNAL PHOTOS

Please refer the document "BL-SZ20B0674-AI-1&AI-2.PDF".

--END OF REPORT--